

APPLICATION CERTIFICATION
On Behalf of
Shenzhen San Fu Da Electronics Co., Ltd.

Wireless Thermometer Hygrometer
Model No.: 608

FCC ID: VVG608TX

Prepared for : Shenzhen San Fu Da Electronics Co., Ltd.
Address : 6/F., Block B, Huali Industrial Building, District 28,
Baoan, Shenzhen, China

Prepared by : ACCURATE TECHNOLOGY CO. LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20080885
Date of Test : May 26, 2008
Date of Report : May 29, 2008

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Description of Test Facility	4
1.3. Measurement Uncertainty	4
2. MEASURING DEVICE AND TEST EQUIPMENT	5
3. SUMMARY OF TEST RESULTS	6
4. CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A)	7
4.1. Block Diagram of Test Setup.....	7
4.2. The Emission Limit For Section 15.207(a)	7
4.3. EUT Configuration on Measurement	8
4.4. Operating Condition of EUT	8
4.5. Test Procedure	8
4.6. Power Line Conducted Emission Measurement Results	9
5. THE FIELD STRENGTH OF RADIATION EMISSION	10
5.1. Block Diagram of Test Setup.....	10
5.2. The Field Strength of Radiation Emission Measurement Limits.....	10
5.3. Configuration of EUT on Measurement	11
5.4. Operating Condition of EUT	11
5.5. Test Procedure	11
5.6. The Field Strength of Radiation Emission Measurement Results	12
6. 20DB OCCUPIED BANDWIDTH	13
6.1. Block Diagram of Test Setup.....	13
6.2. The Bandwidth of Emission Limit According To FCC Part 15 Section 15.231(c)	13
6.3. EUT Configuration on Measurement	14
6.4. Operating Condition of EUT	14
6.5. Test Procedure	14
6.6. Measurement Result	15
7. DURATION TIME AND SILENT PERIOD MEASUREMENT	16
7.1. Block Diagram of Test Setup.....	16
7.2. Duration Time and silent period measurement according to FCC Part 15 Section 15.231(e).....	16
7.3. EUT Configuration on Measurement	17
7.4. Operating Condition of EUT	17
7.5. Test Procedure	17
7.6. Measurement Result	18
8. AVERAGE FACTOR MEASUREMENT	19
8.1. Block Diagram of Test Setup.....	19
8.2. Average factor Measurement according to ANSI 63.4: 2003.....	19
8.3. EUT Configuration on Measurement	20
8.4. Operating Condition of EUT	20
8.5. Test Procedure	20
8.6. Measurement Result	21
APPENDIX I (TEST CURVES) (11pages)	

Test Report Certification

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.231: 2007 & ANSI 63.4: 2003

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.231 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : May 26-June 10, 2008

Prepared by :

1068

sky Wang

(Engineer)

Reviewer :

Sean (-)

(Quality Manager)

Approved & Authorized Signer :

Martin h

(Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Wireless Thermometer Hygrometer

Model Number : 608

Memo : This device is a transmitter

Power Supply : DC 12V

Applicant : Shenzhen San Fu Da Electronics Co., Ltd.

Address : 6/F., Block B, Huali Industrial Building, District 28,
Baoan, Shenzhen, China

Manufacturer : Shenzhen San Fu Da Electronics Co., Ltd.

Address : 6/F., Block B, Huali Industrial Building, District 28,
Baoan, Shenzhen, China

Date of sample received : May 19, 2008

Date of Test : May 26-June 10, 2008

1.2. Description of Test Facility

EMC Lab	: Listed by FCC The Registration Number is 274801
	>Listed by Industry Canada The Registration Number is IC4174
	Accredited by China National Accreditation Committee for Laboratories The Certificate Registration Number is L0579
Name of Firm Site Location	: Shenzhen Academy of Metrology& Quality Inspection : Bldg. Metrology& Quality Inspection, Longzhu Road, Nanshan, Shenzhen, Guangdong, P.R. China

1.3. Measurement Uncertainty

Conducted emission expanded uncertainty = 3.5dB, k=2

Radiated emission expanded uncertainty = 4.5dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	03.29.2009
EMI Test Receiver	Rohde&Schwarz	ESI26	838786/013	01.23.2009
Bilog Antenna	Schwarzbeck	VULB9163	9163-194	03.31.2009
Bilog Antenna	Chase	CBL6112B	2591	01.23.2009
Horn Antenna	Rohde&Schwarz	HF906	100013	01.23.2009
Spectrum Analyzer	Anritsu	MS2651B	6200238856	03.29.2009
Pre-Amplifier	Agilent	8447D	2944A10619	03.29.2009
L.I.S.N.	Rohde&Schwarz	ESH3-Z5	100305	03.29.2009
L.I.S.N.	Rohde&Schwarz	ESH3-Z5	100310	03.29.2009

3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	Compliant
Section 15.231(e)	Radiated Emission	Compliant
Section 15.231(c)	20dB Bandwidth	Compliant
Section 15.231(e)	Release Time Silent period	Compliant

The product is a periodic operated weather station transmitter.


Section 15.231 (a) and (b) are not applicable.

4. CONDUCTED EMISSION FOR FCC PART 15 SECTION

15.207(A)


4.1. Block Diagram of Test Setup

4.1.1. Block diagram of connection between the EUT and simulators



(EUT: Wireless Thermometer Hygrometer)

4.1.2. Shielding Room Test Setup Diagram



(EUT: Wireless Thermometer Hygrometer)

4.2. The Emission Limit For Section 15.207(a)

4.2.1 Radiation Emission Measurement Limits According to Section 15.207(a)

Frequency (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 - 5	56	46
5 - 30	60	50

* Decreases with the logarithm of the frequency.

4.3.EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.3.1. Wireless Thermometer Hygrometer (EUT)

Model Number	:	608
Serial Number	:	N/A
Manufacturer	:	Shenzhen San Fu Da Electronics Co., Ltd.

4.4.Operating Condition of EUT

4.4.1. Setup the EUT and simulator as shown as Section 4.1.

4.4.2. Turn on the power of all equipment.

4.4.3. Let the EUT work in normal operated modes (TX) measure it.

4.5.Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4: 2003 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

All the scanning waveforms are attached in Appendix I.

4.6. Power Line Conducted Emission Measurement Results

PASS.

The frequency range from 150kHz to 30MHz is checked.

Date of Test:	June 10, 2008	Temperature:	25°C
EUT:	Wireless Thermometer Hygrometer	Humidity:	53%
Model No.:	608	Power Supply:	AC 120V/60Hz
Test Mode:	TX	Test Engineer:	Joe

Test Line	Frequency MHz	Emission Level(dB μ V)		Limits(dB μ V)		Margin(dB μ V)	
		QP	AV	QP	AV	QP	AV
Va	-	-	-	-	-	-	-
Vb	-	-	-	-	-	-	-

The spectral diagrams in appendix I display the measurement of un-weighted PK+AV values.

Note:

1. Remark “-“ means that the emission level is too low to be measured.

5. THE FIELD STRENGTH OF RADIATION EMISSION


5.1. Block Diagram of Test Setup

5.1.1. Block diagram of connection between the EUT and simulators



(EUT: Wireless Thermometer Hygrometer)

5.1.2. Anechoic Chamber Test Setup Diagram



(EUT: Wireless Thermometer Hygrometer)

5.2. The Field Strength of Radiation Emission Measurement Limits

5.2.1 Radiation Emission Measurement Limits According to Section 15.231(e)

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Average] [μ V/m]	Field Strength of Spurious Emission [Average] [μ V/m]
40.66-40.70	1000	100
70-130	500	50
130-174	500 - 1500	50-150
174-260	1500	150
260-470	1500-5000	150-500
Above 470	5000	500

Where F is the frequency in MHz, The formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174MHz, $\mu\text{V/m}$ at 3 meters=22.72727(F)-2454.545; For the band 260-470MHz, $\mu\text{V/m}$ at 3 meters=16.6667(F)-2833.3333. The maximum permissible unwanted emission level is 20dB below the maximum permitted fundamental level.

5.2.2 Restricted Band Radiation Emission Measurement Limits According to FCC part 15 Section 15.205 and Section15.209.

5.3.Configuration of EUT on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3.1. Wireless Thermometer Hygrometer (EUT)

Model Number	:	608
Serial Number	:	N/A
Manufacturer	:	Shenzhen San Fu Da Electronics Co., Ltd.

5.4.Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 3.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in measuring modes (TX) measure it.

5.5.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI 63.4 on radiated emission measurement.

The bandwidth of test receiver (R&S ESI26) is set at 120KHz in 30-1000MHz, and 1MHz in 1000-5000MHz.

The frequency range from 30MHz to 5000MHz is checked.

5.6. The Field Strength of Radiation Emission Measurement Results

PASS.

The frequency range 30MHz to 5000MHz is investigated.

Date of Test:	May 26, 2008	Temperature:	26°C
EUT:	Wireless Thermometer Hygrometer	Humidity:	57%
Model No.:	608	Power Supply:	DC 12V
Test Mode:	TX	Test Engineer:	Andy

Frequency (MHz)	Reading	Factor	Average	Result(dB μ V/m)		Limit(dB μ V/m)		Margin(dB μ V/m)		Polarization
	(dB μ V/m)	Corr.	Factor	AV	PEAK	AV	PEAK	AV	PEAK	
	PEAK	(dB)	(dB)							
433.912	67.6	-16.1	-17.0	34.5	51.5	72.8	92.8	38.3	41.3	Horizontal
*1301.774	38.6	-7.2	-17.0	14.4	31.4	54	74	39.6	42.6	
433.912	65.1	-16.1	-17.0	32.0	49.0	72.8	92.8	40.8	43.8	Vertical
*135.503	52.8	-21.2	-17.0	14.6	31.6	43.5	63.5	28.9	31.9	
*1301.774	37.0	-7.2	-17.0	12.8	29.8	54	74	41.2	44.2	

The spectral diagrams in appendix 1 display the measurement of peak values with corrected factors counted

Note:

1. *: Denotes restricted band of operation.

Measurements were made using a peak detector and average detector. Any emission Above 1000MHz and falling within the restricted bands of FCC Part 15 Section 15.205 were compliance with the emission limit of FCC Part 15 Section 15.209.

2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

Where Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss – Amplifier Gain

3. FCC Limit for Average Measurement = $16.6667(433.912)-2833.3333 = 4398.5478\mu\text{V}/\text{m} = 72.8\text{dB}\mu\text{V}/\text{m}$

6. 20DB OCCUPIED BANDWIDTH


6.1. Block Diagram of Test Setup

6.1.1. Block diagram of connection between the EUT and simulators



(EUT: Wireless Thermometer Hygrometer)

6.1.2. Anechoic Chamber Test Setup Diagram



(EUT: Wireless Thermometer Hygrometer)

6.2. The Bandwidth of Emission Limit According To FCC Part 15 Section

15.231(c)

The bandwidth of emission shall be no wider than 0.25% of the center frequency. Therefore, the bandwidth of the emission limit is $433\text{MHz} \times 0.25\% = 1082.5\text{KHz}$. Bandwidth is determined at the two points 20 dB down from the top of modulated carrier.

6.3.EUT Configuration on Measurement

The following equipment are installed on the bandwidth of emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.3.1. Wireless Thermometer Hygrometer (EUT)

Model Number : 608
Serial Number : N/A
Manufacturer : Shenzhen San Fu Da Electronics Co., Ltd.

6.4.Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 4.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in measuring mode (TX) measure it.

6.5.Test Procedure

6.5.1. Set SPA Center Frequency = Fundamental frequency, RBW = 10kHz, VBW = 10kHz, Span = 300kHz.

6.5.2. Set SPA Max hold. Mark peak, -20dB

6.6. Measurement Result

The EUT does meet the FCC requirement.

-20dB bandwidth = 46.2KHz <1082.5KHz.

The spectral diagrams in appendix I.

7. DURATION TIME AND SILENT PERIOD MEASUREMENT


7.1. Block Diagram of Test Setup

7.1.1. Block diagram of connection between the EUT and simulators



(EUT: Wireless Thermometer Hygrometer)

7.1.2. Anechoic Chamber Test Setup Diagram



(EUT: Wireless Thermometer Hygrometer)

7.2. Duration Time and silent period measurement according to FCC Part 15

Section 15.231(e)

Section 15.231(e) In addition, devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

7.3.EUT Configuration on Measurement

The following equipment are installed on duration time and silent period measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.3.1.Wireless Thermometer Hygrometer (EUT)

Model Number : 608
Serial Number : N/A
Manufacturer : Shenzhen San Fu Da Electronics Co., Ltd.

7.4.Operating Condition of EUT

7.4.1.Setup the EUT and simulator as shown as Section 6.1.

7.4.2.Turn on the power of all equipment.

7.4.3.Let the EUT work in measuring mode (TX) measure it.

7.5.Test Procedure

7.5.1. Set SPA Center Frequency = Fundamental frequency, RBW = 100kHz, VBW =100kHz, Span = 0Hz.

7.5.2. Set EUT as normal operation.

7.5.3. Set SPA View. Delta Mark time.

7.6. Measurement Result

The EUT does meet the FCC requirement.

Duration time = 0.963 second <1 second

Silent period = 31.08 seconds > 30 times the duration of the transmission > 10seconds

The spectral diagrams in appendix I.

8. AVERAGE FACTOR MEASUREMENT


8.1. Block Diagram of Test Setup

8.1.1. Block diagram of connection between the EUT and simulators



(EUT: Wireless Thermometer Hygrometer)

8.1.2. Anechoic Chamber Test Setup Diagram



(EUT: Wireless Thermometer Hygrometer)

8.2. Average factor Measurement according to ANSI 63.4: 2003

ANSI 63.4: 2003 Section 13.1.4.2 Devices transmitting pulsed emissions and subject to a limit requiring an average detector function for radiated emissions shall initially be measured with an instrument that uses a peak detector. A radiated emission measured with a peak detector may then be corrected to a true average using the appropriate factor for emission duty cycle. This correction factor relates the measured peak level to the average limit and is derived by averaging absolute field strength over one complete pulse train that is 0.1 s, or less, in length. If the pulse train is longer than 0.1 s, the average shall be determined from the average absolute field strength during the 0.1 s interval in which the field strength is at a maximum. Instructions on calculating the duty cycle of a transmitter with pulsed emissions are provided in ANSI 63.4 H.4, step j.

Average factor in dB = $20 \log (\text{duty cycle})$

8.3.EUT Configuration on Measurement

The following equipment are installed on average factor Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.3.1.Wireless Thermometer Hygrometer (EUT)

Model Number : 608
 Serial Number : N/A
 Manufacturer : Shenzhen San Fu Da Electronics Co., Ltd.

8.4.Operating Condition of EUT

8.4.1.Setup the EUT and simulator as shown as Section 5.1.

8.4.2.Turn on the power of all equipment.

8.4.3.Let the EUT work in measuring mode (TX) measure it.

8.5.Test Procedure

8.5.1. The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation.

8.5.2. Set SPA Center Frequency = Fundamental frequency, RBW = 100kHz, VBW =100kHz, Span = 0Hz.

8.5.3. Set EUT as normal operation.

8.5.4. Set SPA View. Delta Mark time.

8.6. Measurement Result

The duty cycle is simply the on time divided by the period:

Effective period of one cycle = 100ms

Sum of pulse width = 32×0.44 ms = 14.08ms

Duty Cycle = 14.08ms/100ms = 0.1408

Therefore, the average factor is found by $20\log 0.1408 = -17.0\text{dB}$

The spectral diagrams in appendix I.

APPENDIX I (Test Curves)

CONDUCTION EMISSION STANDARD FCC PART15B 10. Jun 08 10:51


EUT: Wireless Thermometer hygrometer M/N:608
 Manuf: SAN FU DA
 Op Cond: TX
 Operator: Joe
 Test Spec: Vb 120V/60Hz
 Comment: Tem25°C Humi53%
 Report No.:ATE20080885 Sample No.:081755

Scan Settings (3 Ranges)

Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp
150k	2M	5k	9k	PK+AV	5ms	AUTO	LN OFF
2M	10M	10k	9k	PK+AV	5ms	AUTO	LN OFF
10M	30M	25k	9k	PK+AV	1ms	AUTO	LN OFF

Final Measurement: x QP / + AV
 Meas Time: 1 s
 Subranges: 16
 Acc Margin: 10dB

Transducer No.	Start	Stop	Name
1	9k	30M	confac



CONDUCTION EMISSION STANDARD FCC PART15B

10. Jun 08 11:05

EUT: Wireless Thermometer hygrometer M/N:608
 Manuf: SAN FU DA
 Op Cond: TX
 Operator: Joe
 Test Spec: Va 120V/60Hz
 Comment: Tem25°C Humi53%
 Report No.:ATE20080885 Sample No.:081755


Scan Settings (3 Ranges)

Frequencies			Receiver Settings			
Start	Stop	Step	IF BW	Detector	M-Time	Atten Preamp
150k	2M	5k	9k	PK+AV	5ms	AUTO LN OFF
2M	10M	10k	9k	PK+AV	5ms	AUTO LN OFF
10M	30M	25k	9k	PK+AV	1ms	AUTO LN OFF

Final Measurement: x QP / + AV


Transducer No.	Start	Stop	Name
1	9k	30M	confac

Meas Time: 1 s
 Subranges: 16
 Acc Margin: 10dB




Radiated Disturbance**FCC Part 15**

EUT: Wireless Thermometer Hygrometer M/N: 608
 Manufacturer: Shenzhen San Fu Da Electronics Co., Ltd.
 Operating Condition: TX
 Test Site: ATC EMC Lab.SAC
 Operator: Feng
 Test Specification: Horizontal
 Comment : DC 12V




Radiated Disturbance**FCC Part 15**

EUT: Wireless Thermometer Hygrometer M/N: 608
 Manufacturer: Shenzhen San Fu Da Electronics Co., Ltd.
 Operating Condition: TX
 Test Site: ATC EMC Lab.SAC
 Operator: Feng
 Test Specification: Vertical
 Comment : DC 12V




Radiated Disturbance**FCC Part 15**


EUT: Wireless Thermometer Hygrometer M/N: 608
Manufacturer: Shenzhen San Fu Da Electronics Co., Ltd.
Operating Condition: TX
Test Site: ATC EMC Lab.SAC
Operator: Feng
Test Specification: Horizontal
Comment : DC 12V





Radiated Disturbance**FCC Part 15**


EUT: Wireless Thermometer Hygrometer M/N: 608
Manufacturer: Shenzhen San Fu Da Electronics Co., Ltd.
Operating Condition: TX
Test Site: ATC EMC Lab.SAC
Operator: Feng
Test Specification: Vertical
Comment : DC 12V












It sums of 32 'on' signals at 100ms.



The graph shows the duration of 'on' signal. From marker 1 to marker 2, duration is 0.44ms.