

No. 1 Workshop, M-10, Middle Section, Science & Technology Park,
District Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594

Email: sgs_internet_operations@sgs.com

Report No.: SZEMO09070366201

Page: 1 of 38

TEST REPORT

Application No: SZEMO090703662RF

Applicant: SHENZHEN XINZHENGSHENG ELECTRONICS CO., LTD

Manufacturer/ Factory: Same as the applicant

FCC ID: VZBCM3935090630

Fundamental Carrier Frequency : 2.402GHz to 2.480GHz

Equipment Under Test (EUT):

Name: wii Balance Board

Model: CM3935

Standards: FCC PART 15 Subpart C
ANSI C63.4 2003

Date of Receipt: 03 July 2009

Date of Test: 03 July to 10 September 2009

Date of Issue: 14 September 2009

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT detailed in this report complied with the standards specified above. Please refer to section 2 of this report for further detail.

Authorized Signature:



Robinson Lo
Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Test Summary

Test	Test Requirement	Standard Paragraph	Result
Antenna Requirement	FCC PART 15	Section 15.247 (c)	PASS
Conducted Emission	FCC PART 15	Section 15.207	PASS
Occupied Bandwidth	FCC PART 15	Section 15.247 (a1)	PASS
Carrier Frequencies Separated	FCC PART 15	Section 15.247(a)(1)	PASS
Hopping Channel Number	FCC PART 15	Section 15.247(a)(1)(iii)	PASS
Dwell Time	FCC PART 15	Section 15.247(a)(1)(iii)	PASS
Pseudorandom Frequency Hopping Sequence	FCC PART 15	Section 15.247(a)(1)	PASS
Maximum Peak Output Power	FCC PART 15	Section 15.247(b)(1)	PASS
RF Exposure Compliance Requirement	FCC PART 15	15.247(b)(4)& TCB Exclusion List (7 July 2002)	PASS
Radiated Emission	FCC PART 15	Section 15.209 15.247(d)&15.205	PASS

Remark:

1. The EUT was tested installing fully charged batteries

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF THE E.U.T	4
4.3 DESCRIPTION OF SUPPORT UNITS	4
4.4 STANDARDS APPLICABLE FOR TESTING	4
4.5 TEST LOCATION	4
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	4
4.7 TEST FACILITY	5
5 EQUIPMENTS USED DURING TEST	6
6 TEST RESULTS	7
6.1 E.U.T. TEST CONDITIONS	7
6.2 ANTENNA REQUIREMENT	7
6.2.1 <i>Standard requirement</i>	7
6.2.2 <i>EUT Antenna</i>	7
6.3 CONDUCTED EMISSIONS AT MAINS TERMINALS	8
6.4 OCCUPIED BANDWIDTH	11
6.5 CARRIER FREQUENCIES SEPARATED	14
6.6 HOPPING CHANNEL NUMBER	17
6.7 DWELL TIME	18
6.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	21
6.8.1 <i>Standard requirement</i>	21
6.8.2 <i>EUT Pseudorandom Frequency Hopping Sequence</i>	21
6.9 MAXIMUM PEAK OUTPUT POWER	22
6.10 BAND EDGE	25
6.11 RADIATED EMISSIONS	28
6.11.1 <i>Radiated emission</i>	30
6.12 TRANSMIT SPURIOUS EMISSIONS	31
6.12.1 <i>Transmitter emission below 1GHz</i>	33
6.12.2 <i>Transmitter emission above 1GHz</i>	34-38

4 General Information

4.1 Client Information

Applicant: SHENZHEN XINZHENGSHENG ELECTRONICS CO., LTD
Address of Applicant: Building 49, Baotian Industrial Zone, Xixiang Town, Baoan District, Shenzhen, China
Manufacturer/ Factory: Same as the applicant
Address of Manufacturer/ Factory: Same as the applicant

4.2 General Description of the E.U.T

Product Name: wii Balance Board
Model: CM3935
Number of Channels: 79 Channels
Channel Separation: 1 MHz
Type of Modulation: FHSS (Frequency Hopping Spread Spectrum); Adaptive Frequency Hopping (AFH) is used.
Technique of Modulation: GFSK
Dwell time: Per channel is less than 0.4s
Antenna Type: Integral
Antenna Gain: 0.5dBi
Power Supply: DC4.5V(3*1.5V "AA"Size Batteries)

4.3 Description of Support Units

The EUT was tested independently

4.4 Standards Applicable for Testing

The customer requested FCC tests for the EUT.

The standard used was FCC PART 15 Subpart C: 2008. ANSI C63.4:2003.and DA 00-705.

4.5 Test Location

All tests were performed at:

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, District Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.6 Other Information Requested by the Customer

None.

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 3m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197 and C-2383 respectively.

Date of Registration: September 29, 2008. Valid until September 28, 2011.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 556682, June 27, 2008.

- **Industry Canada (IC)**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.

5 Equipments Used during Test

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	16-06-2009	15-06-2010
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	12-12-2008	11-12-2009
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	Coaxial cable	SGS	N/A	SEL0028	18-06-2009	17-06-2010
5	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0014	12-08-2009	11-08-2010
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	18-06-2009	17-06-2010
7	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0005	12-08-2009	11-08-2010
8	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	12-08-2009	11-08-2010
9	Pre-amplifier (1-18GHz)	Rohde & Schwarz	AFS42-00101 800-25-S-42	SEL0081	18-06-2009	17-06-2010
10	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	SEL0080	18-06-2009	17-06-2010
11	Band filter	Amindeon	82346	SEL0094	18-06-2009	17-06-2010
12	Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	15-06-2009	14-06-2010

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	N/A	N/A
2	LISN	ETS-LINDGREN	3816/2	SEL0021	18-06-2009	17-06-2010
3	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	21-02-2009	21-02-2010
4	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	21-02-2009	21-02-2010
5	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	EMC0122	21-02-2009	21-02-2010
6	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	18-06-2009	17-06-2010
7	Coaxial Cable	SGS	N/A	SEL0024	18-06-2009	17-06-2010

6 Test Results

6.1 E.U.T. test conditions

Operating Environment:

Temperature: 24.0 °C

Humidity: 50 % RH

Atmospheric Pressure: 1010 mbar

Test frequencies: According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Test frequency is the lowest channel: 0 channel(2402MHz), middle channel: 39 channel(2441MHz) and highest channel: 78 channel(2480MHz)

6.2 Antenna Requirement

6.2.1 Standard requirement

15.203 requirement:

For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

6.2.2 EUT Antenna

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.5dBi.

Test result: The unit does meet the FCC requirements.

6.3 Conducted Emissions at Mains Terminals

Test Requirement: FCC Part 15.207

Test Method: ANSI C63.4: 2003

Frequency Range: 150KHz to 30MHz

Detector: RBW=9KHz VBW=30KHz

Quasi-Peak if maximised peak within 6dB of Quasi-Peak limit

EUT Operation:


Charge + play mode Test in charging mode by WII USB port, and keep the EUT in communicate mode with WII device.

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Charging +Play mode:


Live line:



Site : Shielding Room
Condition : FCC PART15B QP CE LINE
EUT : Wii Balance Board
Job no : 3662RF
Test mode : CHARGE+PLAY

Freq	Cable	LISN	Read	Limit	Over	Over	
	MHz	Loss	Factor				Remark
	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.86643	0.07	-0.05	35.40	35.42	46.00	-10.58 Average
2	0.86643	0.07	-0.05	45.68	45.70	56.00	-10.30 QP
3	2.409	0.13	-0.07	40.10	40.16	56.00	-15.84 QP
4	2.409	0.13	-0.07	33.60	33.66	46.00	-12.34 Average
5 @	2.721	0.13	-0.07	49.60	49.66	56.00	-6.34 QP
6	2.721	0.13	-0.07	36.30	36.36	46.00	-9.64 Average

Neutral line:



Site : Shielding Room
Condition : FCC PART15B QP CE NEUTRAL
EUT : Wii Balance Board
Job no : 3662RF
Test mode : CHARGE+PLAY

Freq	Cable	LISN	Read	Limit	Over	Remark
	Loss	Factor	Level			
	MHz	dB	dB	dBuV	dBuV	dB
1	2.736	0.14	-0.07	42.60	42.66	56.00 -13.34 QP
2 @	2.736	0.14	-0.07	39.80	39.86	46.00 -6.14 Average
3 @	2.917	0.14	-0.08	40.90	40.96	46.00 -5.04 Average
4 @	2.917	0.14	-0.08	50.70	50.76	56.00 -5.24 QP
5	5.005	0.17	-0.12	43.90	43.95	60.00 -16.05 QP
6	5.005	0.17	-0.12	40.60	40.65	50.00 -9.35 Average

Remark: Level = Real Level + Cable loss + LISN factor

TEST RESULTS: The unit does meet the FCC requirements

6.4 Occupied Bandwidth

Test Requirement:	FCC 15.247(a)
Test Method:	ANSI C63.4 2003 & DA 00-705
Test channel:	The lowest channel, the middle channel, the highest channel.
Test Status:	Non-hopping transmitting with GFSK modulation.
Test Procedure:	

The Transmitter output of EUT was connected to the spectrum analyzer. The 20 dB bandwidth of the fundamental frequency was measured. The setting of spectrum analyzer is as follows;


Equipment Mode	Spectrum Analyzer
Detector Function	Peak
RBW	30KHz
VBW	100KHz

Test result:

Lowest channel 2.402GHz	Middle channel 2.441GHz	Highest channel 2.480GHz
1020 KHz	1000 KHz	1004 KHz


Result plot as follows:

1. Lowest Channel:




Date: 29.JUL.2009 09:01:57

2. Middle Channel:



Date: 29.JUL.2009 09:30:12

3. Highest Channel:



Date: 29.JUL.2009 10:10:01

Test result: The unit does meet the FCC requirements.

6.5 Carrier Frequencies Separated

Test Requirement: FCC 15.247(a)

Test Method: ANSI C63.4 2003& DA 00-705

Test channel: The lowest channel, the middle channel, the highest channel.

Test Status: Hopping transmitting with GFSK modulation.

Test requirements: Regulation 15.247(a), (1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure:

1 Connect EUT antenna terminal to the spectrum analyzer with a low loss cable.

Equipment mode: Spectrum analyzer

Equipment Mode	Spectrum Analyzer
Detector Function	Peak Mode
RBW	100KHz
VBW	300KHz

2. By using the Max-Hold function record the separation of two adjacent channels.


3. Measure the frequency difference of these two adjacent channels by spectrum analyzer Marker function.

4. Repeat above procedures until all frequencies measured were complete.

Test result:


Lowest channel 2.402GHz	Middle channel 2.441GHz	Highest channel 2.480GHz
1.008MHz	1.004MHz	1.004MHz

1. Lowest Channel:




Date: 29.JUL.2009 09:13:07

2. Middle Channel:



Date: 29.JUL.2009 09:35:27

3. Highest Channel:



Date: 29.JUL.2009 14:10:42

Test result: The unit does meet the FCC requirements.

6.6 Hopping Channel Number

Test Requirement: FCC 15.247(a)

Test Method: ANSI C63.4:2003, 15.247 & DA 00-705

Requirements: Regulation 15.247 (a) (1) (iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


Test Status: Hopping transmitting with GFSK modulation.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100 kHz. VBW = 300 kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: start frequency = 2400MHz. stop frequency = 2483.5MHz. Submit the test result graph.

Test result: Total channels are 79 channels.

Hopping channel numbers



Date: 29.JUL.2009 09:38:14


Test result: The unit does meet the FCC requirements.

6.7 Dwell Time


Test Standards:	FCC 15.247(a)
Test Method:	ANSI C63.4 2003& DA 00-705
Test channel:	The lowest channel, the middle channel, the highest channel.
Test Status:	Hopping transmitting with GFSK modulation.
Test Requirements:	Regulation 15.247(a) (1) (iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Test Status:	Test in hopping transmitting operating mode.
Test Procedure:	<ol style="list-style-type: none">1. Connect EUT antenna terminal to the spectrum analyzer with a low loss cable. Equipment mode: spectrum analyzer, detector function: Peak RBW=1MHz, VBW=1MHz, Span=zero.2. Adjust the center frequency of spectrum analyzer on any frequency be measured.3. Measure the Dwell Time by spectrum analyzer Marker function.4. Repeat above procedures until all frequencies measured were complete.
Test Result:	<p>The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$</p> <p>The lowest channel (2402MHz), middle channel (2441MHz), highest channel (2480MHz) as blow</p> $\text{DH1 time slot} = 0.450(\text{ms}) * (1600 / (2 * 79)) * 31.6 = 144 \text{ ms}$ $\text{DH3 time slot} = 1.71(\text{ms}) * (1600 / (4 * 79)) * 31.6 = 273.6 \text{ ms}$ $\text{DH5 time slot} = 2.91(\text{ms}) * (1600 / (6 * 79)) * 31.6 = 310.4 \text{ ms}$

The unit does meet the FCC requirements.


Please refer the graph as below:

DH1


Date: 11.AUG.2009 13:33:21

DH3


Date: 11.AUG.2009 13:35:13

DH5

Date: 11.AUG.2009 13:36:20

6.8 Pseudorandom Frequency Hopping Sequence

6.8.1 Standard requirement


15.247(a)(1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

6.8.2 EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

6.9 Maximum Peak Output Power

Test Requirement: FCC Part 15.247 & DA 00-705


Test Method: ANSI C63.4 & DA 00-705

Test channel: The lowest channel, the middle channel, the highest channel.

Test Status: Non-hopping transmitting with GFSK modulation.

Test Limit: Regulation 15.247 (b)(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
Refer to the result "Hopping channel number" of this document. The 1 watt (30.0dBm) limit applies.

Test Configuration:




Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3 MHz. VBW = 10 MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.


Test Result:

Lowest channel 2.402GHz	Middle channel 2.441GHz	Highest channel 2.480GHz
0.07dBm	-1.34 dBm	-1.65 dBm

Test result: The unit does meet the FCC requirements.


Test result plot as follows:**1. Lowest Channel:**

Date: 6.AUG.2009 05:20:34

2. Middle Channel:

Date: 29.JUL.2009 09:24:51


3. Highest Channel:




Date: 29.JUL.2009 10:08:37

6.10 Band edge

Test Requirement:	FCC 15.247(d)
Test Method:	ANSI C63.4:2003 & DA 00-705
Test channel:	Test lowest channel, highest channel.
Test States:	Hopping transmitting with modulation.
Test site:	The transmitter output is connected to spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
Limit:	15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


Out-OFF-band spurious emissions-conducted measurement:
1. The lowest channel


Date: 29.JUL.2009 09:07:57




Date: 29.JUL.2009 08:54:03

3. The highest channel





Date: 29.JUL.2009 10:31:05



Date: 29.JUL.2009 10:06:16

6.11 Radiated Emissions

Test Requirement:	15.209
Test Method:	ANSI C63.4:2003
Test Status:	
Charge + play mode	Test in charging mode by WII USB port, and keep the EUT in communicate mode with WII device.
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)
Test Range	30MHz to 13GHz 30MHz-1000MHz: RBW=100KHz, VBW=300KHz Above 1GHz: RBW=1MHz, VBW=3MHz
Limit:	40.0 dB μ V/m between 30MHz & 88MHz 43.5 dB μ V/m between 88MHz & 216MHz 46.0 dB μ V/m between 216MHz & 960MHz above 960MHz: Average value Limit 54.0 dB μ V/m Peak value Limit 74.0 dB μ V/m.

Test Configuration:**Figure1: 30MHz to 1GHz radiated emissions test configuration****Figure 2: Above 1GHz radiated emissions test configuration**

Test Procedure: The procedure used was ANSI Standard C63.4-2003. The receiver was scanned from 30MHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

6.11.1 Radiated emission

Charge + play mode.

Vertical



Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector
106.630	1.22	8.77	27.81	51.51	33.69	43.50	-9.81	QP
440.310	2.37	16.71	27.54	45.54	37.08	46.00	-8.92	QP
707.060	2.92	21.60	27.26	45.01	42.27	46.00	-3.73	QP
773.990	3.12	22.00	27.02	44.52	42.62	46.00	-3.38	QP
815.700	3.27	22.29	26.85	44.22	42.93	46.00	-3.07	QP
921.430	3.62	23.29	26.43	41.52	42.00	46.00	-4.00	QP
1594.00	5.10	28.68	38.90	45.40	40.28	74.00	-33.72	Peak
1594.00	5.10	28.68	38.90	42.01	36.89	54.00	-17.11	Average
5563.00	12.60	34.78	41.93	40.14	45.59	74.00	-28.41	Peak
5563.00	12.60	34.78	41.93	35.02	40.47	54.00	-13.53	Average

Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector
125.060	1.27	7.80	27.64	55.80	37.23	43.50	-6.27	QP
292.870	1.87	13.58	26.75	48.76	37.46	46.00	-8.54	QP
401.510	2.21	16.31	27.42	49.17	40.27	46.00	-5.73	QP
529.550	2.63	18.59	27.68	48.41	41.95	46.00	-4.05	QP
773.990	3.12	22.00	27.02	43.98	42.08	46.00	-3.92	QP
882.630	3.53	23.06	26.51	42.87	42.95	46.00	-3.05	QP
2998.00	6.68	33.40	38.96	40.39	41.51	74.00	-32.49	Peak
2998.00	6.68	33.40	38.96	37.46	38.58	54.00	-15.42	Average
6778.00	13.44	36.39	40.26	43.32	52.89	74.00	-21.11	Peak
6778.00	13.44	36.39	40.26	35.27	44.84	54.00	-9.16	Average

6.12 Transmit spurious emissions

Test Requirement: 15.247(d), 15.209 & 15.205
Test Method: ANSI C63.4:2003 & DA 00-705
Test channel: The lowest channel, the middle channel, the highest channel.
Test Status: Non-hopping transmitting with GFSK modulation.
Test site: Measurement Distance: 3m (Semi-Anechoic Chamber)
Test Range 30MHz to 25GHz
30MHz-1000MHz: RBW=100KHz, VBW=300KHz
Above 1GHz: PK RBW=1MHz, VBW=3MHz
Average RBW=1MHz, VBW=10Hz
Limit: 40.0 dB μ V/m between 30MHz & 88MHz
43.5 dB μ V/m between 88MHz & 216MHz
46.0 dB μ V/m between 216MHz & 960MHz
above 960MHz: Average value Limit 54.0 dB μ V/m
Peak value Limit 74.0 dB μ V/m.

Test Configuration:**Figure1: 30MHz to 1GHz radiated emissions test configuration****Figure 2: Above 1GHz radiated emissions test configuration**

Test Procedure: The procedure used was ANSI Standard C63.4-2003. The receiver was scanned from 30MHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

6.12.1 Transmitter emission below 1GHz

The lowest channel (2402MHz)

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
173.56	1.36	9.63	27.30	30.66	14.35	43.50	-29.15	Vertical
323.91	1.98	14.76	26.91	30.37	20.20	46.00	-25.80	Vertical
665.35	2.84	21.16	27.39	30.37	26.98	46.00	-19.02	Vertical
96.93	1.17	8.98	27.90	40.79	23.04	43.50	-20.46	Horizontal
341.37	2.03	15.22	27.03	30.93	21.15	46.00	-24.85	Horizontal
815.70	3.27	22.29	26.85	30.42	29.13	46.00	-16.87	Horizontal

The middle channel (2441MHz)

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
88.20	1.10	8.54	27.96	31.99	13.67	43.50	-29.83	Vertical
276.38	1.80	12.85	26.81	34.49	22.33	46.00	-23.67	Vertical
553.80	2.66	18.93	27.66	30.21	24.14	46.00	-21.86	Vertical
118.27	1.25	8.02	27.70	42.39	23.96	43.50	-19.54	Horizontal
238.55	1.62	11.93	26.96	35.05	21.64	46.00	-24.36	Horizontal
675.05	2.85	21.40	27.36	30.70	27.59	46.00	-18.41	Horizontal

The highest channel (2480MHz)

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
125.06	1.26	7.80	27.64	39.77	21.19	43.50	-22.31	Vertical
447.10	2.40	16.84	27.56	31.36	23.04	46.00	-22.96	Vertical
753.62	3.07	21.73	27.09	30.92	28.63	46.00	-17.37	Vertical
62.98	0.80	7.11	28.03	37.98	17.86	40.00	-22.14	Horizontal
219.15	1.51	11.18	27.05	36.61	22.25	46.00	-23.75	Horizontal
454.86	2.43	17.03	27.58	37.65	29.53	46.00	-16.47	Horizontal

6.12.2 Transmitter emission above 1GHz

The lowest channel (2.402GHz)

Peak Measurement

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1035.25	3.08	27.43	37.96	54.55	47.10	74.00	-26.90	Vertical
2385.25	4.92	32.23	37.97	49.55	48.73	74.00	-25.27	Vertical
2400.00	4.97	32.25	37.97	55.18	54.43	74.00	-19.57	Vertical
3902.25	5.98	33.36	38.47	49.47	50.34	74.00	-23.66	Vertical
5735.25	7.11	34.98	39.11	50.88	53.86	74.00	-20.14	Vertical
7192.25	7.65	36.33	37.73	49.61	55.86	74.00	-18.14	Vertical
12632.50	10.51	39.12	34.34	43.32	58.61	74.00	-15.39	Vertical
1035.25	3.08	27.43	37.96	52.41	44.96	74.00	-29.04	Horizontal
1446.50	3.67	27.77	38.20	52.49	45.73	74.00	-28.27	Horizontal
2385.25	4.92	32.23	37.97	48.57	47.75	74.00	-26.25	Horizontal
2400.00	4.97	32.25	37.97	56.34	55.59	74.00	-18.41	Horizontal
6757.50	7.55	36.36	37.87	46.76	52.80	74.00	-21.20	Horizontal
9906.50	8.76	37.21	33.38	40.38	52.97	74.00	-21.03	Horizontal
12350.50	10.22	39.01	34.05	44.18	59.36	74.00	-14.64	Horizontal

Average Measurement

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Polarization
1998.75	4.47	32.00	38.74	31.90	29.63	54.00	-24.37	Vertical
2385.25	4.92	32.23	37.97	34.57	33.75	54.00	-20.25	Vertical
2400.00	4.97	32.25	37.97	40.12	39.37	54.00	-14.63	Vertical
4431.00	6.42	34.01	37.96	34.52	36.99	54.00	-17.01	Vertical
6992.50	7.58	36.70	37.79	31.59	38.08	54.00	-15.92	Vertical
7192.25	7.65	36.33	37.73	34.16	40.41	54.00	-13.59	Vertical
12632.50	10.51	39.12	34.34	27.43	42.72	54.00	-11.28	Vertical
1928.25	4.37	31.45	38.23	31.98	29.57	54.00	-24.43	Horizontal
2385.25	4.92	32.23	37.97	35.42	34.60	54.00	-19.40	Horizontal
2400.00	4.97	32.25	37.97	37.84	37.09	54.00	-16.91	Horizontal
4431.00	6.42	34.01	37.96	31.19	33.66	54.00	-20.34	Horizontal
6992.50	7.73	36.70	37.79	31.53	38.17	54.00	-15.83	Horizontal
10705.50	9.48	38.05	33.10	27.43	41.86	54.00	-12.14	Horizontal
12350.50	10.22	39.01	34.05	26.40	41.58	54.00	-12.42	Horizontal

The middle channel (2.441GHz)**Peak Measurement**

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Polarization
1881.25	4.30	31.12	37.93	51.27	48.76	74.00	-25.24	Vertical
2400.00	4.97	32.25	37.97	52.48	51.73	74.00	-22.27	Vertical
2483.50	5.08	32.29	38.24	51.32	50.45	74.00	-23.55	Vertical
5265.25	6.86	34.38	38.53	51.08	53.79	74.00	-20.21	Vertical
7086.50	7.70	36.55	37.76	46.65	53.14	74.00	-20.86	Vertical
10752.50	9.49	38.10	33.06	41.24	55.77	74.00	-18.23	Vertical
12350.50	10.22	39.01	34.05	42.36	57.54	74.00	-16.46	Vertical
1035.25	3.08	27.43	37.96	54.37	46.92	74.00	-27.08	Horizontal
2400.00	4.97	32.25	37.97	51.62	50.87	74.00	-23.13	Horizontal
2483.50	5.08	32.29	38.24	50.75	49.88	74.00	-24.12	Horizontal
5735.25	7.11	34.98	39.11	48.52	51.50	74.00	-22.50	Horizontal
6851.50	7.62	36.50	37.84	46.89	53.17	74.00	-20.83	Horizontal
8167.50	8.06	36.00	36.94	45.72	52.84	74.00	-21.16	Horizontal
12315.25	10.20	38.99	34.02	42.93	58.10	74.00	-15.90	Horizontal

Average Measurement

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Polarization
1258.50	3.40	27.63	37.27	32.20	25.96	54.00	-28.04	Vertical
2400.00	4.97	32.25	37.97	36.75	36.00	54.00	-18.00	Vertical
2483.50	5.08	32.29	38.24	35.48	34.61	54.00	-19.39	Vertical
4431.00	6.42	34.01	37.96	31.06	33.53	54.00	-20.47	Vertical
6992.50	7.73	36.70	37.79	28.67	35.31	54.00	-18.69	Vertical
10752.50	9.49	38.10	33.06	23.59	38.12	54.00	-15.88	Vertical
12350.50	10.22	39.01	34.05	25.49	40.67	54.00	-13.33	Vertical
2069.25	4.56	32.05	38.50	31.74	29.85	54.00	-24.15	Horizontal
2400.00	4.97	32.25	37.97	35.97	35.22	54.00	-18.78	Horizontal
2483.50	5.08	32.29	38.24	34.18	33.31	54.00	-20.69	Horizontal
4489.75	6.47	34.10	38.13	31.11	33.55	54.00	-20.45	Horizontal
5418.00	6.95	34.59	38.67	31.29	34.16	54.00	-19.84	Horizontal
6992.50	7.73	36.70	37.79	31.47	38.11	54.00	-15.89	Horizontal
12315.25	10.20	38.99	34.02	27.36	42.53	54.00	-11.47	Horizontal

The highest channel (2.480GHz)
Peak Measurement

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Polarization
1035.25	3.08	27.43	37.96	55.17	47.72	74.00	-26.28	Vertical
1446.50	3.67	27.77	38.20	53.27	46.51	74.00	-27.49	Vertical
2483.50	5.08	32.29	38.24	55.49	54.62	74.00	-19.38	Vertical
2492.25	5.10	32.30	38.26	53.05	52.19	74.00	-21.81	Vertical
4466.25	6.45	34.06	38.09	46.13	48.55	74.00	-25.45	Vertical
6616.50	7.42	36.17	37.94	46.97	52.62	74.00	-21.38	Vertical
12350.50	10.22	39.01	34.05	42.43	57.61	74.00	-16.39	Vertical
1035.25	3.08	27.43	37.96	49.68	42.23	74.00	-31.77	Horizontal
1446.50	3.67	27.77	38.20	55.41	48.65	74.00	-25.35	Horizontal
1728.50	4.08	29.86	37.97	54.19	50.16	74.00	-23.84	Horizontal
2483.50	5.08	32.29	38.24	53.67	52.80	74.00	-21.20	Horizontal
2492.25	5.10	32.30	38.26	51.82	50.96	74.00	-23.04	Horizontal
6851.50	7.62	36.50	37.84	45.17	51.45	74.00	-22.55	Horizontal
12080.25	10.13	38.84	33.80	42.51	57.68	74.00	-16.32	Horizontal

Average Measurement

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Polarization
1258.50	3.40	27.63	37.27	31.94	25.70	54.00	-28.30	Vertical
2483.50	5.08	32.29	38.24	36.71	35.84	54.00	-18.16	Vertical
2492.25	5.10	32.30	38.26	34.26	33.40	54.00	-20.60	Vertical
4454.50	6.44	34.05	38.05	30.90	33.34	54.00	-20.66	Vertical
6969.00	7.71	36.67	37.80	31.22	37.80	54.00	-16.20	Vertical
9765.50	8.65	37.10	33.45	28.22	40.52	54.00	-13.48	Vertical
12350.50	10.22	39.01	34.05	27.15	42.33	54.00	-11.67	Vertical
1223.25	3.35	27.60	37.48	31.96	25.43	54.00	-28.57	Horizontal
1857.75	4.25	30.91	37.94	31.69	28.91	54.00	-25.09	Horizontal
2483.50	5.08	32.29	38.24	37.09	36.22	54.00	-17.78	Horizontal
2492.25	5.10	32.30	38.26	34.95	34.09	54.00	-19.91	Horizontal
4489.75	6.47	34.10	38.13	30.92	33.36	54.00	-20.64	Horizontal
6969.00	7.71	36.67	37.80	31.21	37.79	54.00	-16.21	Horizontal
10881.75	9.50	38.20	33.02	27.09	41.77	54.00	-12.23	Horizontal

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor.

Remark: No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.

Remark:

- 1). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.
- 2) Pre-test the Bluetooth normal mode
- 3) For this intentional radiator operates below 25 GHz. The spectrum shall be investigated to the tenth harmonic of the highest fundamental frequency. And above the 7th harmonic of this intentional radiator, the disturbance is very low.

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		

The result: The unit does meet the FCC requirements