



No.198 Kezhu Road, Science Town Economic& Technology  
Development District Guangzhou, China 510663  
Telephone: +86 (0) 20 8215 5555 Fax: +86 (0) 20 8207 5059  
Email: sgs\_internet\_operations@sgs.com

FEDERAL COMMUNICATIONS COMMISSION  
Registration number: 556682

Report No.: SZEMO080401422ETF  
Page: 1 of 9  
FCC ID: WBU-GC887553

## TEST REPORT

**Application No.:** SZEMO080401422ET(SZ SGS NO.:SZTYR080401279/ EL)

**Applicant:** Double Pacific (Asia) Ltd.

**FCC ID:** WBU-GC887553

**Fundamental Frequency :** 27.145MHz

**Equipment Under Test (EUT):**

Name: Radio controlled helicopter

Item No.: 6242

Labelled Age Grading: 8 up

Country of Origin: China

Country of Destination: USA

**Standards:** FCC PART 15, SUBPART C : 2007

**Date of Receipt:** 21 April 2008

**Date of Test:** 21 to 28 April 2008

**Date of Issue:** 13 May 2008

<b>Test Result :</b>	<b>PASS *</b>
----------------------	---------------

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo  
Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of the Company.



## 2 Test Summary

Test	Test Requirement	Standard Paragraph	Result
Radiated Emission (30MHz to 1000MHz)	FCC PART 15 :2007	Section 15.227	PASS
Occupied Bandwidth	FCC PART 15 :2007	Section 15.215	PASS

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

Remark:

The report SZEMO080401422ETF was an additional report copied from the report SZEMO080401421ETF, just changing the applicant, applicant address and Item No.,. Since the electrical circuit design, layout, components used and internal wiring for the Items "6242" in the report SZEMO080401422ETF was exactly the same as the Items "603, 601, 606" in the report SZEMO080401421ETF.

The EUT was tested installing new batteries.



### 3 Contents

	Page
1 COVER PAGE .....	1
2 TEST SUMMARY .....	2
3 CONTENTS .....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION .....	4
4.2 DETAILS OF E.U.T. ....	4
4.3 DESCRIPTION OF SUPPORT UNITS .....	4
4.4 TEST LOCATION .....	4
4.5 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	4
5 TEST RESULTS .....	5
5.1 TEST INSTRUMENTS.....	5
5.2 E.U.T. OPERATION.....	5
5.3 TEST PROCEDURE & MEASUREMENT DATA .....	5
5.3.1 <i>Radiated Emissions</i> .....	5-7
5.3.2 <i>Occupied Bandwidth</i> .....	8-9

## **4 General Information**

### **4.1 Client Information**

Applicant: Double Pacific (Asia) Ltd.  
Address of Applicant: 8<sup>th</sup> Floor, Henley Building 5 Queen's Road, Central Hong Kong

### **4.2 Details of E.U.T.**

Power Supply: 12 V DC (8\* 1.5V 'AA' Size Batteries) for Tx ;  
7.2V DC (Rechargeable Battery) for Rx.  
Power Cord: N/A-

### **4.3 Description of Support Units**

The EUT was tested as an independent unit: 27MHz radio transmitter.

### **4.4 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory, No.198 Kezhu Road, Science Town Economic & Technology Development District Guangzhou, China 510663

Tel: +86 20 8215 5555 Fax: +86 20 8207 5059

### **4.5 Other Information Requested by the Customer**

None.

## 5 Test Results

### 5.1 Test Instruments

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	16-06-2007	15-06-2008
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	12-12-2007	11-12-2008
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	Coaxial cable	SGS	N/A	SEL0028	01-06-2007	31-05-2008
5	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0017	12-08-2007	11-08-2008
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	27-06-2007	26-06-2008
7	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0005	12-08-2007	11-08-2008
8	Pre-amplifier (1-18GHz)	Rohde & Schwarz	AFS42-00101 800-25-S-42	SEL0081	27-06-2007	26-06-2009
9	Band filter	Amindeon	82346	SEL0094	26-08-2007	25-08-2008

### 5.2 E.U.T. Operation

Operating Environment:

Temperature: 26.0 °C

Humidity: 51% RH

Atmospheric Pressure: 1020mbar

EUT Operation: Test the EUT in transmitting mode.

### 5.3 Test Procedure & Measurement Data

#### 5.3.1 Radiated Emissions

**Test Requirement:** FCC Part15 C Section 15.227

**Test Method:** ANSI C63.4

**Measurement Distance:** 3m (Semi-Anechoic Chamber)

**Requirements:** Carrier frequency will not exceed 80dBuV/m AT 3m.

Out of band emissions shall not exceed:

40.0 dB $\mu$ V/m between 30MHz & 88MHz

43.5 dB $\mu$ V/m between 88MHz & 216MHz

46.0 dB $\mu$ V/m between 216MHz & 960MHz

54.0 dB $\mu$ V/m above 960MHz

**Detector:** Peak Scan (9kHz resolution bandwidth for 9kHz to 30MHz;  
120kHz resolution bandwidth for 30MHz to 1000MHz)

FCC ID: WBU-GC887553

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law." Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of the Company.

**Test Procedure:**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

**27.145MHz Mode.**

Test Procedure: For testing performed with the loop antenna, testing was performed in accordance to ANSI C63.4 section 8.2.1. The center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

**Horizontal.**

Test Frequency (MHz)	Peak (dBµV/m)	Limits (dBµV/m)	Margin (dB)
	X		X
27.145	37.2	100.0	62.8

Test Frequency (MHz)	Average (dBµV/m)	Limits (dBµV/m)	Margin (dB)
	X		X
27.145	32.8	80.0	47.2

**Vertical.**

Test Frequency (MHz)	Peak (dBµV/m)	Limits (dBµV/m)	Margin (dB)
	X		X
27.145	49.3	100.0	50.7

Test Frequency (MHz)	Peak (dBµV/m)	Limits (dBµV/m)	Margin (dB)
	X		X
27.145	45.2	80.0	34.8

Y: EUT as per photograph in section 5.3.3 of this report.

X: As Y, but rotate EUT by 90° clockwise.

Z: As X, but rotate EUT by 90° vertically.

**Other emissions**



Test the EUT in transmitting mode.

Horizontal.

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
54.250	0.80	7.92	28.08	34.71	15.35	40.00	-24.65
78.625	1.06	7.61	28.00	34.64	15.31	40.00	-24.69
105.925	1.22	8.81	27.82	31.22	13.43	43.50	-30.07
133.225	1.29	7.84	27.58	32.96	14.51	43.50	-28.99
324.325	1.98	14.80	26.91	33.66	23.53	46.00	-22.47

Vertical.

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
54.250	0.80	7.64	28.08	53.15	33.51	40.00	-6.49
78.625	1.06	7.61	28.00	43.18	23.85	40.00	-16.15
105.925	1.22	8.81	27.82	39.44	21.65	43.50	-21.85
133.225	1.29	7.84	27.58	42.88	24.43	43.50	-19.07
187.825	1.38	10.06	27.22	43.42	27.64	43.50	-15.86

Remark:

According to 15.35 (b) When average radiated emission measurements are specified in the regulations, including emission measurements below 1000 MHz, there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules, e.g., see Section 15.255.

**Test Results: The unit does meet the FCC Part 15 C Section 15.227 requirements.**

### 5.3.2 Occupied Bandwidth

Test Requirement: FCC Part 15 C Section 15.215 (C) and Section 15.227.

Test Method: ANSI C63.4

Operation within the band 26.960 – 27.280 MHz .

#### **26.960–27.280MHz Mode.**

Requirements:

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Method of measurement:

The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector. The vertical Scale is set to 10dB per division. The horizontal scale is set to 32KHz per division.






\*RBW 1 kHz      Marker 1 [T1 ]  
\*VBW 3 kHz      44.20 dBpW  
\*SWT 320 ms      27.144960000 MHz

Ref 83 dBpW

\*Att 20 dB

1 PK  
MAXH



Start 26.96 MHz      32 kHz/      Stop 27.28 MHz

Date: 22.APR.2008 10:21:51

**The results: The unit does meet the FCC Part 15 C Section 15.215 requirements**

FCC ID: WBU-GC887553

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law." Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of the Company.