



Report No.: RZA1012-2086EMC



Part 15B

TEST REPORT

Product Name GSM /WCDMA dual mode mobile phone

FCC ID WLPW110CBW

Model W110

Applicant Shanghai Longcheer3g Technology Co.,Ltd

TA Technology (Shanghai) Co., Ltd.

A red circular stamp with the company name 'TA Technology (Shanghai) Co., Ltd.' around the top edge and '报告专用章' (Report Special Seal) in the center.

GENERAL SUMMARY

Product Name	GSM /WCDMA dual mode mobile phone	Model	W110
FCC ID	WLPW110CBW	Report No.	RZA1012-2086EMC
Client	Shanghai Longcheer3g Technology Co.,Ltd		
Manufacturer	Shanghai Longcheer3g Technology Co.,Ltd		
Reference Standard(s)	<p>FCC Part 15 Subpart B (2009-12) Radio frequency device.</p> <p>ANSI C63.4 (2003) Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9 KHz to 40GHz.</p>		
Conclusion	<p>This portable wireless equipment has been measured in all cases requested by the relevant standards. Test results in Chapter 2 of this test report are below limits specified in the relevant standards.</p> <p>General Judgment : Pass</p> <p style="text-align: center;">(Stamp)</p> <p style="text-align: center;">Date of issue: March 21st, 2011</p> 		
Comment	The test result only responds to the measured sample.		

Approved by 杨伟中

Yang Weizhong

Revised by 范广畅

Fan Guangchang

Performed by 刘伟

Liu Wei

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1012-2086EMC

Registration Num:428261
Page 3 of 27

TABLE OF CONTENT

1. General Information	4
1.1. Notes of the test report	4
1.2. Testing laboratory	4
1.3. Applicant Information	5
1.4. Manufacturer Information.....	5
1.5. Information of EUT.....	6
1.6. Test Date	7
2. Test Information	8
2.1. Summary of test results	8
2.2. Radiated Emission	9
2.3. Conducted Emission.....	17
3. Main Test Instruments	25
ANNEX A: The EUT Appearance and Test Setup	26
A.1 EUT Appearance	26
A.2 Test Setup.....	27

1. General Information

1.1. Notes of the test report

TA Technology (Shanghai) Co., Ltd. guarantees the reliability of the data presented in this test report, which is the results of measurements and tests performed for the items under test on the date and under the conditions stated in this test report and is based on the knowledge and technical facilities available at **TA Technology (Shanghai) Co., Ltd.** at the time of execution of the test.

TA Technology (Shanghai) Co., Ltd. is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the items under test and the results of the test. This report only refers to the item that has undergone the test.

This report standalone does not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities. This report can not be used partially or in full for publicity and/or promotional purposes without previous written approval of **TA Technology (Shanghai) Co., Ltd.** and the Accreditation Bodies, if it applies.

If the electrical report is inconsistent with the printed one, it should be subject to the latter.

1.2. Testing laboratory

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Yang Weizhong
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: yangweizhong@ta-shanghai.com

1.3. Applicant Information

Company: Shanghai Longcheer3g Technology Co.,Ltd
Address: No.1, Building 5, 299 Bisheng Rd, Zhangjiang Hi-Tech Park, Pudong, Shanghai
City: Shanghai
Postal Code: 201204
Country: P.R. China
Contact: Hu Zhengfang
Telephone: +86-21-64088898
Fax: +86-21-54970816

1.4. Manufacturer Information

Company: Shanghai Longcheer3g Technology Co.,Ltd
Address: No.1, Building 5, 299 Bisheng Rd, Zhangjiang Hi-Tech Park, Pudong, Shanghai
City: Shanghai
Postal Code: 201204
Country: P.R. China
Telephone: +86-21-64088898
Fax: +86-21-54970816

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1012-2086EMC

Registration Num:428261
Page 6 of 27

1.5. Information of EUT

General information

Name of EUT:	GSM /WCDMA dual mode mobile phone		
IMEI:	355077010033420		
Hardware Version:	LQWM232A		
Software Version:	LQWHM01.1.0		
Device Operating Configurations:			
Operating Mode(s):	GSM 850(tested); GSM 1900(tested)		
	WCDMA Band IV(tested);		
Power supply:	Battery or Charger		
Rated Power Supply Voltage:	3.8V		
Extreme Voltage:	Minimum: 3.5V Maximum: 4.2V		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824.2~848.8	869.2~893.8
	GSM 1900	1850.2~1909.8	1930.2~1989.8
	WCDMA Band IV	1712.4~1752.6	2112.4~2152.6
Used Host Products:	IBM T61		

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA1012-2086EMC

Page 7 of 27

Auxiliary equipment details

AE1: Battery

Model: BL-4C-800mAh (UL)

Manufacture: SHENZHEN BAK BATTERY CO.,LTD

S/N: BAK1101000123

AE2: Headset

Model: TJ-090026

Manufacture: SHENZHEN TENJI INDUSTRIAL CO., LTD

S/N: /

AE3: Notebook

Model: IBM T61

S/N: L3-C9644

Equipment Under Test (EUT) is GSM /WCDMA dual mode mobile phone with internal antenna. It consists of mobile phone, battery and headset and the detail about these is in chapter 1.5 in this report.

The sample under test was selected by the Client.

Components list please refer to documents of the manufacturer.

1.6. Test Date

The test date is from July 2, 2010 to July 6, 2010 and from March 10,2011 to March 19,2011.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1012-2086EMC

Registration Num:428261
Page 8 of 27

2. Test Information

2.1. Summary of test results

Number	Test Case	Clause in FCC Rules	Verdict
1	Radiated Emission	15.109, ANSI C63.4-2003	PASS
2	Conducted Emission	15.107, ANSI C63.4-2003	PASS

2.2. Radiated Emission

Ambient condition

Temperature	Relative humidity	Pressure
24°C~26°C	45%~50%	102.5kPa


Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2003. Sweep the whole frequency band through the range from 30MHz to 5GHz. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. During the test, EUT is connected to a laptop via a USB cable in the case of USB mode. The EUT is used as the peripheral equipment of the PC. The model of laptop is IBM T61 8892-BAC and the serial number of laptop is L3-C9644. The phone modem drivers were installed on the laptop to be able to communicate with the EUT by continuously sending a querying text file (AT Command) to the phone using Hyper Terminal during the test.


The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Test Setup

Below 1GHz



Above 1GHz



Limits

Frequency (MHz)	Field Strength (dB μ V/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5 th harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$. $U = 3.92$ dB.

TA Technology (Shanghai) Co., Ltd.
Test Report


Registration Num:428261

Report No.: RZA1012-2086EMC

Page 11of 27

Test Results

GSM 850



Note: Red trace is in vertical polarization Blue trace is in horizontal polarization

Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dB μ V/m)	Height (cm)	Polarization	Azimuth (deg)	Margin (dB)	Limit (dB μ V/m)
40.022500	14.3	100.0	V	292.0	25.7	40.0
59.987500	13.6	100.0	V	97.0	26.4	40.0
171.007500	12.2	125.0	H	112.0	31.3	43.5
263.812500	25.5	100.0	H	9.0	20.5	46.0
555.542500	15.1	115.0	V	180.0	30.9	46.0
935.252500	31.7	100.0	V	9.0	14.3	46.0


Note: all emissions level measured above 1GHz was more than 10dB below the limit

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261


Report No.: RZA1012-2086EMC

Page 12of 27



Note: Blue trace uses the peak detection Green trace uses the average detection

Radiated Emission from 1GHz to 3GHz



Note:Blue trace uses the peak detection Green trace uses the average detection

Radiated Emission from 3GHz to 5GHz


TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA1012-2086EMC

Page 13of 27

GSM 1900



Note: Red trace is in vertical polarization Blue trace is in horizontal polarization

Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dB μ V/m)	Height (cm)	Polarization	Azimuth (deg)	Margin (dB)	Limit (dB μ V/m)
47.297500	11.0	116.0	H	22.0	29.0	40.0
207.595000	22.8	125.0	H	74.0	20.7	43.5
480.040000	30.1	100.0	V	86.0	15.9	46.0
698.737500	23.1	100.0	V	183.0	22.9	46.0
799.575000	26.6	100.0	V	281.0	19.4	46.0
935.252500	18.0	100.0	V	10.0	28.0	46.0


Note: all emissions level measured above 1GHz was more than 10dB below the limit

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261


Report No.: RZA1012-2086EMC

Page 14of 27



Note:Blue trace uses the peak detection Green trace uses the average detection

Radiated Emission from 1GHz to 3GHz



Note:Blue trace uses the peak detection Green trace uses the average detection

Radiated Emission from 3GHz to 10GHz


TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA1012-2086EMC

Page 15of 27

WCDMA Band IV



Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dB μ V/m)	Height (cm)	Polarization	Azimuth (deg)	Margin (dB)	Limit (dB μ V/m)
32.470000	31.9	125.0	V	40.0	8.1	40.0
36.340000	25.8	100.0	V	68.0	14.2	40.0
53.200000	13.5	100.0	V	40.0	26.5	40.0
172.790000	23.3	100.0	V	203.0	20.2	43.5
307.220000	20.8	100.0	H	294.0	25.2	46.0
364.810000	22.2	100.0	H	317.0	23.8	46.0


Note: all emissions level measured above 1GHz was more than 10dB below the limit

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261


Report No.: RZA1012-2086EMC

Page 16of 27



Note:Blue trace uses the peak detection Green trace uses the average detection

Radiated Emission from 1GHz to 3GHz



Note: Blue trace uses the peak detection Green trace uses the average detection

Radiated Emission from 3GHz to 10GHz

2.3. Conducted Emission


Ambient condition

Temperature	Relative humidity	Pressure
24°C ~26°C	50%~55%	102.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2003. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. The measurement result should include both L line and N line. During the test, EUT is connected to a laptop via a USB cable in the case of USB mode. The EUT is used as the peripheral equipment of the PC. The model of laptop is IBM T61 8892-BAC and the serial number of laptop is L3-C9644. The phone modem drivers were installed on the laptop to be able to communicate with the EUT by continuously sending a querying text file (AT Command) to the phone using Hyper Terminal during the test, and the EUT is worked at maximum output power.

Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage from 220V/50Hz to 110V/60Hz.

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA1012-2086EMC

Page 18of 27

Limits

Frequency (MHz)	Conducted Limits(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 [*]	56 to 46 [*]
0.5 - 5	56	46
5 - 30	60	50

^{*}: Decreases with the logarithm of the frequency.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$. $U = 2.69$ dB.

TA Technology (Shanghai) Co., Ltd.
Test Report


Registration Num:428261

Report No.: RZA1012-2086EMC

Page 19of 27

Test Results

GSM 850



Note:Blue trace uses the peak detection Green trace uses the average detection

L line


Conducted Emission from 150 KHz to 30 MHz

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA1012-2086EMC

Page 20 of 27



Note: Blue trace uses the peak detection Green trace uses the average detection

N line

Conducted Emission from 150 KHz to 30 MHz

Frequency (MHz)	Detector	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)
0.915	Average	N	10.8	46	35.2
1.135	Average	L	13.1	46	32.9
4.785	Average	L	12	46	34
5	Average	N	9.5	50	40.5
11.35	Average	N	11.9	50	38.1
11.99	Average	L	14.8	50	35.2
0.87	Quasi-peak	N	20	56	36
1.09	Quasi-peak	L	21.7	56	34.3
4.41	Quasi-peak	N	17.3	56	38.7
4.8	Quasi-peak	L	18	56	38
11.385	Quasi-peak	N	17.8	60	42.2
11.995	Quasi-peak	L	19.9	60	40.1


TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA1012-2086EMC

Page 21of 27

GSM 1900



Note: Blue trace uses the peak detection Green trace uses the average detection

L line


Conducted Emission from 150 KHz to 30 MHz

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA1012-2086EMC

Page 22 of 27



Note: Blue trace uses the peak detection Green trace uses the average detection

N line

Conducted Emission from 150 KHz to 30 MHz

Frequency (MHz)	Detector	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)
0.855	Average	N	10.8	46	35.2
0.925	Average	L	13.3	46	32.7
3.3	Average	L	12.3	46	33.7
4.88	Average	N	9.9	46	36.1
10.905	Average	N	11.5	50	38.5
12.27	Average	L	14.1	50	35.9
0.9	Quasi-peak	N	20.1	56	35.9
0.99	Quasi-peak	L	23.5	56	32.5
3.34	Quasi-peak	N	17.6	56	38.4
3.945	Quasi-peak	L	19.7	56	36.3
5.195	Quasi-peak	N	16.5	60	43.5
5.27	Quasi-peak	L	19.4	60	40.6


TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA1012-2086EMC

Page 23of 27

WCDMA Band IV



Note:Blue trace uses the peak detection Green trace uses the average detection

L line


Conducted Emission from 150 KHz to 30 MHz

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA1012-2086EMC

Page 24of 27



Note:Blue trace uses the peak detection Green trace uses the average detection

N line

Conducted Emission from 150 KHz to 30 MHz

Frequency (MHz)	Detector	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)
0.215	Average	L	34.9	53	18.1
0.215	Average	N	33.5	53	19.5
0.54	Average	L	32.5	46	13.5
0.87	Average	N	30.7	46	15.3
1.845	Average	N	36.7	46	9.3
1.845	Average	L	35.5	46	10.5
0.2	Quasi-peak	L	44.9	63.6	18.7
0.215	Quasi-peak	N	47.2	63	15.8
0.87	Quasi-peak	N	49.3	56	6.7
0.87	Quasi-peak	L	47.9	56	8.1
1.84	Quasi-peak	L	49	56	7
1.85	Quasi-peak	N	52.2	56	3.8

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA1012-2086EMC

Page 25of 27

3. Main Test Instruments

No.	Name	Type	Manufacturer	Serial Number	Calibration Date	Valid Period
01	Base Station Simulator	CMU200	R&S	118133	2010-05-27	One year
02	Signal Analyzer	FSV	R&S	100815	2010-06-28	One year
03	Signal generator	SMR27	R&S	100365	2010-07-01	One year
04	EMI Test Receiver	ESCI	R&S	100948	2010-07-01	One year
05	Trilog Antenna	VULB 9163	SCHWARZB ECK	9163-391	2009-05-14	Two years
06	Horn Antenna	HF907	R&S	100126	2009-07-02	Two years
07	LISN	3816/2	EMCO	00084033	2009-12-04	Two years
08	AC Power Source	AFC-11005G	APC	F309040118	2009-08-03	Three years
09	Semi-Anechoic Chamber	9.6*6.7*6.6m	ETS-Lindgren	NA	NA	NA
10	Shielding room	5*4*4m	ETS-Lindgren	NA	NA	NA
11	EMI test software	ES-K1	R&S	NA	NA	NA

*****END OF REPORT BODY*****

ANNEX A: The EUT Appearance and Test Setup

A.1 EUT Appearance



Picture 1 EUT

A.2 Test Setup



Picture 1 Radiated Emission Test Setup



Picture 2 Conducted Emission Test Setup