

Testing Tomorrow's Technology

April 22, 2024

Copeland Cold Chain LF	Model(s): PSASII-04	FCC ID: WPEPSASII-04
------------------------	---------------------	----------------------

is seeking FCC Authorization as a 🔲 <b>Single Modular transmitter / 🖂 Single Limited Modular Approval</b> (Please o	check one)
The EUT meets the requirements for $\square$ <b>Single Modular approval / <math>\boxtimes</math> Single Limited Modular Approval</b> (please o	check one)
as detailed in KDB 996369. Compliance to each of the requirements is described below:	

Item	Modular requirement	Yes	No	Please provide a detailed explanation if the answer is "No."
1	Have its own RF shielding		x	The radio has been tested and shown to meet the applicable emissions requirements without having a shield in place however installation of the module within the host device must be followed to protect the module from unwanted interferences. Please see the user manual and integration manual for installation details. The manufacturers instructions must be followed.
2	Have buffered modulation/data inputs (if such inputs are provided)	х		
3	The modular transmitter must have its own power supply regulation.		x	The radio module shall be installed in host products that will supply regulated voltage to the radio module. Valid hosts are CloudGate.
4	Meet the antenna requirements of section 15.203	х		
5	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing.	х		
6	Be labeled with its own FCC ID number, and if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	х		
7	The modular transmitter is manufactured so that the user can not influence the operation of the transmitter that will operate outside of the scope of the regulations.	х		
8	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093.	х		

## Note:

- (1) LMA may be granted when one or more of the requirements in the table above cannot be demonstrated.
  - LMA will also be issued in those instances where applicants can demonstrate that they will retain control over the final installation of the device, such that compliance of the end product is assured. In such cases, an operating condition on the LMA for the module must state that the module is only approved for use when installed in devices produced by a specific manufacturer.
  - When LMA is sought, the application for equipment certification must specifically state how control of the end product into which the module will be maintained, such that full compliance of the end product is always ensured.
- (2) Please provide Clear and specific instructions describing the conditions, limitations and procedures for third-parties to use and/or integrate the module into a host device.
- (3) For non-Software Defined Radio transmitter modules where software is used to ensure compliance of the device, technical description of how such control is implemented to ensure prevention of third party modification must be provided (see KDB 594280).

**Note 1:** Compliance of a module in its final configuration is the responsibility of the applicant. A host device will not be considered certified if the instructions regarding antenna configuration provided in the original description, of one or more separately certified modules it contains, were not followed. **Example:** A separately certified low-power transceiver module using Bluetooth technology which is housed in a desktop computer, laptop or peripheral does not require the overall system to be recertified, if the desktop computer, laptop or peripheral, as a stand-alone unit, complies with all applicable technical standards.

George Yang

Agent, Copeland Cold Chain LP Laboratory Manager, US Tech

770-740-0717

Gyang@ustech-lab.com