

* RF Exposure

1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissible Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1.0	30

f=frequency in MHz, *=*plane-wave equivalent power density*

MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

3. Calculation Result of RF Exposure

Mode	Target power [dBm]	Tune up tolerance [dB]	Max tune up power [dBm]	Max tune up power [mW]	Ant Gain [dBi]	Ant Gain [mW]	Power Density at 20 cm [mW/cm ²]	Limit [mW/cm ²]
WiFi 2.4 GHz_802.11b_Lowest	23.00	±2.0	25.00	316.23	6.66	4.63	0.291 56	1.000 00
WiFi 5.0 GHz_UNII 3 802.11n HT20_Highest	25.00	±2.0	27.00	501.19	6.73	4.71	0.469 60	1.000 00

4. Target power and tolerance, Max tuneup power

- WiFi 2.4 GHz

Mode	Target power [dBm]	Tolerance [dB]	Max tuneup power [dBm]	Average Power [dBm]
802.11b_Lowest	23.00	±2.0	25.00	24.80
802.11b_Middle	23.00	±2.0	25.00	24.67
802.11b_Highest	23.00	±2.0	25.00	24.32
802.11g_Lowest	15.00	±2.0	17.00	16.81
802.11g_Middle	15.00	±2.0	17.00	16.68
802.11g_Highest	15.00	±2.0	17.00	16.62
802.11n HT20_Lowest	16.00	±2.0	18.00	17.27
802.11n HT20_Middle	16.00	±2.0	18.00	17.17
802.11n HT20_Highest	16.00	±2.0	18.00	16.86
802.11n HT40_Lowest	13.00	±2.0	15.00	14.15
802.11n HT40_Middle	13.00	±2.0	15.00	14.30
802.11n HT40_Highest	13.00	±2.0	15.00	14.12

- WiFi 5.0 GHz

UNII 1

Mode	Target power [dBm]	Tolerance [dB]	Max tune up power [dBm]	Average Power [dBm]
802.11a_Lowest	11.00	±2.0	13.00	12.96
802.11a_Middle	20.00	±2.0	22.00	21.91
802.11a_Highest	20.00	±2.0	22.00	21.81
802.11n HT20 Lowest	12.00	±2.0	14.00	14.11
802.11n HT20 _Middle	21.00	±2.0	23.00	22.23
802.11n HT20 Highest	21.00	±2.0	23.00	21.73
802.11n HT40 Lowest	15.00	±2.0	17.00	16.85
802.11n HT40 _Highest	23.00	±2.0	25.00	24.77
802.11ac VHT20 Lowest	13.00	±2.0	15.00	14.17
802.11ac VHT20 _Middle	20.00	±2.0	22.00	21.23
802.11ac VHT20 Highest	20.00	±2.0	22.00	21.09
802.11ac VHT40 _Lowest	15.00	±2.0	17.00	17.05
802.11ac VHT40 Highest	25.00	±2.0	27.00	25.26
802.11ac VHT80 _Lowest	12.00	±2.0	14.00	13.77

UNII 3

Mode	Target power [dBm]	Tolerance [dB]	Max tune up power [dBm]	Average Power [dBm]
802.11a_Lowest	25.00	±2.0	27.00	26.30
802.11a_Middle	25.00	±2.0	27.00	26.55
802.11a_Highest	25.00	±2.0	27.00	26.47
802.11n HT20 Lowest	24.00	±2.0	26.00	25.95
802.11n HT20 Middle	25.00	±2.0	27.00	26.86
802.11n HT20 Highest	25.00	±2.0	27.00	26.90
802.11n HT40 Lowest	25.00	±2.0	27.00	26.67
802.11n HT40 Highest	25.00	±2.0	27.00	26.73
802.11ac VHT20 Lowest	25.00	±2.0	27.00	25.80
802.11ac VHT20 Middle	25.00	±2.0	27.00	26.27
802.11ac VHT20 Highest	25.00	±2.0	27.00	26.50
802.11ac VHT40 Lowest	25.00	±2.0	27.00	25.58
802.11ac VHT40 Highest	25.00	±2.0	27.00	26.31
802.11ac VHT80 Highest	19.00	±2.0	21.00	20.42