



Engineering and Testing for EMC and Safety Compliance



Accredited under A2LA Testing Certificate # 2653.01

**Certification Application Report for Full Modular Approval  
FCC Part 15.247**

<b>Test Lab:</b>  Rhein Tech Laboratories, Inc.      Tel: 703-689-0368 360 Herndon Parkway      Fax: 703-689-2056 Suite 1400      www.rheintech.com Herndon, VA 20170 E-Mail: atcbinfo@rheintech.com		<b>Applicant:</b>  Capacitec, Inc.      Tel: 978-772-6033 87 Fitchburg Rd      Fax: 978-772-6036 Ayer, MA 01432 U.S.A. Contact: Robert Foster	
<b>FCC ID:</b>	WQV-PC1000RF	<b>Test Report Date:</b>	October 24, 2008
<b>Platform:</b>	N/A	<b>RTL Work Order #:</b>	2008138
<b>Model:</b>	PC1000RF	<b>RTL Quote #:</b>	QRTL08-286
<b>American National Standard Institute:</b>	ANSI C63.4-2003: Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz		
<b>FCC Classification:</b>	DTS – Part 15 Digital Transmission System		
<b>FCC Rule Part(s)/Guidance:</b>	FCC Rules Part 15.247: Operation within the bands 920-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz Direct Sequence System October 1, 2007, DA 00-705		
<b>Digital Interface Information</b>	Digital Interface was found to be compliant		
<b>Frequency Range (MHz)</b>	<b>Output Power (W)*</b>	<b>Frequency Tolerance</b>	<b>Emission Designator</b>
2405 – 2480	0.0003	N/A	1M62FXD

*\* power is peak conducted*

I, the undersigned, hereby declare that the equipment tested and referenced in this report conforms to the identified standard(s) as described in this test report. No modifications were made to the equipment during testing in order to achieve compliance with these standards. Furthermore, there was no deviation from, additions to, or exclusions from, the applicable parts of FCC Part 2, FCC Part 15 and ANSI C63.4.

Signature: 

Date: October 24, 2008

Typed/Printed Name: Desmond A. Fraser

Position: President

*This report may not be reproduced, except in full, without the written approval of Rhein Tech Laboratories, Inc. and Capacitec, Inc. The test results relate only to the item(s) tested.*

## Table of Contents

1	General Information .....	5
1.1	Scope .....	5
1.2	Description of EUT .....	5
1.3	Test Facility .....	5
1.4	Related Submittal(s)/Grant(s) .....	5
1.5	Modifications .....	5
2	Test Information .....	6
2.1	Description of Test Modes .....	6
2.2	Exercising the EUT .....	6
2.3	Test Result Summary.....	6
2.4	Test System Details .....	7
2.5	Configuration of Tested System.....	8
3	Peak Output Power - 15.247(b)(3).....	9
3.1	Power Output Test Procedure.....	9
3.2	Power Output Test Data.....	9
4	Compliance with the Band Edge – FCC 15.247(d).....	10
4.1	Band Edge Test Procedure.....	10
4.2	Band Edge Test Results .....	11
4.2.1	Calculation of Lower Band Edge for module.....	11
4.2.2	Lower Band Edge Plot .....	11
4.2.3	Calculation of Upper Band Edge for module.....	12
4.2.4	Upper Band Edge Plot .....	12
4.2.5	Calculation of Lower Band Edge for black round unit.....	13
4.2.6	Calculation of Upper Band Edge for black round unit.....	13
5	Antenna Conducted Spurious Emissions - 15.247(d).....	14
5.1	Antenna Conducted Spurious Emissions Test Procedures .....	14
5.2	Antenna Conducted Spurious Emissions Test Results.....	14
6	6 dB Bandwidth - 15.247(a)(2).....	15
6.1	6 dB Bandwidth Test Procedure – Minimum 6 dB Bandwidth .....	15
6.2	6 dB Bandwidth Test Results .....	15
7	Power Spectral Density - 15.247(e).....	19
7.1	Power Spectral Density Test Procedure .....	19
7.2	Power Spectral Density Test Data .....	19
8	Conducted Emissions Measurement Limits – FCC 15.207 .....	23
8.1	Limits of Conducted Emissions Measurement.....	23
8.2	Site and Test Description .....	23
8.3	Conducted Emissions Test Data.....	24
9	Radiated Emissions - 15.209.....	26
9.1	Limits of Radiated Emissions Measurement.....	26
9.2	Radiated Emissions Measurement Test Procedure.....	26
9.3	Radiated Emissions Test Results .....	28
9.3.1	Radiated Emissions Harmonics/Spurious Test Data .....	28
10	Conclusion .....	31

## Figure Index

Figure 2-1:	Configuration of System under Test.....	8
-------------	---	---

## Table Index

Table 2-1:	Channels Tested .....	6
Table 2-2:	Test Result Summary – FCC Part 15, Subpart C (Section 15.247).....	6
Table 2-3:	Equipment under Test.....	7
Table 3-1:	Power Output Test Equipment .....	9
Table 3-2:	Power Output Test Data.....	9
Table 4-1:	Band Edge Test Equipment .....	10
Table 5-1:	Antenna Conducted Spurious Emissions Test Equipment .....	14
Table 6-1:	6 dB Bandwidth Test Equipment.....	15
Table 6-2:	6 dB Bandwidth Test Data .....	15
Table 7-1:	Power Spectral Density Test Equipment .....	19
Table 7-2:	Power Spectral Density Test Data .....	19
Table 8-1:	Conducted Emissions Test Equipment .....	23
Table 8-2:	Conducted Emissions Test Data – Neutral - TX Mode .....	24
Table 8-3:	Conducted Emissions Test Data – Hot – TX Mode .....	24
Table 8-4:	Conducted Emissions Test Data – Neutral - RX Mode.....	25
Table 8-5:	Conducted Emissions Test Data – Hot – RX Mode .....	25
Table 9-1:	Radiated Emissions Test Equipment .....	27
Table 9-2:	Radiated Emissions Harmonics/Spurious - 2405 MHz - PCB Antenna .....	28
Table 9-3:	Radiated Emissions Harmonics/Spurious - 2440 MHz – PCB Antenna .....	28
Table 9-4:	Radiated Emissions Harmonics/Spurious - 2480 MHz – PCB Antenna .....	29
Table 9-5:	Radiated Emissions Harmonics/Spurious - 2405 MHz - Wire Antenna .....	29
Table 9-6:	Radiated Emissions Harmonics/Spurious - 2440 MHz – Wire Antenna .....	30
Table 9-7:	Radiated Emissions Harmonics/Spurious - 2480 MHz – Wire Antenna .....	30

## Plot Index

Plot 4-1:	Lower Band Edge.....	11
Plot 4-2:	Upper Band Edge.....	12
Plot 6-1:	6 dB Bandwidth – 2405 MHz.....	16
Plot 6-2:	6 dB Bandwidth – 2440 MHz.....	17
Plot 6-3:	6 dB Bandwidth – 2480 MHz.....	18
Plot 7-1:	Power Spectral Density – 2405 MHz .....	20
Plot 7-2:	Power Spectral Density – 2440 MHz .....	21
Plot 7-3:	Power Spectral Density – 2480 MHz .....	22

---

## Appendix Index

---

Appendix A:	FCC Part 1.1307, 1.1310, 2.1091, 2.1093: RF Exposure .....	32
Appendix B:	ATCB Agency Authorization Letter .....	33
Appendix C:	FCC Confidentiality Request Letter.....	34
Appendix D:	FCC Modular Approval – DA 00-1407 .....	35
Appendix E:	Label and Label Location .....	36
Appendix F:	Technical Operational Description .....	37
Appendix G:	Schematics.....	38
Appendix H:	Block Diagram .....	39
Appendix I:	Manual.....	40
Appendix J:	Test Photographs .....	41
Appendix K:	External Photographs.....	45

---

## Photograph Index

---

Photograph 1:	ID Label & Location .....	36
Photograph 2:	Radiated Emissions Testing – Front View .....	41
Photograph 3:	Radiated Emissions Testing – Back View.....	42
Photograph 4:	Conducted Emissions Testing – Front View .....	43
Photograph 5:	Conducted Emissions Testing – Back View.....	44
Photograph 6:	Radio Module Top, PCB Antenna .....	45
Photograph 7:	Bottom of PCB.....	46
Photograph 8:	Radio Module Top, Wire Antenna .....	47
Photograph 9:	Wire Antenna.....	48

## 1 General Information

### 1.1 Scope

This is an original certification application request.

Applicable Standards:

- FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz.

### 1.2 Description of EUT

<b>Equipment Under Test</b>	Transceiver
<b>Model</b>	PC1000RF
<b>Power Supply</b>	+3 – 6 V DC
<b>Modulation Type</b>	DSSS
<b>Frequency Range</b>	2405 – 2480 MHz
<b>Antenna Types</b>	PCB Antenna (0 dBi printed line antenna) Wire Antenna (-15 dBi wire monopole)

### 1.3 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at 360 Herndon Parkway, Suite 1400, Herndon, Virginia 20170. This site has been fully described in a report and approved by the Federal Communications Commission to perform AC line conducted and radiated emissions testing (ANSI C63.4-2003).

### 1.4 Related Submittal(s)/Grant(s)

This is an original application for **full modular approval** for Capacitec, Inc., Model PC1000RF, FCC ID: WQV-PC1000RF. Two antennas were tested and are to be included with this approval.

### 1.5 Modifications

No modifications were made to the equipment during testing in order to achieve compliance with these standards.

## 2 Test Information

### 2.1 Description of Test Modes

In accordance with FCC 15.31(m), and because the EUT utilizes an operating band greater than 10 MHz, the following frequencies were tested:

**Table 2-1: Channels Tested**

Channel	Frequency
Low	2405
Middle	2440
High	2480

### 2.2 Exercising the EUT

The EUT was supplied with test firmware programmed with a high, mid, and low channel for testing. The EUT was tested in all three orthogonal planes in order to determine worst-case emissions. The EUT was provided with software to continuously transmit during testing. The carrier was also checked to verify that information was being transmitted. There were no deviations from the test standard(s) and/or methods. The test results reported relate only to the item tested.

### 2.3 Test Result Summary

**Table 2-2: Test Result Summary – FCC Part 15, Subpart C (Section 15.247)**

Standard	Test	Pass/Fail or N/A
FCC 15.207	AC Power Conducted Emissions	Pass
FCC 15.209	Radiated Emissions	Pass
FCC 15.247(a)(2)	6 dB Bandwidth	Pass
FCC 15.247(b)	Maximum Peak Power Output	Pass
FCC 15.247(d)	Antenna Conducted Spurious Emissions	Pass
FCC 15.247(e)	Power Spectral Density	Pass
FCC 15.247(d)	Band Edge Measurement	Pass


## 2.4 Test System Details

The test samples were received on September 7, 2008. The FCC identifiers for all applicable equipment, plus descriptions of all cables used in the tested system, are identified in the following table.

**Table 2-3: Equipment under Test**

Part	Manufacturer	Model	Serial Number	FCC ID	Cable Description	RTL Bar Code
Modular Transceiver	Capacitec, Inc.	N/A	N/A	WQV-PC1000RF	2 – 20cm unshielded ribbon cable I/O and power	18619
Module I/O PCB	Capacitec, Inc.	CTL2500	N/A	N/A	70cm unshielded power; 1.7m shielded serial/USB converter	18611

## 2.5 Configuration of Tested System



**Figure 2-1: Configuration of System under Test**



### 3 Peak Output Power - 15.247(b)(3)

#### 3.1 Power Output Test Procedure

A conducted power measurement of the EUT was taken.

**Table 3-1: Power Output Test Equipment**

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901413	Agilent Technologies	E4448A	Spectrum Analyzer (3 Hz – 50 GHz)	US440203416	7/31/09


#### 3.2 Power Output Test Data

**Table 3-2: Power Output Test Data**

Channel	Frequency (MHz)	Peak Power Conducted Output (dBm)
Low	2405	-5.6
Middle	2440	-5.6
High	2480	-5.5

#### Test Personnel:

Daniel W. Baltzell  
Test Engineer



Signature

September 22, 2008  
Date of Test

#### 4 Compliance with the Band Edge – FCC 15.247(d)

##### 4.1 Band Edge Test Procedure

The transmitter output was connected to its appropriate antenna. A conducted antenna port delta measurement was performed from the highest peak in the restricted band to the peak of the fundamental, and subtracted from the radiated field strength; the result was compared to the limit.

**Table 4-1: Band Edge Test Equipment**

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901413	Agilent Technologies	E4448A	Spectrum Analyzer	US44020346	7/31/09
900878	Rhein Tech Laboratories	AM3-1197-0005	3 meter Antenna Mast, polarizing	Outdoor Range 1	Not Required
901425	Insulated Wire, Inc.	KPS-1503-2400-KPS	RF cable, 20'	NA	10/5/09
901424	Insulated Wire Inc.	KPS-1503-360-KPS	RF cable 36"	NA	10/5/09
901242	Rhein Tech Laboratories	WRT-000-0003	Wood Rotating Table	N/A	Not Required
900772	EMCO	3161-02	Horn Antenna 2 - 4 GHz	9804-1044	6/14/10

## 4.2 Band Edge Test Results

### 4.2.1 Calculation of Lower Band Edge for Module

88.3 dBuV/m is the field strength measurement, from which the delta measurement of 58.1 dB is subtracted, resulting in a level of 30.2 dB. This level has a margin of 23.8 dB below the limit of 54 dBuV/m.

Calculation:  $88.3 \text{ dBuV/m} - 58.1 \text{ dB} - 54 \text{ dBuV/m} = -23.8 \text{ dB}$


Peak Field Strength of Lower Band Edge (1 MHz RBW/8 MHz VBW) = 88.3 dBuV/m

Average Field Strength of Lower Band Edge (1 MHz RBW/10 Hz VBW) = 85.8 dBuV/m

Delta measurement = 58.1 dB

### 4.2.2 Lower Band Edge Plot

Plot 4-1: Lower Band Edge



#### 4.2.3 Calculation of Upper Band Edge for Module

89.1 dBuV/m is the field strength measurement, from which the delta measurement of 39.9 dB is subtracted, resulting in a level of 49.2 dB. This level has a margin of 4.8 dB below the limit of 54 dBuV/m.

Calculation:  $89.1 \text{ dBuV/m} - 39.9 \text{ dB} - 54 \text{ dBuV/m} = -4.8 \text{ dB}$


Peak Field Strength of Lower Band Edge (1 MHz RBW/8 MHz VBW) = 89.1 dBuV/m

Average Field Strength of Lower Band Edge (1 MHz RBW/10 Hz VBW) = 87 dBuV/m

Delta measurement = 39.9 dB

#### 4.2.4 Upper Band Edge Plot

Plot 4-2: Upper Band Edge



#### 4.2.5 Calculation of Lower Band Edge for Wire Antenna

76.1 dBuV/m is the field strength measurement, from which the delta measurement of 58.1 dB is subtracted, resulting in a level of 18 dB. This level has a margin of 36 dB below the limit of 54 dBuV/m.

Calculation:  $76.1 \text{ dBuV/m} - 58.1 \text{ dB} - 54 \text{ dBuV/m} = -36 \text{ dB}$

Peak Field Strength of Lower Band Edge (1 MHz RBW/8 MHz VBW) = 76.1 dBuV/m

Average Field Strength of Lower Band Edge (1 MHz RBW/10 Hz VBW) = 72.5 dBuV/m

Delta measurement = 58.1 dB

#### 4.2.6 Calculation of Upper Band Edge for Wire Antenna

75.4 dBuV/m is the field strength measurement, from which the delta measurement of 39.9 dB is subtracted, resulting in a level of 35.5 dB. This level has a margin of 18.5 dB below the limit of 54 dBuV/m.


Calculation:  $75.4 \text{ dBuV/m} - 39.9 \text{ dB} - 54 \text{ dBuV/m} = -18.5 \text{ dB}$

Peak Field Strength of Lower Band Edge (1 MHz RBW/8 MHz VBW) = 75.4 dBuV/m

Average Field Strength of Lower Band Edge (1 MHz RBW/10 Hz VBW) = 73.2 dBuV/m

#### Test Personnel:

Daniel W. Baltzell  
Test Engineer



Signature

September 22, 2008  
Date of Tests

## 5 Antenna Conducted Spurious Emissions - 15.247(d)

### 5.1 Antenna Conducted Spurious Emissions Test Procedures

Antenna spurious emissions per FCC 15.247(c) were measured from the EUT antenna port using a 50 ohm spectrum analyzer with the resolution bandwidth set at 100 kHz, and the video bandwidth set at 1 MHz. The modulated carrier was identified at the following frequencies: 2405 MHz, 2440 MHz and 2480 MHz.

Other than the data presented below, no harmonics or spurs were found within 20 dB (note that we are reporting power as peak) of the limit from the carrier to the 10<sup>th</sup> harmonic of the carrier frequency. Per FCC 15.31(o), no other data is being reported.

**Table 5-1: Antenna Conducted Spurious Emissions Test Equipment**

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901413	Agilent Technologies	E4448A	Spectrum Analyzer	US44020346	7/31/09

### 5.2 Antenna Conducted Spurious Emissions Test Results

All emissions were more than 20 dB below the limit; per 15.31(o) no data is being reported.

#### Test Personnel:

Daniel W. Baltzell  
Test Engineer



Signature

September 22, 2008  
Date of Test

## 6 6 dB Bandwidth - 15.247(a)(2)

### 6.1 6 dB Bandwidth Test Procedure – Minimum 6 dB Bandwidth

The minimum 6 dB bandwidths per FCC 15.247(a)(2) were measured using a 50 ohm spectrum analyzer with the resolution bandwidth set at 100 kHz, and the video bandwidth set at 300 Hz. The device was modulated. The minimum 6 dB bandwidths are presented below.

**Table 6-1: 6 dB Bandwidth Test Equipment**


RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901413	Agilent Technologies	E4448A	Spectrum Analyzer (3 Hz – 50 GHz)	US440203416	7/31/09

### 6.2 6 dB Bandwidth Test Results

**Table 6-2: 6 dB Bandwidth Test Data**


Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass/Fail
2405	1.59	0.5	Pass
2440	1.62	0.5	Pass
2480	1.59	0.5	Pass

**Plot 6-1: 6 dB Bandwidth – 2405 MHz**






**Plot 6-2: 6 dB Bandwidth – 2440 MHz**



**Plot 6-3: 6 dB Bandwidth – 2480 MHz**



**Test Personnel:**

Daniel W. Baltzell  
 Test Engineer

*Daniel W. Baltzell*

Signature

October 20, 2008  
 Date of Tests

## 7 Power Spectral Density - 15.247(e)

### 7.1 Power Spectral Density Test Procedure

The power spectral density per FCC 15.247(d) was measured using a 50 ohm spectrum analyzer with the resolution bandwidth set at 3 kHz, the video bandwidth set at 30 kHz, and the sweep time set at 100 seconds. The spectral lines were resolved for the modulated carriers at 2405, 2440 and 2480 MHz. These levels are below the +8 dBm limit. See the power spectral density table and plots.

**Table 7-1: Power Spectral Density Test Equipment**


RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901413	Agilent Technologies	E4448A	Spectrum Analyzer (3 Hz – 50 GHz)	US440203416	7/31/09

### 7.2 Power Spectral Density Test Data


**Table 7-2: Power Spectral Density Test Data**

Frequency (MHz)	RF Power Level (dBm)	Maximum Limit +8dBm	Pass/Fail
2405	-17.0	8	Pass
2440	-18.2	8	Pass
2480	-16.8	8	Pass


Plot 7-1: Power Spectral Density – 2405 MHz



**Plot 7-2: Power Spectral Density – 2440 MHz**



**Plot 7-3: Power Spectral Density – 2480 MHz**



**Test Personnel:**

Daniel W. Baltzell  
 Test Engineer

*Daniel W. Baltzell*

Signature

September 22, 2008  
 Date of Tests

## 8 Conducted Emissions Measurement Limits – FCC 15.207

### 8.1 Limits of Conducted Emissions Measurement

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

### 8.2 Site and Test Description

The power line conducted emissions measurements were performed in a Series 81 type shielded enclosure manufactured by Rayproof. The EUT was assembled on a wooden table 80 centimeters high. Power was fed to the EUT through a 50 ohm/50 microhenry Line Impedance Stabilization Network (LISN). The EUT LISN was fed power through an A.C. filter box on the outside of the shielded enclosure. The filter box and EUT LISN housing are bonded to the ground plane of the shielded enclosure. A second LISN, the peripheral LISN, provides isolation for the EUT test peripherals. This peripheral LISN was also fed A.C. power. A metal power outlet box, which is bonded to the ground plane and electrically connected to the peripheral LISN, powers the EUT host peripherals.

The spectrum analyzer was connected to the A.C. line through an isolation transformer. The 50 ohm output of the EUT LISN was connected to the spectrum analyzer input through a Solar 100 kHz high-pass filter. The filter is used to prevent overload of the spectrum analyzer from noise below 100 kHz. Conducted emission levels were measured on each current-carrying line with the spectrum analyzer operating in the CISPR quasi-peak mode (or peak mode if applicable).

The analyzer's 6 dB bandwidth was set to 9 kHz. Video filter less than 10 times the resolution bandwidth is not used. Average measurements are performed in linear mode using a 10 kHz resolution bandwidth, a 1 Hz video bandwidth, and by increasing the sweep time in order to obtain a calibrated measurement. The emission spectrum was scanned from 150 kHz to 30 MHz. The highest emission amplitudes relative to the appropriate limits were measured and have been recorded.

**Table 8-1: Conducted Emissions Test Equipment**

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
900896	Hewlett Packard	85662A	Display Section	2816A16471	4/2/09
900897	Hewlett Packard	8567A	HP Spectrum Analyzer (10 KHz - 1.5GHz)	2727A00535	4/2/09
900901	Hewlett Packard	85650A	Quasi-Peak Adapter (30 Hz - 1 GHz)	3145A01599	4/2/09
901082	AFJ International	LS16	16A LISN	16010020081	4/2/09

### 8.3 Conducted Emissions Test Data

**Table 8-2: Conducted Emissions Test Data – Neutral - TX Mode**

Temperature: 74°F Humidity: 26%									
Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	FCC 15.207 QP Limit (dBuV)	FCC 15.207 QP Margin (dBuV)	FCC 15.207 AV Limit (dBuV)	FCC 15.207 AV Margin (dBuV)	Pass/Fail
0.170	Pk	50.1	0.2	50.3	65.0	-14.7	55.0	-4.7	Pass
0.269	Pk	40.6	0.2	40.8	61.1	-20.3	51.1	-10.3	Pass
0.377	Pk	32.1	0.3	32.4	58.3	-25.9	48.3	-15.9	Pass
7.400	Pk	23.8	1.9	25.7	60.0	-34.3	50.0	-24.3	Pass
21.240	Pk	27.7	3.2	30.9	60.0	-29.1	50.0	-19.1	Pass
25.690	Pk	29.3	3.3	32.6	60.0	-27.4	50.0	-17.4	Pass

**Table 8-3: Conducted Emissions Test Data – Hot – TX Mode**

Temperature: 74°F Humidity: 26%									
Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	FCC 15.207 QP Limit (dBuV)	FCC 15.207 QP Margin (dBuV)	FCC 15.207 AV Limit (dBuV)	FCC 15.207 AV Margin (dBuV)	Pass/Fail
0.152	Pk	27.6	0.2	27.8	65.9	-38.1	55.9	-28.1	Pass
0.268	Pk	23.0	0.2	23.2	61.2	-38.0	51.2	-28.0	Pass
0.368	Pk	19.0	0.3	19.3	58.5	-39.2	48.5	-29.2	Pass
7.370	Pk	23.8	1.9	25.7	60.0	-34.3	50.0	-24.3	Pass
20.740	Pk	27.9	3.2	31.1	60.0	-28.9	50.0	-18.9	Pass
27.320	Pk	28.0	3.3	31.3	60.0	-28.7	50.0	-18.7	Pass



**Table 8-4: Conducted Emissions Test Data – Neutral - RX Mode**


Temperature: 74°F Humidity: 26%									
Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	FCC 15.207 QP Limit (dBuV)	FCC 15.207 QP Margin (dBuV)	FCC 15.207 AV Limit (dBuV)	FCC 15.207 AV Margin (dBuV)	Pass/Fail
0.152	Pk	50.3	0.2	50.5	65.9	-15.4	55.9	-5.4	Pass
0.248	Pk	42.0	0.2	42.2	61.8	-19.6	51.8	-9.6	Pass
0.352	Pk	34.3	0.3	34.6	58.9	-24.3	48.9	-14.3	Pass
7.370	Pk	25.0	1.9	26.9	60.0	-33.1	50.0	-23.1	Pass
21.390	Pk	27.9	3.2	31.1	60.0	-28.9	50.0	-18.9	Pass
28.110	Pk	29.8	3.3	33.1	60.0	-26.9	50.0	-16.9	Pass

**Table 8-5: Conducted Emissions Test Data – Hot – RX Mode**

Temperature: 74°F Humidity: 26%									
Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	FCC 15.207 QP Limit (dBuV)	FCC 15.207 QP Margin (dBuV)	FCC 15.207 AV Limit (dBuV)	FCC 15.207 AV Margin (dBuV)	Pass/Fail
0.153	Pk	29.3	0.2	29.5	65.8	-36.3	55.8	-26.3	Pass
0.269	Pk	23.8	0.2	24.0	61.1	-37.1	51.1	-27.1	Pass
0.365	Pk	22.5	0.3	22.8	58.6	-35.8	48.6	-25.8	Pass
7.370	Pk	26.8	1.9	28.7	60.0	-31.3	50.0	-21.3	Pass
21.240	Pk	26.8	3.2	30.0	60.0	-30.0	50.0	-20.0	Pass
24.070	Pk	30.3	3.3	33.6	60.0	-26.4	50.0	-16.4	Pass

**Test Personnel:**

Daniel W. Baltzell  
Test Engineer



Signature

October 22, 2008  
Date of Test

## 9 Radiated Emissions - 15.209

### 9.1 Limits of Radiated Emissions Measurement

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009-0.490	2400/f (kHz)	300
0.490-1.705	2400/f (kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any circumstances of modulation.

### 9.2 Radiated Emissions Measurement Test Procedure

Before final measurements of radiated emissions were made on the open-field three/ten meter range, the EUT was scanned indoors at one and three meter distances. This was done in order to determine its emissions spectrum signature. The physical arrangement of the test system and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. This process was repeated during final radiated emissions measurements on the open-field range, at each frequency, in order to ensure that maximum emission amplitudes were attained.

Final radiated emissions measurements were made on the three/ten-meter, open-field test site. The EUT was placed on a nonconductive turntable 0.8 meters above the ground plane. The spectrum was examined from 9 kHz to the 10<sup>th</sup> harmonic of the highest fundamental transmitter frequency (24.8 GHz).

At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the emission's maximum level. Measurements were taken using both horizontal and vertical antenna polarizations. For frequencies between 30 and 1000 MHz, the spectrum analyzer's 6 dB bandwidth was set to 120 kHz, and the analyzer was operated in the CISPR quasi-peak detection mode. For emissions above 1000 MHz, emissions are measured using the average detector function with a minimum resolution bandwidth of 1 MHz. No video filter less than 10 times the resolution bandwidth was used. The highest emission amplitudes relative to the appropriate limit were measured and recorded in this report.

**Table 9-1: Radiated Emissions Test Equipment**

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
900151	Rohde and Schwarz	HFH2-Z2	Loop Antenna (9 kHz - 30 MHz)	827525/019	9/15/09
901365	MITEQ	JS4-00102600-41-5P	Amplifier, 0.1-26 GHz, 30dB gain	N/A	10/8/09
901281	Rhein Tech Laboratories	PR-1040	Amplifier (10 MHz - 2 GHz)	1004	1/19/09
900878	Rhein Tech Laboratories	AM3-1197-0005	3 meter antenna mast, polarizing	Outdoor Range 1	Not Required
901425	Insulated Wire, Inc.	KPS-1503-2400-KPS	RF cable, 20'	NA	10/5/09
901424	Insulated Wire Inc.	KPS-1503-360-KPS	RF cable 36"	NA	10/5/09
901242	Rhein Tech Laboratories	WRT-000-0003	Wood rotating table	N/A	Not Required
900913	Hewlett Packard	85462A	EMI Receiver RF Section (9 kHz – 6.5 GHz)	3325A00159	4/15/09
901413	Agilent Technologies	E4448A	Spectrum Analyzer	US44020346	7/31/09
900772	EMCO	3161-02	Horn Antenna (2 - 4 GHz)	9804-1044	6/14/10
900321	EMCO	3161-03	Horn Antenna (4.0 - 8.2 GHz)	9508-1020	6/14/10
900323	EMCO	3160-07	Horn Antenna (8.2 - 12.4 GHz)	9605-1054	6/14/10
900356	EMCO	3160-08	Horn Antenna (12.4 - 18 GHz)	9607-1044	6/14/10
900325	EMCO	3160-9	Horn Antennas (18 - 26.5 GHz)	9605-1051	6/14/10

### 9.3 Radiated Emissions Test Results

#### 9.3.1 Radiated Emissions Harmonics/Spurious Test Data

**Table 9-2: Radiated Emissions Harmonics/Spurious - 2405 MHz - PCB Antenna**

Fundamental amplitude = 85.8 dBuV/m

Emission Frequency (MHz)	Peak Analyzer Reading (dBuV) (1 MHz RBW/VBW)	Average Analyzer Reading (dBuV) (1 MHz RBW 10 Hz VBW)	Site Correction Factor (dB/m)	Average Emission Level (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4810.0	47.2	37.2	-0.4	36.8	54.0	-17.2
12025.0	36.2	26.1	10.0	36.1	54.0	-17.9
14430.0	33.0	23.3	13.3	36.6	65.8	-29.2
16835.0	35.2	25.7	12.7	38.4	65.8	-27.5
19240.0	31.6	23.0	20.0	43.0	54.0	-11.0
21645.0	32.5	22.8	21.0	43.8	65.8	-22.1

**Table 9-3: Radiated Emissions Harmonics/Spurious - 2440 MHz – PCB Antenna**

Fundamental amplitude = 83.6dBuV/m

Emission Frequency (MHz)	Peak Analyzer Reading (dBuV) (1 MHz RBW/VBW)	Average Analyzer Reading (dBuV) (1 MHz RBW 10 Hz VBW)	Site Correction Factor (dB/m)	Average Emission Level (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4880.0	47.7	38.0	-0.3	37.7	54.0	-16.3
7320.0	35.8	26.2	1.7	27.9	54.0	-26.1
12200.0	31.5	23.3	10.3	33.6	54.0	-20.4
17080.0	36.3	27.4	12.9	40.3	63.6	-23.3
19520.0	31.2	22.7	17.3	40.0	54.0	-14.0
21960.0	32.5	23.0	21.0	44.0	63.6	-19.6

**Table 9-4: Radiated Emissions Harmonics/Spurious - 2480 MHz – PCB Antenna**

Fundamental amplitude = 87.0 dBuV/m

Emission Frequency (MHz)	Peak Analyzer Reading (dBuV) (1 MHz RBW/VBW)	Average Analyzer Reading (dBuV) (1 MHz RBW 10 Hz VBW)	Site Correction Factor (dB/m)	Average Emission Level (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4960.0	45.1	34.2	-0.3	33.9	54.0	-20.1
7440.0	34.7	25.2	2.2	27.4	54.0	-26.6
12400.0	34.6	24.1	13.7	37.8	54.0	-16.2
17360.0	38.1	27.1	12.6	39.7	67.0	-27.3
19840.0	33.8	25.1	0.0	25.1	67.0	-41.9
22320.0	32.2	23.1	21.2	44.3	54.0	-9.7

**Table 9-5: Radiated Emissions Harmonics/Spurious - 2405 MHz - Wire Antenna**

Fundamental amplitude = 72.5 dBuV/m

Emission Frequency (MHz)	Peak Analyzer Reading (dBuV) (1 MHz RBW/VBW)	Average Analyzer Reading (dBuV) (1 MHz RBW 10 Hz VBW)	Site Correction Factor (dB/m)	Average Emission Level (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4810.0	42.6	31.9	-0.4	31.5	54.0	-22.5
12025.0	38.5	25.5	10.0	35.5	54.0	-18.5
14430.0	37.1	25.5	13.3	38.8	65.8	-27.0
16835.0	37.6	25.1	12.7	37.8	65.8	-28.1
19240.0	35.1	23.7	20.0	43.7	54.0	-10.3
21645.0	36.8	23.7	21.0	44.7	65.8	-21.2

**Table 9-6: Radiated Emissions Harmonics/Spurious - 2440 MHz – Wire Antenna**

Fundamental amplitude = 73.6 dBuV/m

Emission Frequency (MHz)	Peak Analyzer Reading (dBuV) (1 MHz RBW/VBW)	Average Analyzer Reading (dBuV) (1 MHz RBW 10 Hz VBW)	Site Correction Factor (dB/m)	Average Emission Level (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4880.0	44.8	34.3	-0.3	34.0	54.0	-20.0
7320.0	39.5	26.4	1.7	28.1	54.0	-25.9
12200.0	36.6	23.6	10.3	33.9	54.0	-20.1
17080.0	37.4	24.7	12.9	37.6	63.6	-26.0
19520.0	39.1	26.4	17.3	43.7	54.0	-10.3
21960.0	35.8	23.3	21.0	44.3	63.6	-19.3


**Table 9-7: Radiated Emissions Harmonics/Spurious - 2480 MHz – Wire Antenna**

Fundamental amplitude = 73.2 dBuV/m

Emission Frequency (MHz)	Peak Analyzer Reading (dBuV) (1 MHz RBW/VBW)	Average Analyzer Reading (dBuV) (1 MHz RBW 10 Hz VBW)	Site Correction Factor (dB/m)	Average Emission Level (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4960.0	44.9	34.6	-0.3	34.3	54.0	-19.7
7440.0	39.8	26.2	2.2	28.4	54.0	-25.6
12400.0	36.5	24	13.7	37.7	54.0	-16.3
14880.0	39.1	24.8	13.0	37.8	67.0	-29.2
17360.0	38.8	26.1	12.6	38.7	67.0	-28.3
22320.0	34.4	20.9	21.2	42.1	54.0	-11.9

**Test Personnel:**

Daniel W. Baltzell  
Test Engineer



Signature

October 11, 2008  
Date of Test

Rhein Tech Laboratories, Inc.  
360 Herndon Parkway  
Suite 1400  
Herndon, VA 20170  
<http://www.rheintech.com>

Client: Capacitec, Inc.  
Model: PC1000RF  
Standard: FCC 15.247  
FCC ID: WQV-PC1000RF  
Report #: 2008138

## **10 Conclusion**

The data in this measurement report shows that the EUT as tested, Capacitec, Inc. Model PC1000RF, FCC ID: WQV-PC1000RF, complies with all the applicable requirements of Parts 2 and 15 of the FCC Rules and Regulations.