



Excellence in Compliance Testing

Certification Exhibit

FCC ID: WYU-HAND001

FCC Rule Part: 15.247

ACS Report Number: 08-0307 - 15C Handheld DTS

Manufacturer: Orderite, Inc.
Model: TR1000

RF Exposure

General Information:

Applicant: Orderite, Inc.

ACS Project: 08-0307

Device Category: Mobile

Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: Chip Antenna

Antenna Gain: 3 dBi max

Maximum Transmitter Conducted Power: 15.32 dBm

Maximum System EIRP: 18.32 dBm, 68 mW

Exposure Conditions: Greater than 20 centimeters

MPE CalculationThe Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment							
Limits for General Population/Uncontrolled Exposure*							
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm^2)
2462	15.32	1.00	34.04	3	1.995	20	0.014

Installation Guidelines

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

RF Exposure

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

Conclusion

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.