

# **COVER LETTER**

### **Request For Transmitter Module Equipment Authorization**

performed in accordance with

FCC Rules: Code of Federal Regulations (CFR) no. 47
Part 15 Subpart C Section 15.212

PRODUCT	RF Module
MODEL(s) TESTED	K-LC1
FCC ID	XFIPORTRADAVER1
TRADE MARK(s)	Schindler

ADDITIONAL	Schindler elevators Ltd - Via della Pace, 22 -
APPLICANT	6600 Locarno (Switzerland)

#### **Revision Sheet**

Release No.	Date	Revision Description	
Rev. 0	2016-02-22	First edition	
Rev. 1	2016-06-17	Second edition: correct the result of requirements	
Rev. 2	2016-11-04	Third edition: correct result of requirement (ii)	



### 1. REFERENCE DOCUMENT

DOCUMENT		DATE	TITLE
	47 CFR Part 15	2014	Radio Frequency Device
$\boxtimes$	Publication Number: 996369	2013	Transmitter Module Equipment Authorization Guide
$\boxtimes$	PUBLIC NOTE DA 00-1407	2000	Part 15 Unlicensed Modular Transmitter Approval

### 2. MODULE-TYPE DEVICE APPROVAL OPTIONS

	Limited split-modular transmitter	split-modular transmitter that complies with the definition and technical rules for split modules only when constrained to specific operating host(s), and/or associated grant condition(s)
	Limited single-modular transmitter	RF transmission system that complies with the requirements for a single-modular transmitter, that is separated into a radio front-end section and a control element section, and can demonstrate compliance for a range of similar type hosts
$\boxtimes$	Limited single-modular transmitter	single-modular transmitter that complies with the Section 15.212(a)(1) modular rules, only when constrained to specific operating host(s) and/or associated grants condition(s)
	Single-modular transmitter	complete RF transmission sub-assembly, designed to be incorporated into another device, that must demonstrate compliance with FCC rules and policies independent of any host

Date: 2016-11-04



## 3. REQUIREMENTS

POSSIBLE TEST CASE VERDICTS		
Test object does meet the requirement	PASS	
Test object does not meet the requirement	FAIL	
Test case does not apply to the test object	N/A	

Requirement		Description	Result
(i)	The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	The radio module elements does not have their own shielding	PASS
(ii)	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.		FAIL
(iii)	The modular transmitter must have its own power supply regulation.	The radio module does not contains an own voltage regulation	FAIL
(iv)	The modular transmitter must comply with the antenna and transmission system requirements of §15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of §15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.	The module complies with the antenna and transmission system requirements of §15.203, 15.204(b) and 15.204(c) The antenna is permanently attached	PASS

Date: 2016-11-04



(v)	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in §15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see §15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see §15.31(i)).	The radio module meet the requirements under the operating conditions in which the transmitter will be use.  The modular transmitter was tested in a stand-alone configuration (the module was not inside another device during testing for compliance with part 15 requirements, DC power lines and data input/output lines connected to the module not contain ferrites, no coupling was present between the case of the module and supporting equipment) Any accessories, peripherals, or support equipment connected to the module during testing were unmodified and commercially available.	PASS
(vi)	The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number.	The radio module is labelled with its own FCC ID number. When the radio module is installed inside the end-product, the label is not visible. The end-user/integrator is instructed how to apply the exterior label.	PASS
(vii)	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.	The radio module is compliant with all applicable specific FCC rules or operating requirements that ordinarily apply to a complete transmitter.  Detailed instruction are provided with the module to explain any such requirements.	PASS
(viii)	The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	The modular transmitter comply with any applicable RF exposure requirements in its final configuration.	PASS

Date: 2016-11-04