

# FCC Radio Test Report

**FCC ID: XHM-059KU87F12**

**Report No.** : BTL-FCCP-1-2311T136B  
**Equipment** : Panel PC  
**Model Name** : K959(F87U)  
**Brand Name** : FLYTECH  
**Applicant** : FLYTECH TECHNOLOGY CO., LTD  
**Address** : No. 168, Sing-ai Rd., Neihu District, Taipei City, Taiwan  
  
**Radio Function** : RFID (13.56 MHz)  
  
**FCC Rule Part(s)** : FCC CFR Title 47, Part 15, Subpart C (15.225)  
**Measurement** : ANSI C63.10-2013  
**Procedure(s)**  
  
**Date of Receipt** : 2024/12/23  
**Date of Test** : 2025/2/5 ~ 2025/2/18  
**Issued Date** : 2025/2/27

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

**Prepared by** : Brett Shen  
Brett Shen, Engineer



**Approved by** : Jerry Chuang  
Jerry Chuang, Supervisor

**BTL Inc.**

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299 Fax: +886-2-2657-3331 Web: [www.newbtl.com](http://www.newbtl.com) Service mail: [btl\\_qa@newbtl.com](mailto:btl_qa@newbtl.com)

**Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL**'s reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** assumes no responsibility for the data provided by the Customer, any statements, inferences or generalizations drawn by the customer or others from the reports issued by **BTL**.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

**BTL**'s laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

**BTL** is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

**Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

**CONTENTS**

REVISION HISTORY	5
1 SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
1.3 TEST ENVIRONMENT CONDITIONS	7
2 GENERAL INFORMATION	8
2.1 DESCRIPTION OF EUT	8
2.2 TEST MODES	9
2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 SUPPORT UNITS	12
3 AC POWER LINE CONDUCTED EMISSIONS TEST	13
3.1 LIMIT	13
3.2 TEST PROCEDURE	13
3.3 DEVIATION FROM TEST STANDARD	14
3.4 TEST SETUP	14
3.5 TEST RESULT	14
4 RADIATED EMISSIONS TEST	15
4.1 LIMIT	15
4.2 TEST PROCEDURE	16
4.3 DEVIATION FROM TEST STANDARD	16
4.4 TEST SETUP	16
4.5 EUT OPERATING CONDITIONS	17
4.6 TEST RESULT – 9 KHZ TO 30 MHZ – FCC PART 15.209	17
4.7 TEST RESULT – 30 MHZ TO 1 GHZ – FCC PART 15.209	17
4.8 TEST RESULT – FCC PART 15.225	17
5 FREQUENCY STABILITY	18
5.1 LIMIT	18
5.2 TEST PROCEDURE	18
5.3 DEVIATION FROM TEST STANDARD	18
5.4 EUT OPERATING CONDITIONS	18
5.5 TEST RESULT	18
6 20 DB BANDWIDTH	19
6.1 LIMIT	19
6.2 TEST PROCEDURE	19
6.3 DEVIATION FROM TEST STANDARD	19
6.4 TEST SETUP	19
6.5 EUT OPERATING CONDITIONS	19
6.6 TEST RESULT	19
7 LIST OF MEASURING EQUIPMENTS	20
8 EUT TEST PHOTO	21
9 EUT PHOTOS	21
APPENDIX A AC POWER LINE CONDUCTED EMISSIONS	22
APPENDIX B RADIATED EMISSIONS - 9 KHZ TO 30 MHZ	27
APPENDIX C RADIATED EMISSIONS - 30 MHZ TO 1 GHZ	32
APPENDIX D RADIATED EMISSIONS - FCC PART 15.225	35
APPENDIX E FREQUENCY STABILITY MEASUREMENT	38



**REVISION HISTORY**

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-1-2311T136	R00	Original Report.	2024/10/18	Valid
BTL-FCCP-1-2311T136B	R00	Changed RFID model from MD-551L+ ANT4424 to MD-551V+ANT4424.	2025/2/27	Valid

## 1 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards.

Standard(s) Section	Description	Test Result	Judgement	Remark
15.207	AC Power Line Conducted Emissions	APPENDIX A	Pass	-----
15.35 15.205 15.209 15.225	Radiated Emissions	APPENDIX B APPENDIX C APPENDIX D	Pass	-----
15.225(e)	Frequency Stability	APPENDIX E	Pass	-----
15.203	Antenna Requirement	-----	Pass	-----
15.215(c)	20 dB Bandwidth	APPENDIX F	Pass	-----

### Statement of Conformity

The statement of conformity is based on the binary decision rule according to IEC Guide 115 and ILAC G8 "simple acceptance" principle. Without considering measurement uncertainty, its specific risk is less than 50% PFA. (PFA: Probability of False Accept)

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report.
- (2) The report format version is TP.1.1.1.

## 1.1 TEST FACILITY

The test locations stated below are under the TAF Accreditation Number 0659.

The test location(s) used to collect the test data in this report are:

No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan  
(FCC DN: TW0659)

C05       CB08       CB11       SR10       SR11  
No. 72, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan  
(FCC DN: TW0659)

C06       CB21       CB22

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k = 2$ , providing a level of confidence of approximately 95 %.

A. AC power line conducted emissions test:

Test Site	Method	Measurement Frequency Range	U (dB)
C05	CISPR	150 kHz ~ 30MHz	3.44

B. Radiated emissions test :

Test Site	Method	Measurement Frequency Range	U (dB)
CB21	CISPR	9 kHz ~ 150 kHz	2.82
CB21	CISPR	150 kHz ~ 30 MHz	2.58

Test Site	Measurement Frequency Range	U (dB)
CB21	0.03 GHz ~ 0.2 GHz	4.17
	0.2 GHz ~ 1 GHz	4.72
	1 GHz ~ 6 GHz	5.21
	6 GHz ~ 18 GHz	5.51
	18 GHz ~ 26 GHz	3.69
	26 GHz ~ 40 GHz	4.23

### NOTE:

Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

## 1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Environment Condition	Test Voltage	Tested by
AC Power Line Conducted Emissions	24 °C, 56 %	AC 120V	Ken Lan
Radiated emissions (9KHz-30MHz)	Refer to data	AC 120V	Mark Wang
Radiated emissions (30MHz TO 1000MHz)	Refer to data	AC 120V	Mark Wang
Frequency Stability	23.2 °C, 61 %	AC 120V	Ken Lan
20 dB Bandwidth	23.2 °C, 61 %	AC 120V	Ken Lan

## 2 GENERAL INFORMATION

### 2.1 DESCRIPTION OF EUT

Equipment	Panel PC
Model Name	K959(F87U)
Brand Name	FLYTECH
Model Difference	N/A
Power Source	DC voltage supplied from AC/DC Adapter.
Power Rating	<p>For Adapter:</p> <p>(1) A17-120P1A: I/P: 100-240V~, 1.8A, 50-60Hz / O/P: 19V---6.32A (2) ADP-120RH BB: I/P: 100-240V~, 2.0A, 50-60Hz / O/P: 19V---6.32A (3) GSM120A20: I/P: 100-240V~, 1.4-0.7A, 50-60Hz / O/P: 20V---6A (4) ADP-120VH D: I/P: 100-240V~, 2.5A, 50-60Hz / O/P: 20V---6A</p> <p>For Battery:</p> <p>(1) DR-202-35E: DC 10.8V, 10050mAh 108.5Wh (2) DR-202W2: DC 10.8V, 7500mAh 81Wh (3) DR-202-GA: DC 10.8V, 10350mAh 111.78Wh</p>
Products Covered	<p>1 * Mother Board: F87U 1 * CPU: INTEL / i7-1185G7E 2.8G 1 * Main Display: 21.5" 1 * RFID (Front): Sunion / MD-551V+ANT4424 1 * Wlan card: Intel / AX210NGW 1 * HDD/SSD: M.2 SSD 3 * Battery: (1) DR-202-35E (2) DR-202-GA (3) DR-202W2</p> <p>4 * Adapter: (1) Delta / ADP-120RH BB (2) Delta / ADP-120VH D (3) Chicony / A17-120P1A (4) MEAN WELL / GSM120A20</p>
Operation Frequency	13.56 MHz
Max H-field strength	49.08 dBuV/m@1m(Peak)
Test Model	K959(F87U)
Sample Status	Engineering Sample
EUT Modification(s)	N/A

#### NOTE:

(1) The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

(2) Channel List:

Channel	Frequency (MHz)
01	13.56

(3) Table for Filed Antenna:

Antenna	Brand Name	Part No.	Antenna Type	Connector	Gain (dBi)
1	Sunion	ANT-4424-FY-IPX70V1.00B	PCB	I-PEX	NA

(4) The above Antenna information are derived from the antenna data sheet provided by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

(5) This is a supplement report of BTL-FCCP-1-2311T136 report. The differences compared with original report is changed RFID model from MD-551L+ ANT4424 to MD-551V+ANT4424.  
After evaluated, the changes with respect to the original one, all tests need to re-test.

## 2.2 TEST MODES


Test Items	Test mode	Channel	Note
AC power line conducted emissions	Normal/Idle	-	-
Radiated emissions (9KHz-30MHz)	TX	01	-
Radiated emissions (30MHz TO 1000MHz)	TX	01	
Frequency Stability	TX	01	-
20 dB Bandwidth	TX	01	-

**NOTE:**


- (1) The Radiated emissions test was verified based on the worst conducted power and Bandwidth test results reported in the original report.
- (2) All adapter are evaluated, the adapter(GSM120A20) is the worst and recorded as below test data.
- (3) All battery are evaluated, the battery(DR-202-35E) is the worst and recorded as below test data.

### 2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Equipment letters and Cable numbers refer to item numbers described in the tables of clause 2.4.



## Radiated Emissions Test



**2.4 SUPPORT UNITS**

Item	Equipment	Brand	Model No.	Series No.	Remarks
A	ADP	MEAN WELL	GSM120A20	N/A	Supplied by test requester.
B	ADP	N/A	N/A	N/A	Furnished by test lab.
C	Keyboard	N/A	N/A	N/A	Furnished by test lab.
D	Mouse	N/A	N/A	N/A	Furnished by test lab.
E	Microphone	N/A	N/A	N/A	Furnished by test lab.
F	Modem	N/A	N/A	N/A	Furnished by test lab.
G	Printer	N/A	N/A	N/A	Furnished by test lab.
H	USB	N/A	N/A	N/A	Furnished by test lab.
I	USB	N/A	N/A	N/A	Furnished by test lab.
J	USB	N/A	N/A	N/A	Furnished by test lab.
K	AP	N/A	N/A	N/A	Furnished by test lab.
L	USB	N/A	N/A	N/A	Furnished by test lab.
M	Keyboard	N/A	N/A	N/A	Furnished by test lab.
N	Mouse	N/A	N/A	N/A	Furnished by test lab.

Item	Shielded	Ferrite Core	Length	Cable Type	Remarks
1	N/A	N/A	1m	Power Cord	Furnished by test lab.
2	N/A	N/A	5m	LAN Cable	Furnished by test lab.
3	N/A	N/A	5m	LAN Cable	Furnished by test lab.
4	N/A	N/A	5m	LAN Cable	Furnished by test lab.
5	N/A	N/A	5m	LAN Cable	Furnished by test lab.
6	N/A	N/A	1.8m	RS232 Cable	Furnished by test lab.
7	N/A	N/A	1.8m	Printer Cable 24V	Furnished by test lab.
8	N/A	N/A	1m	LAN Cable	Furnished by test lab.
9	N/A	N/A	10m	LAN Cable	Furnished by test lab.

### 3 AC POWER LINE CONDUCTED EMISSIONS TEST

#### 3.1 LIMIT

Frequency (MHz)	Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56 *	56 - 46 *
0.50 - 5.0	56	46
5.0 - 30.0	60	50

NOTE:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.
- (3) The test result calculated as following:

Measurement Value = Reading Level + Correct Factor

Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor (if use)

Margin Level = Measurement Value – Limit Value

Calculation example:

Reading Level (dB $\mu$ V)		Correct Factor (dB)		Measurement Value (dB $\mu$ V)
38.22	+	3.45	=	41.67

Measurement Value (dB $\mu$ V)		Limit Value (dB $\mu$ V)		Margin Level (dB)
41.67	-	60	=	-18.33

The following table is the setting of the receiver.

Receiver Parameter	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 3.2 TEST PROCEDURE

- a. The EUT was placed 0.8 m above the horizontal ground plane with the EUT being connected to the power mains through a line impedance stabilization network (LISN).  
All other support equipment were powered from an additional LISN(s).  
The LISN provides 50 Ohm/50uH of impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle to keep the cable above 40 cm.
- c. Excess I/O cables that are not connected to a peripheral shall be bundled in the center.  
The end of the cable will be terminated, using the correct terminating impedance.  
The overall length shall not exceed 1 m.
- d. The LISN is spaced at least 80 cm from the nearest part of the EUT chassis.
- e. For the actual test configuration, please refer to the related Item - EUT TEST PHOTO.


**NOTE:**

- (1) In the results, each reading is marked as Peak, QP or AVG per the detector used.  
BW=9 kHz (6 dB Bandwidth)
- (2) All readings are Peak unless otherwise stated QP or AVG in column of Note. Both the QP and the AVG readings must be less than the limit for compliance.

### 3.3 DEVIATION FROM TEST STANDARD

No deviation.

### 3.4 TEST SETUP



### 3.5 TEST RESULT

Please refer to the APPENDIX A.

## 4 RADIATED EMISSIONS TEST

### 4.1 LIMIT

<b>FCC Part 15.209</b>				
Frequency (MHz)	Field Strength Limitation		Field Strength Limitation at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
0.009 – 0.490	2400 / F(KHz)	300m	10000 * 2400/F(KHz)	20log 2400/F(KHz) + 80
0.490 – 1.705	24000 / F(KHz)	30m	100 * 24000/F(KHz)	20log 24000/F(KHz) + 40
1.705 – 30.00	30	30m	100* 30	20log 30 + 40
30.0 – 88.0	100	3m	100	20log 100
88.0 – 216.0	150	3m	150	20log 150
216.0 – 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500

<b>FCC Part 15.225(a)/(b)/(c)</b>				
Frequency (MHz)	Field Strength Limitation		Field Strength Limitation at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
13.553 – 13.567	15,848	30 m	15,848*100	124
13.567 – 13.710	334	30 m	334*100	90.5
13.110 – 13.410	106	30 m	106*100	80.5
13.710 – 14.010				

NOTE:

- (1) The tighter limit shall apply at the boundary between two frequency range.
- (2) Limitation expressed in dBuV/m is calculated by 20log Emission Level (uV/m).
- (3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of  $L_{d1} = L_{d2} * (d_2/d_1)^2$ .

Example:

F.S Limit at 30m distance is 30uV/m , then F.S Limitation at 3m distance is adjusted as  $L_{d1} = L_1 = 30uV/m * (10)^2 = 100 * 30 uV/m$

- (4) The test result calculated as following:

Measurement Value = Reading Level + Correct Factor

Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)

Margin Level = Measurement Value – Limit Value

#### 4.2 TEST PROCEDURE

- a. The measuring distance of 1 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 30MHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz).
- c. The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

**NOTE: (FCC PART 15.209)**

- a. Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode with Detector BW=120 kHz.
- b. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.


**NOTE: (FCC PART 15.225)**


- a. Spectrum Setting:  
9 KHz – 150 KHz, RBW= 200Hz, VBW=200Hz, Sweep time = 200 ms.  
150 K Hz – 30 MHz, RBW= 10 KHz, VBW=10 KHz, Sweep time = 200 ms.  
30 MHz – 1000 MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
- b. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- c. The Log-Bicon Antenna will use to test frequency range from 30MHz to 1000MHz and the Loop Antenna will use to test frequency below 30MHz.

#### 4.3 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.4 TEST SETUP





#### 4.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

#### 4.6 TEST RESULT – 9 kHz TO 30 MHz – FCC PART 15.209

Please refer to the APPENDIX B

#### 4.7 TEST RESULT – 30 MHz TO 1 GHz – FCC PART 15.209

Please refer to the APPENDIX C.

#### 4.8 TEST RESULT – FCC PART 15.225

Please refer to the APPENDIX D.

NOTE:

- (1) No limit: This is fundamental signal, the judgment is not applicable.  
For fundamental signal judgment was referred to Peak output test.

## 5 FREQUENCY STABILITY

### 5.1 LIMIT

#### FCC Part 15.225(e)

The frequency tolerance of the carrier signal shall be maintained within +/-0.01% of the operating frequency over a temperature variation of - 20 degrees to + 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

For battery operated equipment, the equipment tests shall be performed using a new battery.

### 5.2 TEST PROCEDURE

- a. The equipment under test was connected to an external AC power supply and the RF output was connected to a frequency counter via feed through attenuators. The EUT was placed inside the temperature chamber.
- b. At room temperature ( $25\pm5^{\circ}\text{C}$ ), an external variable AC power supply was connected to the EUT. The frequency of the transmitter was measured for 115%, 100% and 85% of the nominal operating input voltage.

### 5.3 DEVIATION FROM TEST STANDARD

No deviation.

### 5.4 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

### 5.5 TEST RESULT

Please refer to the APPENDIX E.

## 6 20 DB BANDWIDTH

### 6.1 LIMIT

#### FCC Part 15.215(c)

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.217 through §15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


### 6.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 1 kHz, VBW=1 kHz, Sweep time = 20 ms.

### 6.3 DEVIATION FROM TEST STANDARD

No deviation.

### 6.4 TEST SETUP



### 6.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

### 6.6 TEST RESULT

Please refer to the APPENDIX F.

## 7 LIST OF MEASURING EQUIPMENTS

AC Power Line Conducted Emissions						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	TWO-LINE V-NETWORK	R&S	ENV216	101521	2024/9/5	2025/9/4
2	Test Cable	EMCI	EMCCFD300-BM-BMR-5000	220331	2024/3/30	2025/3/29
3	EMI Test Receiver	R&S	ESR 7	101433	2024/11/7	2025/11/6
4	Measurement Software	EZ	EZ_EMC (Version NB-03A1-01)	N/A	N/A	N/A

Radiated Emissions						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Preamplifier	EMCI	EMC330N	980850	2024/9/5	2025/9/4
2	Preamplifier	EMCI	EMC001340	980579	2024/9/4	2025/9/3
3	Test Cable	EMCI	EMC104-SM-1000	180809	2024/3/8	2025/3/7
4	Test Cable	EMCI	EMC104-SM-SM-3000	220322	2024/3/8	2025/3/7
5	Test Cable	EMCI	EMC104-SM-SM-7000	220324	2024/3/8	2025/3/7
6	EXA Signal Analyzer	keysight	N9020B	MY59050135	2024/11/7	2025/11/6
7	Loop Ant	Electro-Metrics	EMCI-LPA600	291	2024/9/9	2025/9/8
8	Log-bicon Antenna	Schwarzbeck	VULB9168	1369	2024/6/14	2025/6/13
9	6dB Attenuator	EMCI	EMCI-N-6-06	AT-06001	2024/6/14	2025/6/13
10	Measurement Software	EZ	EZ_EMC (Version NB-03A1-01)	N/A	N/A	N/A

Frequency Stability Measurement						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Spectrum Analyzer	R&S	FSP 40	100129	2024/3/27	2025/3/26
2	Thermal Chamber	HOLINK	H-TH-2SP-B	EK04101902	2024/6/28	2025/6/27

20 dB Bandwidth Measurement						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Spectrum Analyzer	R&S	FSP 40	100129	2024/3/27	2025/3/26

Remark: "N/A" denotes no model name, no serial no. or no calibration specified.  
All calibration period of equipment list is one year.

## **8 EUT TEST PHOTO**


Please refer to document Appendix No.: TP-2311T136B-FCCP-1 (APPENDIX-TEST PHOTOS).

## **9 EUT PHOTOS**

Please refer to document Appendix No.: EP-2311T136B-1 (APPENDIX-EUT PHOTOS).

**APPENDIX A AC POWER LINE CONDUCTED EMISSIONS**

Test Mode	Normal	Tested Date	2025/2/18
Test Frequency	-	Phase	Line




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
MHz		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.2377	30.63	9.63	40.26	62.18	-21.92	QP	
2		0.2377	22.39	9.63	32.02	52.18	-20.16	AVG	
3		0.4154	22.33	9.58	31.91	57.54	-25.63	QP	
4		0.4154	9.68	9.58	19.26	47.54	-28.28	AVG	
5		1.2435	17.51	9.56	27.07	56.00	-28.93	QP	
6		1.2435	10.26	9.56	19.82	46.00	-26.18	AVG	
7		3.7612	19.77	9.69	29.46	56.00	-26.54	QP	
8		3.7612	12.31	9.69	22.00	46.00	-24.00	AVG	
9		8.5087	22.68	9.69	32.37	60.00	-27.63	QP	
10		8.5087	13.77	9.69	23.46	50.00	-26.54	AVG	
11		27.1230	30.08	9.61	39.69	60.00	-20.31	QP	
12	*	27.1230	27.05	9.61	36.66	50.00	-13.34	AVG	

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	Normal	Tested Date	2025/2/18
Test Frequency	-	Phase	Neutral




No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Margin	Detector	Comment
			dBuV	dB	dBuV	dB			
1		0.1770	27.12	9.65	36.77	64.63	-27.86	QP	
2		0.1770	10.97	9.65	20.62	54.63	-34.01	AVG	
3		0.3322	33.51	9.59	43.10	59.40	-16.30	QP	
4	*	0.3322	30.25	9.59	39.84	49.40	-9.56	AVG	
5		0.7665	22.50	9.55	32.05	56.00	-23.95	QP	
6		0.7665	15.97	9.55	25.52	46.00	-20.48	AVG	
7		3.3833	19.90	9.68	29.58	56.00	-26.42	QP	
8		3.3833	12.49	9.68	22.17	46.00	-23.83	AVG	
9		8.5155	22.52	9.72	32.24	60.00	-27.76	QP	
10		8.5155	14.21	9.72	23.93	50.00	-26.07	AVG	
11		27.1230	31.25	9.75	41.00	60.00	-19.00	QP	
12		27.1230	28.50	9.75	38.25	50.00	-11.75	AVG	

## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.  
 (2) Margin Level = Measurement Value - Limit Value.

Test Mode	Idle	Tested Date	2025/2/18
Test Frequency	-	Phase	Line




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
MHz		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1793	28.54	9.66	38.20	64.52	-26.32	QP	
2		0.1793	12.96	9.66	22.62	54.52	-31.90	AVG	
3		0.3300	31.65	9.60	41.25	59.45	-18.20	QP	
4		0.3300	25.94	9.60	35.54	49.45	-13.91	AVG	
5		1.4303	20.24	9.56	29.80	56.00	-26.20	QP	
6		1.4303	12.73	9.56	22.29	46.00	-23.71	AVG	
7		3.8040	19.58	9.69	29.27	56.00	-26.73	QP	
8		3.8040	12.53	9.69	22.22	46.00	-23.78	AVG	
9		8.5133	23.01	9.69	32.70	60.00	-27.30	QP	
10		8.5133	14.29	9.69	23.98	50.00	-26.02	AVG	
11		27.1230	29.70	9.61	39.31	60.00	-20.69	QP	
12	*	27.1230	26.81	9.61	36.42	50.00	-13.58	AVG	

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	Idle	Tested Date	2025/2/18
Test Frequency	-	Phase	Neutral




No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Margin	Detector	Comment
			dBuV	dB	dBuV	dB			
1		0.1883	29.30	9.64	38.94	64.11	-25.17	QP	
2		0.1883	21.69	9.64	31.33	54.11	-22.78	AVG	
3		0.3232	32.47	9.59	42.06	59.62	-17.56	QP	
4		0.3232	22.59	9.59	32.18	49.62	-17.44	AVG	
5		0.9487	22.57	9.55	32.12	56.00	-23.88	QP	
6		0.9487	15.43	9.55	24.98	46.00	-21.02	AVG	
7		3.2055	19.33	9.68	29.01	56.00	-26.99	QP	
8		3.2055	12.43	9.68	22.11	46.00	-23.89	AVG	
9		8.5110	22.90	9.72	32.62	60.00	-27.38	QP	
10		8.5110	14.09	9.72	23.81	50.00	-26.19	AVG	
11		27.1230	31.36	9.75	41.11	60.00	-18.89	QP	
12	*	27.1230	28.63	9.75	38.38	50.00	-11.62	AVG	

## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.  
 (2) Margin Level = Measurement Value - Limit Value.

**APPENDIX B RADIATED EMISSIONS - 9 KHZ TO 30 MHZ**

Test Mode	TX	Test Date	2025/2/17
Test Frequency	13.56MHz	Polarization	Vertical
Temp	26°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	0.0320	28.19	27.84	56.03	136.58	-80.55

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX	Test Date	2025/2/17
Test Frequency	13.56MHz	Polarization	Vertical
Temp	26°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector Comment
1		0.1500	35.74	13.96	49.70	123.16	-73.46	AVG
2		3.7797	28.55	-4.01	24.54	88.62	-64.08	QP
3	*	7.5577	34.16	-3.69	30.47	88.62	-58.15	QP
4		10.3140	21.70	-3.04	18.66	88.62	-69.96	QP
5		17.7962	23.88	-3.76	20.12	88.62	-68.50	QP
6		23.7324	31.67	-3.25	28.42	88.62	-60.20	QP

## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.  
 (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX	Test Date	2025/2/17
Test Frequency	13.56MHz	Polarization	Horizontal
Temp	26°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	0.0321	30.45	27.82	58.27	136.55	-78.28
							AVG

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX	Test Date	2025/2/17
Test Frequency	13.56MHz	Polarization	Horizontal
Temp	26°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector Comment
1		0.1500	32.65	13.96	46.61	123.16	-76.55	AVG
2	*	3.7807	31.82	-4.02	27.80	88.62	-60.82	QP
3		7.5607	28.67	-3.69	24.98	88.62	-63.64	QP
4		16.6500	21.06	-3.65	17.41	88.62	-71.21	QP
5		23.7175	28.43	-3.25	25.18	88.62	-63.44	QP
6		29.8776	22.37	-2.06	20.31	88.62	-68.31	QP

## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.  
 (2) Margin Level = Measurement Value - Limit Value.

**APPENDIX C RADIATED EMISSIONS - 30 MHZ TO 1 GHZ**

Test Mode	TX	Test Date	2025/2/17
Test Frequency	13.56MHz	Polarization	Vertical
Temp	26°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	32.3603	50.68	-13.14	37.54	40.00	-2.46	QP	
2	!	50.4993	46.62	-11.67	34.95	40.00	-5.05	QP	
3		152.9960	48.48	-11.85	36.63	43.50	-6.87	peak	
4		312.4640	49.89	-11.16	38.73	46.00	-7.27	peak	
5		418.9375	47.17	-8.32	38.85	46.00	-7.15	peak	
6		960.0360	38.58	0.84	39.42	54.00	-14.58	peak	

## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.  
 (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX	Test Date	2025/2/17
Test Frequency	13.56MHz	Polarization	Horizontal
Temp	26°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector Comment
1	*	64.5643	49.17	-13.22	35.95	40.00	-4.05	QP
2		152.1552	45.92	-11.85	34.07	43.50	-9.43	QP
3		252.0006	49.18	-13.21	35.97	46.00	-10.03	QP
4		399.9902	45.99	-8.97	37.02	46.00	-8.98	peak
5		749.9986	37.07	-1.72	35.35	46.00	-10.65	peak
6		919.0050	36.42	0.26	36.68	46.00	-9.32	peak

## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.  
 (2) Margin Level = Measurement Value - Limit Value.

**APPENDIX D RADIATED EMISSIONS - FCC PART 15.225**

Test Mode	TX	Test Date	2025/2/17
Test Frequency	13.56MHz	Polarization	Vertical
Temp	26°C	Hum.	58%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	13.5610	51.57	-3.36	48.21	143.07	-94.86

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX	Test Date	2025/2/17
Test Frequency	13.56MHz	Polarization	Horizontal
Temp	26°C	Hum.	58%



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	13.5610	52.44	-3.36	49.08	143.07	-93.99 peak

## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.  
(2) Margin Level = Measurement Value - Limit Value.

## **APPENDIX E FREQUENCY STABILITY MEASUREMENT**

Test Mode	TX	Tested Date	2025/2/5
-----------	----	-------------	----------


Condition			Frequency Error (ppm)									
Temperature	Modulation Mode	Test Freq.	0 min	2 min	5 min	10 min	0 min	2 min	5 min	10 min	Limit (ppm)	Result
<b>Normal</b>												
T <sub>20°C</sub> Vmax	CW	13.56	13.561080	13.561080	13.561080	13.561080	79.65	79.65	79.65	79.65	100	Pass
T <sub>20°C</sub> Vmin	CW	13.56	13.561080	13.561080	13.561080	13.561080	79.65	79.65	79.65	79.65		Pass
<b>Extreme</b>												
T <sub>35°C</sub> Vnom	CW	13.56	13.561080	13.561080	13.561080	13.561080	79.65	79.65	79.65	79.65	100	Pass
T <sub>30°C</sub> Vnom	CW	13.56	13.561080	13.561080	13.561080	13.561080	79.65	79.65	79.65	79.65		Pass
T <sub>20°C</sub> Vnom	CW	13.56	13.561080	13.561080	13.561080	13.561080	79.65	79.65	79.65	79.65		Pass
T <sub>10°C</sub> Vnom	CW	13.56	13.561080	13.561080	13.561080	13.561080	79.65	79.65	79.65	79.65		Pass
T <sub>0°C</sub> Vnom	CW	13.56	13.561080	13.561080	13.561080	13.561080	79.65	79.65	79.65	79.65		Pass

NOTE: 0.01 % = 100 ppm.

**APPENDIX F 20 DB BANDWIDTH**

Test Mode	TX
-----------	----

Frequency (MHz)	20 dB Bandwidth (MHz)	Operated Frequency Range (MHz)	Designated Frequency Band (MHz)	Result
13.56	13.56	0.0022	0.014	Complied



Date: 5.FEB.2025 09:34:57

**End of Test Report**