



Report Reference ID:	209925-8TRFWL
----------------------	---------------

Test specification:	Title 47 – Telecommunication Chapter I – Federal Communications Commission Subchapter B – Common carrier services – <b>Part 27 – Miscellaneous wireless communications services</b>
---------------------	--


Applicant:	TEKO Telecom S.p.A. Via Meucci, 24/a I-40024 Castel S. Pietro Terme (BO) (Italy)
------------	--

Apparatus:	<a href="#">Digital Donor Front-End</a>
------------	---

FCC ID:	XM2-DFE
---------	---------

Model:	TDFE-AW
--------	---------

Testing laboratory:	<b>Nemko Italy S.p.A.</b> Via Carroccio, 4 I-20046 Biassono (Italy)
---------------------	---

	Name and title	Date
Tested by:	 G. Curioni, Wireless/EMC Specialist	2012/06/21
Reviewed by:	 P. Barbieri, Wireless/EMC Specialist	2012/06/21

## Table of contents

<b>Section 1: Report summary .....</b>	<b>3</b>
1.1    Test specification.....	3
1.2    Statement of compliance.....	3
1.3    Exclusions .....	3
1.4    Registration number .....	3
1.5    Test report revision history .....	3
1.6    Limits of responsibility .....	3
<b>Section 2: Summary of test results .....</b>	<b>4</b>
2.1    FCC Part 27, test results .....	4
<b>Section 3: Equipment under test (EUT) and application details.....</b>	<b>5</b>
3.1    Applicant details .....	5
3.2    Modular equipment.....	5
3.3    Product details.....	5
3.4    Application purpose.....	5
3.5    Composite/related equipment.....	5
3.6    Sample information.....	5
3.7    EUT technical specifications.....	6
3.8    Operation of the EUT during testing .....	6
3.9    EUT setup diagram.....	6
<b>Section 4: Engineering considerations .....</b>	<b>7</b>
4.1    Modifications incorporated in the EUT.....	7
4.2    Deviations from laboratory tests procedures .....	7
4.3    Technical judgment .....	7
<b>Section 5: Test conditions .....</b>	<b>8</b>
5.1    Power source and ambient temperatures.....	8
<b>Section 6: Measurement uncertainty .....</b>	<b>9</b>
<b>Section 7: Test equipment .....</b>	<b>10</b>
<b>Section 8: Testing data .....</b>	<b>11</b>
8.1    Clause 27.50 (d) Peak output power at RF antenna connector.....	11
8.2    Clause 27.52 RF safety .....	20
8.3    Clause 27.53 (h) Spurious emissions at RF antenna connector .....	21
8.4    Clause 27.53 (h) Radiated spurious emissions .....	49
8.5    Clause 27.53 (f) Radiated spurious emissions within 1559–1610 MHz band.....	51
8.6    Clause 27.54 Frequency stability .....	52
8.7    Clause 2.1049 Occupied bandwidth.....	54
8.8    Clause 2.1047 Modulation characteristics.....	68
<b>Section 9: Filter Frequency Response.....</b>	<b>77</b>
<b>Section 10: Block diagrams of test set-ups .....</b>	<b>78</b>
<b>Section 11: EUT photos.....</b>	<b>79</b>

 <b>Nemko</b>	<b>Section 1: Report summary</b>	<b>Product: TD芬-AW</b>
--	----------------------------------	------------------------

## Section 1: Report summary

### 1.1 Test specification

<b>Specifications</b>	<b>Part 27 – Miscellaneous wireless communications services</b>
-----------------------	---

### 1.2 Statement of compliance

<b>Compliance</b>	In the configuration tested the EUT was found compliant Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
This report contains an assessment of apparatus against specifications based upon tests carried out on samples submitted at Nemko Canada Inc. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 27. Radiated tests were conducted in accordance with ANSI C63.4-2003.	

### 1.3 Exclusions

<b>Exclusions</b>	<b>None</b>
-------------------	-------------

### 1.4 Registration number

<b>Registration number:</b>	481407 (10 m Semi anechoic chamber)
-----------------------------	-------------------------------------

### 1.5 Test report revision history

<b>Revision #</b>	<b>Details of changes made to test report</b>
TRF	Original report issued
---	---

### 1.6 Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

**Section 2: Summary of test results****Product: TDFE-AW****Section 2: Summary of test results****2.1 FCC Part 27, test results**

Part	Test description	Verdict
§27.50(d)	Peak output power at RF antenna connector	Pass
§27.52	RF safety	N/A a)
§27.53(h)	Spurious emissions at RF antenna connector	Pass
§27.53(h)	Radiated spurious emissions	Pass
§27.53(f)	Radiated spurious emissions within 1559–1610 MHz band	N/A b)
§27.54	Frequency stability	Pass
§2.1049	Occupied bandwidth	Pass
§2.1047	Modulation characteristics	Pass
§2-11-04/EAB/RF	Filter Frequency Response	Pass

Notes:

- a) NO Antenna provided
- b) AWS band

 <b>Nemko</b>	<b>Section 3: Equipment under test (EUT) details</b>	<b>Product: TDFE-AW</b>

### Section 3: Equipment under test (EUT) and application details

#### 3.1 Applicant details

<b>Applicant complete business name</b>	Name:	Teko Telecom S.p.A.
	Federal Registration Number (FRN):	0018963462
	Grantee code	XM2
<b>Mailing address</b>	Address: City: Province/State: Post code: Country:	Via Meucci, 24/a Castel S. Pietro Terme Bologna 40024 Italy

#### 3.2 Modular equipment

<b>a) Single modular approval</b>	Single modular approval Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
<b>b) Limited single modular approval</b>	Limited single modular approval Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>

#### 3.3 Product details

<b>FCC ID</b>	Grantee code:	XM2
	Product code:	-DFE
<b>Equipment class</b>	TNB	
<b>Description of product as it is marketed</b>	Digital Donor Front-End	
	Model name/number:	TDFA-AW
	Serial number:	120803001

#### 3.4 Application purpose

<b>Type of application</b>	<input checked="" type="checkbox"/> Original certification
	<input type="checkbox"/> Change in identification of presently authorized equipment
	Original FCC ID: _____ Grant date: _____
	<input type="checkbox"/> Class II permissive change or modification of presently authorized equipment

#### 3.5 Composite/related equipment

<b>a) Composite equipment</b>	The EUT is a composite device subject to an additional equipment authorization Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
<b>b) Related equipment</b>	The EUT is part of a system that operates with, or is marketed with, another device that requires an equipment authorization Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
<b>c) Related FCC ID</b>	If either of the above is "yes": <input type="checkbox"/> has been granted under the FCC ID(s) listed below: <input type="checkbox"/> is in the process of being filled under the FCC ID(s) listed below: <input type="checkbox"/> is pending with the FCC ID(s) listed below: <input type="checkbox"/> has a mix of pending and granted statuses under the FCC ID(s) listed below: i) FCC ID: ii) FCC ID:

#### 3.6 Sample information

<b>Receipt date:</b>	2012-06-11
----------------------	------------

 <b>Nemko</b>	<b>Section 3: Equipment under test (EUT) details</b>	<b>Product: TDFE-AW</b>

<b>Nemko sample ID number:</b>	-----
--------------------------------	-------

### 3.7 EUT technical specifications

<b>Operating band:</b>	AWS: Down Link: 2110–2155 MHz, Up Link: 1710-1755 MHz
<b>Operating frequency:</b>	Wideband
<b>Modulation type:</b>	CDMA, WCDMA, LTE (QAM and QPSK)
<b>Occupied bandwidth:</b>	CDMA: 1,25 MHz, WCDMA: 5 MHz LTE: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz
<b>Channel spacing:</b>	standard
<b>Emission designator:</b>	CDMA, WCDMA: F9W, LTE: D7W
<b>RF Output</b>	Down Link: 10dBm (0,010W) Up Link: 26dBm (0,400W)
<b>Gain</b>	Down Link: 63dB Up Link: 64dB
<b>Antenna type:</b>	External Antenna is not provided, equipment that has an external 50 Ω RF connector
<b>Power source:</b>	28-30 Vdc stand alone 100-240 Vac in subrack with external Ac/Dc power supply

### 3.8 Operation of the EUT during testing

<b>Details:</b>	Normal working at max gain with max RF power output (down link and up link)
-----------------	---

### 3.9 EUT setup diagram



 <b>Nemko</b>	<b>Section 4: Engineering considerations</b>	<b>Product:</b> TDFE-AW
--	--	-------------------------

## Section 4: Engineering considerations

### 4.1 Modifications incorporated in the EUT

<b>Modifications</b>	Modifications performed to the EUT during this assessment None <input checked="" type="checkbox"/> Yes <input type="checkbox"/> , performed by Client <input type="checkbox"/> or Nemko <input type="checkbox"/> Details:
----------------------	---

### 4.2 Deviations from laboratory tests procedures

<b>Deviations</b>	Deviations from laboratory test procedures None <input checked="" type="checkbox"/> Yes <input type="checkbox"/> - details are listed below:
-------------------	---

### 4.3 Technical judgment

<b>Judgment</b>	None
-----------------	------



## Section 5: Test conditions

### 5.1 Power source and ambient temperatures

<b>Normal temperature, humidity and air pressure test conditions</b>	Temperature: 15–30 °C Relative humidity: 20–75 % Air pressure: 860–1060 hPa  When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.
<b>Power supply range:</b>	The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages $\pm 5\%$ , for which the equipment was designed.



## Section 6: Measurement uncertainty

Nemko S.p.A. measurement uncertainty has been calculated using the standard CISPR 16-4-2 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainties, statistics and limit modeling – Uncertainty in EMC measurements". All calculations have been performed to provide a confidence level of 95 % and can be found in Nemko S.p.A. document WML1002.


**Section 7: Test equipment****Product: TD FE-AW****Section 7: Test equipment**

<b>Identification number</b>	<b>Description</b>	<b>Manufacturer model</b>	<b>s/n</b>	<b>Cal. Due</b>
1a	Vector Signal Generator	Agilent N5182A MXG	MY48180714	May 2013
1b	Vector Signal Generator	Agilent E4438C ESG	MY45094485	Ago 2013
2a	Spectrum Analyzer	Agilent E4440A	US40420470	Jul 2012
2b	Spectrum Analyzer	Agilent E9020A MXA	MY48011812	Jul 2012
3	Network Analyzer	Agilent E5071B	MY42301133	Jan 2013
4	Climatic chamber	Angelantoni Hygros 600	7237	Nov 2014

Client's property

<b>Identification number</b>	<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial N°</b>	<b>Cal. due</b>
1	Trilog Broadband Antenna	Schwarzbeck	VULB 9163	VULB 9163-286	04/2013
2	Bilog antenna	Schwarzbeck	STLP 9148-123	123	09/2012
3	Double ridge waveguide horn	Spin	DRH40	061106A40	09/2013
4	Broadband preamplifier	Schwarzbeck	BBV 9718	9718-137	05/2013
5	Broadband preamplifier	Miteq	JS44	1648665	05/2013
6	Spectrum Analyzer 9kHz-40GHz	R&S	FSEK	848255/005	09/2012
7	Controller	EMCO	2090	9511-1099	NSC
8	Antenna Tower	EMCO	2071-2	9601-1940	NSC
9	Turning table Controller	EMCO	1061-1.521	9012-1508	NSC
10	Semi-anechoic chamber	Nemko	3m semi-anechoic chamber	70	04/2013
11	Control room	Siemens	3m control room	3	NSC

Property of Nemko Italy



<b>Section 8: Testing data</b>	<b>Product:</b> TDFE-AW
<b>Test name:</b> Clause 27.52 RF safety	
<b>Test date</b> 11-20 June 2012	<b>Test engineer:</b> G. Curioni
<b>Verdict:</b> Pass	<b>Supply input:</b> 100-240 Vac
<b>Temperature:</b> 25 °C	<b>Air pressure:</b> 860-1060 hPa
<b>Specification:</b> FCC Part 27	<b>Relative humidity:</b> 50 %

## Section 8: Testing data

### 8.1 Clause 27.50(d) Peak output power at RF antenna connector


(1) The power of each fixed or base station transmitting in the 2110-2155 MHz band and located in any county with population density of 100 or fewer persons per square mile, based upon the most recently available population statistics from the Bureau of the Census, is limited to a peak equivalent isotropically radiated power (EIRP) of 3280 watts. The power of each fixed or base station transmitting in the 2110-2155 MHz band from any other location is limited to a peak EIRP of 1640 watts. A licensee operating a base or fixed station utilizing a power of more than 1640 watts EIRP must coordinate such operations in advance with all Government and non-Government satellite entities in the 2025-2110 MHz band. Operations above 1640 watts EIRP must also be coordinated in advance with the following licensees within 120 kilometers (75 miles) of the base or fixed station: all Broadband Radio Service (BRS) licensees authorized under Part 27 in the 2155-2160 MHz band and all AWS licensees in the 2110-2155 MHz band.

(2) Fixed, mobile, and portable (handheld) stations operating in the 1710–1755MHz band are limited to a peak EIRP of 1 watt. Fixed stations operating in this band are limited to a maximum antenna height of 10 meters above ground, and mobile and portable stations must employ a means for limiting power to the minimum necessary for successful communications.

In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13dB.

### Special notes

- The power was measured using spectrum analyzer with RMS detector / average power meter.




<b>Section 8: Testing data</b>		<b>Product:</b> TDFE-AW
<b>Test name:</b> Clause 27.52 RF safety		
<b>Test date</b> 11-20 June 2012	<b>Test engineer:</b> G. Curioni	
<b>Verdict:</b> Pass	<b>Supply input:</b> 100-240 Vac	
<b>Temperature:</b> 25 °C	<b>Air pressure:</b> 860-1060 hPa	<b>Relative humidity:</b> 50 %
<b>Specification:</b> FCC Part 27		

## RF Output Power at RF connectors


Test data					
Direction	Modulation	Frequency (MHz)	RF output Power (W/MHz)	RF output channel Power (W)	PAR (dB)
Down-link	CDMA (1,25MHz)	2132.5	0.008	0.010	8.89
Down-link	WCDMA (5MHz)	2132.5	0.002	0.010	10.56
Down-link	LTE (QAM, 1,4MHz)	2132.5	0.008	0.011	10.09
Down-link	LTE (QPSK, 1,4MHz)	2132.5	0.008	0.011	9.43
Down-link	LTE (QAM, 3MHz)	2132.5	0.003	0.010	10.49
Down-link	LTE (QPSK, 3MHz)	2132.5	0.003	0.010	10.57
Down-link	LTE (QAM, 5MHz)	2132.5	0.002	0.010	10.92
Down-link	LTE (QPSK, 5MHz)	2132.5	0.002	0.010	10.47
Down-link	LTE (QAM, 10MHz)	2132.5	0.001	0.010	10.02
Down-link	LTE (QPSK, 10MHz)	2132.5	0.001	0.010	10.32
Down-link	LTE (QAM, 15MHz)	2132.5	$6.67 \times 10^{-4}$	0.010	10.96
Down-link	LTE (QPSK, 15MHz)	2132.5	$6.67 \times 10^{-4}$	0.010	11.13
Down-link	LTE (QAM, 20MHz)	2132.5	0.0005	0.010	10.68
Down-link	LTE (QPSK, 20MHz)	2132.5	0.00055	0.011	11.23
Up-link	CDMA (1,25MHz)	1732.5	0.3248	0.406	8.81
Up-link	WCDMA (5MHz)	1732.5	0.0822	0.411	10.26
Up-link	LTE (QAM, 1,4MHz)	1732.5	0.29	0.406	9.49
Up-link	LTE (QPSK, 1,4MHz)	1732.5	0.30	0.417	9.17
Up-link	LTE (QAM, 3MHz)	1732.5	0.14	0.419	9.94
Up-link	LTE (QPSK, 3MHz)	1732.5	0.135	0.406	9.94
Up-link	LTE (QAM, 5MHz)	1732.5	0.0814	0.407	9.99
Up-link	LTE (QPSK, 5MHz)	1732.5	0.0814	0.407	9.59
Up-link	LTE (QAM, 10MHz)	1732.5	0.0417	0.417	10.28
Up-link	LTE (QPSK, 10MHz)	1732.5	0.0419	0.419	9.56
Up-link	LTE (QAM, 15MHz)	1732.5	0.0276	0.414	10.75
Up-link	LTE (QPSK, 15MHz)	1732.5	0.0271	0.407	11.41
Up-link	LTE (QAM, 20MHz)	1732.5	0.02085	0.417	9.95
Up-link	LTE (QPSK, 20MHz)	1732.5	0.02055	0.411	10.41

Transmitting these powers by a  $\lambda/2$  dipole tuned on the carriers' frequency we get: erp.





<b>Section 8: Testing data</b>		<b>Product: TDFE-AW</b>
<b>Test name:</b> Clause 27.52 RF safety		
<b>Test date</b> 11-20 June 2012		<b>Test engineer:</b> G. Curioni
<b>Verdict:</b> Pass		<b>Supply input:</b> 100-240 Vac
<b>Temperature:</b> 25 °C	<b>Air pressure:</b> 860-1060 hPa	<b>Relative humidity:</b> 50 %
<b>Specification:</b> FCC Part 27		

## Mod. CDMA




## Mod. WCDMA






<b>Section 8: Testing data</b>		<b>Product:</b> TDFE-AW
<b>Test name:</b> Clause 27.52 RF safety		
<b>Test date</b> 11-20 June 2012	<b>Test engineer:</b> G. Curioni	
<b>Verdict:</b> Pass	<b>Supply input:</b> 100-240 Vac	
<b>Temperature:</b> 25 °C	<b>Air pressure:</b> 860-1060 hPa	<b>Relative humidity:</b> 50 %
<b>Specification:</b> FCC Part 27		

### Mod. LTE 1,4MHz (QAM)




Down-link




Up-link


### Mod. LTE 1,4MHz (QPSK)



Down-link




Up-link





<b>Section 8: Testing data</b>		<b>Product:</b> TDFE-AW
<b>Test name:</b> Clause 27.52 RF safety		
<b>Test date</b> 11-20 June 2012	<b>Test engineer:</b> G. Curioni	
<b>Verdict:</b> Pass	<b>Supply input:</b> 100-240 Vac	
<b>Temperature:</b> 25 °C	<b>Air pressure:</b> 860-1060 hPa	<b>Relative humidity:</b> 50 %
<b>Specification:</b> FCC Part 27		

### Mod. LTE 3MHz (QAM)




### Mod. LTE 3MHz (QPSK)







<b>Section 8: Testing data</b>		<b>Product:</b> TDFE-AW
<b>Test name:</b> Clause 27.52 RF safety		
<b>Test date</b> 11-20 June 2012	<b>Test engineer:</b> G. Curioni	
<b>Verdict:</b> Pass	<b>Supply input:</b> 100-240 Vac	
<b>Temperature:</b> 25 °C	<b>Air pressure:</b> 860-1060 hPa	<b>Relative humidity:</b> 50 %
<b>Specification:</b> FCC Part 27		

### Mod. LTE 5MHz (QAM)




### Mod. LTE 5MHz (QPSK)







<b>Section 8: Testing data</b>		<b>Product:</b> TDFA-AW
<b>Test name:</b> Clause 27.52 RF safety		
<b>Test date</b>	11-20 June 2012	<b>Test engineer:</b> G. Curioni
<b>Verdict:</b>	Pass	<b>Supply input:</b> 100-240 Vac
<b>Temperature:</b>	25 °C	<b>Air pressure:</b> 860-1060 hPa
<b>Specification:</b>	<b>Relative humidity:</b> 50 %	
<b>FCC Part 27</b>		

### Mod. LTE 10MHz (QAM)




### Mod. LTE 10MHz (QPSK)






<b>Section 8: Testing data</b>		<b>Product:</b> TDFE-AW
<b>Test name:</b> Clause 27.52 RF safety		
<b>Test date</b> 11-20 June 2012	<b>Test engineer:</b> G. Curioni	
<b>Verdict:</b> Pass	<b>Supply input:</b> 100-240 Vac	
<b>Temperature:</b> 25 °C	<b>Air pressure:</b> 860-1060 hPa	<b>Relative humidity:</b> 50 %
<b>Specification:</b> FCC Part 27		

## Mod. LTE 15MHz (QAM)




Down-link




Up-link


## Mod. LTE 15MHz (QPSK)



Down-link




Up-link





<b>Section 8: Testing data</b>		<b>Product:</b> TDFE-AW
<b>Test name:</b> Clause 27.52 RF safety		
<b>Test date</b>	11-20 June 2012	<b>Test engineer:</b> G. Curioni
<b>Verdict:</b>	Pass	<b>Supply input:</b> 100-240 Vac
<b>Temperature:</b>	25 °C	<b>Air pressure:</b> 860-1060 hPa
<b>Specification:</b> FCC Part 27		<b>Relative humidity:</b> 50 %

### Mod. LTE 20MHz (QAM)



### Mod. LTE 20MHz (QPSK)





<b>Section 8: Testing data</b>		<b>Product:</b> TDFE-AW
<b>Test name:</b> Clause 27.52 RF safety		
<b>Test date</b> 11-20 June 2012	<b>Test engineer:</b> G. Curioni	
<b>Verdict:</b> Pass	<b>Supply input:</b> 100-240 Vac	
<b>Temperature:</b> 25 °C	<b>Air pressure:</b> 860-1060 hPa	<b>Relative humidity:</b> 50 %
<b>Specification:</b> FCC Part 27		

## 8.2 Clause 27.52 RF safety

Licensees and manufacturers are subject to the radio frequency radiation exposure requirements specified in sections 1.1307(b), 2.1091, and 2.1093 of this chapter, as appropriate. Applications for equipment authorization of mobile or portable devices operating under this section must contain a statement confirming compliance with these requirements for both fundamental emissions and unwanted emissions. Technical information showing the basis for this statement must be submitted to the Commission upon request.

### Special notes

The test was performed using E-field probe slowly moving towards the EUT until E-field equivalent to the maximum permitted power density was measured

Equivalent power density was calculated from electric field strength as follows:

$$S_{[mW/cm^2]} = \frac{0.1 \times E^2 [V/m]}{120 \times \pi} \quad S[W/m^2] = E^2 [V/m] / 377[\Omega]$$

where S is power density and E is electric field strength.

### Test data

Test distance (cm)	Field strength (V/m)	Equivalent power density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Margin (mW/cm <sup>2</sup> )
300				
250				
200				
150				
100				
50				
30				
20				
10				
5				

NOT APPLICABLE; External Antenna not provided



### 8.3 Clause 27.53 (h) Spurious emissions at RF antenna connector

For operations in the 1710-1755 MHz and 2110-2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10} (P)$  dB.

(1) Compliance with the provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

(2) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.



(3) The measurements of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

#### Special notes



- The spectrum was searched from 30 MHz to the 10<sup>th</sup> harmonic.
- All measurements were performed using a peak detector.
- RBW within 30–1000 MHz was 100 kHz 1 MHz above 1 GHz. VBW was wider than RBW.





Test data, continued band edges Inter modulation:





### Mod. CDMA (Down-link)











### Mod. CDMA (Up-link)











**Mod. WCDMA (Down-link)**

**Mod. WCDMA (Up-link)**






**Mod. LTE 1.4MHz (QAM) (Down-link)**

**Low Band Edge**

**High Band Edge**
**Mod. LTE 1.4MHz (QAM) (Up-link)**

**Low Band Edge**

**High Band Edge**





**Mod. LTE 1.4MHz (QPSK) (Down-link)**

**Low Band Edge**

**High Band Edge**
**Mod. LTE 1.4MHz (QPSK) (Up-link)**

**Low Band Edge**

**High Band Edge**




**Mod. LTE 3MHz (QAM) (Down-link)**

**Mod. LTE 3MHz (QAM) (Up-link)**






**Mod. LTE 3MHz (QPSK) (Down-link)**

**Low Band Edge**

**High Band Edge**
**Mod. LTE 3MHz (QPSK) (Up-link)**

**Low Band Edge**

**High Band Edge**





**Mod. LTE 5MHz (QAM) (Down-link)**

**Low Band Edge**

**High Band Edge**
**Mod. LTE 5MHz (QAM) (Up-link)**

**Low Band Edge**

**High Band Edge**





**Mod. LTE 5MHz (QPSK) (Down-link)**

**Low Band Edge**

**High Band Edge**
**Mod. LTE 5MHz (QPSK) (Up-link)**

**Low Band Edge**

**High Band Edge**

**Mod. LTE 10MHz (QAM) (Down-link)**

**Mod. LTE 10MHz (QAM) (Up-link)**


**Mod. LTE 10MHz (QPSK) (Down-link)**

**Mod. LTE 10MHz (QPSK) (Up-link)**


**Mod. LTE 15MHz (QAM) (Down-link)**

**Mod. LTE 15MHz (QAM) (Up-link)**


**Mod. LTE 15MHz (QPSK) (Down-link)**

**Mod. LTE 15MHz (QPSK) (Up-link)**


**Mod. LTE 20MHz (QAM) (Down-link)**

**Low Band Edge**

**High Band Edge**
**Mod. LTE 20MHz (QAM) (Up-link)**

**Low Band Edge**

**High Band Edge**