



Report Reference ID:	209925-2_TRFWL
-----------------------------	----------------

Test specification:	Title 47 – Telecommunication Chapter I – Federal Communications Commission Subchapter B – Common carrier services – Part 27 – Miscellaneous wireless communications services
----------------------------	--

Applicant:	TEKO Telecom S.p.A. Via Meucci, 24/a I-40024 Castel S. Pietro Terme (BO) (Italy)
Apparatus:	Digital Donor Front-End
FCC ID:	XM2-DFE
Model:	TDFE-7SH

Testing laboratory:	Nemko Italy S.p.A. Via Carroccio, 4 I-20046 Biassono (Italy)
----------------------------	--

	Name and title	Date
Tested by:	 G. Curioni, Wireless/EMC Specialist	2012/06/21
Reviewed by:	 P. Barbieri, Wireless/EMC Specialist	2012/06/21



Nemko Canada Inc., a testing laboratory, is accredited by the Standards Council of Canada.
The tests included in this report are within the scope of this accreditation.



Table of contents

Section 1: Report summary	3
1.1 Test specification.....	3
1.2 Statement of compliance	3
1.3 Exclusions	3
1.4 Registration number	3
1.5 Test report revision history	3
1.6 Limits of responsibility	3
Section 2: Summary of test results	4
2.1 FCC Part 27, test results	4
Section 3: Equipment under test (EUT) and application details.....	5
3.1 Applicant details	5
3.2 Modular equipment.....	5
3.3 Product details.....	5
3.4 Application purpose.....	5
3.5 Composite/related equipment.....	5
3.6 Sample information.....	5
3.7 EUT technical specifications.....	6
3.8 Operation of the EUT during testing	6
3.9 EUT setup diagram.....	6
Section 4: Engineering considerations	7
4.1 Modifications incorporated in the EUT.....	7
4.2 Deviations from laboratory tests procedures	7
4.3 Technical judgment	7
Section 5: Test conditions	8
5.1 Power source and ambient temperatures.....	8
Section 6: Measurement uncertainty	9
Section 7: Test equipment	10
7.1 Test equipment list	10
Section 8: Testing data	11
8.1 Clause 27.50(b) Peak output power at RF antenna connector.....	11
8.2 Clause 27.52 RF safety	18
8.3 Clause 27.53 Spurious emissions at RF antenna connector.....	19
8.4 Clause 27.53 Radiated spurious emissions	36
8.5 Clause 27.53(f) Radiated spurious emissions within 1559–1610 MHz band.....	38
8.6 Clause 27.54 Frequency stability	43
8.7 Clause 2.1049 Occupied bandwidth.....	46
8.8 Clause 2.1047 Modulation characteristics.....	55
Section 9: Filter Frequency Response.....	60
Section 10: Block diagrams of test set-ups	61
Section 11: EUT photos.....	62

 Nemko	Section 1: Report summary	Product: TDFE-7SH

Section 1: Report summary

1.1 Test specification

Specifications	Part 27 – Miscellaneous wireless communications services
-----------------------	---

1.2 Statement of compliance

Compliance	In the configuration tested the EUT was found compliant Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
This report contains an assessment of apparatus against specifications based upon tests carried out on samples submitted at Nemko Canada Inc. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 27. Radiated tests were conducted in accordance with ANSI C63.4-2003.	

1.3 Exclusions

Exclusions	None
-------------------	-------------

1.4 Registration number

Registration number:	481407 (10 m Semi anechoic chamber)
-----------------------------	-------------------------------------

1.5 Test report revision history

Revision #	Details of changes made to test report
TRF	Original report issued
---	---

1.6 Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.



Section 2: Summary of test results

2.1 FCC Part 27, test results

Part	Test description	Verdict
§27.50(b)	Peak output power at RF antenna connector	Pass
§27.52	RF safety	N/A a)
§27.53(c)	Spurious emissions at RF antenna connector	Pass
§27.53(c)	Radiated spurious emissions	Pass
§27.53(f)	Radiated spurious emissions within 1559–1610 MHz band	Pass
§27.54	Frequency stability	Pass
§2.1049	Occupied bandwidth	Pass
§2.1047	Modulation characteristics	Pass
§2-11-04/EAB/RF	Filter Frequency Response	Pass

Notes:

- a) NO Antenna provided

 Nemko	Section 3: Equipment under test (EUT) details	Product: TDFE-7SH

Section 3: Equipment under test (EUT) and application details

3.1 Applicant details

Applicant complete business name	Name:	Teko Telecom S.p.A.
	Federal Registration Number (FRN):	0018963462
	Grantee code	XM2
Mailing address	Address: City: Province/State: Post code: Country:	Via Meucci, 24/a Castel S. Pietro Terme Bologna 40024 Italy

3.2 Modular equipment

a) Single modular approval	Single modular approval Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
b) Limited single modular approval	Limited single modular approval Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>

3.3 Product details

FCC ID	Grantee code:	XM2
	Product code:	-DFE
Equipment class	TNB	
Description of product as it is marketed	Digital Donor Front-End	
	Model name/number:	TDFE-7SH
	Serial number:	111121001

3.4 Application purpose

Type of application	<input checked="" type="checkbox"/> Original certification
	<input type="checkbox"/> Change in identification of presently authorized equipment
	Original FCC ID: _____ Grant date: _____
	<input type="checkbox"/> Class II permissive change or modification of presently authorized equipment

3.5 Composite/related equipment

a) Composite equipment	The EUT is a composite device subject to an additional equipment authorization Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
b) Related equipment	The EUT is part of a system that operates with, or is marketed with, another device that requires an equipment authorization Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
c) Related FCC ID	If either of the above is "yes": <input type="checkbox"/> has been granted under the FCC ID(s) listed below: <input type="checkbox"/> is in the process of being filled under the FCC ID(s) listed below: <input type="checkbox"/> is pending with the FCC ID(s) listed below: <input type="checkbox"/> has a mix of pending and granted statuses under the FCC ID(s) listed below: i) FCC ID: ii) FCC ID:

3.6 Sample information

Receipt date:	2012-06-11
----------------------	------------

 Nemko	Section 3: Equipment under test (EUT) details	Product: TDFE-7SH

Nemko sample ID number:	-----
--------------------------------	-------

3.7 EUT technical specifications

Operating band:	Down Link 746–757 MHz, Up Link 776-787 MHz
Operating frequency:	Wideband
Modulation type:	LTE (QAM and QPSK)
Occupied bandwidth:	1,4 MHz – 3 MHz – 5 MHz – 10MHz
Channel spacing:	standard
Emission designator:	D7W
RF Output	Down Link: 10dBm (0,010W) Up Link: 26dBm (0,400W)
Gain	Down Link: 63dB Up Link: 64dB
Antenna type:	External Antenna is not provided, equipment that has an external 50 Ω RF connector
Power source:	28-30 Vdc stand alone 100-240 Vac in subrack with external Ac/Dc power supply

3.8 Operation of the EUT during testing

Details:	Normal working at max gain with max RF power output
-----------------	---

3.9 EUT setup diagram





Nemko Canada Inc.,
303 River Rd, Ottawa, ON, Canada, K1V 1H2

Section 4: Engineering considerations

Product: TDFE-7SH

Section 4: Engineering considerations

4.1 Modifications incorporated in the EUT

Modifications	Modifications performed to the EUT during this assessment None <input checked="" type="checkbox"/> Yes <input type="checkbox"/> , performed by Client <input type="checkbox"/> or Nemko <input type="checkbox"/> Details:
----------------------	---

4.2 Deviations from laboratory tests procedures

Deviations	Deviations from laboratory test procedures None <input checked="" type="checkbox"/> Yes <input type="checkbox"/> - details are listed below:
-------------------	---

4.3 Technical judgment

Judgment	None
-----------------	----------------------

Section 5: Test conditions

5.1 Power source and ambient temperatures

Normal temperature, humidity and air pressure test conditions	Temperature: 15–30 °C Relative humidity: 20–75 % Air pressure: 860–1060 hPa When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.
Power supply range:	The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages $\pm 5\%$, for which the equipment was designed.



Nemko Canada Inc.,
303 River Rd, Ottawa, ON, Canada, K1V 1H2

Section 6: Measurement uncertainty

Product: TDFE-7SH

Section 6: Measurement uncertainty

Nemko S.p.A. measurement uncertainty has been calculated using the standard CISPR 16-4-2 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainties, statistics and limit modeling – Uncertainty in EMC measurements". All calculations have been performed to provide a confidence level of 95 % and can be found in Nemko S.p.A. document WML1002.

Section 7: Test equipment

Identification number	Description	Manufacturer model	s/n	Cal. Due
1a	Vector Signal Generator	Agilent N5182A MXG	MY48180714	May 2013
1b	Vector Signal Generator	Agilent E4438C ESG	MY45094485	Ago 2013
2a	Spectrum Analyzer	Agilent E4440A	US40420470	Jul 2012
2b	Spectrum Analyzer	Agilent E9020A MXA	MY48011812	Jul 2012
3	Network Analyzer	Agilent E5071B	MY42301133	Jan 2013
4	Climatic chamber	Angelantoni Hygros 600	7237	Nov 2014

Client's property

Identification number	Equipment	Manufacturer	Model	Serial N°	Cal. due
1	Trilog Broadband Antenna	Schwarzbeck	VULB 9163	VULB 9163-286	04/2013
2	Bilog antenna	Schwarzbeck	STLP 9148-123	123	09/2012
3	Double ridge waveguide horn	Spin	DRH40	061106A40	09/2013
4	Broadband preamplifier	Schwarzbeck	BBV 9718	9718-137	05/2013
5	Broadband preamplifier	Miteq	JS44	1648665	05/2013
6	Spectrum Analyzer 9kHz-40GHz	R&S	FSEK	848255/005	09/2012
7	Controller	EMCO	2090	9511-1099	NSC
8	Antenna Tower	EMCO	2071-2	9601-1940	NSC
9	Turning table Controller	EMCO	1061-1.521	9012-1508	NSC
10	Semi-anechoic chamber	Nemko	3m semi-anechoic chamber	70	04/2013
11	Control room	Siemens	3m control room	3	NSC

Property of Nemko Italy



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.50(b) Peak output power at RF antenna connector		
Test date: 11-20 June 2012	Test engineer: G. Curioni	
Verdict: Pass	Supply input: 100-240 Vac	
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Section 8: Testing data

8.1 Clause 27.50(b) Peak output power at RF antenna connector

§ 27.50(b) Operation within the bands: 746–763 MHz, 775–793 MHz and 805–806 MHz.

- (1) Fixed and base stations transmitting a signal in the 757–758 and 775–776 MHz bands must not exceed an effective radiated power (ERP) of 1000 watts and an antenna height of 305 m height above average terrain (HAAT), except that antenna heights greater than 305 m HAAT are permitted if power levels are reduced below 1000 watts ERP in accordance with Table 1 of this section.
- (2) Fixed and base stations transmitting a signal in the 746–757 MHz, 758–763 MHz, 776–787 MHz, and 788–793 MHz bands with an emission bandwidth of 1 MHz or less must not exceed an ERP of 1000 watts and an antenna height of 305 m HAAT, except that antenna heights greater than 305 m HAAT are permitted if power levels are reduced below 1000 watts ERP in accordance with Table 1 of this section.
- (3) Fixed and base stations located in a county with population density of 100 or fewer persons per square mile, based upon the most recently available population statistics from the Bureau of the Census, and transmitting a signal in the 746–757 MHz, 758–763 MHz, 776–787 MHz, and 788–793 MHz bands with an emission bandwidth of 1 MHz or less must not exceed an ERP of 2000 watts and an antenna height of 305 m HAAT, except that antenna heights greater than 305 m HAAT are permitted if power levels are reduced below 2000 watts ERP in accordance with Table 2 of this section.
- (4) Fixed and base stations transmitting a signal in the 746–757 MHz, 758–763 MHz, 776–787 MHz, and 788–793 MHz bands with an emission bandwidth greater than 1 MHz must not exceed an ERP of 1000 watts/MHz and an antenna height of 305 m HAAT, except that antenna heights greater than 305 m HAAT are permitted if power levels are reduced below 1000 watts/MHz ERP in accordance with Table 3 of this section.
- (5) Fixed and base stations located in a county with population density of 100 or fewer persons per square mile, based upon the most recently available population statistics from the Bureau of the Census, and transmitting a signal in the 746–757 MHz, 758–763 MHz, 776–787 MHz, and 788–793 MHz bands with an emission bandwidth greater than 1 MHz must not exceed an ERP of 2000 watts/MHz and an antenna height of 305 m HAAT, except that antenna heights greater than 305 m HAAT are permitted if power levels are reduced below 2000 watts/MHz ERP in accordance with Table 4 of this section.
- (6) Licensees of fixed or base stations transmitting a signal in the 746–757 MHz, 758–763 MHz, 776–787 MHz, and 788–793 MHz bands at an ERP greater than 1000 watts must comply with the provisions set forth in paragraph (b)(8) of this section and §27.55(c).
- (7) Licensees seeking to operate a fixed or base station located in a county with population density of 100 or fewer persons per square mile, based upon the most recently available population statistics from the Bureau of the Census, and transmitting a signal in the 746–757 MHz, 758–763 MHz, 776–787 MHz, and 788–793 MHz bands at an ERP greater than 1000 watts must:
 - (i) coordinate in advance with all licensees authorized to operate in the 698–763 MHz, 775–793, and 805–806 MHz bands within 120 kilometers (75 miles) of the base or fixed station
 - (ii) coordinate in advance with all regional planning committees, as identified in §90.527 of this chapter, with jurisdiction within 120 kilometers (75 miles) of the base or fixed station



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.50(b) Peak output power at RF antenna connector		
Test date: 11-20 June 2012	Test engineer: G. Curioni	
Verdict: Pass	Supply input: 100-240 Vac	
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

(8) Licensees authorized to transmit in the 746–757 MHz, 758–763 MHz, 776–787 MHz, and 788–793 MHz bands and intending to operate a base or fixed station at a power level permitted under the provisions of paragraph (b)(6) of this section must provide advanced notice of such operation to the Commission and to licensees authorized in their area of operation. Licensees who must be notified are all licensees authorized to operate in the 763–775 MHz and 793–805 MHz bands under part 90 of this chapter within 75 km of the base or fixed station and all regional planning committees, as identified in §90.527 of this chapter, with jurisdiction within 75 km of the base or fixed station. Notifications must provide the location and operating parameters of the base or fixed station, including the station's ERP, antenna coordinates, antenna height above ground, and vertical antenna pattern, and such notifications must be provided at least 90 days prior to the commencement of station operation.

(9) Control stations and mobile stations transmitting in the 746–757 MHz, 758–763 MHz, 776–793 MHz, and 805–806 MHz bands and fixed stations transmitting in the 787–788 MHz and 805–806 MHz bands are limited to 30 watts ERP.

(10) Portable stations (hand-held devices) transmitting in the 746–757 MHz, 758–763 MHz, 776–793 MHz, and 805–806 MHz bands are limited to 3 watts ERP.

(11) For transmissions in the 757–758, 775–776, 787–788, and 805–806 MHz bands, maximum composite transmit power shall be measured over any interval of continuous transmission using instrumentation calibrated in terms of RMS-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, etc., so as to obtain a true maximum composite measurement for the emission in question over the full bandwidth of the channel.

(12) For transmissions in the 746–757, 758–763, 776–787, and 788–793 MHz bands, licensees may employ equipment operating in compliance with either the measurement techniques described in paragraph (b)(11) of this section or a Commission-approved average power technique. In both instances, equipment employed must be authorized in accordance with the provisions of §27.51

Special notes

- The power was measured using spectrum analyzer with RMS detector / average power meter.



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.50(b) Peak output power at RF antenna connector		
Test date: 11-20 June 2012	Test engineer: G. Curioni	
Verdict: Pass	Supply input: 100-240 Vac	
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		



Test data

Direction	Modulation	Frequency (MHz)	RF output Power (dBm)	RF output channel Power (W)	PAR (dB)
Down-link	LTE (QAM, 1,4MHz)	751.5	10.00	0.010	9.85
Down-link	LTE (QPSK, 1,4MHz)	751.5	10.08	0.010	9.69
Down-link	LTE (QAM, 3MHz)	751.5	10.14	0.010	10.39
Down-link	LTE (QPSK, 3MHz)	751.5	10.05	0.010	10.64
Down-link	LTE (QAM, 5MHz)	751.5	10.03	0.010	10.52
Down-link	LTE (QPSK, 5MHz)	751.5	10.04	0.010	10.01
Down-link	LTE (QAM, 10MHz)	751.5	10.01	0.010	11.10
Down-link	LTE (QPSK, 10MHz)	751.5	10.04	0.010	11.61
Up-link	LTE (QAM, 1,4MHz)	781.5	26.10	0.407	9.42
Up-link	LTE (QPSK, 1,4MHz)	781.5	26.09	0.406	9.05
Up-link	LTE (QAM, 3MHz)	781.5	26.24	0.421	9.44
Up-link	LTE (QPSK, 3MHz)	781.5	26.26	0.423	9.75
Up-link	LTE (QAM, 5MHz)	781.5	26.16	0.403	9.94
Up-link	LTE (QPSK, 5MHz)	781.5	26.20	0.417	9.37
Up-link	LTE (QAM, 10MHz)	781.5	26.01	0.400	10.57
Up-link	LTE (QPSK, 10MHz)	781.5	26.14	0.412	10.77





Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.50(b) Peak output power at RF antenna connector		
Test date: 11-20 June 2012	Test engineer: G. Curioni	
Verdict: Pass	Supply input: 100-240 Vac	
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 1,4MHz (Down-link)





Mod. LTE 3MHz (Down-link)







Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.50(b) Peak output power at RF antenna connector		
Test date: 11-20 June 2012	Test engineer: G. Curioni	
Verdict: Pass	Supply input: 100-240 Vac	
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 3MHz (Down-link)





Mod. LTE 10MHz (Down-link)







Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.50(b) Peak output power at RF antenna connector		
Test date: 11-20 June 2012	Test engineer: G. Curioni	
Verdict: Pass	Supply input: 100-240 Vac	
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 1.4MHz (Up-link)




Mod. LTE 3MHz (Up-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.50(b) Peak output power at RF antenna connector		
Test date: 11-20 June 2012	Test engineer: G. Curioni	
Verdict: Pass	Supply input: 100-240 Vac	
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 5MHz (Up-link)



Mod. LTE 10MHz (Up-link)





Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.52 RF safety		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

8.2 Clause 27.52 RF safety

Licensees and manufacturers are subject to the radio frequency radiation exposure requirements specified in sections 1.1307(b), 2.1091, and 2.1093 of this chapter, as appropriate. Applications for equipment authorization of mobile or portable devices operating under this section must contain a statement confirming compliance with these requirements for both fundamental emissions and unwanted emissions. Technical information showing the basis for this statement must be submitted to the Commission upon request.

Special notes

The test was performed using E-field probe slowly moving towards the EUT until E-field equivalent to the maximum permitted power density was measured

Equivalent power density was calculated from electric field strength as follows:

$$S_{[mW/cm^2]} = \frac{0.1 \times E^2 [V/m]}{120 \times \pi} \quad S[W/m^2] = E^2 [V/m] / 377 [\Omega]$$

where S is power density and E is electric field strength.

Test data

Test distance (cm)	Field strength (V/m)	Equivalent power density (mW/cm ²)	Limit (mW/cm ²)	Margin (mW/cm ²)
300				
250				
200				
150				
100				
50				
30				
20				
10				
5				

NOT APPLICABLE; External Antenna is not provided.



Section 8: Testing data	Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector	
Test date: 11-20 June 2012	Test engineer: G. Curioni
Verdict: Pass	Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa
Specification: FCC Part 27	Relative humidity: 50 %

8.3 Clause 27.53 (c) Spurious emissions at RF antenna connector

(c) For operations in the 746–758 MHz band and the 776–788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746–758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (2) On any frequency outside the 776–788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (3) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;
- (6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

Special notes

- The spectrum was searched from 30 MHz to the 10th harmonic.
- All measurements were performed using a peak detector.
- RBW within 30–1000 MHz was 100 kHz and 30 kHz for bandedge; 1 MHz above 1 GHz. VBW was wider than RBW.



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012	Test engineer: G. Curioni	
Verdict: Pass	Supply input: 100-240 Vac	
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Test data			
Insert plots here			
Spurious emissions measurement results:			
Frequency (MHz)	Spurious emission (dBm)	Limit (dBm)	Margin (dB)
Low channel			
First channel Down-link	Negligible	-13	
First channel Up-link	Negligible	-13	
Mid channel			
751,5 MHz Down-link	Negligible	-13	
781,5 MHz Down-link	Negligible	-13	
High channel			
Last channel Down-link	Negligible	-13	
Last channel Up-link	Negligible	-13	


See Plots below




Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Test data, continued band edges Inter modulation:

Mod. LTE 1.4MHz (QAM) (Down-link)




Mod. LTE 1.4MHz (QAM) (Up-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 1.4MHz (QPSK) (Down-link)




Mod. LTE 1.4MHz (QPSK) (Up-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 3MHz (QAM) (Down-link)




Mod. LTE 3MHz (QAM) (Up-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 3MHz (QPSK) (Down-link)




Mod. LTE 3MHz (QPSK) (Up-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 5MHz (QAM) (Down-link)




Mod. LTE 5MHz (QAM) (Up-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 5MHz (QPSK) (Down-link)




Mod. LTE 5MHz (QPSK) (Up-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 10MHz (QAM) (Down-link)




Mod. LTE 10MHz (QAM) (Up-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 10MHz (QPSK) (Down-link)



Mod. LTE 10MHz (QPSK) (Up-link)









Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012	Test engineer: G. Curioni	
Verdict: Pass	Supply input: 100-240 Vac	
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Clause 24.238 Spurious emissions at antenna terminal,

Mod. LTE 1.4MHz (QAM) (Down-link)







Only 1,4 QAM (Down-link) spurious emission plots are included here, other modulations spurious emission plots are negligible and the same.



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 1.4MHz (QAM) (Up-link)







Only 1,4 QAM (Up-link) spurious emission plots are included here, other modulations spurious emission plots are negligible and the same.



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 1.4MHz (QPSK) (Down-link)







Only 1,4 QPSK (Down-link) spurious emission plots are included here, other modulations spurious emission plots are negligible and the same.



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 1.4MHz (QPSK) (Up-link)





Only 1,4 QPSK (Up-link) spurious emission plots are included here, other modulations spurious emission plots are negligible and the same.





Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 3MHz, only 30M-1G plot (Down-link)





Mod. LTE 3MHz, only 30M-1G plot (Up-link)







Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 5MHz, only 30M-1G plot (Down-link)





Mod. LTE 5MHz, only 30M-1G plot (Up-link)







Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27. 53 (c) Spurious emissions at RF antenna connector		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 10MHz, only 30M-1G plot (Down-link)



Mod. LTE 10MHz, only 30M-1G plot (Up-link)





Section 8: Testing data	Product: TDFE-7SH	
Test name: Clause 27.53 (c) Radiated spurious emissions		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

8.4 Clause 27.53 (c) Radiated spurious emissions

(c) For operations in the 746–758 MHz band and the 776–788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746–758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (2) On any frequency outside the 776–788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (3) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;
- (6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

Special notes

- The spectrum was searched from 30 MHz to the 10th harmonic.
- All measurements were performed using a peak detector.
- The measurements were performed at the distance of 3 m.
- RBW within 30–1000 MHz was 100 kHz and 1 MHz above 1 GHz. VBW was wider than RBW.



Section 8: Testing data	Product: TDFE-7SH	
Test name: Clause 27.53 (c) Radiated spurious emissions		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Test Data:

The D.U.T. was positioned according to the radiated emissions set-up

The D.U.T. antenna connector was terminated by a 50 Ω shielded dummy load.

The spectrum was searched from 30 MHz to 1 GHz (RBW 100 kHz) & 1 GHz (RBW 1 MHz) to the tenth harmonic of the carrier.

There were no emissions detected above the noise floor which was at least 20 dB below the specification limit.



Section 8: Testing data	Product: TDFE-7SH
Test name: Clause 27.53 (f) Radiated spurious emissions within 1559-1610MHz band	
Test date: 11-20 June 2012	Test engineer: G. Curioni
Verdict: Pass	Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa
Specification: FCC Part 27	Relative humidity: 50 %

8.5 Clause 27.53(f) Radiated spurious emissions within 1559–1610 MHz band

(f) For operations in the 746–763 MHz, 775–793 MHz, and 805–806 MHz bands, emissions in the band 1559–1610 MHz shall be limited to –70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and –80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

Special notes


- The spectrum was searched from 1559–1610 MHz.
- All measurements were performed using a peak detector.
- The measurements were performed at the distance of 3 m.
- RBW was set to 1 MHz and VBW was wider than RBW.



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.53 (f) Radiated spurious emissions within 1559-1610MHz band		
Test date: 11-20 June 2012	Test engineer: G. Curioni	
Verdict: Pass	Supply input: 100-240 Vac	
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Result of D.L. 43 dBm, 751.5 MHz, "1.4" QAM occupied bandwidth 1.2 MHz

(the same for "10"QAM occupied bandwidth 9 MHz)





Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.53 (f) Radiated spurious emissions within 1559-1610MHz band		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

D.L. 43 dBm 751.5 MHz

Spurious emissions measurement results:				
Frequency (MHz)	Polarization. V/H	Result Eirp (dBm)	Limit eirp (dBm)	Margin (dB)
1563.49	V(max. eirp)	-53.08	-50	-3.08
Note:				
. Method of measurement according to TIA-603-C (EIRP in GNSS band: 1.556 to 1.610 GHz) .				
Δ Band = 51 MHz, Correction Factor calculated at central band 1604.5 MHz. in Fraunhofer Region.				


Limit used for discrete emissions: -80 dBw = -50 dBm



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.53 (f) Radiated spurious emissions within 1559-1610MHz band		
Test date: 11-20 June 2012	Test engineer: G. Curioni	
Verdict: Pass	Supply input: 100-240 Vac	
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Result of U.L. 4 dBm, 781.5 MHz, "1.4" QAM occupied bandwidth 1.2 MHz

(the same for "10"QAM occupied bandwidth 9 MHz)



Date: 20.JUN.2012 12:37:51



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.53 (f) Radiated spurious emissions within 1559-1610MHz band		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

U.L. 4 dBm 781.5 MHz

Spurious emissions measurement results:				
Frequency (MHz)	Polarization. V/H	Result Eirp (dBm)	Limit eirp (dBm)	Margin (dB)
1586.49	V(max. eirp)	-53.15	-50	-3.15
Note:				
. Method of measurement according to TIA-603-C (EIRP in GNSS band: 1.556 to 1.610 GHz) .				
Δ Band = 51 MHz, Correction Factor calculated at central band 1604.5 MHz. in Fraunhofer Region.				

Limit used for discrete emissions: -80 dBw = -50 dBm



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.54 Frequency Stability		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

8.6 Clause 27.54 Frequency stability

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

Special notes


- 26 dBc points including frequency tolerance were assessed to remain within assigned band.
- The resolution bandwidth was set to 100 kHz, video bandwidth was set to 100 kHz



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.54 Frequency Stability		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Test data

26 dBc points measurement:



Down-link

Frequency tolerance measurements:


Test conditions	Δ Frequency (Hz)	Offset (Hz)
+50 °C, Nominal	141500	0
+40 °C, Nominal	141500	0
+30 °C, Nominal	141500	0
+20 °C, +15 %	141500	0
+20 °C, Nominal	141500	Reference
+20 °C, -15 %	141500	0
+10 °C, Nominal	141500	0
0 °C, Nominal	141500	0
-10 °C, Nominal	141500	0
-20 °C, Nominal	EUT doesn't work	
-30 °C, Nominal	EUT doesn't work	



Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 27.54 Frequency Stability		
Test date: 11-20 June 2012	Test engineer: G. Curioni	
Verdict: Pass	Supply input: 100-240 Vac	
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Test data

26 dBc points measurement:



Frequency tolerance measurements:

Test conditions	Δ Frequency (Hz)	Offset (Hz)
+50 °C, Nominal	141500	0
+40 °C, Nominal	141500	0
+30 °C, Nominal	141500	0
+20 °C, +15 %	141500	0
+20 °C, Nominal	141500	Reference
+20 °C, -15 %	141500	0
+10 °C, Nominal	141500	0
0 °C, Nominal	141500	0
-10 °C, Nominal	141500	0
-20 °C, Nominal	EUT doesn't work	
-30 °C, Nominal	EUT doesn't work	



Section 8: Testing data	Product: TDFE-7SH
Test name: Clause 2.1049 Occupied bandwidth	
Test date: 11-20 June 2012	Test engineer: G. Curioni
Verdict: Pass	Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa
Specification: FCC Part 27	Relative humidity: 50 %

8.7 Clause 2.1049 Occupied bandwidth

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


Special notes

- 26 dBc points provided in terms of attenuation below unmodulated carrier.
- RBW was set to 1 % of emissions bandwidth.




Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 1.4MHz (QAM) (Down-link)




Mod. LTE 1.4MHz (QPSK) (Down-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 3MHz (QAM) (Down-link)




Mod. LTE 3MHz (QPSK) (Down-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 5MHz (QAM) (Down-link)




Mod. LTE 5 MHz (QPSK) (Down-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 10MHz (QAM) (Down-link)




Mod. LTE 10MHz (QPSK) (Down-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 1.4MHz (QAM) (Up-link)




Mod. LTE 1.4MHz (QPSK) (Up-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 3MHz (QAM) (Up-link)




Mod. LTE 3MHz (QPSK) (Up-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 5MHz (QAM) (Up-link)




Mod. LTE 5MHz (QPSK) (Up-link)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 10MHz (QAM) (Up-link)



Mod. LTE 10MHz (QPSK) (Up-link)





Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

8.8 Clause 2.1047 Modulation characteristics

Unless specified elsewhere in this part, stations will be authorized emissions as provided for in paragraphs (b) through (n) of this section.

§ 2.1047 Measurements required: Modulation characteristics.

- (a) Voice modulated communication equipment. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be submitted. For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter, or of all circuitry installed between the modulation limiter and the modulated stage shall be submitted.
- (b) Equipment which employs modulation limiting. A curve or family of curves showing the percentage of modulation versus the modulation input voltage shall be supplied. The information submitted shall be sufficient to show modulation limiting capability throughout the range of modulating frequencies and input modulating signal levels employed.
- (c) Single sideband and independent sideband radiotelephone transmitters which employ a device or circuit to limit peak envelope power. A curve showing the peak envelope power output versus the modulation input voltage shall be supplied. The modulating signals shall be the same in frequency as specified in paragraph (c) of §2.1049 for the occupied bandwidth tests.
- (d) Other types of equipment. A curve or equivalent data which shows that the equipment will meet the modulation requirements of the rules under which the equipment is to be licensed.

Test date: 2012-06-11

Test results: Pass



Test data

None





Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 1.4MHz (QAM)




Mod. LTE 1.4MHz (QPSK)






Section 8: Testing data		Product: TDCE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 3MHz (QAM)




Down-link




Up-link

Mod. LTE 3MHz (QPSK)



Down-link




Up-link




Section 8: Testing data		Product: TDPE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		

Mod. LTE 5MHz (QAM)




Mod. LTE 5MHz (QPSK)






Section 8: Testing data		Product: TDFE-7SH
Test name: Clause 2.1049 Occupied bandwidth		
Test date: 11-20 June 2012		Test engineer: G. Curioni
Verdict: Pass		Supply input: 100-240 Vac
Temperature: 25 °C	Air pressure: 860-1060 hPa	Relative humidity: 50 %
Specification: FCC Part 27		


Mod. LTE 10MHz (QAM)



Mod. LTE 10MHz (QPSK)




Section 9: Filter Frequency Response



Section 10: Block diagrams of test set-ups

Radiated emissions set-up



Section 11: EUT photos

Photo Set up





Photo EUT



