



## 47 CFR PART 22 SUBPART H & 24 SUBPART E

# TEST REPORT

of

### GPS TRACKER

Model Name: GT300  
Brand Name: QUECTEL  
Report No.: SH09070021BR01  
FCC ID: XMR-16182009001

*prepared for*

**Quectel Wireless Solutions Co.,Ltd**

Room 801, Building E, No 1618 Yishan Road, Shanghai, China, 201103

*prepared by*

**Shenzhen Electronic Product Quality Testing Center**

**Morlab Laboratory**

3/F, Electronic Testing Building, Shahe Road, Xili,  
Nanshan District, Shenzhen, 518055 P. R. China

Tel: +86 755 86130398

Fax: +86 755 86130218



**CTIA Authorized Test Lab**  
LAB CODE 20081223-00

**NOTE:** This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.

**TABLE OF CONTENTS**

<b>1. TEST CERTIFICATION.....</b>	<b>4</b>
<b>2. GENERAL INFORMATION .....</b>	<b>5</b>
2.1 EUT Description.....	5
2.2 Test Standards and Results .....	7
2.3 Facilities and Accreditations.....	8
2.3.1 Facilities .....	8
2.3.2 Test Environment Conditions.....	8
<b>3. 47 CFR PART 2, PART 22H REQUIREMENTS .....</b>	<b>9</b>
3.1 Frequencies.....	9
3.1.1 Requirement .....	9
3.1.2 Test Description .....	9
3.1.3 Test Result.....	10
3.2 Conducted RF Output Power.....	15
3.2.1 Requirement .....	15
3.2.2 Test Description .....	15
3.2.3 Test Result.....	15
3.3 20dB Occupied Bandwidth.....	22
3.3.1 Definition .....	22
3.3.2 Test Description .....	22
3.3.3 Test Verdict.....	22
3.4 Frequency Stability.....	29
3.4.1 Requirement .....	29
3.4.2 Test Description .....	29
3.4.3 Test Verdict.....	29
3.5 Conducted Out of Band Emissions.....	31
3.5.1 Requirement .....	31
3.5.2 Test Description .....	31
3.5.3 Test Result.....	31
3.6 Band Edge.....	44
3.6.1 Requirement .....	44
3.6.2 Test Description .....	44

3.6.3	Test Result.....	44
3.7	Transmitter Radiated Power (EIRP/ERP).....	49
3.7.1	Requirement .....	49
3.7.2	Test Description .....	49
3.7.3	Test Result.....	50
3.8	Radiated Out of Band Emissions.....	57
3.8.1	Requirement .....	57
3.8.2	Test Description .....	57
3.8.3	Test Result.....	57
<b>APPENDIX I:</b>	<b>PHOTOGRAPH OF THE TEST SETUP.....</b>	<b>58</b>
<b>APPENDIX II:</b>	<b>PHOTOGRAPH OF THE EUT .....</b>	<b>58</b>



## 1. TEST CERTIFICATION

Equipment under Test: GPS TRACKER

Brand Name: QUECTEL

Model Name: GT300

FCC ID: XMR-16182009001

Applicant: Quectel Wireless Solutions Co.,Ltd

Room 801, Building E, No 1618 Yishan Road,  
Shanghai, China, 201103

Manufacturer: Quectel Wireless Solutions Co.,Ltd

Room 801, Building E, No 1618 Yishan Road,  
Shanghai, China, 201103

Test Standards: 47 CFR Part 2

47 CFR Part 22 Subpart H

47 CFR Part 24 Subpart E

Test Date(s): July 25, 2009 – July 31, 2009

Test Result: PASS

### \* We Hereby Certify That:

The equipment under test was tested by Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the requirement of related FCC rules.

The test results of this report only apply for the tested sample equipment identified above. The test report shall be invalid without all the signatures of the test engineer, the reviewer and the approver.

Tested by:

Huang Yunlong  
Huang Yunlong

2009.8.14

Reviewed by:


Zhang Jun  
Zhang Jun

2009.8.14

Approved by:

Su Feng  
Su Feng

2009.8.14



## 2. GENERAL INFORMATION

### 2.1 EUT Description

EUT Type .....: GPS TRACKER  
Model Name .....: GT300  
Serial No. ....: N/A  
IMEI .....: N/A  
Hardware Version .....: V1.02  
Software Version .....: B01V10  
Frequency Range .....: GSM 850MHz:  
Tx: 824.20 - 848.80MHz (at intervals of 200kHz);  
Rx: 869.20 - 893.80MHz (at intervals of 200kHz)  
GSM 1900MHz:  
Tx: 1850.20 - 1909.80MHz (at intervals of 200kHz);  
Rx: 1930.20 - 1989.80MHz (at intervals of 200kHz)  
Modulation Type.....: GMSK  
Emission Designators .....: 300KGXW  
Ancillary Equipments.....:  
AC Adapter:  
Model Name: P-051B-050050  
Brand Name: SOMETHING  
Serial No.: (n.a. marked #1 by test site)  
Rated Input: ~100-240V, 0.2A,50/60Hz  
Rated Output: = 5V, 0.5A  
Manufacturer: SOMETHING HIGH ELECTRIC (XIAMEN) Co.,Ltd.  
Manufacturer Address: No.421, Xiahushe, Houkengshe Area, Huli Industrial Park, Xiamen, China  
Wire Length: 120cm  
Battery:  
Model Name: BP85A(JLFT)  
Brand Name: JIADE  
Serial No.: (n.a. marked #1 by test site)  
Capacitance: 850mAh  
Rated Voltage: 3.7V  
Charge Limit: 4.2V  
Manufacturer: Jiade Energy Technology(ZHUHAI)Co.,Ltd.  
Manufacturer Address: 2/F,Helping Industrial Center Building,#209 Shihua Road West, Jida Area Zhuhai, China

*Note 1:* The EUT is a GPS tracker operating in GSM 850MHz, GSM 900MHz, GSM 1800MHz, GSM1900MHz bands, the GSM 850MHz and GSM1900MHz are tested in this report.

*Note 2:* The transmitter (Tx) frequency arrangement of the Cellular 850MHz band used by the EUT can be represented with the formula  $F(n)=824.2+0.2*(n-128)$ ,  $128 \leq n \leq 251$ ; the lowest, middle, highest channel numbers (ARFCHs) used and tested in this report are separately 128 (824.2MHz), 190 (836.6MHz) and 251 (848.8MHz).

*Note 3:* The transmitter (Tx) frequency arrangement of the PCS 1900MHz band used by the EUT can be represented with the formula  $F(n)=1850.2+0.2*(n-512)$ ,  $512 \leq n \leq 810$ ; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 512 (1850.2MHz), 661 (1880.0MHz) and 810 (1909.8MHz).

*Note 4:* For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

## 2.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 2, Part 22 and Part 24 for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 2 (10-1-05 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 (10-1-05 Edition)	Public Mobile Services
3	47 CFR Part 24 (10-1-05 Edition)	Personal Communications Services

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	2.106 22.905 24.229	Frequencies	PASS
2	2.1046	Conducted RF Output Power	PASS
3	2.1049	20dB Occupied Bandwidth	PASS
4	2.1055 22.355 24.235	Frequency Stability	PASS
5	2.1051 2.1057 22.917 24.238	Conducted Out of Band Emissions	PASS
6	2.1051 2.1057 22.917 24.238	Band Edge	PASS
7	22.913 24.232	Transmitter Radiated Power (EIPR/ERP)	PASS
8	2.1053 2.1057 22.917 24.238	Radiated Out of Band Emissions	PASS

## 2.3 Facilities and Accreditations

### 2.3.1 Facilities

Shenzhen Electronic Product Quality Testing Center Morlab Laboratory is a testing organization accredited by China National Accreditation Board for Laboratories (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

All measurement facilities used to collect the measurement data are located at Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen 518055 CHINA. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

### 2.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	20 - 25
Relative Humidity (%):	40 - 60
Atmospheric Pressure (kPa):	960

### 3. 47 CFR PART 2, PART 22H REQUIREMENTS

#### 3.1 Frequencies

##### 3.1.1 Requirement

According to FCC section 22.905, the frequency blocks assignment for the cellular radiotelephone service is listed as below:


- (a) Channel Block A:
  - Mobile 824 - 835MHz, Base 869 - 880MHz;
  - Mobile 845 - 846.5MHz, Base 890 - 891.5MHz
- (b) Channel Block B:
  - Mobile 835 - 845 MHz, Base 880 - 890MHz;
  - Mobile 846.5 - 849 MHz, Base 891.5 - 894MHz

According to FCC section 24.229, the frequencies available in the Broadband PCS services are listed as below, in accordance with the frequency allocations table of FCC section 2.106.

- (a) The following frequency blocks are available for assignment on an MTA basis:
  - Block A: 1850 - 1865MHz paired with 1930 - 1945MHz;
  - Block B: 1870 - 1885MHz paired with 1950 - 1965MHz.
- (b) The following frequency blocks are available for assignment on a BTA basis:
  - Block C: 1895 - 1910 MHz paired with 1975 - 1990MHz;
  - Block D: 1865 - 1870 MHz paired with 1945 - 1950MHz;
  - Block E: 1885 - 1890 MHz paired with 1965 - 1970MHz;
  - Block F: 1890 - 1895 MHz paired with 1970 - 1975MHz.

##### 3.1.2 Test Description

###### 1. Test Setup:



The EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna

terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

## 2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	Anritsu	MT8820A	6100255046	2009.06	1year
Spectrum Analyzer	Rohde-Schwarz	FSEM	DE23811	2009.07	1year
Power Splitter	Weinschel	1506A	NW521	(n.a.)	(n.a.)
Attenuator 1	Resnet	10dB	(n.a.)	(n.a.)	(n.a.)

### 3.1.3 Test Result


The Tx frequency arrangement of the Cellular 850MHz band employed by the EUT should be from 824.2MHz to 848.8MHz (the corresponding frequency block is from 824MHz to 849MHz), and Tx frequency arrangement of the PCS 1900MHz band employed by the EUT should be from 1850.2MHz to 1909.8MHz (the corresponding frequency block is from 1850MHz to 1910MHz). Here the lowest and highest channels are tested to verify the EUT's using the frequency block required.

#### 1. Test Verdict:


The required frequency block is employed legally, the verdict is PASS.

Band	Channel	Frequency (MHz)	Measured Carrier (dBm)	Refer to Plot
GSM 850MHz	128	824.2	25.86	Plot A1
	251	848.8	24.03	Plot B1
GSM 1900MHz	512	1850.2	22.30	Plot C1
	810	1909.8	20.72	Plot D1
GPRS 850MHz	128	824.2	22.12	Plot A2
	251	848.8	20.93	Plot B2
GPRS 1900MHz	512	1850.2	19.42	Plot C2
	810	1909.8	20.47	Plot D2


## 2. Test Plot of GSM:




(Plot A1:GSM 850MHz Channel = 128)



(Plot B1:GSM 850MHz Channel = 251)




(Plot C1:GSM 1900MHz Channel = 512)




(Plot D1:GSM 1900MHz Channel = 810)


### 3. Test Plot of GPRS:




(Plot A2: GPRS 850MHz Channel =128 )



(Plot B2: GPRS 850MHz Channel =251 )



(Plot C2: GPRS 1900MHz Channel =512 )



(Plot D2: GPRS 1900MHz Channel =810 )

## 3.2 Conducted RF Output Power

### 3.2.1 Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

### 3.2.2 Test Description

See section 3.1.2 of this report.


### 3.2.3 Test Result

Here the lowest, middle and highest channels are selected to perform testing to verify the conducted RF output power of the EUT. For the GSM 850MHz operates at PCL=5 (where Power Class is 4), the rated conducted RF output power is 33dBm within the tolerance of  $\pm 3$ dB, and For the GSM 1900MHz operates at PCL=0 (where Power Class is 1), the rated conducted RF output power is 30dBm within the tolerance of  $\pm 3$ dB.


#### 1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Output Power		Rated Output Power		Verdict
			dBm	Refer to Plot	dBm	Tolerance (dB)	
GSM 850MHz	128	824.2	32.42	Plot A1	33	$\pm 3$	PASS
	190	836.6	32.56	Plot B1			PASS
	251	848.8	32.48	Plot C1			PASS
GSM 1900MHz	512	1850.2	29.67	Plot D1	30	$\pm 3$	PASS
	661	1880.0	29.66	Plot E1			PASS
	810	1909.8	29.79	Plot F1			PASS
GPRS 850MHz	128	824.2	28.70	Plot A2	33	$\pm 3$	PASS
	190	836.6	29.10	Plot B2			PASS
	251	848.8	28.96	Plot C2			PASS
GPRS 1900MHz	512	1850.2	27.15	Plot D2	30	$\pm 3$	PASS
	661	1880.0	27.14	Plot E2			PASS
	810	1909.8	27.32	Plot F2			PASS


## 2. Test Plot of GSM




(Plot A1:GSM 850MHz Channel = 128)




(Plot B1:GSM 850MHz Channel = 190)




(Plot C1:GSM 850MHz Channel = 251)



(Plot D1:GSM 1900MHz Channel = 512)




(Plot E1:GSM 1900MHz Channel = 661)




(Plot F1:GSM 1900MHz Channel = 810)


### 3. Test Plot of GPRS




(Plot A2: GPRS 850MHz Channel =128)




(Plot B2: GPRS 850MHz Channel =190 )




(Plot C2: GPRS 850MHz Channel =251 )



(Plot D2: GPRS 1900MHz Channel =512 )



(Plot E2: GPRS 1900MHz Channel =661 )



(Plot F2: GPRS 1900MHz Channel =810 )

### 3.3 20dB Occupied Bandwidth

#### 3.3.1 Definition

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

Occupied bandwidth is also known as the 99% emission bandwidth, or 20dB bandwidth ( $10 \times \log 1\% = 20\text{dB}$ ) taking the total RF output power as reference.

#### 3.3.2 Test Description

See section 3.1.2 of this report.


#### 3.3.3 Test Verdict

Here the lowest, middle and highest channels are tested to record the 20dB occupied bandwidth, it's about 300kHz.


##### 1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured 20dB Occupied Bandwidth (kHz)	Refer to Plot
GSM 850MHz	128	824.2	288	Plot A1
	190	836.6	288	Plot B1
	251	848.8	270	Plot C1
GSM 1900MHz	512	1850.2	282	Plot D1
	661	1880.0	264	Plot E1
	810	1909.8	282	Plot F1
GPRS 850MHz	128	824.2	282	Plot A2
	190	836.6	282	Plot B2
	251	848.8	288	Plot C2
GPRS 1900MHz	512	1850.2	288	Plot D2
	661	1880.0	288	Plot E2
	810	1909.8	282	Plot F2


## 2. Test Plot of GSM




(Plot A1:GSM 850MHz Channel = 128)




(Plot B1:GSM 850MHz Channel = 190)




(Plot C1:GSM 850MHz Channel = 251)



(Plot D1:GSM 1900MHz Channel = 512)




(Plot E1:GSM 1900MHz Channel = 661)




(Plot F1:GSM 1900MHz Channel = 810)


### 3. Test Plot of GPRS




(Plot A2;GPRS 850MHz Channel = 128)




(Plot B2;GPRS 850MHz Channel = 190)




(Plot C2:GPRS 850MHz Channel = 251)



(Plot D2:GPRS 1900MHz Channel = 512)



(Plot E2:GPRS 1900MHz Channel = 661)



(Plot F2:GPRS 1900MHz Channel = 810)

## 3.4 Frequency Stability


### 3.4.1 Requirement

According to FCC section 22.355 and FCC section 24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- (a) The temperature is varied from -30°C to +50°C at intervals of not more than 10°C.
- (b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

### 3.4.2 Test Description

#### 1. Test Setup:



The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS via a Common Antenna.

#### 2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	Anritsu	MT8820A	6100255046	2009.06	1year
DC Power Supply	Good Will	GPS-3030DD	EF920938	2009.06	2year
Temperature Chamber	YinHe Experimental Equip.	HL4003T	(n.a.)	2009.03	1year

### 3.4.3 Test Verdict

The nominal, highest and lowest extreme voltages are separately 3.7VDC, 4.2VDC and 3.6VDC, which are specified by the applicant; the normal temperature here used is 25°C. The frequency

deviation limit is  $\pm 2.5$ ppm.

Band	Test Conditions		Frequency Deviation						Verdict	
	Power (VD C)	Temperature (°C)	Channel = 128 (824.2MHz)		Channel = 190 (836.6MHz)		Channel = 251 (848.8MHz)			
			Hz	Limit	Hz	Limit	Hz	Limit		
GSM 850MHz	3.7	-30	-11.24	$\pm 2060.5$	11.52	$\pm 2091.5$	-13.59	$\pm 2122.0$	PASS	
		-20	15.11		-13.37		-10.37			
		-10	13.53		12.01		12.53			
		0	-12.35		10.25		17.21			
		+10	-11.63		11.56		11.58			
		+20	-13.52		-12.63		12.34			
		+30	10.25		9.21		13.46			
		+40	-13.15		-11.59		12.38			
		+50	-11.74		-15.73		12.54			
		4.2	+25		-14.57		13.16			
GSM 1900MHz	3.7	3.6	+25		-12.51		12.18			
		-30	24.35	$\pm 1550.2$	-23.47	$\pm 1550.0$	19.64	$\pm 1707.5$	PASS	
		-20	17.15		16.20		13.55			
		-10	-12.34		9.21		-12.35			
		0	13.46		11.47		-11.56			
		+10	10.27		15.45		13.16			
		+20	15.28		21.54		-22.22			
		+30	-11.76		-12.47		-11.62			
		+40	-15.77		13.25		13.06			
		+50	13.32		21.90		-17.24			
		4.2	+25		-8.67		-12.53			
		3.6	+25		-15.47		18.53			

## 3.5 Conducted Out of Band Emissions

### 3.5.1 Requirement

According to FCC section 22.717(a) and FCC section 24.235(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$ dB. This calculated to be -13dBm.

### 3.5.2 Test Description

See section 3.1.2 of this report.

### 3.5.3 Test Result

The measurement frequency range is from 30MHz to the 10<sup>th</sup> harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the out of band emissions.


#### 1. Test Verdict:

Band	Channe 1	Frequency (MHz)	Measured Max. Spurious Emission (dBm)	Refer to Plot	Limit (dBm)	Verdic t
GSM 850MHz	128	824.2	-29.18	Plot A1/A2	-13	PASS
	190	836.6	-28.66	Plot B1/B2		PASS
	251	848.8	-29.61	Plot C1/C2		PASS
GSM 1900MHz	512	1850.2	-29.74	Plot D1/D2	-13	PASS
	661	1880.0	-29.84	Plot E1/E2		PASS
	810	1909.8	-29.98	Plot F1/F2		PASS
GSM 850MHz	128	824.2	-25.04	Plot A3/A4	-13	PASS
	190	836.6	-26.51	Plot B3/B4		PASS
	251	848.8	-27.24	Plot C3/C4		PASS
GSM 1900MHz	512	1850.2	-28.43	Plot D3/D4	-13	PASS
	661	1880.0	-27.69	Plot E3/E4		PASS
	810	1909.8	-28.34	Plot F3/F4		PASS


#### 2. Test Plot for the Whole Measurement Frequency Range:

Note: the power of the EUT transmitting frequency should be ignored.


### Test Plot of GSM




(Plot A1:GSM 850MHz Channel = 128, 30MHz to 1GHz)




(Plot A2: GSM 850MHz Channel = 128, 1GHz to 9GHz)




(Plot B1: GSM 850MHz Channel = 190, 30MHz to 1GHz)




(Plot B2:GSM 850MHz Channel = 190, 1GHz to 9GHz)




(Plot C1:GSM 850MHz Channel = 251, 30MHz to 1GHz)




(Plot C2:GSM 850MHz Channel = 251, 1GHz to 9GHz)




(Plot D1:GSM 1900MHz Channel = 512, 30MHz to 2GHz)




(Plot D2:GSM 1900MHz Channel = 512, 2GHz to 20GHz)




(Plot E1:GSM 1900MHz Channel = 661, 30MHz to 2GHz)



(Plot E2:GSM 1900MHz Channel = 661, 2GHz to 20GHz)




(Plot F1:GSM 1900MHz Channel = 810, 30MHz to 2GHz)




(Plot F2:GSM 1900MHz Channel = 810, 2GHz to 20GHz)


## Test Plot of GPRS:




(Plot A3: GPRS 850MHz Channel = 128, 30MHz to 1GHz)




(Plot A4: GPRS 850MHz Channel = 128, 1GHz to 9GHz)




(Plot B3: GPRS 850MHz Channel = 190, 30MHz to 1GHz)




(Plot B4: GPRS 850MHz Channel = 190, 1GHz to 9GHz)




(Plot C3: GPRS 850MHz Channel = 251, 30MHz to 1GHz)




(Plot C4: GPRS 850MHz Channel = 251, 1GHz to 9GHz)




(Plot D3: GPRS 1900MHz Channel = 512, 30MHz to 2GHz)




(Plot D4: GPRS 1900MHz Channel = 512, 2GHz to 20GHz)




(Plot E3: GPRS 1900MHz Channel = 661, 30MHz to 2GHz)



(Plot E4: GPRS 1900MHz Channel = 661, 2GHz to 20GHz)



(Plot F3: GPRS 1900MHz Channel = 810, 30MHz to 2GHz)



(Plot F4: GPRS 1900MHz Channel = 810, 2GHz to 20GHz)

## 3.6 Band Edge

### 3.6.1 Requirement

According to FCC section 22.717(b) and FCC section 24.235(b), in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth (26dB emission bandwidth) of the fundamental emission of the transmitter may be employed.

### 3.6.2 Test Description

See section 3.1.2 of this report.


### 3.6.3 Test Result

The lowest and highest channels are tested to verify the band edge emissions.


#### 1. Test Verdict:

Band	Channe 1	Frequency (MHz)	Measured Max. Band Edge Emission (dBm)	Refer to Plot	Limit (dBm)	Verdict
GSM 850MHz	128	824.2	-13.46	Plot A1	-13	PASS
	251	848.8	-13.27	Plot B1		PASS
GSM 1900MHz	512	1850.2	-13.63	Plot C1	-13	PASS
	810	1909.8	-14.03	Plot D1		PASS
GPRS 850MHz	128	824.2	-13.51	Plot A2	-13	PASS
	251	848.8	-14.93	Plot B2		PASS
GPRS 1900MHz	512	1850.2	-14.84	Plot C2	-13	PASS
	810	1909.8	-16.15	Plot D2		PASS


## 2. Test Plot of GSM:




(Plot A1:GSM 850MHz Channel = 128)



(Plot B1:GSM 850MHz Channel = 251)




(Plot C1: GSM 1900MHz Channel = 512)




(Plot D1: GSM 1900MHz Channel = 810)


### 3. Test Plot of GPRS:




(Plot A2;GPRS 850MHz Channel = 128)



(Plot B2;GPRS 850MHz Channel = 251)



(Plot C2:GPRS 1900MHz Channel = 512)



(Plot D2:GPRS 1900MHz Channel = 810)


### 3.7 Transmitter Radiated Power (EIRP/ERP)

#### 3.7.1 Requirement

According to FCC section 22.713, the Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7Watts, and FCC section 24.232, the broadband PCS mobile station is limited to 2Watts e.i.r.p. peak power.

#### 3.7.2 Test Description

##### 1. Test Setup:



The EUT, which is powered by the Battery charged with the AC Adapter, is located in a 3m Full-Anechoic Chamber; the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. GSM550MHz band Power Control Level (PCL) = 5 and Power Class = 4 and GSM1700MHz band Power Control Level (PCL) = 0 and Power Class = 1. A call is established between the EUT and the SS via a Common Antenna.

The Test Antenna is a Bi-Log one (used for 30MHz to 1GHz) or a Horn one (used for above 3GHz), and it's located at the same height as the EUT. The Filters consists of Notch Filters and High Pass Filter.

## 2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	R&S	CMU200	105571	2008.12	1year
Spectrum Analyzer	R&S	FSP30	101020	2008.10	1year
Full-Anechoic Chamber	ETS • LINDGREN	9m*6m*6m	(n.a.)	2008.10	2year
Bi-Log Antenna	R&S	HL562	100385	2008.10	1year
Horn Antenna	R&S	HF906	100565	2008.10	1year


## 3.7.3 Test Result

The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested.


## 1. Test Verdict:

Band	Chann el	Frequency (MHz)	Measured ERP			Limit		Verdict
			dBm	W	Refer to Plot	dBm	W	
GSM 850MHz	128	824.2	23.66	0.23	Plot A1	35.45	7	PASS
	190	836.6	24.75	0.3	Plot B1			PASS
	251	848.8	23.11	0.2	Plot C1			PASS
GSM 1900MHz	512	1850.2	20.13	0.1	Plot D1	33	2	PASS
	661	1880.0	19.51	0.09	Plot E1			PASS
	810	1909.8	19.13	0.08	Plot F1			PASS
GPRS 850MHz	128	824.2	21.03	0.13	Plot A2	35.45	7	PASS
	190	836.6	21.03	0.13	Plot B2			PASS
	251	848.8	21.09	0.13	Plot C2			PASS
GPRS 1900MHz	512	1850.2	18.52	0.07	Plot D2	33	2	PASS
	661	1880.0	16.88	0.05	Plot E2			PASS
	810	1909.8	16.07	0.04	Plot F2			PASS


## 2. Test Plot of GSM:




(Plot A1:GSM 850MHz Channel = 128)




(Plot B1: GSM 850MHz Channel = 190)




(Plot C1:GSM 850MHz Channel = 251)



(Plot D1: GSM 1900MHz Channel = 512)




(Plot E1: GSM 1900MHz Channel = 661)




(Plot F1: GSM 1900MHz Channel = 810)


## 3. Test Plot of GPRS:




(Plot A2;GPRS 850MHz Channel = 128)




(Plot B2;GPRS 850MHz Channel = 190)




(Plot C2:GPRS 850MHz Channel = 251)



(Plot D2:GPRS 1900MHz Channel = 512)



(Plot E2:GPRS 1900MHz Channel = 661)



(Plot F2:GPRS 1900MHz Channel = 810)

## 3.8 Radiated Out of Band Emissions

### 3.8.1 Requirement

According to FCC section 22.717(a) and section 24.235(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$  dB. This calculated to be -13dBm.

### 3.8.2 Test Description

See section 3.7.2 of this report.

### 3.8.3 Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from  $0^\circ$  to  $360^\circ$ , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

#### 1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Max. Spurious Emission (dBm)		Limit (dBm)	Verdict
			Test Antenna Horizontal	Test Antenna Vertical		
GSM 850MHz	128	824.2	< -30	< -30	-13	PASS
	190	836.6	< -30	< -30		PASS
	251	848.8	< -30	< -30		PASS
GSM 1900MHz	512	1850.2	< -25	< -25	-13	PASS
	661	1880.0	< -25	< -25		PASS
	810	1909.8	< -25	< -25		PASS


**Appendix I: PHOTOGRAPH OF THE TEST SETUP**

## 1. Conducted RF Test

**Appendix II: PHOTOGRAPH OF THE EUT**

## 1. Appearance of the GPS TRACKER







## 2. Inside of the GPS TRACKER



3. Appearance of MS base



4. Appearance of the Charge



5. Cable



\*\* END OF REPORT \*\*