



RF TEST REPORT

Applicant Quectel Wireless Solutions Co., Ltd

FCC ID XMR201910BG95M3

Product LTE Cat M1 & Cat NB2 & EGPRS Module

Brand Quectel

Model BG95-M3, BG95-M3 MINIPCIE

Report No. R2106A0549-R6

Issue Date September 6, 2021

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2020)/ FCC CFR47 Part 27C (2020)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Peng Tao

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1	Test Laboratory	5
1.1	Notes of the Test Report	5
1.2	Test facility	5
1.3	Testing Location	5
2	General Description of Equipment under Test	6
3	Applied Standards	8
4	Test Configuration	9
5	Test Case Results	10
5.1	RF Power Output and Effective Radiated Power	10
5.2	Occupied Bandwidth	15
5.3	Band Edge Compliance	33
5.4	Peak-to-Average Power Ratio (PAPR)	49
5.5	Frequency Stability	51
5.6	Spurious Emissions at Antenna Terminals	59
5.7	Radiates Spurious Emission	69
6	Main Test Instruments	91
ANNEX A: The EUT Appearance		93
ANNEX B: Test Setup Photos		94
ANNEX C: Product Change Description		95

Summary of Measurement Results

Number	Test Case	Clause in FCC rules	Verdict
1	RF Power Output and Effective Isotropic Radiated Power	2.1046 /27.50(d)(4) /27.50(b)(10) /27.50(c)(10)	PASS
2	Occupied Bandwidth	2.1049	PASS
3	Band Edge Compliance	27.53(h) /27.53(g) /27.53(f) /27.53(c)	PASS
4	Peak-to-Average Power Ratio	27.50(d)/KDB971168 D01(5.7)	PASS
5	Frequency Stability	2.1055 / 27.54	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 /27.53(h) /27.53(g) /27.53(f) /27.53(c)	PASS
7	Radiates Spurious Emission	2.1053 /27.53(h) /27.53(g) /27.53(f) /27.53(c)	PASS
Date of Testing (original): March 5, 2020 ~March 30, 2020 and June 6, 2020 ~ June 8, 2020 (variant): July 14, 2021 ~ August 9, 2021			
Note: PASS: The EUT complies with the essential requirements in the standard. FAIL: The EUT does not comply with the essential requirements in the standard. All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			



BG95-M3, BG95-M3 MINIPCIE (Report No.: R2106A0549-R6) is a variant model of BG95-M3, BG95-M3 MINIPCIE (Report No.: R2006A0361-R6V1). The product only changes PA components. Test values duplicated from Original for variant. Test items tested see the table below.

Test Case	original	variant
RF Power Output and Effective Isotropic Radiated Power	PASS	Retest
Occupied Bandwidth	PASS	Retest(NB-IoT band 71)
Band Edge Compliance	PASS	Retest(NB-IoT band 71)
Peak-to-Average Power Ratio	PASS	Refer to original
Frequency Stability	PASS	Refer to original
Spurious Emissions at Antenna Terminals	PASS	Refer to original
Radiates Spurious Emission	PASS	Refer to original

The detailed product change description please refers to the Difference Declaration Letter.



1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

1.3 Testing Location

Company:	TA Technology (Shanghai) Co., Ltd.
Address:	No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Xu Kai
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	http://www.ta-shanghai.com
E-mail:	xukai@ta-shanghai.com

2 General Description of Equipment under Test

Client Information

Applicant	Quectel Wireless Solutions Co., Ltd
Applicant address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233
Manufacturer	Quectel Wireless Solutions Co., Ltd
Manufacturer address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233

General information

EUT Description		
Model	BG95-M3, BG95-M3 MINIPCIE	
IMEI	BG95-M3: 864475048391303 BG95-M3 MINIPCIE: 864475048389810	
Hardware Version	R2.1	
Software Version	BG95M3LAR02A03	
Power Supply	External Power Supply	
Antenna Type	External Antenna	
Antenna Gain	NB-IoT 4: 1.9dBi NB-IoT 12: 4dBi NB-IoT 13: 4.5dBi NB-IoT 66: 2dBi NB-IoT 71: 3dBi NB-IoT 85: 4dBi	
Test Mode(s)	NB-IoT Band 4/12/13/66/71/85	
Test Modulation	BPSK, QPSK	
Category	NB2	
Deployment	stand-alone	
Sub-carrier spacing	3.75KHz, 15KHz	
Ntones	single-tone, multi-tone	
Maximum E.I.R.P.	NB-IoT 4:	22.98dBm
	NB-IoT 66:	23.13dBm
Maximum E.R.P.	NB-IoT 12:	22.47dBm
	NB-IoT 13:	23.28dBm
	NB-IoT 71:	22.77dBm
	NB-IoT 85:	22.63dBm
Rated Power Supply Voltage:	3.8V	
Extreme Voltage	Minimum: 3.3V Maximum: 4.3V	
Extreme Temperature	Lowest: -40°C Highest: +85°C	



Frequency Range(s)	Mode	Tx (MHz)	Rx (MHz)
	NB-IoT Band 4	1710 ~ 1755	2110 ~ 2155
	NB-IoT Band 12	699 ~ 716	729 ~ 746
	NB-IoT Band 13	777 ~ 787	746 ~ 756
	NB-IoT Band 66	1710 ~ 1780	2110 ~ 2180
	NB-IoT Band 71	663 ~ 698	617 ~ 652
	NB-IoT Band 85	698 ~ 716	728 ~ 746
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant. 2. The series model number is: BG95-M3 MINIPCIE. The difference of these models are have different marketing requirement.			



3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR47 Part 27C (2020)

ANSI C63.26 (2015)

Reference standard:

FCC CFR47 Part 2 (2020)

KDB 971168 D01 Power Meas License Digital Systems v03r01

4 Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, horizontal polarization) and the worst case was recorded.

All modes as Subcarrier Spacing, modulations, Channel were investigated.

Subsequently, only the worst case emissions are reported.

The following testing in NB-IoT is set based on the maximum RF Output Power.

The following testing in different mode is set to detail in the following table:

Test modes are chosen to be reported as the worst case configuration below for NB-IoT Band 4/12/13/66/71/85:

Test items	Deployment mode	Subcarrier Spacing (kHz)		Modulation		Test Channel		
	Stand-alone	3.75	15	BPSK	QPSK	L	M	H
RF power output and Effective Radiated Power	O	O	O	O	O	O	O	O
Occupied Bandwidth	O	O	O	O	O	O	O	O
Band Edge Compliance	O	O	O	O	O	O	-	O
Peak-to-Average Power Ratio	O	O	O	O	O	-	O	-
Frequency Stability	O	O	O	O	O	O	O	O
Conducted Spurious Emissions	O	-	O	-	O	O	O	O
Radiates Spurious Emission	O	-	O	-	O	O	O	O
Note 1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.								

5 Test Case Results

5.1 RF Power Output and Effective Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT was connected to the Base Station Simulator with a known loss. The EUT is controlled by the Base Station Simulator test set to ensure max power transmission with proper modulation.


ERP can then be calculated as follows:

$$\text{EIRP (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBi)}$$

where: dBd refers to gain relative to an ideal dipole.

$$\text{EIRP (dBm)} = \text{ERP (dBm)} + 2.15 \text{ (dB)}$$

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

No specific RF power output requirements in part 2.1046.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U=0.4$ dB.



Test Results

Original

Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Conducted Power (dBm) for low/mid/high channel		
				19952/1710.2	20175/1732.5	20398/1754.8
NB-IOT Band 4 Standalone	BPSK	3.75	1@0	20.18	20.19	20.19
			1@47	20.16	20.08	20.12
		15	1@0	20.18	20.12	20.15
			1@11	20.13	20.11	20.11
	QPSK	3.75	1@0	20.14	20.14	20.14
			1@47	20.13	20.17	20.12
		15	1@0	20.12	20.16	20.13
			1@11	20.15	20.15	20.19
		15	12@0	18.97	18.69	18.97
Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Conducted Power (dBm) for low/mid/high channel		
				23012/699.2	23095/707.5	23178/715.8
NB-IOT Band 12 Standalone	BPSK	3.75	1@0	20.65	20.61	20.66
			1@47	20.47	20.51	20.56
		15	1@0	20.34	20.66	20.66
			1@11	20.26	20.64	20.54
	QPSK	3.75	1@0	20.47	20.52	20.53
			1@47	20.49	20.38	20.64
		15	1@0	20.30	20.61	20.65
			1@11	20.29	20.63	20.66
		15	12@0	19.03	18.95	19.35
Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Conducted Power (dBm) for low/mid/high channel		
				23182/777.2	23230/782	23278/786.8
NB-IOT Band 13 Standalone	BPSK	3.75	1@0	20.34	20.61	20.51
			1@47	20.23	20.49	20.49
		15	1@0	20.45	20.59	20.21
			1@11	20.41	20.56	20.14
	QPSK	3.75	1@0	20.35	20.44	20.62
			1@47	20.33	20.46	20.35
		15	1@0	20.45	20.55	20.51
			1@11	20.43	20.54	20.54
		15	12@0	19.42	19.52	19.45
Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Conducted Power (dBm) for low/mid/high channel		
				131974/1710.2	132322/1745	132670/1779.8
NB-IOT	BPSK	3.75	1@0	19.60	20.01	20.08



Band 66 Standalone		15	1@47	19.61	19.98	20.07
			1@0	19.62	20.08	20.01
			1@11	19.57	20.01	19.99
	QPSK	3.75	1@0	19.53	19.95	20.03
			1@47	19.54	19.93	20.02
		15	1@0	19.53	20.07	20.07
			1@11	19.57	20.06	20.06
		15	12@0	18.75	18.86	18.88
Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Conducted Power (dBm) for low/mid/high channel		
				133124/663.2	133297/680.5	133470/697.8
NB-IOT Band 71 Standalone	BPSK	3.75	1@0	20.44	20.33	20.54
			1@47	20.43	20.24	20.51
		15	1@0	20.54	20.28	20.43
			1@11	20.53	20.27	20.47
	QPSK	3.75	1@0	20.49	20.20	20.52
			1@47	20.43	20.19	20.42
		15	1@0	20.50	20.27	20.41
			1@11	20.54	20.28	20.54
		15	12@0	19.45	19.10	19.08
Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Conducted Power (dBm) for low/mid/high channel		
				134004/698.2	134092/707	134180/715.8
NB-IOT Band 85 Standalone	BPSK	3.75	1@0	20.24	20.71	20.38
			1@47	20.13	20.58	20.26
		15	1@0	20.22	20.85	20.80
			1@11	20.20	20.84	20.82
	QPSK	3.75	1@0	20.17	20.81	20.34
			1@47	20.27	20.83	20.24
		15	1@0	20.24	20.80	20.83
			1@11	20.16	20.79	20.84
		15	12@0	18.36	18.99	18.89



Variant

Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Maximum Output Power(dBm)			EIRP (dBm)		
				19952/ 1710.2	20175/ 1732.5	20398/ 1754.8	19952/ 1710.2	20175/ 1732.5	20398/ 1754.8
Band 4 Standalone	BPSK	3.75	1@0	20.95	21.02	20.91	22.85	22.92	22.81
			1@47	20.89	20.96	20.83	22.79	22.86	22.73
		15	1@0	20.49	21.08	20.56	22.39	22.98	22.46
			1@11	20.51	20.97	20.47	22.41	22.87	22.37
	QPSK	3.75	1@0	20.92	21.01	20.82	22.82	22.91	22.72
			1@47	20.87	21.00	20.79	22.77	22.90	22.69
		15	1@0	20.62	21.07	20.57	22.52	22.97	22.47
			1@11	20.57	21.03	20.59	22.47	22.93	22.49
		15	12@0	18.77	19.14	18.64	20.67	21.04	20.54

Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Maximum Output Power(dBm)			ERP (dBm)		
				23012/ 699.2	23095/ 707.5	23178/ 715.8	23012/ 699.2	23095/ 707.5	23178/ 715.8
Band 12 Standalone	BPSK	3.75	1@0	20.61	20.40	20.51	22.46	22.25	22.36
			1@47	20.60	20.39	20.39	22.45	22.24	22.24
		15	1@0	20.19	20.23	20.55	22.04	22.08	22.40
			1@11	20.18	20.18	20.49	22.03	22.03	22.34
	QPSK	3.75	1@0	20.62	20.41	20.45	22.47	22.26	22.30
			1@47	20.56	20.43	20.46	22.41	22.28	22.31
		15	1@0	20.25	20.21	20.53	22.10	22.06	22.38
			1@11	20.33	20.29	20.51	22.18	22.14	22.36
		15	12@0	18.47	18.36	18.61	20.32	20.21	20.46

Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Maximum Output Power(dBm)			ERP (dBm)		
				23182/ 777.2	23230/ 782	23278/ 786.8	23182/ 777.2	23230/ 782	23278/ 786.8
Band 13 Standalone	BPSK	3.75	1@0	20.93	20.74	20.62	23.28	23.09	22.97
			1@47	20.78	20.66	20.58	23.13	23.01	22.93
		15	1@0	20.69	20.84	20.85	23.04	23.19	23.20
			1@11	20.59	20.86	20.79	22.94	23.21	23.14
	QPSK	3.75	1@0	20.86	20.68	20.65	23.21	23.03	23.00
			1@47	20.78	20.72	20.70	23.13	23.07	23.05
		15	1@0	20.70	20.80	20.77	23.05	23.15	23.12
			1@11	20.75	20.78	20.79	23.10	23.13	23.14
		15	12@0	18.70	18.97	18.85	21.05	21.32	21.20



Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Maximum Output Power(dBm)			EIRP (dBm)		
				131974 /1710.2	132322/ 1745	132670/ 1779.8	131974/ 1710.2	132322/ 1745	132670/ 1779.8
Band 66 Standalone	BPSK	3.75	1@0	20.72	20.78	20.62	22.72	22.78	22.62
			1@47	20.68	20.72	20.61	22.68	22.72	22.61
		15	1@0	20.72	20.02	20.48	22.72	22.02	22.48
			1@11	20.71	21.04	20.46	22.71	23.04	22.46
	QPSK	3.75	1@0	20.70	20.77	20.61	22.70	22.77	22.61
			1@47	20.67	20.78	20.58	22.67	22.78	22.58
		15	1@0	20.75	21.13	20.55	22.75	23.13	22.55
			1@11	20.73	21.12	20.53	22.73	23.12	22.53
		15	12@0	18.77	18.92	18.38	20.77	20.92	20.38

Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Maximum Output Power(dBm)			ERP (dBm)		
				133124/ 663.2	133297/ 680.5	133470/ 697.8	133124/ 663.2	133297/ 680.5	133470/ 697.8
Band 71 Standalone	BPSK	3.75	1@0	21.86	21.39	20.87	22.71	22.24	21.72
			1@47	21.87	21.34	20.90	22.72	22.19	21.75
		15	1@0	21.75	21.38	20.98	22.60	22.23	21.83
			1@11	21.72	21.37	20.96	22.57	22.22	21.81
	QPSK	3.75	1@0	21.92	21.28	20.94	22.77	22.13	21.79
			1@47	21.85	21.33	20.85	22.70	22.18	21.70
		15	1@0	21.72	21.31	20.99	22.57	22.16	21.84
			1@11	21.67	21.43	20.91	22.52	22.28	21.76
		15	12@0	19.39	19.33	19.16	20.24	20.18	20.01

Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Maximum Output Power(dBm)			ERP (dBm)		
				134004/ 698.2	134092/ 707	134180/ 715.8	134004/ 698.2	134092/ 707	134180/ 715.8
Band 85 Standalone	BPSK	3.75	1@0	20.69	20.58	20.66	22.54	22.43	22.51
			1@47	20.64	20.51	20.54	22.49	22.36	22.39
		15	1@0	20.63	20.65	20.74	22.48	22.50	22.59
			1@11	20.69	20.63	20.64	22.54	22.48	22.49
	QPSK	3.75	1@0	20.58	20.57	20.57	22.43	22.42	22.42
			1@47	20.62	20.57	20.63	22.47	22.42	22.48
		15	1@0	20.72	20.68	20.71	22.57	22.53	22.56
			1@11	20.67	20.70	20.78	22.52	22.55	22.63
		15	12@0	18.60	18.63	18.85	20.45	20.48	20.70

5.2 Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to 2kHz, VBW is set to 6.2kHz for NB-IoT Band 4/12/13/66/71/85.

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U=624\text{Hz}$.




Test Result

Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Bandwidth(KHz) for low/mid/high channel					
				19952/1710.2		20175/1732.5		20398/1754.8	
				99% Power	-26dBc	99% Power	-26dBc	99% Power	-26dBc
NB-IoT Band 4 Standalone	BPSK	3.75	1@0	60.99	40.55	60.29	41.08	59.95	41.36
	QPSK	3.75	1@0	68.41	39.96	66.80	40.06	68.52	40.46
	BPSK	15	1@0	129.52	105.80	123.80	103.70	130.08	118.10
	QPSK	15	1@0	117.15	117.70	116.99	117.80	129.52	131.40
	QPSK	15	12@0	184.58	237.30	185.01	241.20	185.41	239.20
Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Bandwidth(KHz) for low/mid/high channel					
				23012/699.2		23095/707.5		23178/715.8	
				99% Power	-26dBc	99% Power	-26dBc	99% Power	-26dBc
NB-IoT Band 12 Standalone	BPSK	3.75	1@0	58.49	40.43	58.78	40.49	58.97	40.95
	QPSK	3.75	1@0	68.47	41.12	63.88	39.98	64.65	41.19
	BPSK	15	1@0	117.18	102.80	127.46	116.80	131.62	128.40
	QPSK	15	1@0	119.90	130.40	115.74	104.40	115.08	117.00
	QPSK	15	12@0	184.67	254.40	184.53	259.40	183.98	253.00
Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Bandwidth(KHz) for low/mid/high channel					
				23182/777.2		23230/782		23278/786.8	
				99% Power	-26dBc	99% Power	-26dBc	99% Power	-26dBc
NB-IoT Band 13 Standalone	BPSK	3.75	1@0	59.47	41.45	60.31	40.50	58.64	41.22
	QPSK	3.75	1@0	65.88	39.92	67.76	43.93	67.47	41.69
	BPSK	15	1@0	121.14	115.20	124.55	106.30	129.30	118.20
	QPSK	15	1@0	120.65	116.90	115.68	116.40	111.06	103.10
	QPSK	15	12@0	182.63	241.00	183.63	242.70	184.12	241.20
Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Bandwidth(KHz) for low/mid/high channel					
				131974/1710.2		132322/1745		132670/1779.8	
				99% Power	-26dBc	99% Power	-26dBc	99% Power	-26dBc
NB-IoT Band 66 Standalone	BPSK	3.75	1@0	59.80	41.30	60.27	41.23	60.39	40.68
	QPSK	3.75	1@0	67.87	39.83	68.79	39.79	68.29	42.43
	BPSK	15	1@0	119.15	103.00	132.52	118.20	121.20	105.70
	QPSK	15	1@0	117.50	115.70	118.18	118.10	120.91	105.70
	QPSK	15	12@0	184.58	248.00	183.84	251.50	183.19	240.20
Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Bandwidth(KHz) for low/mid/high channel					
				133124/663.2		133297/680.5		133470/697.8	
				99% Power	-26dBc	99% Power	-26dBc	99% Power	-26dBc



NB-IoT Band 71 Standalone	BPSK	3.75	1@0	59.028	41.52	59.208	41.15	58.865	41.25
	QPSK	3.75	1@0	69.429	40.54	68.688	40.02	69.312	40.59
	BPSK	15	1@0	124.58	113.10	126.13	104.10	119.11	104.90
	QPSK	15	1@0	119.48	117.6	119.24	131.40	120.22	104.10
	QPSK	15	12@0	189.76	252.80	186.29	259.70	185.10	256.10
Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Bandwidth(KHz) for low/mid/high channel					
				134004/698.2		134092/707		134180/715.8	
				99% Power	-26dBc	99% Power	-26dBc	99% Power	-26dBc
NB-IoT Band 85 Standalone	BPSK	3.75	1@0	59.10	41.29	58.66	41.26	58.62	41.00
	QPSK	3.75	1@0	66.18	40.09	67.31	41.31	68.43	42.72
	BPSK	15	1@0	126.53	115.70	130.40	116.00	131.32	114.40
	QPSK	15	1@0	116.77	116.90	116.13	104.00	117.46	130.90
	QPSK	15	12@0	184.75	241.10	183.45	104.70	183.64	240.00


NB-IoT Band 4 BPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 4 BPSK 15kHz 1@0 CH-Low




NB-IoT Band 4 BPSK 3.75kHz 1@0 CH-Middle



NB-IoT Band 4 BPSK 15kHz 1@0 CH-Middle



NB-IoT Band 4 BPSK 3.75kHz 1@0 CH-High



NB-IoT Band 4 BPSK 15kHz 1@0 CH-High






NB-IoT Band 4 QPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 4 QPSK 15kHz 1@0 CH-Low




NB-IoT Band 4 QPSK 3.75kHz 1@0 CH-Middle



NB-IoT Band 4 QPSK 15kHz 1@0 CH-Middle



NB-IoT Band 4 QPSK 3.75kHz 1@0 CH-High



NB-IoT Band 4 QPSK 15kHz 1@0 CH-High






NB-IoT Band 4 QPSK 15kHz 12@0 CH-Low




NB-IoT Band 12 BPSK 3.75kHz 1@0 CH-Low

NB-IoT Band 4 QPSK 15kHz 12@0
CH-MiddleNB-IoT Band 12 BPSK 3.75kHz 1@0
CH-Middle

NB-IoT Band 4 QPSK 15kHz 12@0 CH-High




NB-IoT Band 12 BPSK 3.75kHz 1@0 CH-High



NB-IoT Band 12 BPSK 15kHz 1@0 CH-Low



NB-IoT Band 12 QPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 12 BPSK 15kHz 1@0 CH-Middle



NB-IoT Band 12 QPSK 3.75kHz 1@0 CH-Middle



NB-IoT Band 12 BPSK 15kHz 1@0 CH-High



NB-IoT Band 12 QPSK 3.75kHz 1@0 CH-High





NB-IoT Band 12 QPSK 15kHz 1@0 CH-Low



NB-IoT Band 12 QPSK 15kHz 12@0 CH-Low



NB-IoT Band 12 QPSK 15kHz 1@0 CH-Middle



NB-IoT Band 12 QPSK 15kHz 12@0 CH-Middle



NB-IoT Band 12 QPSK 15kHz 1@0 CH-High




NB-IoT Band 12 QPSK 15kHz 12@0 CH-High







NB-IoT Band 13 BPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 13 BPSK 15kHz 1@0 CH-Low

NB-IoT Band 13 BPSK 3.75kHz 1@0
CH-MiddleNB-IoT Band 13 BPSK 15kHz 1@0
CH-Middle

NB-IoT Band 13 BPSK 3.75kHz 1@0 CH-High




NB-IoT Band 13 BPSK 15kHz 1@0 CH-High






NB-IoT Band 13 QPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 13 QPSK 15kHz 1@0 CH-Low

NB-IoT Band 13 QPSK 3.75kHz 1@0
CH-MiddleNB-IoT Band 13 QPSK 15kHz 1@0
CH-Middle

NB-IoT Band 13 QPSK 3.75kHz 1@0 CH-High




NB-IoT Band 13 QPSK 15kHz 1@0 CH-High






NB-IoT Band 13 QPSK 15kHz 12@0 CH-Low




NB-IoT Band 66 BPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 13 QPSK 15kHz 12@0 CH-Middle




NB-IoT Band 66 BPSK 3.75kHz 1@0 CH-Middle



NB-IoT Band 13 QPSK 15kHz 12@0 CH-High



NB-IoT Band 66 BPSK 3.75kHz 1@0 CH-High






NB-IoT Band 66 BPSK 15kHz 1@0 CH-Low




NB-IoT Band 66 QPSK 3.75kHz 1@0 CH-Low




NB-IoT Band 66 BPSK 15kHz 1@0 CH-Middle




NB-IoT Band 66 QPSK 3.75kHz 1@0 CH-Middle



NB-IoT Band 66 BPSK 15kHz 1@0 CH-High



NB-IoT Band 66 QPSK 3.75kHz 1@0 CH-High






NB-IoT Band 66 QPSK 15kHz 1@0 CH-Low



NB-IoT Band 66 QPSK 15kHz 12@0 CH-Low

NB-IoT Band 66 QPSK 15kHz 1@0
CH-Middle


NB-IoT Band 66 QPSK 15kHz 12@0 CH-Middle



NB-IoT Band 66 QPSK 15kHz 1@0 CH-High




NB-IoT Band 66 QPSK 15kHz 12@0 CH-High







NB-IoT Band 71 BPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 71 BPSK 15kHz 1@0 CH-Low

NB-IoT Band 71 BPSK 3.75kHz 1@0
CH-MiddleNB-IoT Band 71 BPSK 15kHz 1@0
CH-Middle

NB-IoT Band 71 BPSK 3.75kHz 1@0 CH-High




NB-IoT Band 71 BPSK 15kHz 1@0 CH-High







NB-IoT Band 71 QPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 71 QPSK 15kHz 1@0 CH-Low

NB-IoT Band 71 QPSK 3.75kHz 1@0
CH-MiddleNB-IoT Band 71 QPSK 15kHz 1@0
CH-Middle

NB-IoT Band 71 QPSK 3.75kHz 1@0 CH-High




NB-IoT Band 71 QPSK 15kHz 1@0 CH-High






NB-IoT Band 71 QPSK 15kHz 12@0 CH-Low



NB-IoT Band 85 BPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 71 QPSK 15kHz 12@0 CH-Middle




NB-IoT Band 85 BPSK 3.75kHz 1@0 CH-Middle



NB-IoT Band 71 QPSK 15kHz 12@0 CH-High



NB-IoT Band 85 BPSK 3.75kHz 1@0 CH-High



NB-IoT Band 85 BPSK 15kHz 1@0 CH-Low



NB-IoT Band 85 QPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 85 BPSK 15kHz 1@0 CH-Middle



NB-IoT Band 85 QPSK 3.75kHz 1@0 CH-Middle



NB-IoT Band 85 BPSK 15kHz 1@0 CH-High



NB-IoT Band 85 QPSK 3.75kHz 1@0 CH-High





NB-IoT Band 85 QPSK 15kHz 1@0 CH-Low



NB-IoT Band 85 QPSK 15kHz 12@0 CH-Low



NB-IoT Band 85 QPSK 15kHz 1@0 CH-Middle



NB-IoT Band 85 QPSK 15kHz 12@0 CH-Middle



NB-IoT Band 85 QPSK 15kHz 1@0 CH-High



NB-IoT Band 85 QPSK 15kHz 12@0 CH-High



5.3 Band Edge Compliance

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured.

The testing follows KDB 971168 D01 v03r01 Section 6.0

The EUT was connected to spectrum analyzer and system simulator via a power divider.

The band edges of low and high channels for the highest RF powers were measured.

RBW is set to 750Hz, VBW is set to 2.4kHz for NB-IoT Band 4/66 with 3.75KHz single carrier,

RBW is set to 1.3kHz, VBW is set to 3.9kHz for NB-IoT Band 4/66 with 15KHz single carrier,

RBW is set to 2kHz, VBW is set to 6.2KHz for NB-IoT Band 4/66 with 15KHz full carrier.


RBW is set to 30kHz, VBW is set to 100kHz for NB-IoT Band 12/13/71/85.

Set spectrum analyzer with RMS detector.

The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

Checked that all the results comply with the emission limit line.

Test Setup



Limits

Rule Part 27.53(h) specifies that “ for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee’s frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB”

Rule Part 27.53(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any

emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

Rule Part 27.53(f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

Rule Part 27.53 (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

Measurement Uncertainty


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684$ dB.




Test Result

All the test traces in the plots shows the test results clearly.


NB-IoT Band 4 BPSK 3.75kHz 1@0 CH-Low




NB-IoT Band 4 BPSK 3.75kHz 1@47 CH-High




NB-IoT Band 4 BPSK 15kHz 1@0 CH-Low




NB-IoT Band 4 BPSK 15kHz 1@11 CH-High



NB-IoT Band 4 QPSK 3.75kHz 1@0 CH-Low




NB-IoT Band 4 QPSK 3.75kHz 1@47 CH-High







NB-IoT Band 4 QPSK 15kHz 1@0 CH-Low



NB-IoT Band 4 QPSK 15kHz 1@11 CH-High



NB-IoT Band 4 QPSK 15kHz 12@0 CH-Low



NB-IoT Band 4 QPSK 15kHz 12@0 CH-High



NB-IoT Band 12 BPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 12 BPSK 3.75kHz 1@47 CH-High



NB-IoT Band 12 BPSK 15kHz 1@0 CH-Low



NB-IoT Band 12 BPSK 15kHz 1@11 CH-High



NB-IoT Band 12 QPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 12 QPSK 3.75kHz 1@47 CH-High





NB-IoT Band 12 QPSK 15kHz 1@0 CH-Low



NB-IoT Band 12 QPSK 15kHz 1@11 CH-High



NB-IoT Band 12 QPSK 15kHz 12@0 CH-Low



NB-IoT Band 12 QPSK 15kHz 12@0 CH-High






NB-IoT Band 13 BPSK 3.75kHz 1@0 CH-Low



NB-IoT Band 13 BPSK 3.75kHz 1@47 CH-High




NB-IoT Band 13 BPSK 15kHz 1@0 CH-Low



NB-IoT Band 13 BPSK 15kHz 1@11 CH-High

NB-IoT Band 13 QPSK 3.75kHz 1@0
CH-Low

NB-IoT Band 13 QPSK 3.75kHz 1@47 CH-High





NB-IoT Band 13 QPSK 15kHz 1@0 CH-Low



NB-IoT Band 13 QPSK 15kHz 1@11 CH-High



NB-IoT Band 13 QPSK 15kHz 12@0 CH-Low



NB-IoT Band 13 QPSK 15kHz 12@0 CH-High

