

FCC RF EXPOSURE REPORT


FCC ID: XMR2019SC650TNA

Project No. : 2001H013
Equipment : Smart Module
Brand Name : QUECTEL
Test Model : SC650T-NA
Series Model : N/A
Applicant : Quectel Wireless Solutions Co., Ltd.
Address : Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233.
Manufacturer : Quectel Wireless Solutions Co., Ltd.
Address : Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233.
Date of Receipt : Jan. 15, 2020
Date of Test : Jan. 15, 2020~Feb. 27, 2020
Issued Date : Mar. 16, 2020
Report Version : R00
Test Sample : Engineering Sample No.: SH2020011452
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.



Prepared by : Iscaa Min



Approved by : Krain Wu



Certificate # 5123.03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China

TEL: +86-021-61765666

Web: www.newbtl.com

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue	Mar. 16, 2020

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

For 2.4G Wifi

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	Saintenna	SAA31092A	Dipole	IPEX	5.38

For 5G Wifi

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	Saintenna	SAA31092A	Dipole	IPEX	5.05

For BT:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Saintenna	SAA31092A	Dipole	IPEX	5.38

For LE

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Saintenna	SAA31092A	Dipole	IPEX	5.38

For LTE Band 2

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Saintenna	SAA30968A	Dipole	IPEX	1.59

For LTE Band 4

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Saintenna	SAA30968A	Dipole	IPEX	2

For LTE Band 5

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Saintenna	SAA30968A	Dipole	IPEX	2.53

For LTE Band 7

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Saintenna	SAA30968A	Dipole	IPEX	3

For LTE Band 12

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Saintenna	SAA30968A	Dipole	IPEX	3.95

For LTE Band 13

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Saintenna	SAA30968A	Dipole	IPEX	4.45

For LTE Band 14

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Saintenna	SAA30968A	Dipole	IPEX	4.45

For LTE Band 25

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Saintenna	SAA30968A	Dipole	IPEX	1.59

For LTE Band 26

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Saintenna	SAA30968A	Dipole	IPEX	3.19

For LTE Band 66

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Saintenna	SAA30968A	Dipole	IPEX	2

2. TEST RESULTS

For BT:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Max. Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.38	3.4514	8	6.3096	0.00433	1	Complies

For LE:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Max. Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.38	3.4514	4	2.5119	0.00173	1	Complies

For 2.4GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.38	3.4514	24	251.1886	0.17256	1	Complies

For 5GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.05	3.1989	19	79.4328	0.05058	1	Complies

For LTE Band 2

Max EIRP (dBm)	Max EIRP (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density S) (mW/cm ²)	Test Result
26.00	398.1072	0.07924	1	Complies

For LTE Band 4

Max EIRP (dBm)	Max EIRP (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density S) (mW/cm ²)	Test Result
26.00	398.1072	0.07924	1	Complies

For LTE Band 7

Max EIRP (dBm)	Max EIRP (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density S) (mW/cm ²)	Test Result
27.00	501.1872	0.09976	1	Complies

For LTE Band 66

Max EIRP (dBm)	Max EIRP (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density S) (mW/cm ²)	Test Result
27.00	501.1872	0.09976	1	Complies

For LTE Band 25

Max EIRP (dBm)	Max EIRP (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
26.00	398.1072	0.07924	1	Complies

For LTE Band 5

ERP=EIRP-2.15

Max EIRP (dBm)	Max EIRP (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
26.15	412.0975	0.08203	1	Complies

For LTE Band 26

ERP=EIRP-2.15

Max EIRP (dBm)	Max EIRP (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
27.15	518.8000	0.10326	1	Complies

For LTE Band 12

ERP=EIRP-2.15

Max EIRP (dBm)	Max EIRP (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
28.15	653.1306	0.13000	1	Complies

For LTE Band 13

ERP=EIRP-2.15

Max EIRP (dBm)	Max EIRP (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
28.15	653.1306	0.13000	1	Complies

For LTE Band 14

ERP=EIRP-2.15

Max EIRP (dBm)	Max EIRP (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
28.15	653.1306	0.13000	1	Complies

For the max simultaneous transmission MPE:

BT+LE+2.4G+5G

Power Density (S) (mW/cm ²)	Power Density (S) (mW/cm ²)	Power Density (S) (mW/cm ²)	Power Density (S) (mW/cm ²)	Total	Limit of Power Density (S) (mW/cm ²)	Test Result
BT	2.4GHz	5GHz	LTE			
0.00433		0.05058	0.13000	0.18491	1	Complies
0.00433	0.17256		0.13000	0.30689	1	Complies

Note: The calculated distance is 20 cm.
Output power including tune up tolerance.

End of Test Report