

MPE TEST REPORT

Applicant Quectel Wireless Solutions Co., Ltd.

FCC ID XMR2023EG950ALA

Product LTE Cat4 Module

Brand Quectel

Model EG950A-LA

Report No. R2308A0904-M1V1

Issue Date October 12, 2023

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Wei Fangying

Approved by: Fan Guangchang

TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory.....	4
1.1	Notes of the Test Report	4
1.2	Test Facility.....	4
1.3	Testing Location.....	4
1.4	Laboratory Environment.....	4
2	Description of Equipment Under Test	5
3	Maximum Tune up and Antenna Gain	6
4	Test Result	7
	ANNEX A: The EUT Appearance.....	11

Version	Revision Description	Issue Date
Rev.0	Initial issue of report.	September 22, 2023
Rev.1	Update data.	October 12, 2023

Note: This revised report (Report No.: R2308A0904-M1V1) supersedes and replaces the previously issued report (Report No.: R2308A0904-M1). Please discard or destroy the previously issued report and dispose of it accordingly.

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Fan Guangchang
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: fanguangchang@ta-shanghai.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	Quectel Wireless Solutions Co., Ltd.
Applicant address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China, 200233
Manufacturer	Quectel Wireless Solutions Co., Ltd.
Manufacturer address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China, 200233

General Technologies

EUT Description						
Model	EG950A-LA					
SN	D1A23GT0C000195					
Hardware Version	R1.0					
Software Version	EG950ALALAR01A02M16					
Frequency	Band	TX (MHz)	RX (MHz)			
	WCDMA Band II	1850 ~ 1910	1930 ~ 1990			
	WCDMA Band IV	1710 ~ 1755	2110 ~ 2155			
	WCDMA Band V	824 ~ 849	869 ~ 894			
	LTE Band 2	1850 ~ 1910	1930 ~ 1990			
	LTE Band 4	1710 ~ 1755	2110 ~ 2155			
	LTE Band 5	824 ~ 849	869 ~ 894			
	LTE Band 7	2500 ~ 2570	2620 ~ 2690			
	LTE Band 66	1710 ~ 1780	2110 ~ 2180			
Date of Sample Received	August 29, 2023					
Note:						
1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.						
2. All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.						

3 Maximum Tune up

The numeric gain (G) of the antenna with a gain specified in dB is determined by

$$\text{Numeric gain (G)} = 10^{\text{(antenna gain/10)}}$$

Band	Maximum Tune up		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
WCDMA Band II	25.000	316.228	1.590	1.442
WCDMA Band IV	25.000	316.228	2.000	1.585
WCDMA Band V	25.000	316.228	2.530	1.791
LTE Band 2	25.000	316.228	1.590	1.442
LTE Band 4	25.000	316.228	2.000	1.585
LTE Band 5	25.000	316.228	2.530	1.791
LTE Band 7	25.000	316.228	3.000	1.995
LTE Band 66	25.000	316.228	2.000	1.585

4 Test Result

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	f/300	6
1500-100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 300~1500 MHz is f/1500, for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
WCDMA Band II	1.000
WCDMA Band IV	1.000
WCDMA Band V	0.549
LTE Band 2	1.000
LTE Band 4	1.000
LTE Band 5	0.549
LTE Band 7	1.000
LTE Band 66	1.000

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in KDB 447498 D01 is used in the calculation.

Equation from KDB 447498 D01 General RF Exposure Guidance v06 (10/23/2015) is:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Tune up (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm ²)	Limit Value (mW/cm ²)
WCDMA Band II	25.000	1.590	26.590	456.037	0.091	1.000
WCDMA Band IV	25.000	2.000	27.000	501.187	0.100	1.000
WCDMA Band V	25.000	2.530	27.530	566.239	0.113	0.549
LTE Band 2	25.000	1.590	26.590	456.037	0.091	1.000
LTE Band 4	25.000	2.000	27.000	501.187	0.100	1.000
LTE Band 5	25.000	2.530	27.530	566.239	0.113	0.549
LTE Band 7	25.000	3.000	28.000	630.957	0.126	1.000
LTE Band 66	25.000	2.000	27.000	501.187	0.100	1.000

Note: R = 20cm
 $\pi = 3.1416$

According to customer requirements, the maximum gain RF exposure evaluation results based on theoretical deduction are as follows:

Band	Maximum tune up (dBm)	EIRP Limit (dBm)	Margin 1 (dB)	Power Density Limit (mW/cm ²)	PG (dBm)	Margin 2 (dB)	Final Margin (dB)	Gain (dBi)
WCDMA Band II	25.000	33.000	8.000	1.000	37.013	12.013	8.000	8.000
WCDMA Band IV	25.000	30.000	5.000	1.000	37.013	12.013	5.000	5.000
WCDMA Band V	25.000	40.600	15.600	0.549	34.408	9.408	9.408	9.408
LTE Band 2	25.000	33.000	8.000	1.000	37.013	12.013	8.000	8.000
LTE Band 4	25.000	30.000	5.000	1.000	37.013	12.013	5.000	5.000
LTE Band 5	25.000	40.600	15.600	0.549	34.408	9.408	9.408	9.408
LTE Band 7	25.000	33.000	8.000	1.000	37.013	12.013	8.000	8.000
LTE Band 66	25.000	30.000	5.000	1.000	37.013	12.013	5.000	5.000

Note: 1. The Maximum allowed antenna gain per Band should be less than or equal to the **Final Margin** which is the allowable maximum gain value to comply with limits for maximum permissible exposure (MPE).
2. The Final Margin is determined and selected to the worst-case of Margin 1 and Margin 2.
3. Margin 1=EIRP Limit (dBm)-Maximum Output Power (dBm). EIRP limit reference standard part 22/ part 24 and part 27 for each band, EIRP = ERP + 2.15 (dB).
4. Margin 2=PG (dBm)-Maximum Output Power (dBm).

PG (dBm): Based on the limit value of power density at 20cm.

Band	Maximum Tune up (dBm)	Antenna Gain (dBi)	PG (mW)	Result (mW/cm ²)	Limit Value (mW/cm ²)	Conclusion
WCDMA Band II	25.000	8.000	1995.262	0.397	1.000	Pass
WCDMA Band IV	25.000	5.000	1000.000	0.199	1.000	Pass
WCDMA Band V	25.000	9.408	2759.307	0.549	0.549	Pass
LTE Band 2	25.000	8.000	1995.262	0.397	1.000	Pass
LTE Band 4	25.000	5.000	1000.000	0.199	1.000	Pass
LTE Band 5	25.000	9.408	2759.307	0.549	0.549	Pass
LTE Band 7	25.000	8.000	1995.262	0.397	1.000	Pass
LTE Band 66	25.000	5.000	1000.000	0.199	1.000	Pass

Note: $R = 20\text{cm}$

$\pi = 3.1416$

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT*****