



RF Test Report

Applicant: Quectel Wireless Solutions Co., Ltd.

Address: Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, 200233 China

Product: Wi-Fi & Bluetooth Module

Model No.: FCM362K

Brand Name: QUECTEL

FCC ID: XMR2023FCM362K

Standards: FCC CFR47 Part 15C

Report No.: PD20250012-R3A

Issue Date: 2025/05/07

Test Result: PASS *

* Testing performed at Hefei Panwin Technology Co., Ltd. on the above equipment indicates the product meets the requirements of the relevant standards.

Reviewed By: Jerry Zhang

Approved By: Alec Yang

Hefei Panwin Technology Co., Ltd.

Floor 1, Zone E, Plant 2#, Mingzhu Industrial Park, No.106 Chuangxin Avenue, High-tech Zone, Hefei City, Anhui Province, China
TEL: +86-0551-63811775

Revision History

Report No.	Version	Description	Issue Date	Note
PD20250012-R3A	01	Initial Report	2025/05/07	Valid

Remark:

The customer claims that product with ordering code FCM362KAAMD-0P-04 and FCM362KABMD-0P-04 both use AIC8800M40B chipset, share the same chipset baseline, same software and hardware design, the difference is PCB antenna matching is in consistent. Distinguish by changing the position of one resistor. Above changes won't impact the protocol and RF performance for same frequency.

We have verified the RF output power, and there is no deterioration compared to the original report data. Therefore this report records the verification data of Radiated Band Edges and Spurious Emission. Other test data is referred to in the original report (Report No.: FR3N1003A) released by Sporton International Inc. (KunShan) on Jan. 12, 2024.

CONTENTS

1 General Information	5
1.1 Notes of the Test Report	5
1.2 Test Facility	5
1.3 Testing Laboratory	5
2 General Description of Equipment under Test.....	6
2.1 Details of Application	6
2.2 General Information	6
2.3 Application Standards	7
3 Test Condition	8
3.1 Test Configuration	8
3.2 Carrier Frequency Channel	9
3.3 Equipment List	10
3.4 Support Equipment List	11
3.5 Test Uncertainty	11
4 Test Items Description	12
4.1 Output Power Measurement	12
4.2 20dB and 99% Bandwidth Measurement	14
4.3 Conducted Band Edges Measurement	15
4.4 Dwell Time Measurement	16
4.5 Hopping Channel Separation Measurement	17
4.6 Number of Channel Measurement	18
4.7 Conducted Spurious Emission Measurement	19
4.8 Radiated Band Edges and Spurious Emission Measurement	20
4.9 AC Conducted Emission Measurement	23
4.10 Antenna Requirements	25
ANNEX A: Test Results of Conducted Test	26
ANNEX B: Test Results of Radiated Test	27
ANNEX C: The EUT Appearance	35
ANNEX D: Test Setup Photograph	36

Summary of Test Results

No.	Test Case	FCC Rules	Verdict
1	Peak Output Power	15.247(b)(1)	Refer to original report
2	20dB and 99% Bandwidth	15.247(a)(1)	Refer to original report
3	Conducted Band Edges	15.247(d)	Refer to original report
4	Dwell Time of Each Channel	15.247(a)(1)	Refer to original report
5	Hopping Channel Separation	15.247(a)(1)	Refer to original report
6	Number of Channels	15.247(a)(1)	Refer to original report
7	Conducted Spurious Emission	15.247(d)	Refer to original report
8	Radiated Band Edges and Radiated Spurious Emission	15.247(d)	PASS
9	AC Conducted Emission	15.207	NA
10	Antenna Requirement	15.203 & 15.247(b)	PASS

Date of Testing: 2025/03/03 to 2025/04/26

Date of Sample Received: 2025/01/26

- We, Hefei Panwin Technology Co., Ltd., would like to declare that the tested sample has been evaluated in accordance with the procedures given in applied standard(s) in **Section 2.3** of this report and shown compliance with the applicable technical standards.
- All indications of PASS/FAIL in this report are based on interpretations and/or observations of test results.

Measurement Uncertainties were not taken into account and are published for informational purposes only.

1 General Information

1.1 Notes of the Test Report

This report is invalid without signature of auditor and approver or with any alterations. The report shall not be partially reproduced without written approval of the testing company. Entrusted test results are only responsible for incoming samples. If there is any objection to the testing report, it shall be raised to the testing company within 15 days from the date of receiving the report. In the test results, "NA" means "not applicable", and the test items marked with " Δ " are subcontracted projects.

1.2 Test Facility

A2LA (Certificate Number: 6849.01)

Hefei Panwin Technology Co., Ltd. has been accredited by American Association for Laboratory Accreditation to perform measurement.

FCC (Designation Number: CN1361, Test Firm Registration Number: 473156)

Hefei Panwin Technology Co., Ltd. has been accredited on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Laboratory

Company Name	Hefei Panwin Technology Co., Ltd.
Address	Floor 1, Zone E, Plant 2#, Mingzhu Industrial Park, No.106 Chuangxin Avenue, High-tech Zone, Hefei City, Anhui Province, China
Telephone	+86-0551-63811775
Post Code	230031

2 General Description of Equipment under Test

2.1 Details of Application

Applicant	Quectel Wireless Solutions Co., Ltd.
Applicant Address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, 200233 China
Manufacturer	Quectel Wireless Solutions Co., Ltd.
Manufacturer Address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, 200233 China

2.2 General Information

Product	Wi-Fi & Bluetooth Module
Model	FCM362K
SN	Conducted: D1M24J70J000152 Radiated: D1M24J70D000136 & D1M24K70D000126
Hardware Version	R1.1
Software Version	FCM362KAAR03A03M04
Antenna Type	PCB Antenna
Antenna Gain	1.10dBi
Operating voltage	Typical 3.3Vdc
Modulation Type	Frequency Hopping Spread Spectrum (FHSS):GFSK, $\pi/4$ -DQPSK, 8-DPSK
Operating Frequency Range(s)	Bluetooth : 2402 ~2480 MHz
Number of channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78

Note: The declared of product specification for EUT and/or Antenna presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

2.3 Application Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

3 Test Condition

3.1 Test Configuration

Test mode

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). The worst cases were recorded in this report.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes (Z, X, Y axis), receiver antenna polarization (horizontal and vertical), the worst emission was found in Z position and the worst case was recorded. This report presents the data for the worst polarity.

3.2 Carrier Frequency Channel

Frequency Band	Channel	Freq (MHz)	Channel	Freq (MHz)	Channel	Freq (MHz)
2400-2483.5MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

3.3 Equipment List

Conducted

Instrument	Manufacturer	Model	Asset No.	Cal. Interval	Cal. Due Date
Spectrum Analyzer	KEYSIGHT	N9020B	PWC0048	1 Year	2025/09/11
RF Control Unit	Tonseced	JS0806-2	PWC0055	/	/
Shielded Chamber	Maorui	MR543	PWC0041	3 Years	2026/08/26
Test Software	Tonseced	JS1120-3 V3.2.22	/	/	/

Radiated

Instrument	Manufacturer	Model	Asset No.	Cal. Interval	Cal. Due Date
EMI Test Receiver	R&S	ESR7	PWB0023	1 Year	2025/09/11
Spectrum Analyzer	R&S	FSV3044	PWB0024	1 Year	2025/09/11
Loop Antenna	R&S	HFH2-Z2E	PWB0026	1 Year	2025/09/13
TRILOG Broadband	Schwarzbeck	VULB9162	PWB0029	1 Year	2025/09/09
Double-Ridged Guide Antenna	ETS-Lindgren	3117	PWB0031	1 Year	2025/09/26
k Type Horn Antenna	Steatite Antennas	QMS-00880	PWB0035	1 Year	2025/09/08
Pre-Amplifier	R&S	SCU40F1	PWB0036	1 Year	2025/09/11
Pre-Amplifier	COM-MW	DLNA8	PWB0094	1 Year	2025/09/11
Pre-Amplifier	R&S	SCU18F	PWB0034	1 Year	2025/09/11
Pre-Amplifier	R&S	OSP220 (OSP-B155G)	PWB0042	1 Year	2025/09/11
Anechoic Chamber	ETS.LINDGREN	Fact 3-2m	PWB0003	3 Years	2026/06/05
Test Software	Tonscend	TS+ V5.0.0	/	/	/

3.4 Support Equipment List

Equipment	Manufacturer	Description	Model	Serial Number
EVB	Quectel	/	/	/
RF cable	/	2.4G:0.5dB; 5G:1dB	/	/

3.5 Test Uncertainty

No.	Parameter	Uncertainty
1	20dB Emission Bandwidth	1.9%
2	Occupied channel bandwidth	1.9%
3	Carrier Frequency Separation	1.9%
4	Band-edge Spurious Emission	1.21dB
5	Conducted RF Spurious Emission	9kHz-7GHz:1.21dB 7GHz-40GHz: 3.31dB
6	Radiated Band Edges and Spurious Emission	Below 1GHz: 4.88 dB Above 1GHz: 5.06 dB
7	Temperature	3 °C
8	Humidity	1.3 %
9	Supply voltages	0.006 V

4 Test Items Description

Ambient condition

Anechoic Chamber

Temperature [°C]	20.5 to 23.2
Humidity [%RH]	30 to 48
Pressure [kPa]	99.5 to 102.5

4.1 Output Power Measurement

4.1.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band:1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


4.1.2 Measuring Instruments

The measuring equipment is listed in the section 3.3 of this test report.

4.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings for 20dB Bandwidth measurement
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW \geq RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
 - 7) Allow trace to stabilize.
 - 8) Use the marker-to-peak function to set the marker to the peak of the emission.
4. The indicated level is the peak output power, after any corrections for external attenuators and cables.
5. A plot of the test results and setup description shall be included in the test report.

4.1.4 Test Setup



4.1.5 Test Results

See ANNEX A.

4.2 20dB and 99% Bandwidth Measurement

4.2.1 Limit of 20dB and 99% Bandwidth

Reporting only


4.2.2 Measuring Instruments

The measuring equipment is listed in the section 3.3 of this test report.

4.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;
Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement;
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;
Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

4.2.4 Test Setup



4.2.5 Test Results

See ANNEX A.

4.3 Conducted Band Edges Measurement

4.3.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


4.3.2 Measuring Instruments

The measuring equipment is listed in the section 3.3 of this test report.

4.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

4.3.4 Test Setup



4.3.5 Test Results

See ANNEX A.

4.4 Dwell Time Measurement

4.4.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


4.4.2 Measuring Instruments

The measuring equipment is listed in the section 3.3 of this test report

4.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

4.4.4 Test Setup



4.4.5 Test Results

See ANNEX A.

4.5 Hopping Channel Separation Measurement

4.5.1 Limit of Hopping Channel Separation

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


4.5.2 Measuring Instruments

The measuring equipment is listed in the section 3.3 of this test report.

4.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

4.5.4 Test Setup



4.5.5 Test Results

See ANNEX A.

4.6 Number of Channel Measurement

4.6.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels


4.6.2 Measuring Instruments

The measuring equipment is listed in the section 3.3 of this test report.

4.6.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

4.6.4 Test Setup



4.6.5 Test Results

See ANNEX A.

4.7 Conducted Spurious Emission Measurement

4.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


4.7.2 Measuring Instruments

The measuring equipment is listed in the section 3.3 of this test report

4.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW= 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

4.7.4 Test Setup



4.7.5 Test Results

See ANNEX A.

4.8 Radiated Band Edges and Spurious Emission Measurement

4.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency of emission (MHz)	Field strength (microvolts/meter)	Measurement Distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490– 1.705	24000/F(kHz)	30
1.705–30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above960	500	3

4.8.2 Measuring Instruments

The measuring equipment is listed in the section 3.3 of this test report.

4.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured.
 - (2) Set RBW=100 kHz for f< 1 GH, RBW=1MHz for f>1GHz ; VBW ≥ RBW; Sweep = auto;Detector function = peak;Trace = max hold for peak.
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds

On time = $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$


Where N_1 is number of type 1 pulses, L , is length of type 1 pulses, etc.

Average Emission Level = Peak Emission Level + $20 \cdot \log(\text{Duty cycle})$.


6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Pre-amp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

4.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



4.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported. There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

4.8.6 Test Result of Radiated Spurious at Band Edges

See ANNEX B.1.

4.8.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

See ANNEX B.1.

4.8.8 Duty cycle correction factor for average measurement

See ANNEX A.

4.9 AC Conducted Emission Measurement

4.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

Decreases with the logarithm of the frequency.


4.9.2 Measuring Instruments

The section 3.3 of List of Measuring Equipment of this test report is used for test.

4.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth =9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

4.6.4 Test Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

4.9.5 Uncertainty Measurement

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT. The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

CASE	Uncertainty
Continuous Emission (AC port)	2.92 dB

4.9.6 Test Result

Remark: The product is DC powered, this test item is not applicable.

4.10 Antenna Requirements

4.10.1 Standard Applicable

15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.10.2 Antenna Anti-Replacement Construction

The antenna is Internal on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.10dBi.

----- THE END -----

ANNEX A: Test Results of Conducted Test

Test Result

For detailed test data, please refer to the original report number which is issued separately.

Test Report No.	Original Report No.
PD20250012-R3A	FR3N1003A

ANNEX B: Test Results of Radiated Test


B.1 Radiated Band Edges and Spurious Emission

Test Result_Band Edges

Note: Both vertical and horizontal polarities have been evaluated, and the test data only shows the worst-case.
Level=Reading+Factor; Margin=Limit-Level; V=Vertical , H=Horizontal.

Data List									
Test Mode	Frequency [MHz]	Reading [dB μ V]	Level [dB μ V/m]	Factor [dB/m]	Limit [dB μ V/m]	Margin [dB]	Pol.	Det	
BT_DH5_2402	2387.8375	48.98	61.06	12.08	74.00	12.94	V	PK	
	2387.8375	-	36.27	-	54.00	17.73	V	AV	
BT_DH5_2480	2484.95	49.48	62.26	12.78	74.00	11.74	H	PK	
	2484.95	-	37.47	-	54.00	16.53	H	AV	
BT_3DH5_2402	2386.6675	49.93	62.07	12.14	74.00	11.93	V	PK	
	2386.6675	-	37.28	-	54.00	16.72	V	AV	
BT_3DH5_2480	2484.9625	49.94	62.72	12.78	74.00	11.28	H	PK	
	2484.9625	-	37.93	-	54.00	16.07	H	AV	

Test Graphs_Band Edges



Test Result_Spurious Emission

Note1: Test result Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier the Emissions in the frequency band 9kHz-30MHz and 18GHz-26.5GHz are more than 20dB below the limit are not reported.

Note2: Both vertical and horizontal polarities have been evaluated, and the test data only shows the worst-case. Level=Reading+Factor; Margin=Limit-Level; V=Vertical , H=Horizontal.

Data List									
Test Mode	Frequency [MHz]	Reading [dB μ V]	Level [dB μ V/m]	Factor [dB/m]	Limit [dB μ V/m]	Margin [dB]	Pol.	Det	
BT_DH5_2402	4804	44.18	51.52	7.34	74.00	22.48	V	PK	
	7206	44.86	58.54	13.68	74.00	15.46	V	PK	
	9608	33.60	48.31	14.71	74.00	25.69	V	PK	
	12010	33.17	49.00	15.83	74.00	25.00	H	PK	
	14412	32.64	50.99	18.35	74.00	23.01	V	PK	
	16814	31.79	55.03	23.24	74.00	18.97	H	PK	
	4804	-	26.73	-	54.00	27.27	V	AV	
	7206	-	33.75	-	54.00	20.25	V	AV	
	9608	-	23.52	-	54.00	30.48	V	AV	
	12010	-	24.21	-	54.00	29.79	H	AV	
	14412	-	26.2	-	54.00	27.8	V	AV	
	16814	-	30.24	-	54.00	23.76	H	AV	
BT_DH5_2441	4882	44.02	51.38	7.36	74.00	22.62	H	PK	
	7323	43.13	57.06	13.93	74.00	16.94	V	PK	
	9764	34.19	49.23	15.04	74.00	24.77	V	PK	
	12205	34.02	49.57	15.55	74.00	24.43	V	PK	
	14646	32.41	50.87	18.46	74.00	23.13	H	PK	
	17087	30.25	54.74	24.49	74.00	19.26	H	PK	
	4882	-	26.59	-	54.00	27.41	H	AV	
	7323	-	32.27	-	54.00	21.73	V	AV	
	9764	-	24.44	-	54.00	29.56	V	AV	
	12205	-	24.78	-	54.00	29.22	V	AV	

	14646	-	26.08	-	54.00	27.92	H	AV
	17087	-	29.95	-	54.00	24.05	H	AV
BT_DH5_2480	4960	45.83	53.22	7.39	74.00	20.78	H	PK
	7440	43.69	58.16	14.47	74.00	15.84	V	PK
	9920	33.98	49.02	15.04	74.00	24.98	H	PK
	12400	33.92	50.39	16.47	74.00	23.61	V	PK
	14880	32.33	50.85	18.52	74.00	23.15	V	PK
	17360	30.44	55.26	24.82	74.00	18.74	V	PK
	4960	-	28.43	-	54.00	25.57	H	AV
	7440	-	33.37	-	54.00	20.63	V	AV
	9920	-	24.23	-	54.00	29.77	H	AV
	12400	-	25.6	-	54.00	28.4	V	AV
	14880	-	26.06	-	54.00	27.94	V	AV
	17360	-	30.47	-	54.00	23.53	V	AV
BT_2DH5_2402	4804	44.98	52.32	7.34	74.00	21.68	H	PK
	7206	43.05	56.73	13.68	74.00	17.27	H	PK
	9608	34.49	49.20	14.71	74.00	24.80	H	PK
	12010	33.68	49.51	15.83	74.00	24.49	H	PK
	14412	32.84	51.19	18.35	74.00	22.81	H	PK
	16814	32.46	55.70	23.24	74.00	18.30	H	PK
	4804	-	27.53	-	54.00	26.47	H	AV
	7206	-	31.94	-	54.00	22.06	H	AV
	9608	-	24.41	-	54.00	29.59	H	AV
	12010	-	24.72	-	54.00	29.28	H	AV
	14412	-	26.4	-	54.00	27.6	H	AV
	16814	-	30.91	-	54.00	23.09	H	AV
BT_2DH5_2441	4882	45.10	52.46	7.36	74.00	21.54	H	PK
	7323	44.08	58.01	13.93	74.00	15.99	H	PK
	9764	34.96	50.00	15.04	74.00	24.00	H	PK


BT_2DH5_2480	12205	34.42	49.97	15.55	74.00	24.03	V	PK
	14646	32.12	50.58	18.46	74.00	23.42	V	PK
	17087	29.72	54.21	24.49	74.00	19.79	H	PK
	4882	-	27.67	-	54.00	26.33	H	AV
	7323	-	33.22	-	54.00	20.78	H	AV
	9764	-	25.21	-	54.00	28.79	H	AV
	12205	-	25.18	-	54.00	28.82	V	AV
	14646	-	25.79	-	54.00	28.21	V	AV
	17087	-	29.42	-	54.00	24.58	H	AV
	4960	44.40	51.79	7.39	74.00	22.21	V	PK
BT_3DH5_2402	7440	43.83	58.30	14.47	74.00	15.70	V	PK
	9920	34.47	49.51	15.04	74.00	24.49	H	PK
	12400	33.74	50.21	16.47	74.00	23.79	V	PK
	14880	32.53	51.05	18.52	74.00	22.95	V	PK
	17360	30.08	54.90	24.82	74.00	19.10	H	PK
	4960	-	27.00	-	54.00	27.00	V	AV
	7440	-	33.51	-	54.00	20.49	V	AV
	9920	-	24.72	-	54.00	29.28	H	AV
	12400	-	25.42	-	54.00	28.58	V	AV
	14880	-	26.26	-	54.00	27.74	V	AV
	17360	-	30.11	-	54.00	23.89	H	AV
BT_3DH5_2402	4804	43.75	51.09	7.34	74.00	22.91	H	PK
	7206	44.04	57.72	13.68	74.00	16.28	V	PK
	9608	33.33	48.04	14.71	74.00	25.96	H	PK
	12010	33.70	49.53	15.83	74.00	24.47	H	PK
	14412	31.93	50.28	18.35	74.00	23.72	H	PK
	16814	31.29	54.53	23.24	74.00	19.47	H	PK
	4804	-	26.30	-	54.00	27.70	H	AV
	7206	-	32.93	-	54.00	21.07	V	AV


BT_3DH5_2441	9608	-	23.25	-	54.00	30.75	H	AV
	12010	-	24.74	-	54.00	29.26	H	AV
	14412	-	25.49	-	54.00	28.51	H	AV
	16814	-	29.74	-	54.00	24.26	H	AV
	4882	45.31	52.67	7.36	74.00	21.33	H	PK
	7323	43.49	57.42	13.93	74.00	16.58	V	PK
	9764	34.61	49.65	15.04	74.00	24.35	H	PK
	12205	33.36	48.91	15.55	74.00	25.09	V	PK
	14646	32.49	50.95	18.46	74.00	23.05	H	PK
	17087	29.42	53.91	24.49	74.00	20.09	H	PK
	4882	-	27.88	-	54.00	26.12	H	AV
	7323	-	32.63	-	54.00	21.37	V	AV
BT_3DH5_2480	9764	-	24.86	-	54.00	29.14	H	AV
	12205	-	24.12	-	54.00	29.88	V	AV
	14646	-	26.16	-	54.00	27.84	H	AV
	17087	-	29.12	-	54.00	24.88	H	AV
	4960	43.98	51.37	7.39	74.00	22.63	V	PK
	7440	42.84	57.31	14.47	74.00	16.69	V	PK
	9920	34.24	49.28	15.04	74.00	24.72	V	PK
	12400	33.37	49.84	16.47	74.00	24.16	V	PK
	14880	31.85	50.37	18.52	74.00	23.63	V	PK
	17360	29.22	54.04	24.82	74.00	19.96	H	PK
	4960	-	26.58	-	54.00	27.42	V	AV
	7440	-	32.52	-	54.00	21.48	V	AV
	9920	-	24.49	-	54.00	29.51	V	AV
	12400	-	25.05	-	54.00	28.95	V	AV
	14880	-	25.58	-	54.00	28.42	V	AV
	17360	-	29.25	-	54.00	24.75	H	AV

Data List

Test Mode	Frequency [MHz]	Reading [dB μ V]	Level [dB μ V/m]	Factor [dB/m]	Limit [dB μ V/m]	Margin [dB]	Pol.	Det
BT_DH5_2441	34.661691	32.62	14.72	-17.90	40.00	25.28	V	QP
	51.554457	38.28	23.26	-15.02	40.00	16.74	V	QP
	139.28467	33.37	13.25	-20.12	43.50	30.25	V	QP
	280.31438	24.89	10.97	-13.92	46.00	35.03	V	QP
	520.30568	25.29	14.66	-10.63	46.00	31.34	V	QP
	902.9925	23.65	20.73	-2.92	46.00	25.27	H	QP

Test Graphs_Spurious Emission





ANNEX C: The EUT Appearance

The EUT Appearance (internal and external photographs) are submitted separately.

ANNEX D: Test Setup Photograph

The Test Setup Photographs are submitted separately.