

LTE

Data List							
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.
LTE_B2_20M_CH19100	111.0355	-61.32	-58.39	2.93	-13.00	45.39	V
	877.7189	-59.61	-50.97	8.64	-13.00	37.97	H
	3782.0000	-66.43	-52.16	14.27	-13.00	39.16	V
	5200.4401	-67.96	-49.95	18.01	-13.00	36.95	V
	5673.0000	-71.61	-53.02	18.59	-13.00	40.02	V
	7564.0000	-72.80	-48.92	23.88	-13.00	35.92	V
	9455.0000	-79.05	-55.39	23.66	-13.00	42.39	V
	11346.0000	-79.65	-54.30	25.35	-13.00	41.30	V
	13237.0000	-79.66	-53.50	26.16	-13.00	40.50	V
	15128.0000	-80.46	-51.67	28.79	-13.00	38.67	V
	17019.0000	-80.65	-46.89	33.76	-13.00	33.89	V
LTE_B4_20M_CH20300	108.1241	-73.29	-71.16	2.13	-13.00	58.16	V
	473.0265	-72.19	-72.33	-0.14	-13.00	59.33	H
	3472.0000	-57.52	-44.34	13.18	-13.00	31.34	H
	5208.0000	-72.05	-53.83	18.22	-13.00	40.83	V
	6944.0000	-72.28	-50.23	22.05	-13.00	37.23	H
	8680.0000	-76.99	-54.86	22.13	-13.00	41.86	H
	10416.0000	-79.41	-54.39	25.02	-13.00	41.39	V
	12152.0000	-79.10	-54.03	25.07	-13.00	41.03	V
	13888.0000	-80.02	-53.54	26.48	-13.00	40.54	V
	15624.0000	-80.14	-50.49	29.65	-13.00	37.49	V
	17360.0000	-80.33	-45.81	34.52	-13.00	32.81	V
LTE_B5_10M_CH20600	109.0945	-60.82	-58.48	2.34	-13.00	45.48	V
	252.7264	-60.66	-58.79	1.87	-13.00	45.79	H
	1678.0000	-70.24	-54.42	15.82	-13.00	41.42	H
	2517.0000	-69.79	-47.66	22.13	-13.00	34.66	H
	3356.0000	-70.89	-57.83	13.06	-13.00	44.83	V
	4195.0000	-71.59	-56.14	15.45	-13.00	43.14	H

	5034.0000	-72.32	-54.33	17.99	-13.00	41.33	V
	5873.0000	-72.20	-52.79	19.41	-13.00	39.79	H
	6712.0000	-72.71	-51.52	21.19	-13.00	38.52	H
	7551.0000	-73.15	-49.35	23.80	-13.00	36.35	H
	8390.0000	-78.11	-55.43	22.68	-13.00	42.43	V
LTE_B7_20M_CH21350	110.065	-60.50	-57.84	2.66	-25.00	32.84	V
	251.7559	-61.20	-59.02	2.18	-25.00	34.02	H
	5102.0000	-64.71	-46.62	18.09	-25.00	21.62	V
	7653.0000	-73.22	-48.95	24.27	-25.00	23.95	H
	10204.0000	-77.99	-53.13	24.86	-25.00	28.13	V
	12755.0000	-79.07	-52.63	26.44	-25.00	27.63	V
	15306.0000	-79.13	-50.28	28.85	-25.00	25.28	V
	17857.0000	-79.22	-44.86	34.36	-25.00	19.86	H
LTE_B66_20M_CH132072	109.5798	-61.08	-58.59	2.49	-13.00	45.59	V
	252.2411	-60.80	-58.78	2.02	-13.00	45.78	H
	3422.0000	-61.47	-48.46	13.01	-13.00	35.46	V
	5133.0000	-72.35	-54.37	17.98	-13.00	41.37	V
	6844.0000	-72.70	-50.73	21.97	-13.00	37.73	H
	8555.0000	-77.01	-54.92	22.09	-13.00	41.92	V
	10266.0000	-78.71	-53.88	24.83	-13.00	40.88	V
	11977.0000	-79.07	-53.44	25.63	-13.00	40.44	V
	13688.0000	-79.65	-53.53	26.12	-13.00	40.53	H
	15399.0000	-79.09	-50.19	28.90	-13.00	37.19	H
	17110.0000	-79.99	-46.46	33.53	-13.00	33.46	V

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal