



# RF Test Report

**Applicant:** Quectel Wireless Solutions Co., Ltd.

**Address:** Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233

**Product:** Wi-Fi & Bluetooth Module

**Model No.:** FCM363X, FCM363X-L

**Brand Name:** QUECTEL

**FCC ID:** XMR2025FCM363X

**Standards:** FCC CFR47 Part 2.1091  
FCC KDB 447498 D01 v06

**Report No.:** PD20250047-R3E

**Issue Date:** 2025/07/21

**Test Result:** PASS \*

\* Testing performed at Hefei Panwin Technology Co., Ltd. on the above equipment indicates the product meets the requirements of the relevant standards.

**Reviewed By:** Jerry Zhang

**Approved By:** Alec Yang

## Hefei Panwin Technology Co., Ltd.

Floor 1, Zone E, Plant 2#, Mingzhu Industrial Park, No.106 Chuangxin Avenue, High-tech Zone, Hefei City, Anhui Province, China  
TEL: +86-0551-63811775

# Test Report

Report No.: PD20250047-R3E  
Report Version: 01

## Revision History

Report No.	Version	Description	Issue Date	Note
PD20250047-R3E	01	Initial Report	2025/07/21	Valid

### Remark:

- The samples tested have been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and have been proven to meet the applicable limit requirements.

## CONTENTS

<b>1 Test Laboratory .....</b>	<b>4</b>
1.1 Notes of the Test Report .....	4
1.2 Testing Laboratory .....	4
<b>2 General Description of Equipment under Test .....</b>	<b>5</b>
2.1 Details of Application .....	5
2.2 Details of EUT .....	5
<b>3 Test Condition .....</b>	<b>6</b>
3.1 Laboratory Environment .....	6
<b>4 Maximum Permissible Exposure (EMF) .....</b>	<b>7</b>
<b>ANNEX A – Test Results .....</b>	<b>8</b>
<b>ANNEX B – The EUT Appearance .....</b>	<b>10</b>

## 1 Test Laboratory

### 1.1 Notes of the Test Report

This report is invalid without signature of auditor and approver or with any alterations. The report shall not be partially reproduced without written approval of the testing company. Entrusted test results are only responsible for incoming samples. If there is any objection to the testing report, it shall be raised to the testing company within 15 days from the date of receiving the report. In the test results, "NA" means "not applicable", and the test items marked with "Δ" are subcontracted projects.

### 1.2 Testing Laboratory

Company Name	Hefei Panwin Technology Co., Ltd.
Address	Floor 1, Zone E, Plant 2#, Mingzhu Industrial Park, No.106 Chuangxin Avenue, High-tech Zone, Hefei City, Anhui Province,China
Telephone	+86-0551-63811775
Post Code	230031

## 2 General Description of Equipment under Test

### 2.1 Details of Application

<b>Applicant</b>	Quectel Wireless Solutions Co., Ltd.	
<b>Applicant Address</b>	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233	
<b>Manufacturer</b>	Quectel Wireless Solutions Co., Ltd.	
<b>Manufacturer Address</b>	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233	

### 2.2 Details of EUT

<b>Product</b>	Wi-Fi & Bluetooth Module		
<b>Model</b>	FCM363X		FCM363X-L
<b>Software Version</b>	FCM363XAAR02A02M08		FCM363XLAAR02A02M08
<b>Hardware Version</b>	R1.0	R1.1	R1.0
<b>Antenna Type</b>	PCB Antenna		

<b>Model</b>	<b>HW Version</b>	<b>Difference Description</b>
FCM363X	R1.0	FCM363X R1.0 does not have low power 32k crystal and RAM chip.
	R1.1	FCM363X R1.1 has 32k crystal and RAM chip. 32kHz crystal is for BB timer hibernation to reduce power consumption, it is not the crystal for BT/Wi-Fi RF operation. Above changes won't impact the protocol and RF performance for same frequency.
<b>Model</b>	<b>HW Version</b>	<b>Difference Description</b>
FCM363X	R1.0	FCM363X has 38 LCC pins and 35 LGA pins.
FCM363X-L	R1.0	FCM363X-L has 38 LCC pins and 9 LGA pins, LGA pins from 39 to 64 are deleted. 38 LCC pins and 9 LGA pins that at the same position are totally same. Above changes won't impact the protocol and RF performance for same frequency.

**Note :** The declared of product specification for EUT and/or Antenna presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

## 3 Test Condition

### 3.1 Laboratory Environment

Temperature	Min.= 20°C, Max.=30°C
Relative Humidity	Min.= 25%, Max.=75%
Ground System Resistance	< 1 Ω

Ambient noise is checked and found very low and in compliance with requirement of standards.

Reflection of surrounding objects is minimized and in compliance with requirement of standards.

## 4 Maximum Permissible Exposure (EMF)

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Table 1 to § 1.1310(e)(1)—Limits for Maximum Permissible Exposure (MPE)				
Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30–300	61.4	0.163	1.0	<6
300–1,500	--	--	f/300	<6
1,500–100,000	--	--	5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30–300	27.5	0.073	0.2	<30
300–1,500	--	--	f/1500	<30
1,500–100,000	--	--	1.0	<30

f = frequency in MHz. \* = Plane-wave equivalent power density.

The transmitter is using external antennas that operate at 20 cm or more from nearby persons. The maximum permitted level is calculated using the general equation:

$$S = PG / 4\pi R^2$$

Where:

**S** = power density (in appropriate units, e.g. W/m<sup>2</sup>)

**P** = power input to the antenna (in appropriate units, e.g., W)

**G** = power gain of the antenna in the direction of interest relative to an isotropic radiator

**R** = distance to the center of radiation of the antenna (appropriate units, e.g., m)

Solve S, the power density at 20 cm is shown in Appendix A, so the limit is kept.

----- THE END -----

**ANNEX A: Test Results****A.1 Maximum Measured Conducted Output Power and Antenna Gain**

Band	TX Freq. (MHz)	Maximum Tune-up power (dBm)	Maximum Antenna Gain (dBi)
Bluetooth LE	2402 to 2480	16.00	2.40
Wi-Fi 2.4G	2412 to 2462	21.00	2.40
Wi-Fi 5G	5150 to 5850	20.00	3.10

**A.2 Test Results of Maximum Permissible Exposure**

Band	Maximum Tune-up power (dBm)	Antenna Gain(dBi)	Maximum EIRP(dBm)	PG (mW)	Test Result (mW/cm <sup>2</sup> )	Limit Value (mW/cm <sup>2</sup> )	FCC MPE Limit Ratio
Bluetooth LE	16.00	2.40	18.40	69.183	0.014	1.000	0.014
Wi-Fi 2.4G	21.00	2.40	23.40	218.776	0.044	1.000	0.044
Wi-Fi 5G	20.00	3.10	23.10	204.174	0.041	1.000	0.041

**Note:** For mobile or fixed location transmitters, minimum separation distance is 20cm, even if calculations indicate EMF distance is less.

## A.3 Exposure calculations for multiple sources

In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

The product also has multiple transmitters. The Simultaneous Transmission Possibilities are as below:

Simultaneous Tx Combination	Configuration
1	Wi-Fi 5G + Bluetooth LE

No.	Mode	Result Ratio	Total Ratio	Limit	Result
1	Wi-Fi 5G	0.041	0.055	1.000	PASS
	Bluetooth LE	0.014			

### Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

## ANNEX B: The EUT Appearance

The EUT Appearance (internal and external photographs) are submitted separately.