

FCC Measurement/Technical Report on FHM35A

Contains FCC ID: X02-SPB620
Contains IC: 8713A-SPB620

Test Report Reference: MDE_HDW_2401_FCC_01

Test Laboratory:

7layers GmbH
Borsigstrasse 11
40880 Ratingen
Germany



Deutsche
Akkreditierungsstelle
D-PL-12140-01-00

Note:

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

7layers GmbH

Borsigstraße 11
40880 Ratingen, Germany
T +49 (0) 2102 749 0
F +49 (0) 2102 749 350

Geschäftsführer/
Managing Directors:
Jörg-Timm Kilisch
Bernhard Retka

www.7layers.com

Registergericht/registered:
Düsseldorf HRB 75554
USt-Id.-Nr./VAT-No. DE203159652
Steuer-Nr./TAX-No. 147/5869/0385

*a Bureau Veritas
Group Company*

Table of Contents

1 Applied Standards and Test Summary	3
1.1 Applied Standards	3
1.2 FCC-IC Correlation Table	4
1.3 Measurement Summary	4
2 Revision History / Signatures	8
3 Administrative Data	9
3.1 Testing Laboratory	9
3.2 Project Data	9
3.3 Applicant Data	9
3.4 Manufacturer Data	10
4 Test object Data	11
4.1 General EUT Description	11
4.2 EUT Main components	11
4.3 Ancillary Equipment	12
4.4 Auxiliary Equipment	12
4.5 EUT Setups	13
4.6 Operating Modes / Test Channels	13
4.7 Product labelling	13
5 Test Results	16
5.1 Transmitter Spurious Radiated Emissions	16
5.2 Band Edge Compliance Radiated	31
6 Test Equipment	65
6.1 Test Equipment Hardware	65
6.2 Test Equipment Software	67
7 Antenna Factors, Cable Loss and Sample Calculations	68
7.1 LISN R&S ESH3-Z5 (150 kHz – 30 MHz)	68
7.2 Antenna R&S HFH2-Z2 (9 kHz – 30 MHz)	69
7.3 Antenna R&S HL562 (30 MHz – 1 GHz)	70
7.4 Antenna R&S HF907 (1 GHz – 18 GHz)	71
7.5 Antenna EMCO 3160-09 (18 GHz – 26.5 GHz)	72
7.6 Antenna EMCO 3160-10 (26.5 GHz – 40 GHz)	73
8 Measurement Uncertainties	74
9 Photo Report	75

1 APPLIED STANDARDS AND TEST SUMMARY

1.1 APPLIED STANDARDS

Type of Authorization

Certification for an Intentional Radiator.

Applicable FCC Rules

Prepared in accordance with the requirements of FCC Rules and Regulations as listed in 47 CFR Ch.1 Parts 2 and 15 (10-1-23 Edition). The following subparts are applicable to the results in this test report.

Part 2, Subpart J - Equipment Authorization Procedures, Certification

Part 15, Subpart C – Intentional Radiators

§ 15.201 Equipment authorization requirement

§ 15.207 Conducted limits

§ 15.209 Radiated emission limits; general requirements

§ 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz

Note:

The tests were selected and performed with reference to the FCC Public Notice "Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of the FCC Rules, 558074 D01 15.247 Meas Guidance v05r02, 2019-04-02".
ANSI C63.10-2013 is applied.

1.2 FCC-IC CORRELATION TABLE

Correlation of measurement requirements for DTS (e.g. WLAN 2.4 GHz, BT LE) equipment from FCC and IC

DTS equipment

Measurement	FCC reference	IC reference
Conducted emissions on AC Mains	§ 15.207	RSS-Gen Issue 5 & AMD 1 & AMD 2: 8.8
Occupied bandwidth	§ 15.247 (a) (2)	RSS-247 Issue 3: 5.2 (a)
Peak conducted output power	§ 15.247 (b) (3), (4)	RSS-247 Issue 3: 5.4 (d)
Transmitter spurious RF conducted emissions	§ 15.247 (d)	RSS-Gen Issue 5 & AMD 1 & AMD 2: 6.13 / 8.9/8.10; RSS-247 Issue 3: 5.5
Transmitter spurious radiated emissions	§ 15.247 (d); § 15.209 (a)	RSS-Gen Issue 5 & AMD 1 & AMD 2: 6.13 / 8.9/8.10; RSS-247 Issue 3: 5.5
Band edge compliance	§ 15.247 (d)	RSS-247 Issue 3: 5.5
Power density	§ 15.247 (e)	RSS-247 Issue 3: 5.2 (b)
Antenna requirement	§ 15.203 / 15.204	RSS-Gen Issue 5 & AMD 1 & AMD 2: 8.3
Receiver spurious emissions	–	–

1.3 MEASUREMENT SUMMARY

Position 6

47 CFR CHAPTER I FCC PART 15 § 15.247 (d) **Subpart C §15.247**

Transmitter Spurious Radiated Emissions

The measurement was performed according to ANSI C63.10, chapter 6.4, 6.5, 6.6.5

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency, Measurement range				
WLAN b, high, 1 GHz - 26 GHz	S06_AC02	2024-12-19	Passed	Passed
WLAN b, high, 30 MHz - 1 GHz	S06_AC02	2025-01-12	Passed	Passed
WLAN n 20 MHz MIMO, mid, 1 GHz - 8 GHz	S06_AC02	2024-12-19	Passed	Passed
WLAN n 20 MHz MIMO, mid, 30 MHz - 1 GHz	S06_AC02	2025-01-12	Passed	Passed

47 CFR CHAPTER I FCC PART 15 § 15.247 (d) **Subpart C §15.247**

Band Edge Compliance Radiated

The measurement was performed according to ANSI C63.10, chapter 6.6.5

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency, Band Edge				
WLAN ax 20 MHz MIMO, high, high	S06_AC02	2024-12-19	Passed	Passed
WLAN ax 20 MHz, high, high	S06_AC02	2024-12-19	Passed	Passed
WLAN ax 40 MHz MIMO, high, high	S06_AC02	2024-12-19	Passed	Passed
WLAN ax 40 MHz, high, high	S06_AC02	2024-12-19	Passed	Passed
WLAN b, high, high	S06_AC02	2024-12-19	Passed	Passed
WLAN n 20 MHz MIMO, high, high	S06_AC02	2024-12-19	Passed	Passed
WLAN n 20 MHz, high, high	S06_AC02	2024-12-19	Passed	Passed
WLAN n 40 MHz MIMO, high, high	S06_AC02	2024-12-19	Passed	Passed
WLAN n 40 MHz, high, high	S06_AC02	2024-12-19	Passed	Passed

Position 1

47 CFR CHAPTER I FCC PART 15 § 15.247 (d)
Subpart C §15.247

Transmitter Spurious Radiated Emissions

The measurement was performed according to ANSI C63.10, chapter 6.4, 6.5, 6.6.5

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency, Measurement range				
WLAN g, high, 1 GHz - 8 GHz	S01_AC02	2024-12-25	Passed	Passed
WLAN g, high, 30 MHz - 1 GHz	S01_AC02	2025-01-22	Passed	Passed

47 CFR CHAPTER I FCC PART 15 § 15.247 (d)
Subpart C §15.247

Band Edge Compliance Radiated

The measurement was performed according to ANSI C63.10, chapter 6.6.5

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency, Band Edge				
WLAN ax 20 MHz MIMO, high, high	S01_AC02	2024-12-25	Passed	Passed
WLAN ax 20 MHz, high, high	S01_AC02	2024-12-25	Passed	Passed
WLAN ax 40 MHz MIMO, high, high	S01_AC02	2024-12-25	Passed	Passed
WLAN ax 40 MHz, high, high	S01_AC02	2024-12-25	Passed	Passed
WLAN b, high, high	S01_AC02	2024-12-25	Passed	Passed
WLAN g, high, high	S01_AC02	2024-12-25	Passed	Passed
WLAN n 20 MHz MIMO, high, high	S01_AC02	2024-12-25	Passed	Passed
WLAN n 20 MHz, high, high	S01_AC02	2024-12-25	Passed	Passed
WLAN n 40 MHz MIMO, high, high	S01_AC02	2024-12-25	Passed	Passed
WLAN n 40 MHz, high, high	S01_AC02	2024-12-25	Passed	Passed

Position 4

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency, Measurement range				
WLAN g, high, 1 GHz - 26 GHz	S04_AC02	2025-01-01	Passed	Passed
WLAN g, high, 30 MHz - 1 GHz	S04_AC02	2025-01-22	Passed	Passed

47 CFR CHAPTER I FCC PART 15 § 15.247 (d) **Subpart C §15.247**

Band Edge Compliance Radiated
 The measurement was performed according to ANSI C63.10, chapter 6.6.5

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency, Band Edge				
WLAN ax 20 MHz MIMO, high, high	S04_AC02	2025-01-01	Passed	Passed
WLAN ax 20 MHz, high, high	S04_AC02	2025-01-01	Passed	Passed
WLAN ax 40 MHz MIMO, high, high	S04_AC02	2025-01-01	Passed	Passed
WLAN ax 40 MHz, high, high	S04_AC02	2025-01-01	Passed	Passed
WLAN g, high, high	S04_AC02	2025-01-01	Passed	Passed
WLAN n 20 MHz MIMO, high, high	S04_AC02	2025-01-01	Passed	Passed
WLAN n 20 MHz, high, high	S04_AC02	2025-01-01	Passed	Passed
WLAN n 40 MHz MIMO, high, high	S04_AC02	2025-01-01	Passed	Passed
WLAN n 40 MHz, high, high	S04_AC02	2025-01-01	Passed	Passed

N/A: Not applicable

N/P: Not performed

2 REVISION HISTORY / SIGNATURES

Report version control			
Version	Release date	Change Description	Version validity
initial	2025-03-28	--	valid
--	--	--	--

COMMENT: -



(responsible for accreditation scope)
Daniel Gall



(responsible for testing and report)
Mohamed Fraitat



7 layers GmbH, Borsigstr. 11
40880 Ratingen, Germany
Phone +49 (0)2102 749 0

3 ADMINISTRATIVE DATA

3.1 TESTING LABORATORY

Company Name: 7layers GmbH
Address: Borsigstr. 11
40880 Ratingen
Germany

The test facility is accredited by the following accreditation organisation:

Laboratory accreditation no: DAKKS D-PL-12140-01-00
FCC Designation Number: DE0015
FCC Test Firm Registration: 929146
ISED CAB Identifier DE0007; ISED#: 3699A

Responsible for accreditation scope: Daniel Gall
Report Template Version: 2024-11-06

3.2 PROJECT DATA

Responsible for testing and report: Mohamed Fraitat
Employees who performed the tests: documented internally at 7Layers
Date of Report: 2025-03-28
Testing Period: 2024-12-19 to 2025-01-12

3.3 APPLICANT DATA

Company Name: H&D Wireless AB
Address: Färögatan 33, Kista Science Tower
164 51 Kista
Sweden
Contact Person: Mikael Olsson

3.4 MANUFACTURER DATA

Company Name: SEW-Eurodrive GmbH & Co KG

Address: Ernst-Blickle-Straße 42
76646 Bruchsal
Germany

Contact Person: Dr. Thomas Schäfer

4 TEST OBJECT DATA

4.1 GENERAL EUT DESCRIPTION

Kind of Device product description	Mobile Network Controller (SEW Eurodrive)
Product name	FHM35A
Type	FHM35A
Declared EUT data by the supplier	
Voltage Type	DC
Voltage Level	24 V
Antenna / Gain	External - HnS SWA-2459/360/4/45 (position 6) → 4 dBi @ 2.4 GHz - Leaky wave coupler 5G (position 1) → 3 dBi @ 2.4 GHz - Wave guide coupler 5G (position 4) → 0 dBi @ 2.4 GHz
Tested Modulation Type	WLAN b: DSSS WLAN g/n/ax: OFDM
General product description	The EUT is a Mobile Network Controller supporting WLAN.
Specific product description for the EUT	For WLAN in the 2.4 GHz band followings modes are supported: WLAN b, g, n, ax 20 and 40 MHz bandwidth.
Tested datarates	WLAN b: 1 Mbit WLAN g: 54 Mbit WLAN n: MCS7 WLAN ax: MCS9
Special software used for testing	Labtool on computer board provided by applicant.

4.2 EUT MAIN COMPONENTS

Sample Name	Sample Code	Description
EUT AC02	DE1495003ac02	Radio Labtool sample
Sample Parameter	Value	
Serial No.	28317386.004.24	
HW Version	v57	
SW Version	self-1.1rc8	
Comment		

NOTE: The short description is used to simplify the identification of the EUT in this test report.

4.3 ANCILLARY EQUIPMENT

For the purposes of this test report, ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Ancillary Equipment can influence the test results.

-	-	-
---	---	---

4.4 AUXILIARY EQUIPMENT

For the purposes of this test report, auxiliary equipment is defined as equipment which is used temporarily to enable operational and control features especially used for the tests of the EUT which is not used during normal operation or equipment that is used during the tests in combination with the EUT but is not subject of this test report. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Auxiliary Equipment can influence the test results.

Device	Details (Manufacturer, Type Model, HW, SW, S/N)	Description
AUX 1	HUBER+SUHNER, 1399-17-0040, -, -, P/N: 84000442	WLAN antenna 1 HnS SWA- 2459/360/4/45 (Position 6)
AUX 2	HUBER+SUHNER, 1399-17-0040, -, -, P/N: 84000442	WLAN antenna 2 HnS SWA- 2459/360/4/45 (Position 6)
AUX 3	SEW Eurodrive, R-SMA 2,4 GHz, -, -, 002.22	WLAN antenna 1 Near field coupler 5G (Position 1)
AUX 4	SEW Eurodrive, R-SMA 2,4 GHz, -, -, 006.22	WLAN antenna 2 Near field coupler 5G (Position 1)
AUX 5	SEW Eurodrive, Waveguide Coupler R- SMA 2.4 GHz, -, -, P/N: 18134718.52	WLAN antenna 1 Wave guide coupler 5G (Position 4)
AUX 6	SEW Eurodrive, Waveguide Coupler R- SMA 2.4 GHz, -, -, P/N: 18134718.52	WLAN antenna 2 Wave guide coupler 5G (Position 4)

4.5 EUT SETUPS

This chapter describes the combination of EUTs and equipment used for testing. The rationale for selecting the EUTs, ancillary and auxiliary equipment and interconnecting cables, is to test a representative configuration meeting the requirements of the referenced standards.

Setup	Combination of EUTs	Description and Rationale
S06_AC02	EUT AC02, AUX 1, AUX 2,	Setup for radiated measurement (position 6)
S01_AC02	EUT AC02, AUX 3, AUX 4,	Setup for radiated measurement (position 1)
S04_AC02	EUT AC02, AUX 5, AUX 6,	Setup for radiated measurement (position 4)

4.6 OPERATING MODES / TEST CHANNELS

This chapter describes the operating modes of the EUTs used for testing.

WLAN

20 MHz Test Channels:

Channel:

Frequency [MHz]

2.4 GHz ISM 2400 - 2483.5 MHz		
low	mid	high
1	6	11
2412	2437	2462

40 MHz Test Channels:

Channel:


Frequency [MHz]

low	mid	high
3	6	9
2422	2437	2452


4.7 DUTY CYCLE

Test Mode	T _{on+off} (ms)	T _{on} (ms)	Duty cycle (%)
WLAN b	969	956	99
WLAN g	195	179	92
WLAN n 20	183	168	91
WLAN n 40	115	100	87
WLAN ax 20	145	129	89
WLAN ax 40	112	96	86


WLAN b




WLAN g




WLAN n 20




WLAN n 40



WLAN ax 20



WLAN ax 40



4.8 PRODUCT LABELLING

4.8.1 FCC ID LABEL

Please refer to the documentation of the applicant.

4.8.2 LOCATION OF THE LABEL ON THE EUT

Please refer to the documentation of the applicant.

5 TEST RESULTS

5.1 TRANSMITTER SPURIOUS RADIATED EMISSIONS

Standard **FCC Part 15 Subpart C**

The test was performed according to:

ANSI C63.10, chapter 6.4, 6.5, 6.6.5

5.1.1 TEST DESCRIPTION

The test set-up was made in accordance to the general provisions of ANSI C63.10 in a typical installation configuration. The measurements were performed according the following sub-chapters of ANSI C63.10:


- < 30 MHz: Chapter 6.4
- 30 MHz – 1 GHz: Chapter 6.5
- > 1 GHz: Chapter 6.6 (procedure according 6.6.5 used)

The measurement procedure is implemented into the EMI test software EMC32 from R&S. Exploratory tests are performed at 3 orthogonal axes to determine the worst-case orientation of a body-worn or handheld EUT. The final test on all kind of EUTs is also performed at 3 axes. A pre-check is performed while the EUT is powered.

Below 1 GHz:

The Equipment Under Test (EUT) was set up on a non-conductive table in the semi-anechoic chamber. The influence of the EUT support table that is used between 30–1000 MHz was evaluated.

1. Measurement up to 30 MHz



Test Setup; Spurious Emission Radiated (SAC), 9 kHz – 30 MHz

The Loop antenna HFH2-Z2 is used.

Step 1: pre measurement

- Anechoic chamber
- Antenna distance: 3 m
- Antenna height: 1 m
- Detector: Peak-Maxhold
- Frequency range: 0.009 - 0.15 MHz and 0.15 - 30 MHz
- Frequency steps: 0.05 kHz and 2.25 kHz
- IF-Bandwidth: 0.2 kHz and 9 kHz
- Measuring time / Frequency step: 100 ms (FFT-based)


Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

Step 2: final measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is to find the maximum emission level.

- Detector: Quasi-Peak (9 kHz - 150 kHz, Peak / Average 150 kHz- 30 MHz)
- Frequency range: 0.009 - 30 MHz
- Frequency steps: measurement at frequencies detected in step 1
- IF-Bandwidth: 0.2 - 10 kHz
- Measuring time / Frequency step: 1 s

2. Measurement above 30 MHz and up to 1 GHz



Test Setup; Spurious Emission Radiated (SAC), 30 MHz- 1GHz

Step 1: Preliminary scan

This is a preliminary test to identify the highest amplitudes relative to the limit.

Settings for step 1:

- Antenna distance: 3 m
- Detector: Peak-Maxhold / Quasipeak (FFT-based)
- Frequency range: 30 - 1000 MHz
- Frequency steps: 30 kHz
- IF-Bandwidth: 120 kHz
- Measuring time / Frequency step: 100 ms

- Turntable angle range: -180° to 90°
- Turntable step size: 90°
- Height variation range: 1 – 4 m
- Height variation step size: 1.5 m
- Polarisation: Horizontal + Vertical

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

Step 2: Adjustment measurement

In this step the accuracy of the turntable azimuth and antenna height will be improved. This is necessary to find out the maximum value of every frequency.

For each frequency, which was determined the turntable azimuth and antenna height will be adjusted. The turntable azimuth will slowly vary by 360° . During this action, the value of emission is continuously measured. The turntable azimuth at the highest emission will be recorded and adjusted. In this position, the antenna height will also slowly vary between 1 – 4 meter. During this action, the value of emission is also continuously measured. The antenna height of the highest emission will also be recorded and adjusted.

- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100 ms
- Turntable angle range: 360°
- Height variation range: 1 – 4 m
- Antenna Polarisation: max. value determined in step 1

Step 3: Final measurement with QP detector

With the settings determined in step 2, the final measurement will be performed:

EMI receiver settings for step 3:

- Detector: Quasi-Peak (< 1 GHz)
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 1 s


After the measurement a plot will be generated which contains a diagram with the results of the preliminary scan and a chart with the frequencies and values of the results of the final measurement.

Above 1 GHz:

The Equipment Under Test (EUT) was set up on a non-conductive support (tilt device) at 1.5 m height in the fully-anechoic chamber.

All steps were performed with one height (1.5 m) of the receiving antenna only.

3. Measurement above 1 GHz



Test Setup; Spurious Emission Radiated (FAC), 1 GHz-26.5 GHz

Step 1:

The EUT is turned during the preliminary measurement across the elevation axis, with a step size of 90 °.

The turn table step size (azimuth angle) for the preliminary measurement is 45 °.

Spectrum analyser settings:

- Detector: Peak, Average
- RBW = 1 MHz
- VBW = 3 MHz

Step 2:

The turn table azimuth will slowly vary by $\pm 22.5^\circ$.

The elevation angle will slowly vary by $\pm 45^\circ$

Spectrum analyser settings:

- Detector: Peak

Step 3:

Spectrum analyser settings for step 3:

- Detector: Peak / CISPR Average
- Measured frequencies: in step 1 determined frequencies
- RBW = 1 MHz
- VBW = 3 MHz
- Measuring time: 1 s

5.1.2 TEST REQUIREMENTS / LIMITS

FCC Part 15, Subpart C, §15.247 (d)

... In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

FCC Part 15, Subpart C, §15.209, Radiated Emission Limits

Frequency in MHz	Limit (µV/m)	Measurement distance (m)	Limits (dBµV/m)
0.009 – 0.49	2400/F(kHz)@300m	3	(48.5 – 13.8)@300m
0.49 – 1.705	24000/F(kHz)@30m	3	(33.8 – 23.0)@30m
1.705 – 30	30@30m	3	29.5@30m

The measured values are corrected with an inverse linear distance extrapolation factor (40 dB/decade) according FCC 15.31 (2).

Frequency in MHz	Limit (µV/m)	Measurement distance (m)	Limits (dBµV/m)
30 – 88	100@3m	3	40.0@3m
88 – 216	150@3m	3	43.5@3m
216 – 960	200@3m	3	46.0@3m
960 – 26000	500@3m	3	54.0@3m
26000 – 40000	500@3m	1	54.0@3m

The measured values above 26 GHz are corrected with an inverse linear distance extrapolation factor (20 dB/decade).

§15.35(b) ..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor: $\text{Limit (dBµV/m)} = 20 \log (\text{Limit (µV/m)}/1\mu\text{V/m})$

5.1.3 TEST PROTOCOL

Ambient temperature: 22–25 °C
 Air Pressure: 1002–1023 hPa
 Humidity: 38–43 %

Position 6

WLAN b-Mode; 20 MHz; 1 Mbit/s

Applied duty cycle correction (AV): 0 dB

Ch. No.	Ch. Center Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]	Limit Type
11	2462	74.4	21.7	QP	120	40.0	18.3	RB
11	2462	108.0	28.1	QP	120	43.5	15.5	RB
11	2462	127.6	30.0	QP	120	43.5	13.5	RB
11	2462	171.9	30.6	QP	120	43.5	12.9	RB
11	2462	408.9	26.0	QP	120	46.0	20.0	RB
11	2462	1000.0	34.2	QP	120	54.0	19.8	RB

WLAN n-Mode; 20 MHz; MCS0; MIMO

Applied duty cycle correction (AV): 0 dB

Ch. No	Ch. Center Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]	Limit Type
6	2437	75.0	22.8	QP	120	40.0	17.2	RB
6	2437	108.0	30.2	QP	120	43.5	13.3	RB
6	2437	150.0	30.6	QP	120	43.5	12.9	RB
6	2437	400.0	26.4	QP	120	46.0	19.6	RB
6	2437	1200.2	40.0	AV	1000	54.0	14.0	RB
6	2437	1200.2	50.1	PEAK	1000	74.0	23.9	RB
6	2437	1721.4	35.8	AV	1000	54.0	18.2	RB
6	2437	1721.4	48.5	PEAK	1000	74.0	25.5	RB
6	2437	1721.4	35.8	AV	1000	54.0	18.2	RB
6	2437	1721.4	48.9	PEAK	1000	74.0	25.1	RB
6	2437	4000.0	40.7	AV	1000	54.0	13.3	RB
6	2437	4000.0	49.5	PEAK	1000	74.0	24.5	RB

Position 1

WLAN g-Mode; 20 MHz; 6 Mbit/s

Applied duty cycle correction (AV): 0 dB

Ch. No.	Ch. Center Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]	Limit Type
11	2462	108.5	28.2	QP	120	43.5	15.4	RB
11	2462	150.0	27.2	QP	120	43.5	16.3	RB
11	2462	1200.0	48.4	PEAK	1000	74.0	25.6	RB
11	2462	1200.0	36.5	AV	1000	54.0	17.5	RB
11	2462	2888.5	56.4	PEAK	1000	74.0	17.6	RB
11	2462	2888.5	43.7	AV	1000	54.0	10.3	RB
11	2462	4000.0	51.0	PEAK	1000	74.0	23.0	RB
11	2462	4000.0	42.6	AV	1000	54.0	11.4	RB

Position 4

WLAN g-Mode; 20 MHz; 54 Mbit/s

Applied duty cycle correction (AV): 0.7 dB


Ch. No.	Ch. Center Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]	Limit Type
11	2462	110.0	26.7	QP	120	43.5	16.8	RB
11	2462	150.0	30.6	QP	120	43.5	12.9	RB
11	2462	164.1	22.9	QP	120	43.5	20.6	RB
11	2462	405.7	23.2	QP	120	46.0	22.8	RB
11	2462	1000.0	35.1	QP	120	54.0	18.9	RB
11	2462	1200.0	48.1	PEAK	1000	74.0	25.9	RB
11	2462	1200.0	37.5	AV	1000	54.0	16.5	RB
11	2462	4000.0	49.6	PEAK	1000	74.0	24.4	RB
11	2462	4000.0	41.8	AV	1000	54.0	12.2	RB

Remark: Please see next sub-clause for the measurement plot.

5.1.4 MEASUREMENT PLOT (EXAMPLE PLOT, SHOWING WORST CASE, IF APPLICABLE)

Position 6


Radio Technology = WLAN b, Operating Frequency = high
 Measurement range = 30 MHz – 1 GHz
 (S06_AC02)



Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
74.440000	21.66	40.00	18.34	1000.0	120.000	115.0	V	147.0	9.8
108.030000	28.05	43.50	15.45	1000.0	120.000	118.0	V	245.0	12.1
127.620000	29.96	43.50	13.54	1000.0	120.000	105.0	V	98.0	11.6
171.890000	30.61	43.50	12.89	1000.0	120.000	104.0	V	104.0	10.5
408.870000	26.02	46.00	19.98	1000.0	120.000	131.0	V	62.0	18.3
999.990000	34.21	54.00	19.79	1000.0	120.000	110.0	V	177.0	29.4


Radio Technology = WLAN b, Operating Frequency = high
Measurement range = 1 GHz – 26 GHz
(S06_AC02)



Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.063	---	41.1	54.00	12.88	1000.0	1000.000	150.0	V	-144.0	15.0	8.0
2484.063	54.2	---	74.00	19.83	1000.0	1000.000	150.0	V	-144.0	15.0	8.0


Radio Technology = WLAN n 20 MHz MIMO, Operating Frequency = high
 Measurement range = 30 MHz – 1 GHz
 (S06_AC02)



Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
75.040000	22.79	40.00	17.21	1000.0	120.000	122.0	V	104.0	9.9
108.000000	30.16	43.50	13.34	1000.0	120.000	109.0	V	121.0	12.1
149.990000	30.59	43.50	12.91	1000.0	120.000	104.0	V	42.0	9.9
399.990000	26.38	46.00	19.62	1000.0	120.000	123.0	V	353.0	18.1

Radio Technology = WLAN n 20 MHz MIMO, Operating Frequency = high
Measurement range = 1 GHz – 8 GHz
(S06_AC02)




Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
1200.160	---	40.0	54.00	13.98	1000.0	1000.000	150.0	V	158.0	-4.0	3.2
1200.160	50.1	---	74.00	23.92	1000.0	1000.000	150.0	V	158.0	-4.0	3.2
1721.350	---	35.8	54.00	18.22	1000.0	1000.000	150.0	V	70.0	-12.0	5.5
1721.350	48.5	---	74.00	25.45	1000.0	1000.000	150.0	V	70.0	-12.0	5.5
1721.384	---	35.8	54.00	18.24	1000.0	1000.000	150.0	V	73.0	5.0	5.5
1721.384	48.9	---	74.00	25.10	1000.0	1000.000	150.0	V	73.0	5.0	5.5
2483.688	---	39.4	54.00	14.60	1000.0	1000.000	150.0	V	-15.0	110.0	8.0
2483.688	53.2	---	74.00	20.81	1000.0	1000.000	150.0	V	-15.0	110.0	8.0
2483.750	---	39.4	54.00	14.59	1000.0	1000.000	150.0	V	-165.0	22.0	8.0
2483.750	52.6	---	74.00	21.38	1000.0	1000.000	150.0	V	-165.0	22.0	8.0
4000.000	---	40.7	54.00	13.33	1000.0	1000.000	150.0	V	1.0	83.0	3.8
4000.000	49.5	---	74.00	24.55	1000.0	1000.000	150.0	V	1.0	83.0	3.8

Position 1


Radio Technology = WLAN g, Operating Frequency = high
 Measurement range = 30 MHz – 1 GHz
 (S01_AC02)



Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
108.450000	28.15	43.50	15.35	1000.0	120.000	109.0	V	108.0	12.1
150.020000	27.19	43.50	16.31	1000.0	120.000	104.0	V	37.0	9.9

Radio Technology = WLAN g, Operating Frequency = high
Measurement range = 1 GHz – 8 GHz
(S01_AC02)




Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
1200.040	---	36.5	54.00	17.52	1000.0	1000.000	150.0	H	-174.0	96.0	36.2
1200.040	48.4	---	74.00	25.60	1000.0	1000.000	150.0	H	-174.0	96.0	36.2
2483.688	---	46.2	54.00	7.77	1000.0	1000.000	150.0	H	-50.0	81.0	43.8
2483.688	67.8	---	74.00	6.17	1000.0	1000.000	150.0	H	-50.0	81.0	43.8
2888.450	---	43.7	54.00	10.29	1000.0	1000.000	150.0	H	-189.0	33.0	45.1
2888.450	56.4	---	74.00	17.55	1000.0	1000.000	150.0	H	-189.0	33.0	45.1
4000.000	---	42.6	54.00	11.37	1000.0	1000.000	150.0	V	-3.0	58.0	3.8
4000.000	51.0	---	74.00	23.01	1000.0	1000.000	150.0	V	-3.0	58.0	3.8

Position 4


Radio Technology = WLAN g, Operating Frequency = high
 Measurement range = 30 MHz – 1 GHz
 (S04_AC02)



Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
109.980000	26.71	43.50	16.79	1000.0	120.000	109.0	V	147.0	12.1
149.990000	30.57	43.50	12.93	1000.0	120.000	111.0	V	1.0	9.9
164.052500	22.94	43.50	20.56	1000.0	120.000	115.0	V	340.0	9.9
405.720000	23.24	46.00	22.76	1000.0	120.000	119.0	H	57.0	18.3
999.990000	35.10	54.00	18.90	1000.0	120.000	107.0	V	291.0	29.4

Radio Technology = WLAN g, Operating Frequency = high
Measurement range = 1 GHz – 8 GHz
(S04_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
1200.040	---	36.8	54.00	17.20	1000.0	1000.000	150.0	H	-93.0	93.0	36.2
1200.040	48.1	---	74.00	25.92	1000.0	1000.000	150.0	H	-93.0	93.0	36.2
2483.750	---	48.7	54.00	5.31	1000.0	1000.000	150.0	H	-28.0	-6.0	43.8
2483.750	70.6	---	74.00	3.38	1000.0	1000.000	150.0	H	-28.0	-6.0	43.8
4000.000	---	41.1	54.00	12.86	1000.0	1000.000	150.0	V	-3.0	34.0	3.8
4000.000	49.6	---	74.00	24.35	1000.0	1000.000	150.0	V	-3.0	34.0	3.8

5.1.5 TEST EQUIPMENT USED

- Radiated Emissions FAR 2.4 GHz FCC
- Radiated Emissions SAC up to 1 GHz

5.2 BAND EDGE COMPLIANCE RADIATED

Standard **FCC Part 15 Subpart C**

The test was performed according to:

ANSI C63.10, chapter 6.6.5

5.2.1 TEST DESCRIPTION


The test set-up was made in accordance to the general provisions of ANSI C63.10 in a typical installation configuration. The measurements were performed according the following sub-chapter of ANSI C63.10:

- Chapter 6.10.5

The Equipment Under Test (EUT) was set up on a non-conductive support (tilt device) at 1.5 m height in the fully-anechoic chamber.

All steps were performed with one height (1.5 m) of the receiving antenna only (procedure according ANSI C63.10, chapter 6.6.5).

3. Measurement above 1 GHz



Test Setup; Spurious Emission Radiated (FAC), 1 GHz-26.5 GHz

Step 1:

The EUT is turned during the preliminary measurement across the elevation axis, with a step size of 90 °.

The turn table step size (azimuth angle) for the preliminary measurement is 45 °.

Spectrum analyser settings:

- Detector: Peak, Average
- RBW = 1 MHz
- VBW = 3 MHz

Step 2:

The turn table azimuth will slowly vary by $\pm 22.5^\circ$.

The elevation angle will slowly vary by $\pm 45^\circ$

Spectrum analyser settings:

- Detector: Peak

Step 3:

Spectrum analyser settings for step 3:

- Detector: Peak / CISPR Average
- Measured frequencies: in step 1 determined frequencies
- RBW = 1 MHz
- VBW = 3 MHz
- Measuring time: 1 s

5.2.2 TEST REQUIREMENTS / LIMITS

For band edges connected to a restricted band, the limits are specified in Section 15.209(a)

FCC Part 15, Subpart C, §15.209, Radiated Emission Limits

Frequency in MHz	Limit (µV/m)	Measurement distance (m)	Limits (dBµV/m)
0.009 – 0.49	2400/F(kHz)@300m	3	(48.5 – 13.8)@300m
0.49 – 1.705	24000/F(kHz)@30m	3	(33.8 – 23.0)@30m
1.705 – 30	30@30m	3	29.5@30m

The measured values are corrected with an inverse linear distance extrapolation factor (40 dB/decade) according FCC 15.31 (2).

Frequency in MHz	Limit (µV/m)	Measurement distance (m)	Limits (dBµV/m)
30 – 88	100@3m	3	40.0@3m
88 – 216	150@3m	3	43.5@3m
216 – 960	200@3m	3	46.0@3m
960 – 26000	500@3m	3	54.0@3m
26000 – 40000	500@3m	1	54.0@3m

The measured values above 26 GHz are corrected with an inverse linear distance extrapolation factor (20 dB/decade).

§15.35(b) ..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor: Limit (dBµV/m) = 20 log (Limit (µV/m)/1µV/m)

5.2.3 TEST PROTOCOL

Ambient temperature: 22–25 °C
 Air Pressure: 1002–1023 hPa
 Humidity: 38–43 %

Position 6

WLAN b-Mode; 20 MHz; 1 Mbit/s
 Applied duty cycle correction (AV): 0 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	54.2	PEAK	1000	74.0	19.8
11	2462	2483.5	41.1	AV	1000	54.0	12.9

WLAN n-Mode; 20 MHz; MCS0
 Applied duty cycle correction (AV): 0.7 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	66.0	PEAK	1000	74.0	8.0
11	2462	2483.5	46.2	AV	1000	54.0	7.8

WLAN n-Mode; 40 MHz; MCS0
 Applied duty cycle correction (AV): 1.2 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
9	2452	2483.5	71.6	PEAK	1000	74.0	2.4
9	2452	2483.5	52.3	AV	1000	54.0	1.7

WLAN ax-Mode; 20 MHz; MCS0
 Applied duty cycle correction (AV): 0.9 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	65.0	PEAK	1000	74.0	9.0
11	2462	2483.5	45.6	AV	1000	54.0	8.4

WLAN ax-Mode; 40 MHz; MCS0
 Applied duty cycle correction (AV): 1.3 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
9	2452	2483.5	68.9	PEAK	1000	74.0	5.1
9	2452	2483.5	53.7	AV	1000	54.0	0.3

WLAN n-Mode; 20 MHz; MCS0; MIMO
 Applied duty cycle correction (AV): 0.8 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	62.4	PEAK	1000	74.0	11.6
11	2462	2483.5	44.7	AV	1000	54.0	9.3

WLAN n-Mode; 40 MHz; MCS0; MIMO
 Applied duty cycle correction (AV): 1.2 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
9	2452	2483.5	67.6	PEAK	1000	74.0	6.4
9	2452	2483.5	47.9	AV	1000	54.0	6.1

WLAN ax-Mode; 20 MHz; MCS0; MIMO
 Applied duty cycle correction (AV): 0.9 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	72.5	PEAK	1000	74.0	1.5
11	2462	2483.5	50.1	AV	1000	54.0	3.9

WLAN ax-Mode; 40 MHz; MCS0; MIMO
 Applied duty cycle correction (AV): 1.3 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
9	2452	2483.5	62.5	PEAK	1000	74.0	11.5
9	2452	2483.5	46.8	AV	1000	54.0	7.2

Position 1

WLAN b-Mode; 20 MHz; 1 Mbit/s
 Applied duty cycle correction (AV): 0 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	55.6	PEAK	1000	74.0	18.4
11	2462	2483.5	42.9	AV	1000	54.0	11.1

WLAN g-Mode; 20 MHz; 6 Mbit/s; Diversity
 Applied duty cycle correction (AV): 0 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	66.6	PEAK	1000	74.0	7.4
11	2462	2483.5	45.9	AV	1000	54.0	8.1

WLAN g-Mode; 20 MHz; 6 Mbit/s
 Applied duty cycle correction (AV): 0.7 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	67.8	PEAK	1000	74.0	6.2
11	2462	2483.5	46.2	AV	1000	54.0	7.1

WLAN n-Mode; 20 MHz; MCS0
 Applied duty cycle correction (AV): 0.7 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	67.3	PEAK	1000	74.0	6.7
11	2462	2483.5	46.5	AV	1000	54.0	7.5

WLAN n-Mode; 40 MHz; MCS0
 Applied duty cycle correction (AV): 1.2 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
9	2452	2483.5	73.5	PEAK	1000	74.0	0.5
9	2452	2483.5	48.9	AV	1000	54.0	5.1

WLAN ax-Mode; 20 MHz; MCS0
 Applied duty cycle correction (AV): 0.9 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	59.7	PEAK	1000	74.0	14.3
11	2462	2483.5	45.0	AV	1000	54.0	9.0

WLAN ax-Mode; 40 MHz; MCS0
 Applied duty cycle correction (AV): 1.3 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
9	2452	2483.5	63.1	PEAK	1000	74.0	10.9
9	2452	2483.5	46.5	AV	1000	54.0	7.5

WLAN n-Mode; 20 MHz; MCS0; MIMO
Applied duty cycle correction (AV): 0.8 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	64.2	PEAK	1000	74.0	9.8
11	2462	2483.5	46.0	AV	1000	54.0	8.0

WLAN n-Mode; 40 MHz; MCS0; MIMO
Applied duty cycle correction (AV): 1.2 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
9	2452	2483.5	66.4	PEAK	1000	74.0	7.6
9	2452	2483.5	47.6	AV	1000	54.0	6.4

WLAN ax-Mode; 20 MHz; MCS0; MIMO
Applied duty cycle correction (AV): 0.9 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	62.0	PEAK	1000	74.0	12.0
11	2462	2483.5	45.4	AV	1000	54.0	8.6

WLAN ax-Mode; 40 MHz; MCS0; MIMO
Applied duty cycle correction (AV): 1.3 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
9	2452	2483.5	63.9	PEAK	1000	74.0	10.1
9	2452	2483.5	48.7	AV	1000	54.0	5.3

Position 4

WLAN g-Mode; 20 MHz; 6 Mbit/s
Applied duty cycle correction (AV): 0.7 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	70.6	PEAK	1000	74.0	3.4
11	2462	2483.5	49.4	AV	1000	54.0	4.6

WLAN n-Mode; 20 MHz; MCS0
Applied duty cycle correction (AV): 0.7 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	69.2	PEAK	1000	74.0	4.8
11	2462	2483.5	47.4	AV	1000	54.0	6.6

WLAN n-Mode; 40 MHz; MCS0
Applied duty cycle correction (AV): 1.2 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
9	2452	2483.5	70.7	PEAK	1000	74.0	3.3
9	2452	2483.5	53.5	AV	1000	54.0	0.5

WLAN ax-Mode; 20 MHz; MCS0
Applied duty cycle correction (AV): 0.9 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
11	2462	2483.5	63.6	PEAK	1000	74.0	10.4
11	2462	2483.5	44.9	AV	1000	54.0	9.1

WLAN ax-Mode; 40 MHz; MCS0
Applied duty cycle correction (AV): 1.3 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]
9	2452	2483.5	63.3	PEAK	1000	74.0	10.7
9	2452	2483.5	49.1	AV	1000	54.0	4.9

WLAN n-Mode; 20 MHz; MCS0; MIMO
Applied duty cycle correction (AV): 0.8 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dB μ V/m]	Detector	RBW [kHz]	Limit [dB μ V/m]	Margin to Limit [dB]
11	2462	2483.5	59.6	PEAK	1000	74.0	14.4
11	2462	2483.5	44.2	AV	1000	54.0	9.8

WLAN n-Mode; 40 MHz; MCS0; MIMO
Applied duty cycle correction (AV): 1.2 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dB μ V/m]	Detector	RBW [kHz]	Limit [dB μ V/m]	Margin to Limit [dB]
9	2452	2483.5	67.0	PEAK	1000	74.0	7.0
9	2452	2483.5	48.7	AV	1000	54.0	5.3

WLAN ax-Mode; 20 MHz; MCS0; MIMO
Applied duty cycle correction (AV): 0.9 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dB μ V/m]	Detector	RBW [kHz]	Limit [dB μ V/m]	Margin to Limit [dB]
11	2462	2483.5	63.4	PEAK	1000	74.0	10.6
11	2462	2483.5	44.8	AV	1000	54.0	9.2

WLAN ax-Mode; 40 MHz; MCS0; MIMO
Applied duty cycle correction (AV): 1.3 dB


Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dB μ V/m]	Detector	RBW [kHz]	Limit [dB μ V/m]	Margin to Limit [dB]
9	2452	2483.5	64.4	PEAK	1000	74.0	9.6
9	2452	2483.5	49.9	AV	1000	54.0	4.1

Remark: Please see next sub-clause for the measurement plot.

5.2.4 MEASUREMENT PLOT (EXAMPLE PLOT, SHOWING WORST CASE, IF APPLICABLE)

Position 6


Radio Technology = WLAN b, Operating Frequency = high, Band Edge = high
(S06_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.063	54.2	---	74.00	19.83	1000.0	1000.000	150.0	V	-144.0	15.0	8.0
2484.063	---	41.1	54.00	12.88	1000.0	1000.000	150.0	V	-144.0	15.0	8.0


Radio Technology = WLAN n 20 MHz, Operating Frequency = high, Band Edge = high
(S06_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.938	---	45.4	54.00	8.61	1000.0	1000.000	150.0	V	34.0	90.0	43.8
2483.938	65.7	---	74.00	8.30	1000.0	1000.000	150.0	V	34.0	90.0	43.8
2484.125	---	45.5	54.00	8.46	1000.0	1000.000	150.0	V	32.0	93.0	43.8
2484.125	66.0	---	74.00	8.00	1000.0	1000.000	150.0	V	32.0	93.0	43.8


Radio Technology = WLAN n 40 MHz, Operating Frequency = high, Band Edge = high
 (S06_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.563	---	51.1	54.00	2.90	1000.0	1000.000	150.0	V	-139.0	14.0	43.8
2483.563	71.6	---	74.00	2.39	1000.0	1000.000	150.0	V	-139.0	14.0	43.8
2483.625	---	49.3	54.00	4.70	1000.0	1000.000	150.0	H	-129.0	-15.0	43.8
2483.625	70.0	---	74.00	4.03	1000.0	1000.000	150.0	H	-129.0	-15.0	43.8


Radio Technology = WLAN n 20 MHz MIMO, Operating Frequency = high, Band Edge = high
(S06_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.063	---	43.9	54.00	10.10	1000.0	1000.000	150.0	H	28.0	100.0	43.8
2484.063	62.4	---	74.00	11.57	1000.0	1000.000	150.0	H	28.0	100.0	43.8


Radio Technology = WLAN n 40 MHz MIMO, Operating Frequency = high, Band Edge = high
(S06_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.750	---	45.9	54.00	8.09	1000.0	1000.000	150.0	H	-6.0	88.0	43.8
2483.750	65.4	---	74.00	8.58	1000.0	1000.000	150.0	H	-6.0	88.0	43.8
2485.375	---	46.7	54.00	7.26	1000.0	1000.000	150.0	H	-130.0	105.0	43.8
2485.375	67.6	---	74.00	6.37	1000.0	1000.000	150.0	H	-130.0	105.0	43.8


Radio Technology = WLAN ax 20 MHz, Operating Frequency = high, Band Edge = high
(S06_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.500	---	44.7	54.00	9.27	1000.0	1000.000	150.0	V	-41.0	86.0	8.0
2483.500	65.0	---	74.00	9.00	1000.0	1000.000	150.0	V	-41.0	86.0	8.0


Radio Technology = WLAN ax 40 MHz, Operating Frequency = high, Band Edge = high
 (S06_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.500	---	52.4	54.00	1.63	1000.0	1000.000	150.0	V	-29.0	90.0	8.0
2483.500	68.9	---	74.00	5.13	1000.0	1000.000	150.0	V	-29.0	90.0	8.0


Radio Technology = WLAN ax 20 MHz MIMO, Operating Frequency = high, Band Edge = high
(S06_AC02)



Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.500	---	49.2	54.00	4.77	1000.0	1000.000	150.0	V	20.0	89.0	8.0
2483.500	72.5	---	74.00	1.49	1000.0	1000.000	150.0	V	20.0	89.0	8.0
2484.875	---	47.9	54.00	6.12	1000.0	1000.000	150.0	V	21.0	90.0	8.0
2484.875	71.6	---	74.00	2.44	1000.0	1000.000	150.0	V	21.0	90.0	8.0

Radio Technology = WLAN ax 40 MHz MIMO, Operating Frequency = high, Band Edge = high
(S06_AC02)




Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.250	---	45.5	54.00	8.47	1000.0	1000.000	150.0	V	28.0	86.0	43.8
2484.250	62.5	---	74.00	11.53	1000.0	1000.000	150.0	V	28.0	86.0	43.8

Position 1


Radio Technology = WLAN b mode, Operating Frequency = high, Band Edge = high (S01_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.125	---	42.9	54.00	11.14	1000.0	1000.000	150.0	H	-67.0	88.0	43.8
2484.125	55.6	---	74.00	18.39	1000.0	1000.000	150.0	H	-67.0	88.0	43.8


Radio Technology = WLAN g mode, Operating Frequency = high, Band Edge = high
(S01_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.375	---	45.9	54.00	8.11	1000.0	1000.000	150.0	H	53.0	105.0	43.8
2484.375	66.6	---	74.00	7.43	1000.0	1000.000	150.0	H	53.0	105.0	43.8


Radio Technology = WLAN n 20 MHz, Operating Frequency = high, Band Edge = high
(S01_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.000	---	45.8	54.00	8.15	1000.0	1000.000	150.0	H	-60.0	92.0	43.8
2484.000	67.3	---	74.00	6.68	1000.0	1000.000	150.0	H	-60.0	92.0	43.8


Radio Technology = WLAN n 40 MHz, Operating Frequency = high, Band Edge = high
(S01_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.125	---	47.7	54.00	6.33	1000.0	1000.000	150.0	H	-61.0	92.0	43.8
2484.125	73.5	---	74.00	0.55	1000.0	1000.000	150.0	H	-61.0	92.0	43.8


Radio Technology = WLAN ax 20 MHz, Operating Frequency = high, Band Edge = high
(S01_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.750	---	44.1	54.00	9.95	1000.0	1000.000	150.0	H	-49.0	82.0	43.8
2483.750	59.7	---	74.00	14.33	1000.0	1000.000	150.0	H	-49.0	82.0	43.8
2485.625	---	44.3	54.00	9.74	1000.0	1000.000	150.0	H	-61.0	89.0	43.8
2485.625	60.9	---	74.00	13.14	1000.0	1000.000	150.0	H	-61.0	89.0	43.8


Radio Technology = WLAN ax 40 MHz, Operating Frequency = high, Band Edge = high
(S01_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.500	---	45.2	54.00	8.83	1000.0	1000.000	150.0	H	-58.0	94.0	43.8
2484.500	63.1	---	74.00	10.85	1000.0	1000.000	150.0	H	-58.0	94.0	43.8
2491.313	---	44.5	54.00	9.54	1000.0	1000.000	150.0	H	-62.0	94.0	43.9
2491.313	61.0	---	74.00	13.05	1000.0	1000.000	150.0	H	-62.0	94.0	43.9


Radio Technology = WLAN n 20 MHz MIMO, Operating Frequency = high, Band Edge = high
(S01_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.063	---	45.2	54.00	8.76	1000.0	1000.000	150.0	H	58.0	105.0	43.8
2484.063	64.2	---	74.00	9.75	1000.0	1000.000	150.0	H	58.0	105.0	43.8


Radio Technology = WLAN n 40 MHz MIMO, Operating Frequency = high, Band Edge = high
(S01_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.500	---	46.4	54.00	7.62	1000.0	1000.000	150.0	H	63.0	105.0	43.8
2483.500	66.4	---	74.00	7.57	1000.0	1000.000	150.0	H	63.0	105.0	43.8
2489.875	---	44.1	54.00	9.89	1000.0	1000.000	150.0	H	119.0	-6.0	43.9
2489.875	64.5	---	74.00	9.46	1000.0	1000.000	150.0	H	119.0	-6.0	43.9


Radio Technology = WLAN ax 20 MHz MIMO, Operating Frequency = high, Band Edge = high
(S01_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.938	---	44.5	54.00	9.50	1000.0	1000.000	150.0	H	11.0	78.0	43.8
2483.938	62.0	---	74.00	12.02	1000.0	1000.000	150.0	H	11.0	78.0	43.8

Radio Technology = WLAN ax 40 MHz MIMO, Operating Frequency = high, Band Edge = high
(S01_AC02)




Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.500	---	47.4	54.00	6.65	1000.0	1000.000	150.0	H	55.0	105.0	43.8
2483.500	63.9	---	74.00	10.14	1000.0	1000.000	150.0	H	55.0	105.0	43.8
2485.375	---	46.9	54.00	7.13	1000.0	1000.000	150.0	H	58.0	96.0	43.8
2485.375	63.8	---	74.00	10.21	1000.0	1000.000	150.0	H	58.0	96.0	43.8

Position 4


Radio Technology = WLAN g mode, Operating Frequency = high, Band Edge = high
(S04_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
1200.040	---	36.8	54.00	17.20	1000.0	1000.000	150.0	H	-93.0	93.0	36.2
1200.040	48.1	---	74.00	25.92	1000.0	1000.000	150.0	H	-93.0	93.0	36.2
2483.750	---	48.7	54.00	5.31	1000.0	1000.000	150.0	H	-28.0	-6.0	43.8
2483.750	70.6	---	74.00	3.38	1000.0	1000.000	150.0	H	-28.0	-6.0	43.8
4000.000	---	41.1	54.00	12.86	1000.0	1000.000	150.0	V	-3.0	34.0	3.8
4000.000	49.6	---	74.00	24.35	1000.0	1000.000	150.0	V	-3.0	34.0	3.8


Radio Technology = WLAN n 20 MHz, Operating Frequency = high, Band Edge = high
(S04_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.938	---	46.7	54.00	7.30	1000.0	1000.000	150.0	H	-31.0	-5.0	43.8
2483.938	69.2	---	74.00	4.76	1000.0	1000.000	150.0	H	-31.0	-5.0	43.8


Radio Technology = WLAN n 40 MHz, Operating Frequency = high, Band Edge = high
(S04_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.750	---	51.8	54.00	2.19	1000.0	1000.000	150.0	H	-30.0	-2.0	43.8
2483.750	70.7	---	74.00	3.34	1000.0	1000.000	150.0	H	-30.0	-2.0	43.8
2484.563	---	52.3	54.00	1.70	1000.0	1000.000	150.0	H	-23.0	-3.0	43.8
2484.563	70.4	---	74.00	3.65	1000.0	1000.000	150.0	H	-23.0	-3.0	43.8
2487.625	---	52.1	54.00	1.93	1000.0	1000.000	150.0	H	-26.0	-6.0	43.9
2487.625	70.7	---	74.00	3.26	1000.0	1000.000	150.0	H	-26.0	-6.0	43.9


Radio Technology = WLAN ax 20 MHz, Operating Frequency = high, Band Edge = high
(S04_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.563	---	44.0	54.00	10.00	1000.0	1000.000	150.0	H	60.0	8.0	43.8
2483.563	63.6	---	74.00	10.39	1000.0	1000.000	150.0	H	60.0	8.0	43.8


Radio Technology = WLAN ax 40 MHz, Operating Frequency = high, Band Edge = high
(S04_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.500	---	47.8	54.00	6.15	1000.0	1000.000	150.0	H	60.0	15.0	43.8
2483.500	63.3	---	74.00	10.66	1000.0	1000.000	150.0	H	60.0	15.0	43.8


Radio Technology = WLAN n 20 MHz MIMO, Operating Frequency = high, Band Edge = high
(S04_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.313	---	43.4	54.00	10.60	1000.0	1000.000	150.0	H	3.0	87.0	43.8
2484.313	59.6	---	74.00	14.40	1000.0	1000.000	150.0	H	3.0	87.0	43.8


Radio Technology = WLAN n 40 MHz MIMO, Operating Frequency = high, Band Edge = high
(S04_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.688	---	46.8	54.00	7.19	1000.0	1000.000	150.0	H	-1.0	88.0	43.8
2484.688	63.5	---	74.00	10.47	1000.0	1000.000	150.0	H	-1.0	88.0	43.8
2485.375	---	47.5	54.00	6.47	1000.0	1000.000	150.0	H	-29.0	-6.0	43.8
2485.375	67.0	---	74.00	6.95	1000.0	1000.000	150.0	H	-29.0	-6.0	43.8


Radio Technology = WLAN ax 20 MHz MIMO, Operating Frequency = high, Band Edge = high
(S04_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2483.813	---	43.9	54.00	10.09	1000.0	1000.000	150.0	H	0.0	-4.0	43.8
2483.813	63.4	---	74.00	10.58	1000.0	1000.000	150.0	H	0.0	-4.0	43.8

Radio Technology = WLAN ax 40 MHz MIMO, Operating Frequency = high, Band Edge = high
(S04_AC02)



Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB/m)
2484.438	---	48.6	54.00	5.36	1000.0	1000.000	150.0	H	4.0	92.0	43.8
2484.438	64.4	---	74.00	9.63	1000.0	1000.000	150.0	H	4.0	92.0	43.8
2485.688	---	47.8	54.00	6.24	1000.0	1000.000	150.0	H	1.0	-15.0	43.8
2485.688	66.5	---	74.00	7.51	1000.0	1000.000	150.0	H	1.0	-15.0	43.8

5.2.5 TEST EQUIPMENT USED

- Radiated Emissions FAR 2.4 GHz FCC

6 TEST EQUIPMENT

6.1 TEST EQUIPMENT HARDWARE

- 1 Radiated Emissions FAR 2.4 GHz FCC
Radiated emission tests for 2.4 GHz ISM devices in a fully anechoic room

Ref.No.	Device Name	Description	Manufacturer	Serial Number	Last Calibration	Calibration Due
1.1	Opus10 TPR (8253.00)	T/P Logger 13	Lufft Mess- und Regeltechnik GmbH	13936	2023-12	2025-12
1.2	Innco Systems CO3000	Controller for bore sight mast FAC	innco systems GmbH	CO3000/1460/54740522/P	N/A	N/A
1.3	AMF-7D00101800-30-10P-R	Broadband Amplifier 100 MHz - 18 GHz	Miteq		N/A	N/A
1.4	Anechoic Chamber 03	FAR, 8.80m x 4.60m x 4.05m (l x w x h)	Albatross Projects	P26971-647-001-PRB	N/A	N/A
1.5	Fluke 177	Digital Multimeter 03 (Multimeter)	Fluke Europe B.V.	86670383	2023-08	2025-08
1.6	HF 906	Double-ridged horn	Rohde & Schwarz	357357/002	2022-07	2025-07
1.7	JS4-18002600-32-5P	Broadband Amplifier 18 GHz - 26 GHz	Miteq	849785	N/A	N/A
1.8	FSW43	Spectrum Analyzer	Rohde & Schwarz GmbH & Co. KG	103779	2023-04	2025-04
1.9	EP 1200/B, NA/B1	AC Source, Amplifier with integrated variable Oscillator	Spitzenberger & Spies GmbH & Co. KG	B6278	N/A	N/A
1.10	3160-09	Standard Gain / Pyramidal Horn Antenna 26.5 GHz	EMCO Elektronik GmbH	00083069	N/A	N/A
1.11	WHKX 7.0/18G-8SS	High Pass Filter	Wainwright Instruments GmbH	09	N/A	N/A
1.12	MA3000/0800-XP-ET-compact	Bore Sight Antenna Mast	innco systems GmbH	9210522	N/A	N/A
1.13	TT 1.5 WI	Turn Table	Maturo GmbH	-	N/A	N/A
1.14	5HC3500/18000-1.2-KK	High Pass Filter	Trilithic	200035008	N/A	N/A
1.15	Opus 20 THI (8120.00)	ThermoHygro Datalogger	Lufft Mess- und Regeltechnik GmbH	115.0318.0802.033	2023-08	2025-08
1.16	TD1.5-10kg	EUT Tilt Device (Rohacell)	Maturo GmbH	TD1.5-10kg/024/3790709	N/A	N/A
1.17	AFS42-00101800-25-S-42	Broadband Amplifier 25 MHz - 18 GHz	Miteq	2035324	N/A	N/A
1.18	HF 907	Double-ridged horn	Rohde & Schwarz	102444	2024-10	2027-10

- 2 Radiated Emissions SAC up to 1 GHz

Radiated emission tests up to 1 GHz in a semi anechoic room

Ref.No.	Device Name	Description	Manufacturer	Serial Number	Last Calibration	Calibration Due
2.1	N5000/NP	Filter for EUT, 2 Lines, 250 V, 16 A	ETS-LINDGREN	241515	N/A	N/A
2.2	Opus10 TPR (8253.00)	T/P Logger 13	Lufth Mess- und Regeltechnik GmbH	13936	2023-12	2025-12
2.3	ESW44	EMI Receiver / Spectrum Analyzer	Rohde & Schwarz GmbH & Co. KG	101603	2024-03	2026-03
2.4	Anechoic Chamber 01	SAC/FAR, 10.58 m x 6.38 m x 6.00 m	Frankonia Germany EMC Solution GmbH	none	N/A	N/A
2.5	HL 562 ULTRALOG	Biconical-log-per antenna (30 MHz - 3 GHz) with HL 562E biconicals	Rohde & Schwarz GmbH & Co. KG	830547/003		
2.6	Fluke 177	Digital Multimeter 03 (Multimeter)	Fluke Europe B.V.	86670383	2023-08	2025-08
2.7	Opus10 THI (8152.00)	T/H Logger 10	Lufth Mess- und Regeltechnik GmbH	12488	2023-12	2025-12
2.8	EP 1200/B, NA/B1	AC Source, Amplifier with integrated variable Oscillator	Spitzenberger & Spies GmbH & Co. KG	B6278	N/A	N/A
2.9	DS 420S	Turn Table 2 m diameter	HD GmbH	420/573/99	N/A	N/A
2.10	HL562E ULTRALOG	Biconical-log-per Antenna (30 MHz - 6 GHz)	Rohde & Schwarz GmbH & Co. KG	102299	2024-07	2027-07
2.11	Chase CBL6111C + INMET 64671 18N-6dB	Hybrid Antenna with 6dB Attenuator		2624 Kartei-Nr E-003226/K1026	2023-03	2026-03
2.12	CS-RUB6	Rubidium Frequency Standard	Rohde & Schwarz GmbH & Co. KG	100321	2023-10	2025-10
2.13	AM 4.0	Antenna Mast 4 m	Maturo GmbH	AM4.0/180/1192 0513	N/A	N/A

The calibration interval is the time interval between "Last Calibration" and "Calibration Due"

6.2 TEST EQUIPMENT SOFTWARE

Semi-Anechoic Chamber:	
Software	Version
EMC32 Measurement Software	10.60.10
INNCO Mast Controller	1.02.62
INNCO Mast Height	34.10
INNCO Mast Elevation	36.11
MATURO Controller	1.24
MATURO Mast	12.19
MATURO Turn-Table	30.10
Fully-Anechoic Chamber:	
Software	Version
EMC32 Measurement Software	10.60.10
MATURO Controller	1.30
MATURO Turn-Unit	11.10
MATURO Mast	12.10
MATURO Turntable	12.11
INNCO Controller	1.03.02
INNCO Mast Height	34.10
INNCO Mast Elevation	36.11
TS 8997	
WMS32 Measurement Software	11.60.00 (till 2024-03-19), 11.70.00 + Hotfix 01
Conducted AC Emissions:	
Software	Version
EMC32 Measurement Software	10.60.20

7 ANTENNA FACTORS, CABLE LOSS AND SAMPLE CALCULATIONS

This chapter contains the antenna factors with their corresponding path loss of the used measurement path for all antennas as well as the insertion loss of the LISN.

7.1 LISN R&S ESH3-Z5 (150 KHZ – 30 MHZ)

Frequency		Corr.	LISN insertion loss ESH3-Z5	cable loss (incl. 10 dB atten- uator)
MHz		dB	dB	dB
0.15		10.1	0.1	10.0
5		10.3	0.1	10.2
7		10.5	0.2	10.3
10		10.5	0.2	10.3
12		10.7	0.3	10.4
14		10.7	0.3	10.4
16		10.8	0.4	10.4
18		10.9	0.4	10.5
20		10.9	0.4	10.5
22		11.1	0.5	10.6
24		11.1	0.5	10.6
26		11.2	0.5	10.7
28		11.2	0.5	10.7
30		11.3	0.5	10.8

Sample calculation

$$U_{\text{LISN}} (\text{dB } \mu\text{V}) = U (\text{dB } \mu\text{V}) + \text{Corr. (dB)}$$

U = Receiver reading

LISN Insertion loss = Voltage Division Factor of LISN

Corr. = sum of single correction factors of used LISN, cables, switch units (if used)

Linear interpolation will be used for frequencies in between the values in the table.

7.2 ANTENNA R&S HFH2-Z2 (9 KHZ – 30 MHZ)

Frequency	AF HFH- Z2)	Corr.	cable loss 1 (inside chamber)	cable loss 2 (outside chamber)	cable loss 3 (switch unit)	cable loss 4 (to receiver)	distance corr. (-40 dB/ decade)	d _{Limit} (meas. distance (limit)	d _{used} (meas. distance (used)
MHz	dB (1/m)	dB	dB	dB	dB	dB	dB	m	m
0.009	20.50	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.01	20.45	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.015	20.37	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.02	20.36	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.025	20.38	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.03	20.32	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.05	20.35	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.08	20.30	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.1	20.20	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.2	20.17	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.3	20.14	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.49	20.12	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.490001	20.12	-39.6	0.1	0.1	0.1	0.1	-40	30	3
0.5	20.11	-39.6	0.1	0.1	0.1	0.1	-40	30	3
0.8	20.10	-39.6	0.1	0.1	0.1	0.1	-40	30	3
1	20.09	-39.6	0.1	0.1	0.1	0.1	-40	30	3
2	20.08	-39.6	0.1	0.1	0.1	0.1	-40	30	3
3	20.06	-39.6	0.1	0.1	0.1	0.1	-40	30	3
4	20.05	-39.5	0.2	0.1	0.1	0.1	-40	30	3
5	20.05	-39.5	0.2	0.1	0.1	0.1	-40	30	3
6	20.02	-39.5	0.2	0.1	0.1	0.1	-40	30	3
8	19.95	-39.5	0.2	0.1	0.1	0.1	-40	30	3
10	19.83	-39.4	0.2	0.1	0.2	0.1	-40	30	3
12	19.71	-39.4	0.2	0.1	0.2	0.1	-40	30	3
14	19.54	-39.4	0.2	0.1	0.2	0.1	-40	30	3
16	19.53	-39.3	0.3	0.1	0.2	0.1	-40	30	3
18	19.50	-39.3	0.3	0.1	0.2	0.1	-40	30	3
20	19.57	-39.3	0.3	0.1	0.2	0.1	-40	30	3
22	19.61	-39.3	0.3	0.1	0.2	0.1	-40	30	3
24	19.61	-39.3	0.3	0.1	0.2	0.1	-40	30	3
26	19.54	-39.3	0.3	0.1	0.2	0.1	-40	30	3
28	19.46	-39.2	0.3	0.1	0.3	0.1	-40	30	3
30	19.73	-39.1	0.4	0.1	0.3	0.1	-40	30	3

Sample calculation

$E \text{ (dB } \mu\text{V/m)} = U \text{ (dB } \mu\text{V)} + AF \text{ (dB 1/m)} + Corr. \text{ (dB)}$

U = Receiver reading

AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)

distance correction = $-40 * \text{LOG} (d_{\text{Limit}} / d_{\text{used}})$

Linear interpolation will be used for frequencies in between the values in the table.

Table shows an extract of values

7.3 ANTENNA R&S HL562 (30 MHZ – 1 GHZ)

($d_{\text{Limit}} = 3 \text{ m}$)

Frequency	AF R&S HL562	Corr.
MHz	dB (1/m)	dB
30	18.6	0.6
50	6.0	0.9
100	9.7	1.2
150	7.9	1.6
200	7.6	1.9
250	9.5	2.1
300	11.0	2.3
350	12.4	2.6
400	13.6	2.9
450	14.7	3.1
500	15.6	3.2
550	16.3	3.5
600	17.2	3.5
650	18.1	3.6
700	18.5	3.6
750	19.1	4.1
800	19.6	4.1
850	20.1	4.4
900	20.8	4.7
950	21.1	4.8
1000	21.6	4.9

cable loss 1 (inside chamber)	cable loss 2 (outside chamber)	cable loss 3 (switch unit)	cable loss 4 (to receiver)	distance corr. (-20 dB/ decade)	d_{Limit} (meas. distance (limit))	d_{used} (meas. distance (used))
dB	dB	dB	dB	dB	m	m
0.29	0.04	0.23	0.02	0.0	3	3
0.39	0.09	0.32	0.08	0.0	3	3
0.56	0.14	0.47	0.08	0.0	3	3
0.73	0.20	0.59	0.12	0.0	3	3
0.84	0.21	0.70	0.11	0.0	3	3
0.98	0.24	0.80	0.13	0.0	3	3
1.04	0.26	0.89	0.15	0.0	3	3
1.18	0.31	0.96	0.13	0.0	3	3
1.28	0.35	1.03	0.19	0.0	3	3
1.39	0.38	1.11	0.22	0.0	3	3
1.44	0.39	1.20	0.19	0.0	3	3
1.55	0.46	1.24	0.23	0.0	3	3
1.59	0.43	1.29	0.23	0.0	3	3
1.67	0.34	1.35	0.22	0.0	3	3
1.67	0.42	1.41	0.15	0.0	3	3
1.87	0.54	1.46	0.25	0.0	3	3
1.90	0.46	1.51	0.25	0.0	3	3
1.99	0.60	1.56	0.27	0.0	3	3
2.14	0.60	1.63	0.29	0.0	3	3
2.22	0.60	1.66	0.33	0.0	3	3
2.23	0.61	1.71	0.30	0.0	3	3

($d_{\text{Limit}} = 10 \text{ m}$)

30	18.6	-9.9
50	6.0	-9.6
100	9.7	-9.2
150	7.9	-8.8
200	7.6	-8.6
250	9.5	-8.3
300	11.0	-8.1
350	12.4	-7.9
400	13.6	-7.6
450	14.7	-7.4
500	15.6	-7.2
550	16.3	-7.0
600	17.2	-6.9
650	18.1	-6.9
700	18.5	-6.8
750	19.1	-6.3
800	19.6	-6.3
850	20.1	-6.0
900	20.8	-5.8
950	21.1	-5.6
1000	21.6	-5.6

0.29	0.04	0.23	0.02	-10.5	10	3
0.39	0.09	0.32	0.08	-10.5	10	3
0.56	0.14	0.47	0.08	-10.5	10	3
0.73	0.20	0.59	0.12	-10.5	10	3
0.84	0.21	0.70	0.11	-10.5	10	3
0.98	0.24	0.80	0.13	-10.5	10	3
1.04	0.26	0.89	0.15	-10.5	10	3
1.18	0.31	0.96	0.13	-10.5	10	3
1.28	0.35	1.03	0.19	-10.5	10	3
1.39	0.38	1.11	0.22	-10.5	10	3
1.44	0.39	1.20	0.19	-10.5	10	3
1.55	0.46	1.24	0.23	-10.5	10	3
1.59	0.43	1.29	0.23	-10.5	10	3
1.67	0.34	1.35	0.22	-10.5	10	3
1.67	0.42	1.41	0.15	-10.5	10	3
1.87	0.54	1.46	0.25	-10.5	10	3
1.90	0.46	1.51	0.25	-10.5	10	3
1.99	0.60	1.56	0.27	-10.5	10	3
2.14	0.60	1.63	0.29	-10.5	10	3
2.22	0.60	1.66	0.33	-10.5	10	3
2.23	0.61	1.71	0.30	-10.5	10	3

Sample calculation

$E \text{ (dB } \mu\text{V/m)} = U \text{ (dB } \mu\text{V)} + \text{AF (dB 1/m)} + \text{Corr. (dB)}$
 U = Receiver reading
 AF = Antenna factor
 Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)
 distance correction = $-20 * \text{LOG} (d_{\text{Limit}} / d_{\text{used}})$
 Linear interpolation will be used for frequencies in between the values in the table.
 Tables show an extract of values.

7.4 ANTENNA R&S HF907 (1 GHZ – 18 GHZ)

Frequency	AF R&S HF907	Corr.
MHz	dB (1/m)	dB
1000	24.4	-19.4
2000	28.5	-17.4
3000	31.0	-16.1
4000	33.1	-14.7
5000	34.4	-13.7
6000	34.7	-12.7
7000	35.6	-11.0

cable loss 1 (relay + cable inside chamber)	cable loss 2 (outside chamber)	cable loss 3 (switch unit, atten- uator & pre-amp)	cable loss 4 (to receiver)		
dB	dB	dB	dB		
0.99	0.31	-21.51	0.79		
1.44	0.44	-20.63	1.38		
1.87	0.53	-19.85	1.33		
2.41	0.67	-19.13	1.31		
2.78	0.86	-18.71	1.40		
2.74	0.90	-17.83	1.47		
2.82	0.86	-16.19	1.46		

Frequency	AF R&S HF907	Corr.
MHz	dB (1/m)	dB
3000	31.0	-23.4
4000	33.1	-23.3
5000	34.4	-21.7
6000	34.7	-21.2
7000	35.6	-19.8

cable loss 1 (relay inside chamber)	cable loss 2 (inside chamber)	cable loss 3 (outside chamber)	cable loss 4 (switch unit, atten- uator & pre-amp)	cable loss 5 (to receiver)	used for FCC 15.247
dB	dB	dB	dB	dB	
0.47	1.87	0.53	-27.58	1.33	
0.56	2.41	0.67	-28.23	1.31	
0.61	2.78	0.86	-27.35	1.40	
0.58	2.74	0.90	-26.89	1.47	
0.66	2.82	0.86	-25.58	1.46	

Frequency	AF R&S HF907	Corr.
MHz	dB (1/m)	dB
7000	35.6	-57.3
8000	36.3	-56.3
9000	37.1	-55.3
10000	37.5	-56.2
11000	37.5	-55.3
12000	37.6	-53.7
13000	38.2	-53.5
14000	39.9	-56.3
15000	40.9	-54.1
16000	41.3	-54.1
17000	42.8	-54.4
18000	44.2	-54.7

cable loss 1 (relay inside chamber)	cable loss 2 (High Pass)	cable loss 3 (pre- amp)	cable loss 4 (inside chamber)	cable loss 5 (outside chamber)	cable loss 6 (to receiver)
dB	dB	dB	dB	dB	dB
0.56	1.28	-62.72	2.66	0.94	1.46
0.69	0.71	-61.49	2.84	1.00	1.53
0.68	0.65	-60.80	3.06	1.09	1.60
0.70	0.54	-61.91	3.28	1.20	1.67
0.80	0.61	-61.40	3.43	1.27	1.70
0.84	0.42	-59.70	3.53	1.26	1.73
0.83	0.44	-59.81	3.75	1.32	1.83
0.91	0.53	-63.03	3.91	1.40	1.77
0.98	0.54	-61.05	4.02	1.44	1.83
1.23	0.49	-61.51	4.17	1.51	1.85
1.36	0.76	-62.36	4.34	1.53	2.00
1.70	0.53	-62.88	4.41	1.55	1.91

Sample calculation

$E \text{ (dB } \mu\text{V/m)} = U \text{ (dB } \mu\text{V)} + AF \text{ (dB 1/m)} + Corr. \text{ (dB)}$

U = Receiver reading

AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)

Linear interpolation will be used for frequencies in between the values in the table.

Tables show an extract of values.

7.5 ANTENNA EMCO 3160-09 (18 GHZ – 26.5 GHZ)

Frequency	AF EMCO 3160-09	Corr.	cable loss 1 (inside chamber)	cable loss 2 (pre- amp)	cable loss 3 (inside chamber)	cable loss 4 (switch unit)	cable loss 5 (to receiver)
MHz	dB (1/m)	dB	dB	dB	dB	dB	dB
18000	40.2	-23.5	0.72	-35.85	6.20	2.81	2.65
18500	40.2	-23.2	0.69	-35.71	6.46	2.76	2.59
19000	40.2	-22.0	0.76	-35.44	6.69	3.15	2.79
19500	40.3	-21.3	0.74	-35.07	7.04	3.11	2.91
20000	40.3	-20.3	0.72	-34.49	7.30	3.07	3.05
20500	40.3	-19.9	0.78	-34.46	7.48	3.12	3.15
21000	40.3	-19.1	0.87	-34.07	7.61	3.20	3.33
21500	40.3	-19.1	0.90	-33.96	7.47	3.28	3.19
22000	40.3	-18.7	0.89	-33.57	7.34	3.35	3.28
22500	40.4	-19.0	0.87	-33.66	7.06	3.75	2.94
23000	40.4	-19.5	0.88	-33.75	6.92	3.77	2.70
23500	40.4	-19.3	0.90	-33.35	6.99	3.52	2.66
24000	40.4	-19.8	0.88	-33.99	6.88	3.88	2.58
24500	40.4	-19.5	0.91	-33.89	7.01	3.93	2.51
25000	40.4	-19.3	0.88	-33.00	6.72	3.96	2.14
25500	40.5	-20.4	0.89	-34.07	6.90	3.66	2.22
26000	40.5	-21.3	0.86	-35.11	7.02	3.69	2.28
26500	40.5	-21.1	0.90	-35.20	7.15	3.91	2.36

Sample calculation

$E \text{ (dB } \mu\text{V/m)} = U \text{ (dB } \mu\text{V)} + AF \text{ (dB 1/m)} + Corr. \text{ (dB)}$

U = Receiver reading

AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)

Linear interpolation will be used for frequencies in between the values in the table.

Table shows an extract of values.

7.6 ANTENNA EMCO 3160-10 (26.5 GHZ – 40 GHZ)

Frequency GHz	AF EMCO 3160-10 dB (1/m)	Corr. dB	cable loss 1 (inside chamber) dB	cable loss 2 (outside chamber) dB	cable loss 3 (switch unit) dB	cable loss 4 (to receiver) dB	distance corr. (-20 dB/ decade) dB	d _{Limit} (meas. distance (limit) m	d _{used} (meas. distance (used) m
26.5	43.4	-11.2	4.4				-9.5	3	1.0
27.0	43.4	-11.2	4.4				-9.5	3	1.0
28.0	43.4	-11.1	4.5				-9.5	3	1.0
29.0	43.5	-11.0	4.6				-9.5	3	1.0
30.0	43.5	-10.9	4.7				-9.5	3	1.0
31.0	43.5	-10.8	4.7				-9.5	3	1.0
32.0	43.5	-10.7	4.8				-9.5	3	1.0
33.0	43.6	-10.7	4.9				-9.5	3	1.0
34.0	43.6	-10.6	5.0				-9.5	3	1.0
35.0	43.6	-10.5	5.1				-9.5	3	1.0
36.0	43.6	-10.4	5.1				-9.5	3	1.0
37.0	43.7	-10.3	5.2				-9.5	3	1.0
38.0	43.7	-10.2	5.3				-9.5	3	1.0
39.0	43.7	-10.2	5.4				-9.5	3	1.0
40.0	43.8	-10.1	5.5				-9.5	3	1.0

Sample calculation

$E \text{ (dB } \mu\text{V/m)} = U \text{ (dB } \mu\text{V)} + AF \text{ (dB 1/m)} + Corr. \text{ (dB)}$

U = Receiver reading

AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)

Linear interpolation will be used for frequencies in between the values in the table.

distance correction = $-20 * \text{LOG} (d_{\text{Limit}} / d_{\text{used}})$


Linear interpolation will be used for frequencies in between the values in the table.

Table shows an extract of values.

8 MEASUREMENT UNCERTAINTIES

Test Case	Parameter	Uncertainty
AC Power Line	Power	± 3.4 dB
Field Strength of spurious radiation	Power	± 5.5 dB
6 dB / 26 dB / 99% Bandwidth	Power Frequency	± 2.9 dB ± 11.2 kHz
Conducted Output Power	Power	± 2.2 dB
Band Edge Compliance	Power Frequency	± 2.2 dB ± 11.2 kHz
Frequency Stability	Frequency	± 25 Hz
Power Spectral Density	Power	± 2.2 dB

The measurement uncertainties for all parameters are calculated with an expansion factor (coverage factor) $k = 1.96$. This means, that the true value is in the corresponding interval with a probability of 95 %.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	on pass mark	within pass mark	Passed
4	above pass mark	within pass mark	Failed
5	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.

9 PHOTO REPORT

Please see separate photo report.

*****END OF TEST REPORT*****