

Maximum Permissible Exposure Report

For

Shenzhen Qiyue Optronics Company Limited

Flat3, Tower 3, Excellence Meilin Center Plaza, Zhongkang Road 128, Shangmeilin, Futian District, Shenzhen, China

FCC ID: XOMRNSMU4336A

FCC Rule(s):	<u>FCC 47CFR Part 1.1310</u>
Product Description:	<u>43 inches SMART 4K UHD TV</u>
Tested Model:	<u>D43GA064-U-A-I RNSMU4336</u> <u>XXXXXXXXXXXX43XXXXXXXXXXXX</u> <u>(Where "X"can be any alphanumeric of a-z, A-Z or 0-9 or blank & "-".)</u>
Report No.:	<u>SEM1811039-2</u>
Sample Receipt Date:	<u>October 23, 2018</u>
Tested Date:	<u>October 24 ~ November 22, 2018</u>
Issued Date:	<u>November 23, 2018</u>
Tested By:	<u>Jason Su / Engineer</u> 
Reviewed By:	<u>Silin Chen / EMC Manager</u> 
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u> 
Prepared By:	<p>Shenzhen SEM Test Technology Co. Ltd 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, 518101,China Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn</p>

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 STANDARD APPLICABLE.....	4
1.3 MPE CALCULATION METHOD	4
1.4 MPE CALCULATION RESULT.....	5

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information	
Applicant:	Shenzhen Qiyue Optronics Company Limited
Address of applicant:	Flat3,Tower 3, Excellence Meilin Center Plaza, Zhongkang Road 128, Shangmeilin, Futian District, Shenzhen, China
Manufacturer:	SHENZHEN QIYUE OPTRONICS COMPANY LIMITED BRANCH
Address of manufacturer:	SEIYU INDUSTRIAL PARK, DA SAN VILLAGE, DA SHUI KENG, GUANLAN TOWN, LONGHUA NEW DISTRICT, SHENZHEN, P.R.C

General Description of EUT	
Product Name:	43 inches SMART 4K UHD TV
Trade Name:	RCA
Model No.:	D43GA064-U-A-I RNSMU4336 XXXXXXXXXXXX43XXXXXXXXXXXX (Where "X"can be any alphanumeric of a-z, A-Z or 0-9 or blank &"-".)
Test Model(s):	RNSMU4336
Rated Voltage:	AC 100-120V~ 60Hz, 68W
Power Adapter Model:	/
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	IEEE 802.11b/ g / nHT20: 2412MHz~2462MHz IEEE802.11nHT40: 2422MHz~2452MHz
RF Output Power:	Max output power in total is 12.69dBm (Conducted)
Modulation:	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)
Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Type of Antenna:	Wi-Fi Antenna
Antenna Gain:	Antenna 1: 3 dBi Antenna 2: 3 dBi

1.2 Standard Applicable

According to § 1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Model No.: D43GA064-U-A-I

XXXXXXXXXXXX43XXXXXXXXXXXX

(Where "X" can be any alphanumeric of a-z, A-Z or 0-9 or blank & "-".)

FCC ID: XOMRNSMU4336A

Device category: Mobile device

Maximum peak output power: 11.29(dBm)

Maximum peak output power at antenna input terminal: 13.5(mW)

Prediction distance: >20(cm)

Prediction frequency: 2437 (MHz)@ N20

Antenna gain: 3.0 (dBi)

Directional gain: 2.0(numeric)

The worst case is power density at prediction frequency at 20cm: 0.0054(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

$0.0054(\text{mw/cm}^2) < 1 (\text{mw/cm}^2)$

So the transmitter complies with the RF exposure requirements and the SAR is not required.