



FCC and IC TEST REPORT

for

KADENCE DESIGNS LLC

Subwoofer W6.2.0

Model Number: W6.2.0

Prepared for : KADENCE DESIGNS LLC
Address : P.O.Box 2359, Thompson Falls, MT 59873

Prepared By : NS Technology Co., Ltd.
Address : Chenwu Industrial Zone, Houjie Town, Dongguan City,
Guangdong, China

Tel: +86-769-85935656
Fax: +86-769-85991080

Report Number : NSE-F10085105
Date of Test : Jul. 30, 2010
Date of Report : Aug. 9, 2010





NS Technology Co., Ltd.

Applicant:	KADENCE DESIGNS LLC		
Address:	P.O.Box 2359,Thompson Falls,MT 59873		
Manufacturer:	Celewave Electronics(shenzhen) Co.,Ltd		
Address:	No 1-2 building,No 2 Industry District, Shang Heng lang Huaxing Road, Dalang Street,Baoan District, Shenzhen City,China		
E.U.T:	Subwoofer W6.2.0		
Model Number:	W6.2.0		
Report Number:	NSE-F10085185		
Trade Name:	Klipsch	e²	ebode Luxsound™
Operating Frequency:	2412~2464MHz		
Date of Receipt:	Jul.17, 2010	Date of Test:	Jul. 30, 2010
Test Specification:	RSS-210 Issue 7 2007 47 CFR FCC Part 2 Subpart J, section 2.1091		
Test Result:	The equipment under test was found to be compliance with the requirements of the standards applied.		
Issue Date: Aug. 9, 2010			
Tested by:	Reviewed by:	Approved by:	
Jade/ Engineer	Iceman Hu / Supervisor	Steven Lee / Manager	
Other Aspects: None.			
Abbreviations: <i>OK/P=passed</i> <i>fail/F=failed</i> <i>n.a/N=not applicable</i> <i>E.U.T=equipment under tested</i>			
<i>This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of NS Technology Co., Ltd.</i>			



Maximum Permissible Exposure

1 Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density(S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density(S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2 MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.



3 Calculated Result and Limit

Mode	CH	Output power (dBm)	Output power (mW)	Antenna Gain (dBi)	MPE estimation result (mW/cm ²) at 20cm	Limit of MPE Estimation (mW/cm ²)	Test result
Antenna1	CH1:2412MHz	15.19	33.04	5.5	0.0486	1	Compiles
	CH2:2438MHz	15.05	31.99	5.5	0.0471	1	Compiles
	CH3:2464MHz	14.91	30.97	5.5	0.0447	1	Compiles
Antenna2	CH1:2412MHz	14.82	30.34	5.5	0.0447	1	Compiles
	CH2:2438MHz	14.29	26.85	5.5	0.0395	1	Compiles
	CH3:2464MHz	14.34	27.16	5.5	0.0400	1	Compiles

