

RF Exposure

This calculation is based on the highest EIRP possible from the Remote or the Base considering maximum power and antenna gain. The following formulas were used:

The highest output power of the EUT is 14 mW equivalent radiated Power

1 MINIMUM SEPARATION DISTANCE PER OET 65

The following information provides the minimum separation distance for the EUT, as calculated from **FCC OET 65 Appendix B, Table 1B** "Guidelines for General Population/Uncontrolled Exposure"

Freq. MHz	S GP limit mW/cm^2	Maximum RF power dBm	Antenna Gain dB	EIRP dBm	EIRP watts	MSD d meters
2437	1	11.5	0	11.5	0.0141	0.0106

GP is the limit for general Population/Uncontrolled Exposure

MSD is the minimum Separation Distance

Notes on above table.

(S) GP limit is from OET 65 table 1B

EIRP = Power in dBm + Antenna Gain in dBi

MSD (Minimum Separation Distance) = $((EIRP*30)/3770*S))^{0.5}$

NOTE: For mobile or fixed location transmitters, minimum separation distance is 20 cm, even if calculations indicate MPE distance is less.

The low threshold for a device operated within 2.5 cm from human body is $60/(f \text{ GHz}) = 60/2.440 = 24.59 \text{ mw}$
Since the hand held version of this device has a power which is lower than 24.59 mw, no SAR is required.

2 RF EVALUATION FOR RSS-102E

Since the e.i.r.p. of the Product is 14 mW it is exempt from routine SAR and RF exposure evaluations in accordance to Sections 2.5.1 or 2.5.2 of RSS-102e.

The following information provides the calculation for section 4.2 of RSS-102e for the General Public.

Freq. MHz	RF Power dBm	Antenna Gain dB	Effective RF power dBm	Measurement Distance meters	RF field from EUT V/m	Exposure GP limit V/m rms
2437	11.5	0	11.5	14.13	0.025	26.0

GP is the limit for general Public

Note on above table.

ERP = $(V/m * \text{dist})^{2/30}$