



TESTING LABORATORY  
CERTIFICATE # 4821.01



## FCC PART 90

### TEST REPORT

For

### RCA Communications Systems

133 West Market Street, Suite 227, Indianapolis, Indiana 46204, United States

**FCC ID: XYH-RDR6350U**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Digital Two-Way Radio
<b>Report Number:</b> <u>RSZ180308006-00B</u>	
<b>Report Date:</b> <u>2018-04-17</u>	
Reviewed By: <u>Rocky Kang</u> <b>Reviewed By:</b> <u>RF Engineer</u>	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. \* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “\*”.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION</b> .....	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION</b> .....	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS .....	6
SUPPORT EQUIPMENT LIST AND DETAILS .....	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS</b> .....	<b>8</b>
<b>TEST EQUIPMENT LIST</b> .....	<b>9</b>
<b>FCC §1.1307 (b) (1) &amp; §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)</b> .....	<b>10</b>
APPLICABLE STANDARD .....	10
RESULT .....	10
<b>FCC §2.1046 &amp; §90.205 - RF OUTPUT POWER</b> .....	<b>12</b>
APPLICABLE STANDARD .....	12
TEST PROCEDURE .....	12
TEST DATA .....	12
<b>FCC §2.1047 &amp; §90.207 - MODULATION CHARACTERISTIC</b> .....	<b>14</b>
APPLICABLE STANDARD .....	14
TEST PROCEDURE .....	14
TEST DATA .....	14
<b>FCC §2.1049 &amp; §90.210 – OCCUPIED BANDWIDTH &amp; EMISSION MASK</b> .....	<b>20</b>
APPLICABLE STANDARD .....	20
TEST PROCEDURE .....	20
TEST DATA .....	20
<b>FCC §2.1051 &amp; §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS</b> .....	<b>28</b>
APPLICABLE STANDARD .....	28
TEST PROCEDURE .....	28
TEST DATA .....	28
<b>FCC §2.1053 &amp; §90.210 - RADIATED SPURIOUS EMISSIONS</b> .....	<b>31</b>
APPLICABLE STANDARD .....	31
TEST PROCEDURE .....	31
TEST DATA .....	31
<b>FCC §2.1055 &amp; §90.213 - FREQUENCY STABILITY</b> .....	<b>33</b>
APPLICABLE STANDARD .....	33
TEST PROCEDURE .....	33

TEST DATA .....	33
<b>FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR.....</b>	<b>35</b>
APPLICABLE STANDARD .....	35
TEST PROCEDURE .....	35
TEST DATA .....	36

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

The *RCA Communications Systems*'s product, model number: *RDR6350U* (*FCC ID: XYH-RDR6350U*) or the "EUT" in this report was a *Digital Two-Way Radio*, which was measured approximately: 17 cm (L) \* 17 cm (W) \* 6 cm (H), rated with input voltage: DC 13.6V.

Type	Parameter
Frequency Range(MHz)	400-470
Rated Output power(Watts)	40 (High) / 25 (Middle) / 5 (Low)
Modulation	FM/ 4FSK
Channel Spacing(kHz)	12.5 (Analog)
	12.5 (Digital)

*\*All measurement and test data in this report was gathered from production sample serial number: 1800278 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2018-03-08.*

### Objective

This test report is prepared on behalf of *RCA Communications Systems* in accordance with Part 2, and Part 90 of the Federal Communication Commissions rules.

### Related Submittal(s)/Grant(s)

Part 15.247 DSS submission with FCC ID: XYH-RDR6350U.

### Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 90 – Private Land Mobile Radio Service

Applicable Standards: TIA 603-D.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	±5%	
RF output power, conducted	±1.5dB	
Unwanted Emission, conducted	±1.5dB	
Emissions, radiated	Below 1GHz Above 1GHz	±4.70dB ±4.80dB
Temperature	±1 °C	
Supply voltages	±0.4%	

## Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in a test mode which has been done in the factory.

### EUT Exercise Software

No exercise software was used.

### Special Accessories

No special accessory was used.

### Equipment Modifications

No modification was made to the EUT tested.


### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Matrix	Battery	NP100-12	N/A
N/A	Load	N/A	N/A

### External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-shielded Un-detachable DC cable	2.0	Battery	EUT

### Block Diagram of Test Setup



## SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§1.1307(b), §2.1091	Maximum Permissible exposure (MPE)	Compliance
§2.1046; §90.205	RF Output Power	Compliance
§2.1047; §90.207	Modulation Characteristic	Compliance
§2.1049; §90.210	Occupied Bandwidth & Emission Mask	Compliance
§2.1051;§90.210	Spurious Emission at Antenna Terminal	Compliance
§2.1053;§90.210	Spurious Radiated Emissions	Compliance
§2.1055;§90.213	Frequency Stability	Compliance
§90.214	Transient Frequency Behavior	Compliance

## TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2018-01-11	2019-01-11
HP	Amplifier	HP8447E	1937A01046	2017-11-19	2018-05-17
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2017-04-24	2018-04-24
Sunol Sciences	Horn Antenna	DRH-118	A052604	2017-12-22	2020-12-21
HP	Synthesized Sweeper	HP 8341B	2624A00116	2017-07-02	2018-07-01
Mini	Amplifier	ZVA-183-S+	5969001149	2017-05-21	2018-05-21
A.H. System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2017-11-19	2018-05-17
Ducommun technologies	RF Cable	104PEA	218124002	2017-11-19	2018-05-17
Ducommun technologies	RF Cable	RG-214	1	2017-11-19	2018-05-17
Ducommun technologies	RF Cable	RG-214	2	2017-11-22	2018-05-22
COM POWER	Dipole Antenna	AD-100	041000	2017-08-18	2018-08-18
<b>RF Conducted test</b>					
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2017-12-05	2018-12-05
HP	RF Communication test set	8920A	3325U00859	2017-06-14	2018-06-13
LEADER	MILLIVOLTMETER	LMV-181A	6041126	2017-10-12	2018-10-12
Hewlett-Packard	Frequency Counter	5343A	2232A00827	2016-08-29	2019-08-29
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2017-11-22	2018-11-22
Ducommun technologies	RF Cable	RG-214	3	2017-11-22	2018-05-22
N/A	30dB Attenuator	53-30-43	PG633	2017-11-22	2018-05-22
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2017-04-24	2018-04-24

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**FCC §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)****Applicable Standard**

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

**Limits for Occupational/Controlled Exposure**

Limits for occupational/Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	6
1.34-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5.0	6

f = frequency in MHz

\* = Plane-wave equivalent power density

**Result****Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency Range (MHz)	Antenna Gain		Conducted Power (mW)	Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Strictest MPE Limit (mW/cm <sup>2</sup> )
	(dBi)	(numeric)				
400-470	5.5	3.55	26240.375	80	1.16	1.33

Note: The rated max tune-up output power is 47.2dBm(52480.75mW), 50% duty cycle was used in evaluation, so the power is 26240.375mW

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Simultaneous transmitting consideration: (referring to the bluetooth report, the highest MPE is 0.0001mW/cm<sup>2</sup>)

The ratio=MPE/limit<sub>TNB</sub>+MPE/limit<sub>DSS</sub>=1.16/1.33+0.0001/1=0.8723<1.0

**Result: Compliance.** The device meets MPE requirement for Occupational/Controlled use at 80cm distance.

## **FCC §2.1046 & §90.205 - RF OUTPUT POWER**

### **Applicable Standard**

FCC §2.1046 and §90.205

### **Test Procedure**

Conducted RF Output Power:

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Spectrum Analyzer Setting:

R B/W      Video B/W  
100 kHz      300 kHz

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Tracy Hu on 2018-03-14.*

*Test Mode: Transmitting*

**Test Result:** Compliance. Please refer to following table.

Mode	Frequency Spacing (kHz)	Frequency (MHz)	Power level	Output Power (dBm)	Output Power (W)	Result
Analog	12.5	400.0125	High	46.77	47.53	Pass
			Low	36.78	4.76	Pass
			Middle	44.02	25.23	Pass
		453.2125	High	46.75	47.32	Pass
			Low	36.78	4.76	Pass
			Middle	43.88	24.43	Pass
		469.9875	High	46.73	47.10	Pass
			Low	36.81	4.80	Pass
			Middle	43.91	24.60	Pass
Digital		400.0125	High	46.78	47.64	Pass
			Low	36.87	4.86	Pass
			Middle	44.01	25.18	Pass
		453.2125	High	46.76	47.42	Pass
			Low	36.84	4.83	Pass
			Middle	43.9	24.55	Pass
		469.9875	High	46.74	47.21	Pass
			Low	36.88	4.88	Pass
			Middle	43.94	24.77	Pass

**Note:** The rated high power is 40W. The limit of the high output power is 32W-48W.

The rated low power is 5W. The limit of the low output power is 4W-6W.

The rated middle power is 25W. The limit of the middle output power is 20W-30W.

## **FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC**

### **Applicable Standard**

FCC§2.1047 and §90.207:

- (a) Equipment which utilizes voice modulated communication shall show the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz. for equipment which is required to have a low pass filter, the frequency response of the filter, or all of the circuitry installed between the modulation limited and the modulated stage shall be supplied.
- (b) Equipment which employs modulation limiting, a curve showing the percentage of modulation versus the modulation input voltage shall be supplied.

### **Test Procedure**

Test Method: TIA/EIA-603-D

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa


*The testing was performed by Tracy Hu on 2018-03-14.*

Please refer to the following tables and plots.

**Analog Modulation:****MODULATION LIMITING**

Carrier Frequency: 453.2125 MHz, Channel Separation=12.5 kHz


Audio Frequency (Hz)	Instantaneous		Steady-state		FCC Limit [kHz]
	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	
300	2.303	0.073	2.296	0.069	2.500
400	2.261	0.088	2.259	0.086	2.500
500	2.262	0.093	2.256	0.090	2.500
600	2.216	0.214	2.209	0.212	2.500
700	2.216	0.369	2.208	0.367	2.500
800	2.292	0.368	2.184	0.367	2.500
900	2.157	0.368	2.153	0.367	2.500
1000	2.173	0.400	2.170	0.398	2.500
1200	2.173	0.399	2.165	0.398	2.500
1400	2.190	0.399	2.188	0.398	2.500
1600	2.153	0.401	2.149	0.398	2.500
1800	2.133	0.399	2.125	0.398	2.500
2000	2.140	0.399	2.131	0.398	2.500
2100	2.271	0.400	2.265	0.398	2.500
2200	2.202	0.399	2.191	0.398	2.500
2300	2.182	0.400	2.174	0.398	2.500
2400	2.172	0.401	2.163	0.399	2.500
2500	2.182	0.588	2.179	0.586	2.500
2600	2.172	0.587	2.168	0.586	2.500
2700	2.161	0.588	2.154	0.586	2.500
2800	2.143	0.589	2.136	0.586	2.500
2900	2.164	0.588	2.148	0.586	2.500
3000	2.173	0.587	2.164	0.586	2.500



**Audio Frequency Response**

Carrier Frequency: 453.2125 MHz, Channel Separation=12.5 kHz


Audio Frequency (Hz)	Response Attenuation (dB)
300	-11.24
400	-8.78
500	-6.71
600	-4.85
700	-3.30
800	-2.07
900	-0.86
1000	0.00
1200	1.60
1400	2.87
1600	4.01
1800	5.28
2000	6.17
2100	6.70
2200	6.91
2300	7.61
2400	7.70
2500	8.06
2600	8.51
2700	8.89
2800	9.26
2900	9.70
3000	9.97



**Audio frequency lows pass filter response**

Carrier Frequency: 453.2125 MHz, Channel Separation=12.5 kHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-36.5	0.0
4.0	-43.1	-12.5
5.0	-57.8	-22.2
6.0	-65.8	-30.1
7.0	-74.3	-36.8
8.0	-76.1	-42.6
9.0	-80.0	-47.7
10.0	-86.3	-52.3
12.0	-94.1	-60.2
14.0	-88.3	-66.9
16.0	-86.4	-72.7
18.0	-91.8	-77.8
20.0	-89.6	-82.5



## **FCC §2.1049 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK**

### **Applicable Standard**

FCC §2.1049 and §90.210

Emission Mask D - 12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- 1) For any frequency removed from the center of the authorized bandwidth  $f_0$  to 5.625 kHz removed from  $f_0$ , 0dB.
- 2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 5.626 kHz but no more than 12.5 kHz, at least 7.27 ( $f_d - 2.88$  kHz) dB.
- 3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 12.5 kHz at least: At least  $50 + 10 \log (P)$  dB or 70 dB, whichever is the lesser attenuation.

### **Test Procedure**

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 100 Hz and the spectrum was recorded in the frequency band  $\pm 50$  kHz from the carrier frequency.

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Tracy Hu on 2018-04-02 and 2018-04-03.*

*Test mode: transmitting*

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power Level	99% Occupied Bandwidth (kHz)	26 dB Emissions Bandwidth (kHz)
Analog	12.5	453.2125	High	10.02	10.34
	12.5		Middle	10.02	10.34
	12.5		Low	10.02	10.34
Digital	12.5	453.2125	High	6.97	9.38
	12.5		Middle	6.65	9.05
	12.5		Low	6.97	9.62

*Note: Emission designator is base on calculation instead of measurement.*

*Emission Designator Per CFR 47 §2.201 & §2.202 &, Bn = 2M + 2D*

**For FM Mode (Channel Spacing: 12.5 kHz)**

*Emission Designator 11K0F3E* In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.  $BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} \rightarrow 11K0$

*F3E portion of the designator represents an FM voice transmission Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.*


**For Digital Mode (Channel Spacing: 12.5 kHz)**

*Emission Designator 7K60F1D and 7K60F1E*


*The 99% energy rule (title 47CFR 2.1049) was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 6.97 kHz. The emission mask was obtained from 47CFR 90.210(d).*

*F1D and F1E portion of the designator indicates digital information.*

*Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F1D and 7K60F1E.*


**Analog Modulation:****Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, High Power**

Date: 2.APR.2018 23:10:42

**Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, Middle Power**


Date: 2.APR.2018 23:09:40

## Frequency 453.2125 MHz: 99% Occupied &amp; 26 dB Bandwidth, Low Power




Date: 2.APR.2018 23:06:42


## Frequency 453.2125 MHz: Emission Mask D, High Power




Date: 3.APR.2018 00:32:22

**Frequency 453.2125 MHz: Emission Mask D, Middle Power**


Date: 3.APR.2018 00:32:56

**Frequency 453.2125 MHz: Emission Mask D, Low Power**

Date: 3.APR.2018 00:33:31


**Digital Modulation:****Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, High Power**

Date: 2.APR.2018 23:49:04

**Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, Middle Power**


Date: 2.APR.2018 23:43:16

## Frequency 453.2125 MHz: 99% Occupied &amp; 26 dB Bandwidth, Low Power




Date: 2.APR.2018 23:42:03


## Frequency 453.2125 MHz: Emission Mask D, High Power



Date: 3.APR.2018 00:31:16

**Frequency 453.2125 MHz: Emission Mask D, Middle Power**

Date: 3.APR.2018 00:30:18

**Frequency 453.2125 MHz: Emission Mask D, Low Power**

Date: 3.APR.2018 00:29:35

## FCC §2.1051 & §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS

### Applicable Standard

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- 1) For any frequency removed from the center of the authorized bandwidth  $f_0$  to 5.625 kHz removed from  $f_0$ , 0 dB.
- 2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 5.626 kHz but no more than 12.5 kHz, at least 7.27 ( $f_d - 2.88$  kHz) dB.
- 3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 12.5 kHz: At least  $50 + 10 \log (P)$  dB or 70 dB, whichever is the lesser attenuation.

### Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100kHz for below 1GHz, and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10<sup>th</sup> harmonic.


### Test Data

#### Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

*The testing was performed by Tracy Hu on 2018-03-14.*


*Test Mode: Transmitting, worst case for High power level, please refer to the following plots.*

**Analog Modulation:****30MHz – 1 GHz, 453.2125 MHz**Fund.test with  
filter


Date: 14.MAR.2018 22:01:48

**1 GHz – 5 GHz, 453.2125 MHz**

Date: 14.MAR.2018 22:04:56

**Digital Modulation:****30MHz – 1 GHz, 453.2125 MHz**Fund.test with  
filter

Date: 14.MAR.2018 22:01:19

**1 GHz – 5 GHz, 453.2125 MHz**

Date: 14.MAR.2018 22:05:09

## FCC §2.1053 & §90.210 - RADIATED SPURIOUS EMISSIONS

### Applicable Standard

FCC §2.1053 and §90.210

### Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to teeth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \log_{10}(\text{TXpwr in Watts}/0.001)$ -the absolute level

Spurious attenuation limit in dB = $50 + 10 \log_{10}(\text{power out in Watts})$  for EUT with a 12.5 kHz channel bandwidth.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

*The testing was performed by Tracy Hu on 2018-03-14.*

*Test Mode: Transmitting, worst case for High power level.*

**30MHz - 5GHz:**

Frequency (MHz)	Receiver Reading (dB $\mu$ V)	Turn Table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
Analog Modulation, 453.2125MHz, 12.5 kHz										
906.425	60.54	297	1.1	H	-34.5	0.28	0.0	-34.78	-20	14.78
906.425	58.03	49	2.3	V	-36.0	0.28	0.0	-36.28	-20	16.28
1359.6375	61.62	138	1.3	H	-46.2	1.60	7.90	-39.90	-20	19.90
1359.6375	54.35	193	1.7	V	-53.7	1.60	7.90	-47.40	-20	27.40
1812.85	43.68	104	2.4	H	-62.4	1.30	9.30	-54.40	-20	34.40
1812.85	42.74	148	1.5	V	-63.0	1.30	9.30	-55.00	-20	35.00
2266.0625	50.7	280	2.3	H	-53.8	1.30	10.00	-45.10	-20	25.10
2266.0625	51.54	292	2.2	V	-52.9	1.30	10.00	-44.20	-20	24.20
Digital Modulation, 453.2125MHz, 12.5 kHz										
906.425	59.93	275	2.3	H	-35.1	0.28	0.0	-35.38	-20	15.38
906.425	55.01	166	1.8	V	-39.0	0.28	0.0	-39.28	-20	19.28
1359.6375	57.17	104	1.2	H	-50.7	1.60	7.90	-44.40	-20	24.40
1359.6375	57.11	45	1.8	V	-51.0	1.60	7.90	-44.70	-20	24.70
1812.85	49.06	6	1.1	H	-57.0	1.30	9.30	-49.00	-20	29.00
1812.85	45.83	215	2.1	V	-59.9	1.30	9.30	-51.90	-20	31.90
2266.0625	58.27	205	2.1	H	-46.2	1.30	10.00	-37.50	-20	17.50
2266.0625	55.48	68	2.0	V	-48.9	1.30	10.00	-40.20	-20	20.20

**Note:**

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

## FCC §2.1055 & §90.213 - FREQUENCY STABILITY

### Applicable Standard

FCC §2.1055 and §90.213

### Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external AC/DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The power cable and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

*The testing was performed by Tracy Hu on 2018-03-14.*

*Test Mode: Transmitting*

Note: The device is intended for fixed using.

For 12.5 kHz:

Analog Modulation, Reference Frequency: 453.2125 MHz, Limit: $\pm 2.5$ ppm			
Test Environment		Frequency Measure with Time Elapsed	
Temperature (°C)	Voltage Supplied (V <sub>DC</sub> )	Measured Frequency (MHz)	Frequency Error (ppm)
Frequency Stability versus Input Temperature			
50	13.6	453.21255	0.1147
40	13.6	453.21260	0.2251
30	13.6	453.21250	0.0044
20	13.6	453.21251	0.0265
10	13.6	453.21252	0.0485
0	13.6	453.21254	0.0927
-10	13.6	453.21259	0.2030
-20	13.6	453.21257	0.1589
-30	13.6	453.21257	0.1589
Frequency Stability versus Input Voltage			
20	11.6	453.21252	0.0485

Digital Modulation, Reference Frequency: 453.2125 MHz, Limit: $\pm 2.5$ ppm			
Test Environment		Frequency Measure with Time Elapsed	
Temperature (°C)	Voltage Supplied (V <sub>DC</sub> )	Measured Frequency (MHz)	Frequency Error (ppm)
Frequency Stability versus Input Temperature			
50	13.6	453.21255	0.1147
40	13.6	453.21256	0.1368
30	13.6	453.21256	0.1368
20	13.6	453.21255	0.1147
10	13.6	453.21251	0.0265
0	13.6	453.21258	0.1809
-10	13.6	453.21252	0.0485
-20	13.6	453.21253	0.0706
-30	13.6	453.21255	0.1147
Frequency Stability versus Input Voltage			
20	11.6	453.21255	0.1147

## FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR


### Applicable Standard

Regulations: FCC §90.214

Test method: ANSI/TIA-603-D 2010, section 2.2.19.3

### Test Procedure

- a) Connect the EUT and test equipment as shown on the following block diagram.
- b) Set the Spectrum Analyzer to measure FM deviation, and tune the RF frequency to the transmitter assigned frequency.
- c) Set the signal generator to the assigned transmitter frequency and modulate it with a 1 kHz tone at  $\pm 12.5$  kHz deviation and set its output level to -100dBm.
- d) Turn on the transmitter.
- e) Supply sufficient attenuation via the RF attenuator to provide an input level to the Spectrum Analyzer that is 40 dB below the maximum allowed input power when the transmitter is operating at its rated power level. Note this power level on the Spectrum Analyzer as  $P_0$ .
- f) Turn off the transmitter.
- g) Adjust the RF level of the signal generator to provide RF power equal to  $P_0$ . This signal generator RF level shall be maintained throughout the rest of the measurement.
- h) Remove the attenuation 1, so the input power to the Spectrum Analyzer is increased by 30 dB when the transmitter is turned on.
- i) Adjust the vertical amplitude control of the spectrum analyzer to display the 1000 Hz at  $\pm 4$  divisions vertically centered on the display. Set trigger mode of the Spectrum Analyzer to “Video”, and tune the “trigger level” on suitable level. Then set the “tiger offset” to -10ms for turn on and -15ms for turn off.
- j) Turn on the transmitter and the transient wave will be captured on the screen of Spectrum Analyzer. Observe the stored display. The instant when the 1 kHz test signal is completely suppressed is considered to be  $t_{on}$ . The trace should be maintained within the allowed divisions during the period  $t_1$  and  $t_2$ .
- k) Then turn off the transmitter, and another transient wave will be captured on the screen of Spectrum Analyzer. The trace should be maintained within the allowed divisions during the period  $t_3$ .



## Test Data

### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Tracy Hu on 2018-03-13.


Channel Separation (kHz)	Transient Period (ms)	Transient Frequency	Result
12.5	10 (t1)	<+/-12.5 kHz	Pass
	25 (t2)	<+/-6.25 kHz	
	10 (t3)	<+/-12.5 kHz	

Please refer to the following plots.

### Channel: 453.2125 MHz, 12.5 kHz

Turn on



**Turn off**

\*\*\*\*\* END OF REPORT \*\*\*\*\*