

Maximum Permissible Exposure Report

1. Product Information

FCC ID:	Y3H710331032004
Product name	wireless video transmitter system
Model number	7103&3103
Test Model	7103&3103
Power supply	Input: 100-240V~, 50/60Hz, 0.75A Output:12V---2000mA
Operation frequency	5180MHz-5240MHz 5745MHz-5825MHz
Antenna Type	External Antenna
Antenna Gain	2.5dBi
Hardware version	02
Software version	1.05
Channel Number	4 channels for 20MHz bandwidth (5180-5240MHz) 2 channels for 40MHz bandwidth (5190~5230MHz) 5 channels for 20MHz bandwidth (5745-5825MHz) 2 channels for 40MHz bandwidth (5755~5795MHz)
Channel Spacing	5MHz
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Fixed Device

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3. 1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

3. 2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

wireless video transmitter system can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Antenna 0	External Antenna	5000 MHz – 5800 MHz	2.5 dBi	WiFi Antenna
Antenna 1	External Antenna	5000 MHz – 5800 MHz	2.5 dBi	WiFi Antenna

6. Conducted Power

[5G U-NII-1 WIFI Max Conducted Power]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)	Max Conducted Power(dBm)
			ANT 0	ANT 1
11N20 SISO	36	5180	12.30	11.78
	40	5200	12.11	11.97
	48	5240	11.46	10.63
11N40 SISO	38	5190	9.95	6.50
	46	5230	9.93	6.17

[5G U-NII-1 WIFI MIMO Max Conducted Power]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)	
			ANT 0+1	
11N20 SISO	36	5180	15.06	
	40	5200	15.05	
	48	5240	14.08	
11N40 SISO	38	5190	11.57	
	46	5230	11.46	

[5G U-NII-3 WIFI Max Conducted Power]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)	Max Conducted Power(dBm)
			ANT 0	ANT 1
11N20 SISO	149	5745	16.87	9.69
	157	5785	10.08	10.04
	165	5825	10.39	9.52
11N40 SISO	151	5755	10.01	10.87
	159	5795	10.67	10.24

[5G U-NII-3 WIFI MIMO Max Conducted Power]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)	
			ANT 0+1	
11N20 SISO	149	5745	17.63	
	157	5785	13.07	
	165	5825	12.99	
11N40 SISO	151	5755	13.47	
	159	5795	13.47	

7. Measurement Results

5G U-NII-1WIFI

11N20 SISO (Peak)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	15.0	15.0	14.0
Tolerance \pm (dB)	1.0	1.0	1.0
11N40 SISO (Peak)			
Channel	Channel 38		Channel 46
Target (dBm)	11.0		11.0
Tolerance \pm (dB)	1.0		1.0

5G U-NII-3 WIFI

11N20 SISO (Peak)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	17.0	13.0	13.0
Tolerance \pm (dB)	1.0	1.0	1.0
11N40 SISO (Peak)			
Channel	Channel 151		Channel 159
Target (dBm)	13.0		13.0
Tolerance \pm (dB)	1.0		1.0

8. Evaluation Results

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

5G U-NII-1 WIFI

Band/Mode	f (GHz)	RF output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
		dBm	mW				
11N20 SISO	5.200	16.0	39.8107	5.51	3.5563	0.0282	1.0000
11N40 SISO	5.200	12.0	15.8489	5.51	3.5563	0.0112	1.0000

5G U-NII-3 WIFI

Band/Mode	f (GHz)	RF output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
		dBm	mW				
11N20 SISO	5.745	18.0	63.0957	5.51	3.5563	0.0446	1.0000
11N40 SISO	5.745	14.0	25.1189	5.51	3.5563	0.0178	1.0000

Remark:

1. Output power including turn-up tolerance;
2. Output power is burst average power;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer;
4. MPE values = $PG/4\pi R^2$

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----