

ALTO
PROFESSIONAL
TS108C
 600-WATT 8" PORTABLE
 COLUMNAR ARRAY LOUDSPEAKER

- a. Finland (Suomi): Laitte on liitettävä suojakoskettimilla varustettuun pistorasiaan.
- b. Norway (Norge): Apparatet må tilkoples jordat stikkontakt.
- c. Sweden (Sverige): Apparaten skall anslutas till jordat uttag.
- d. Denmark (Danmark): Apparatets stikprop skal tilsluttes en stikkontakt med jord, som giver forbindelse til stikproppens jord.

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION


DESIGNED IN USA

MODEL



FCC ID: Y40-TSA1
 IC: 11215A-TSA1
 CAN ICES-003(B) / NMB-003(B)

SERIAL



Intertek
 5000925

CONFORMS TO UL
 STD. 62368-1
 CERTIFIED TO CSA
 STD. C22.2 NO.62368-1



AC INPUT
 ● 100-120V-50/60Hz
 ● 220-240V-50/60Hz
POWER CONSUMPTION: 300W

