

# RF TEST REPORT



Report No.: 17020459-FCC-R1

Supersede Report No.: N/A

Applicant	CHAMPION POWER EQUIPMENT, INC	
Product Name	Remote Controller	
Main Model	K185-2	
Serial Model	N/A	
Test Standard	FCC Part 15.231: 2016, ANSI C63.10: 2013	
Test Date	April 24, 2017	
Issue Date	April 25, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification		<input checked="" type="checkbox"/>
Equipment did not comply with the specification		<input type="checkbox"/>
Deon Dai	Miro Bao	
Deon Dai Test Engineer	Miro Bao Checked By	
<p>This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only</p>		

Issued by:

SIEMIC (Nanjing-China) Laboratories

2-1 Longcang Avenue Yuhua Economic and  
Technology Development Park, Nanjing, China

Tel: +86(25)86730138 Fax: +86(25)86730127 Email: China@siemic.com.cn

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC , RF/Wireless , Telecom
Canada	EMC, RF/Wireless , Telecom
Taiwan	EMC, RF, Telecom , Safety
Hong Kong	RF/Wireless , Telecom
Australia	EMC, RF, Telecom , Safety
Korea	EMI, EMS, RF , Telecom, Safety
Japan	EMI, RF/Wireless, Telecom
Singapore	EMC , RF , Telecom
Europe	EMC, RF, Telecom , Safety

Test Report No.	17020459-FCC-R1
Page	3 of 31

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY.....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. TEST SUMMARY .....	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	8
6.1 ANTENNA REQUIREMENT .....	8
6.2 AC CONDUCTED EMISSIONS VOLTAGE .....	9
6.3 20DB OCCUPIED BANDWIDTH.....	10
6.4 RADIATED FUNDAMENTAL AND SPURIOUS EMISSION.....	12
6.5 DEACTIVATION.....	19
ANNEX A. TEST INSTRUMENT.....	21
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS .....	22
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	28
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST.....	30
ANNEX E. DECLARATION OF SIMILARITY .....	31

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
17020459-FCC-R1	NONE	Original	April 25, 2017

## 2. Customer information

Applicant Name	CHAMPION POWER EQUIPMENT, INC
Applicant Add	12039 Smith Avenue, Santa Fe Springs, CA90670, USA
Manufacturer Name	Zhongshan Kingcobra Electronics Co.,Ltd.
Manufacturer Add	20#Tongxing East Road, Dongsheng Town, Zhongshan City, Guangdong, China

## 3. Test site information

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Add	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	986914
IC Test Site No.	4842B-1
Test Software	EZ_EMC

#### 4. Equipment Under Test (EUT) Information

Description of EUT: Remote Controller

Main Model: K185-2

Serial Model: N/A

Date EUT received: April 21, 2017

Test Date(s): April 24, 2017

Antenna Gain: 2 dBi

Type of Modulation: ASK

RF Operating Frequency (ies): Tx:433.90MHz

Number of Channels: 1 CH

Port: N/A

Power: DC6V

Trade Name: CHAMPION

FCC ID: YA3-K185

## 5. Test Summary

The product was tested in accordance with the following specifications.  
All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207	Conducted Emissions Voltage	N/A*
§15.231(b)	Fundamental & Radiated Spurious Emission	Compliance
§15.231(c)	20dB Bandwidth	Compliance
§15.231(a)(1)	Deactivation	Compliance

Note: Preliminary radiated emission testing has been performed on X, Y, Z axis, only worst case test result is presented in this test report.

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	3.92dB

N/A\*: EUT is Power Supply by Battery

## **6. Measurements, Examination And Derived Results**

### **6.1 Antenna Requirement**

#### **Applicable Standard**

Requirement(s): 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

The antenna is permanently attached to the device which meets the requirement.


Result: Compliance.

## 6.2 AC Conducted Emissions Voltage

Temperature	-
Relative Humidity	-
Atmospheric Pressure	-
Test date :	-
Tested By :	-

### Conducted Emission Limit


Frequency ranges (MHz)	Limit (dB $\mu$ V)	
	QP	Average
0.15 ~ 0.5	66 – 56	56 – 46
0.5 ~ 5	56	46
5 ~ 30	60	50

Spec	Item	Requirement	Applicable
47CFR§15.20 7, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequency ranges.	<input type="checkbox"/>
Test Setup	 <p><b>Note:</b> 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>		
Procedure	<ul style="list-style-type: none"> <li>The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.</li> <li>The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.</li> <li>The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.</li> <li>All other supporting equipment were powered separately from another main supply.</li> </ul>		
Remark	EUT is Power Supply by Battery		
Result	<input checked="" type="checkbox"/> N/A <input type="checkbox"/> Fail		

## 6.3 20dB Occupied Bandwidth

Temperature	25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	April 24, 2017
Tested By :	Deon Dai

Requirement(s):

Spec	Item	Requirement	Applicable
§15.231(c)	a)	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz.	<input checked="" type="checkbox"/>
	b)	For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency.	<input type="checkbox"/>
Test Setup			
Test Procedure	<p><u>20dB Emission bandwidth measurement procedure</u></p> <ul style="list-style-type: none"> <li>- Set RBW = 100 kHz.</li> <li>- Set the video bandwidth (VBW) <math>\geq 3 \times</math> RBW.</li> <li>- Detector = Peak.</li> <li>- Trace mode = max hold.</li> <li>- Sweep = auto couple.</li> <li>- Allow the trace to stabilize.</li> </ul> <p>Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.</p>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data     Yes       N/A


Test Plot     Yes       N/A

### 20dB Bandwidth measurement result

Type	Freq (MHz)	CH	Measured 20dB Bandwidth (kHz)	Limit (kHz)	Result
20dB BW	433.90	1 CH	280.3	1084.75	Pass

### Test Plots


#### 20dB Bandwidth measurement result




## 6.4 Radiated Fundamental and Spurious Emission

Temperature	25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	April 24, 2017
Tested By :	Deon Dai

Requirement(s):

Spec	Item	Requirement	Applicable																					
§15.231(b)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Fundamental frequency (MHz)</th> <th>Field strength of fundamental (microvolts/meter)</th> <th>Field strength of spurious emissions (microvolts/meter)</th> </tr> </thead> <tbody> <tr> <td>40.66-40.70</td> <td>2250</td> <td>225</td> </tr> <tr> <td>70-130</td> <td>1250</td> <td>125</td> </tr> <tr> <td>130-174</td> <td>1250 to 3750</td> <td>125 to 375</td> </tr> <tr> <td>174-260</td> <td>3750</td> <td>375</td> </tr> <tr> <td>260-470</td> <td>3750-12500</td> <td>375 to 1250</td> </tr> <tr> <td>Above 470</td> <td>12500</td> <td>1250</td> </tr> </tbody> </table> <p>Note: All 3 axes have been investigated. Only worst case is presented in the test report.</p>	Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)	40.66-40.70	2250	225	70-130	1250	125	130-174	1250 to 3750	125 to 375	174-260	3750	375	260-470	3750-12500	375 to 1250	Above 470	12500	1250	<input checked="" type="checkbox"/>
Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)																						
40.66-40.70	2250	225																						
70-130	1250	125																						
130-174	1250 to 3750	125 to 375																						
174-260	3750	375																						
260-470	3750-12500	375 to 1250																						
Above 470	12500	1250																						
Test Setup		<p>A: &lt; 1GHz</p>  <p>The diagram shows a test setup for frequencies below 1GHz. An 'EUT &amp; Support Units' is mounted on a 'Turn Table' at a height of 80cm from a 'Ground Plane'. The turn table is positioned 3m away from an 'Ant. Tower' which is mounted on a '1-4m Variable' height post. A 'Test Receiver' is connected to the system to measure the emissions.</p> <p>B: &gt;1GHz</p>																						

	 <p>The diagram illustrates the test setup. An EUT (Equipment Under Test) and its support units are placed on a turntable, which is positioned 150 cm above a ground plane. A 3m distance separates the EUT from an antenna tower. The antenna tower is a 1-4m variable height antenna mounted on a wheeled base. A test receiver is connected to the antenna tower to measure the emissions.</p>
Procedure	<ol style="list-style-type: none"> <li>1. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>2. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:           <ol style="list-style-type: none"> <li>a. Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</li> <li>b. The EUT was then rotated to the direction that gave the maximum emission.</li> <li>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</li> </ol> </li> <li>3. A Quasi-peak measurement was then made for that frequency point.</li> <li>4. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</li> </ol>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A

Test Plot  Yes (See below)  N/A

**Data sample**

No.	Frequency (MHz)	Reading (dB $\mu$ V/m)	Detector	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Degree (°)

Frequency (MHz) = Emission frequency in MHz

Reading (dB $\mu$ V/m) = Receiver Reading Value

Detector= Peak Detector or Quasi Peak Detector

Ant\_F=Antenna Factor

PA\_G=Pre-Amplifier Gain

Cab\_L=Cable Loss

Result (dB $\mu$ V/m) = Read ing Value + Corrected Value

Limit (dB $\mu$ V/m) = Limit stated in standard


Height (cm) = Height of Receiver antenna

Degree = Turn table degree

Calculation Formula:

Margin (dB) = Result (dB $\mu$ V/m) – limit (dB $\mu$ V/m)

Fundamental



Vertical Polarity Plot @3m

Field strength of fundamental Result


No.	Frequency (MHz)	Reading (dB $\mu$ V/m)	Detector	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Degree (°)
6	433.90	85.07	Pk	16.43	49.13	3.35	55.72	100.8	-45.08	200	222
6	433.90	-	Ave	-	-	-	44.5	80.8	-36.3	-	-

Field strength of spurious emissions Result

No.	Frequency (MHz)	Reading (dB $\mu$ V/m)	Detector	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Degree (°)
8	867.80	69.46	peak	23.02	46.12	4.76	51.12	80.8	-29.68	200	83
8	867.80	-	Ave	-	-	-	39.9	60.8	-20.9	-	-

Notes: Duty cycle is 27.49%,  $20\log(\text{duty cycle}) = -11.22\text{dB}$  correction was used to determine the average level from the peak reading.

Average = peak reading +  $20\log(\text{duty cycle})$ , Final Average = peak reading -  $11.22\text{dB}$



### Field strength of fundamental Result

No.	Frequency (MHz)	Reading (dB $\mu$ V/m)	Detector	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Degree (°)
3	433.90	94.97	Pk	16.00	49.13	3.35	65.19	100.8	-35.61	200	291
3	433.90	-	Ave	-	-	-	53.97	80.8	-26.83	-	-

### Field strength of spurious emissions Result

No.	Frequency (MHz)	Reading (dB $\mu$ V/m)	Detector	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Degree (°)
7	867.80	81.15	Pk	22.79	46.12	4.76	62.58	80.8	-18.22	200	360
7	867.80	-	Ave	-	-	-	51.36	60.8	-9.44	-	-

Notes: Duty cycle is 27.49%,  $20\log(\text{duty cycle}) = -11.22\text{dB}$  correction was used to determine the average level from the peak reading.

Average = peak reading +  $20\log(\text{duty cycle})$ , Final Average = peak reading -  $11.22\text{dB}$

## Spurious Emissions (< 1GHz) Measurement Result

Vertical Polarity Plot @3m

No.	Frequency (MHz)	Reading (dB $\mu$ V/m)	Detector	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Degree (°)
1	31.6202	50.10	peak	20.66	45.67	0.90	25.99	40.00	-14.01	100	172
2	50.7637	52.73	peak	8.96	46.49	1.25	16.45	40.00	-23.55	100	46
3	70.0903	53.52	peak	10.42	47.88	1.44	17.50	40.00	-22.50	200	6
4	129.4678	48.19	peak	16.34	47.26	1.86	19.13	43.50	-24.37	100	72
5	220.6171	49.65	peak	14.87	47.80	2.36	19.08	46.00	-26.92	100	41
7	729.3583	49.22	peak	22.28	45.46	4.34	30.38	46.00	-15.62	119	360

Horizontal Polarity Plot @3m

No.	Frequency (MHz)	Reading (dB $\mu$ V/m)	Detector	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Degree (°)
1	125.8864	48.49	peak	15.67	47.00	1.83	18.99	43.50	-24.51	300	191
2	265.6757	50.41	peak	15.70	48.22	2.59	20.48	46.00	-25.52	300	48
4	590.9737	51.32	peak	20.79	48.67	3.90	27.34	46.00	-18.66	300	242
5	645.1195	49.36	peak	21.77	47.47	4.08	27.74	46.00	-18.26	300	14
6	729.3583	49.17	peak	22.58	45.46	4.34	30.63	46.00	-15.37	300	76
8	1000.0000	47.88	peak	25.10	46.17	5.06	31.87	54.00	-22.13	200	279

Notes:

1. Duty cycle is 27.49%, 20log (duty cycle) = -11.22dB correction was used to determine the average level from the peak reading.  
Average = peak reading + 20log (duty cycle), Final Average= peak reading -11.22dB
2. All the data measurement of peak values.
3. FCC Limit for Average Measurement=41.67\* (433.90MHz)-7083.3333=10998.1131 $\mu$ V/m=80.8dB $\mu$ V/m
4. Average pulsed signal over one complete pulse train or 100 ms time frame if pulse train exceeds 100 ms
5. Maximum average in 100 ms
6. Calculate duty cycle for pulse train or 100 ms
7. Duty cycle =  $(t_1 + t_2 + t_3 + \dots + t_n)/T$  where  $t_n$  = pulse width,  $T$  = pulse train length or 100 ms

### Spurious Emissions (>1GHz) Measurement Result

Frequency GHz	Reading (dB $\mu$ V/m)	Direction Degree	Height Meter	Polar H/V	Ant_F (dB/M)	PA_G (dB)	Cab_L (dB)	correct (dB $\mu$ V/m)	FCC 15.231 Limit (dB $\mu$ V/m)	Margin	Comments
1.302	81.24	276	2	H	24.64	51.56	2.85	57.17	74	-16.83	Peak
1.302	-	-	-	H	-	-	-	45.95	54	-8.05	Ave
1.736	77.26	131	1	H	25.99	50.98	3.99	56.26	80.8	-24.54	Peak
1.736	-	-	-	H	-	-	-	45.04	60.8	-15.76	Ave
2.169	73.25	56	2	H	27.84	52.38	4.17	52.88	80.8	-27.92	Peak
2.169	-	-	-	H	-	-	-	41.66	60.8	-19.14	Ave
2.603	77.25	89	1	H	29.26	52.68	4.13	57.96	80.8	-22.84	Peak
2.603	-	-	-	H	-	-	-	46.74	60.8	-14.06	Ave
3.037	76.93	355	2	H	29.33	52.82	4.5	57.94	80.8	-22.86	Peak
3.037	-	-	-	H	-	-	-	46.72	60.8	-14.08	Ave
3.471	68.02	244	1	H	32.02	52.88	4.91	52.07	74	-21.93	Peak
3.471	-	-	-	H	-	-	-	40.85	54	-13.15	Ave
1.302	64.89	65	2	V	24.64	51.56	2.85	40.82	74	-33.18	Peak
1.302	-	-	-	V	-	-	-	29.60	54	-24.4	Ave
1.736	61.26	138	1	V	25.99	50.98	3.99	40.26	80.8	-40.54	Peak
1.736	-	-	-	V	-	-	-	29.04	60.8	-31.76	Ave
2.169	79.79	319	2	V	27.84	52.38	4.17	59.42	80.8	-21.38	Peak
2.169	-	-	-	V	-	-	-	48.2	60.8	-12.6	Ave
2.603	78.92	286	2	V	29.26	52.68	4.13	59.63	80.8	-21.17	Peak
2.603	-	-	-	V	-	-	-	48.41	60.8	-12.39	Ave
3.037	74.48	188	2	V	29.33	52.82	4.5	55.49	80.8	-25.31	Peak
3.037	-	-	-	V	-	-	-	47.96	60.8	-12.84	Ave
3.471	79.27	2	2	V	32.02	52.88	4.91	63.32	74	-10.68	Peak
3.471	-	-	-	V	-	-	-	52.1	57	-4.9	Ave

Note: Duty cycle is 27.49%, 20log (duty cycle) = -11.22dB correction was used to determine the average level from the peak reading.

Average = peak reading + 20log (duty cycle), final Average= peak reading -11.22dB

Note:


Narrow Pulse: 0.2344ms

2/NP = 2/0.2344ms =8.53kHz

RBW > 2/NP (8.53kHz)


Therefore PDCF is not needed.

## Duty Cycle Measurement Result



Duty Cycle 1#

Duty Cycle 2#



Duty Cycle 3#

Wide Pulse: 0.2344ms  
 Narrow Pulse: 1.113ms  
 $\text{Duty cycle} = (1.113*9+0.2344*16)/50.08 = 27.49\%$   
 Average Duty Factor:  $20 * \log(\text{Duty Cycle}) = -11.22\text{dB}$

Pulse Duty Cycle

## 6.5 Deactivation

Temperature	25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	April 24, 2017
Tested By :	Deon Dai


Requirement(s):

Spec	Item	Requirement	Applicable
§15.231 (a)(1)	a)	A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.	<input checked="" type="checkbox"/>
Test Setup		<div style="border: 1px solid black; padding: 5px; display: inline-block;">Spectrum Analyzer</div> <span style="margin: 0 10px;">—</span> <div style="border: 1px solid black; padding: 5px; display: inline-block;">EUT</div>	
Test Procedure	<p><u>measurement procedure</u></p> <ul style="list-style-type: none"> <li>- Set analyzer center frequency to channel center frequency.</li> <li>- Set the span to 0Hz.</li> <li>- Set the RBW = 100 kHz</li> <li>- Set the VBW <math>\geq 3' RBW</math>.</li> <li>- Detector = peak.</li> <li>- Sweep time = auto couple.</li> <li>- Trace mode = max hold.</li> <li>- Allow trace to fully stabilize.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data     Yes       N/A  
 Test Plot     Yes (See below)       N/A

## Test Plots

### Deactivation Measurement Result



## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>AC Line Conducted Emissions</b>					
R&S EMI Test Receiver	ESPI3	101216	03/31/2017	03/31/2018	<input type="checkbox"/>
V-LISN	ESH3-Z5	838979/005	03/31/2017	03/31/2018	<input type="checkbox"/>
SIEMIC EZ_EMC software Conducted Emissions	Ver.ICP-03A1	N/A	N/A	N/A	<input type="checkbox"/>
<b>RF conducted test</b>					
Spectrum Analyzer	N9010A	MY47191130	03/11/2017	03/10/2018	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	1007H	N/A	01/07/2017	01/06/2018	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
Agilent Technologies	N9010A	MY47191130	03/11/2017	03/10/2018	<input checked="" type="checkbox"/>
R&S EMI Receiver	ESPI3	101216	03/31/2017	03/31/2018	<input checked="" type="checkbox"/>
Antenna (30MHz~6GHz)	JB6	A121411	10/31/2016	10/31/2017	<input checked="" type="checkbox"/>
EMCO Horn Antenna (1 ~18GHz)	3115	N/A	10/09/2016	10/08/2017	<input checked="" type="checkbox"/>
Hp Agilent Pre-Amplifier	8447F	1937A01160	10/27/2016	10/26/2017	<input checked="" type="checkbox"/>
Pre-Amplifier	8449B	3008A02224	10/30/2016	10/30/2017	<input checked="" type="checkbox"/>
SIEMIC EZ_EMC software Radiated Emissions	Ver.ICP-03A1	N/A	N/A	N/A	<input checked="" type="checkbox"/>

## Annex B. EUT And Test Setup Photographs

### Annex B.i. Photograph: EUT External Photos



Top View of EUT



Bottom View of EUT



Front View of EUT



Rear View of EUT



Left View of EUT




Right View of EUT


Annex B.ii. Photograph EUT Internal Photos



EUT Uncover- Front View




EUT PCBA – Front View



EUT PCBA 1 – Rear View

**Annex B.iii. Photograph: Test Setup Photo**



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above 1GHz

## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex C.i. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



### Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model
N/A	N/A	N/A

Test Report No.	17020459-FCC-R1
Page	30 of 31

## Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

## Annex E. DECLARATION OF SIMILARITY

N/A

Thank you!

Printed name/title: Purchasing Manager

FCC ID: 2AGCVT7XXX2017

Signature: Hangzhou HILAND Technology CO., LTD

Address: 4TH BUILDING, 2XIYUANWU ROAD, WESTLAKE  
TECHNOLOGY GRADEN, HANGZHOU, CHINA

Company representative

