

# TEST REPORT

Applicant Name: Grandstream Networks, Inc.  
Address: 126 Brookline Ave., 3rd Floor Boston, MA 02215, USA  
Report Number: 2501R01185E-EM-00  
FCC ID: YZZGCC6021

**Test Standard (s)**

FCC Part 15, Subpart B (Class A)

**Sample Description**


Product Type: Multi-Port UC/Network Convergence Gateway  
Model No.: GCC6021  
Multiple Model(s) No.: N/A  
Trade Mark: GRANDSTREAM  
Date Received: 2025/03/14  
Issue Date: 2025/05/12

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

**Prepared and Checked By:**

Carl Lu  
EMC Engineer

**Approved By:**

Moon Liu  
EMC Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

**Bay Area Compliance Laboratories Corp. (Shenzhen)**

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China  
Tel: +86-755-33320018    Fax: +86-755-33320008    [www.baclcorp.com.cn](http://www.baclcorp.com.cn)

## **TABLE OF CONTENTS**

<b>DOCUMENT REVISION HISTORY .....</b>	<b>3</b>
<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	6
EQUIPMENT MODIFICATIONS .....	6
SUPPORT EQUIPMENT LIST AND DETAILS .....	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>10</b>
<b>FCC §15.107 - AC LINE CONDUCTED EMISSIONS.....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
EUT SETUP .....	11
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE .....	12
LEVEL & OVER LIMIT CALCULATION .....	12
TEST DATA .....	12
<b>FCC §15.109 - RADIATED EMISSIONS .....</b>	<b>19</b>
APPLICABLE STANDARD .....	19
EUT SETUP .....	19
EMI TEST RECEIVER AND SPECTRUM ANALYZER SETUP .....	20
TEST PROCEDURE .....	20
LEVEL & OVER LIMIT CALCULATION .....	21
TEST DATA .....	21
<b>EUT PHOTOGRAPHS.....</b>	<b>34</b>
<b>TEST SETUP PHOTOGRAPHS .....</b>	<b>35</b>

## DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2501R01185E-EM-00	Original Report	2025/05/12

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Product	Multi-Port UC/Network Convergence Gateway
Tested Model	GCC6021
Multiple Model(s)	N/A
Voltage Range	AC 100-240V 50/60Hz or DC 54V from DC port
Highest operating frequency <sup>#</sup>	1800MHz (Provided by the applicant)
Equipment Class	Class A
Sample number	Sample1(G1766-0400W): 2ZS1-1 Sample2(D1602-F420S54-A): 2ZS1-2 (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A

### Objective

This test report is in accordance with Part 2-Subpart J, Part 15B Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15B.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters. Each test item follows test standards and with no deviation.

## Measurement Uncertainty

Item	Frequency Range		Expanded Measurement uncertainty
Conducted Emissions	AC Mains	150 kHz ~30MHz	3.66dB(k=2, 95% level of confidence)
Radiated Disturbance	30MHz~200MHz	Horizontal	5.32dB(k=2, 95% level of confidence)
	30MHz~200MHz	Vertical	5.43dB(k=2, 95% level of confidence)
	200MHz~1000MHz	Horizontal	5.77dB(k=2, 95% level of confidence)
	200MHz~1000MHz	Vertical	5.73dB(k=2, 95% level of confidence)
	1GHz~6GHz	/	5.34dB(k=2, 95% level of confidence)
	6GHz~18GHz	/	5.40dB(k=2, 95% level of confidence)
	18GHz~40GHz	/	5.64dB(k=2, 95% level of confidence)

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

Each test item follows test standards and with no deviation.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in worst case condition.

Test Mode 1: Data transmitting+ Full load +Sample1

Test Mode 2: Data transmitting+ Full load +Sample2

Test Mode 3: Data transmitting+ Full load +Sample1+ Adapter (PA-1301-66C3)

### EUT exercise software

No exercise software was used.

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
TP-link	POE load	PPEL-24	N/A
DELL	PC1	Latitude E6520	DL0ZCS1
DELL	PC2	Latitude E5570	GNDLKC2
LITEON	Adapter	PA-1301-66C3	N/A
TP-Link	Fiber module*4	N/A	N/A


### External I/O Cable

Cable Description	Length (m)	From/Port	To
Unshielded detachable AC cable	1.2	EUT	Mains
Unshielded detachable AC cable	1.5	Socket	LISN
Unshielded detachable AC cable	1.2	Socket	Adapter
Unshielded detachable DC cable	1.8	Adapter	EUT
Unshielded detachable RJ45 cable*12	1.0	EUT	POE load
Unshielded detachable Fiber cable*2	1.0	Fiber module	Fiber module
Unshielded detachable RJ45 cable	10.0	EUT	PC1
Unshielded detachable RJ45 cable	10.0	EUT	PC2


## Block Diagram of Test Setup

For Conducted Emission:

Test Mode 1&2




Test Mode 3




For Radiated Emission:

Test Mode 1&2



Test Mode 3



## **SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Results</b>
§15.107	AC Line Conducted Emissions	Compliant
§15.109	Radiated Emissions	Compliant

## TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>AC Line Conducted Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/12/04	2025/12/03
Rohde & Schwarz	LISN	ENV216	101613	2024/12/04	2025/12/03
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2024/05/21	2025/05/20
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2024/05/21	2025/05/20
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
<b>Radiated Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/12/04	2025/12/03
Sonoma instrument	Pre-amplifier	310 N	186238	2024/05/21	2025/05/20
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	Chamber A Cable 1	N/A	2024/06/18	2025/06/17
Unknown	Cable	XH500C	J-10M-A	2024/06/18	2025/06/17
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2025/03/26	2026/03/25
A.H.System	Preamplifier	PAM-0118P	489	2024/11/15	2025/11/14
Schwarzbeck	Horn Antenna	BBHA9120D(1 201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	735	2024/12/06	2025/12/05
Unknown	RF Cable	UFA147	219661	2024/12/06	2025/12/05
Audix	EMI Test software	E3	191218(V9)	NCR	NCR


**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## FCC §15.107 - AC LINE CONDUCTED EMISSIONS

### Applicable Standard

According to FCC§15.107

### EUT Setup



**Note:** 1. Support units were connected to second LISN.  
2. Both of LISNs (AMIN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.4-2014. The related limit was specified in FCC Part 15.107.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz – 30 MHz	9 kHz

## Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Level & Over Limit Calculation

The Level is calculated by adding the LISN Factor, Cable Loss and the Read Level. The basic equation is as follows:

$$\text{Level (dBuV)} = \text{Read Level (dBuV)} + \text{LISN Factor} + \text{Cable Loss}$$

The “Over limit” column of the following data tables indicates the degree of compliance with the applicable limit.

$$\text{Over Limit (dB)} = \text{Level (dBuV)} - \text{Limit Line (dBuV)}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

## Test Data


### Environmental Conditions

<b>Temperature:</b>	23.8~25.2 °C
<b>Relative Humidity:</b>	46~47 %
<b>ATM Pressure:</b>	100.6~101.3 kPa

*The testing was performed by Macy Shi on 2025-04-03 and 2025-04-15.*

Test Mode 1

AC 120V/60 Hz, Line




Condition: Line

Project : 2501R01185E-EM

test Mode: Mode1

tester : Macy.shi Setting:RBW:9kHz

Freq	Read	LISN	Cable	Limit	Over	Remark
	Level	Level	Factor	Loss	Line	
1	0.172	18.14	38.78	10.54	10.10	66.00 -27.22 Average
2	0.172	26.51	47.15	10.54	10.10	79.00 -31.85 QP
3	0.220	7.86	28.63	10.68	10.09	66.00 -37.37 Average
4	0.220	13.98	34.75	10.68	10.09	79.00 -44.25 QP
5	1.991	7.15	28.44	11.10	10.19	60.00 -31.56 Average
6	1.991	10.97	32.26	11.10	10.19	73.00 -40.74 QP
7	4.746	14.78	35.78	10.81	10.19	60.00 -24.22 Average
8	4.746	21.19	42.19	10.81	10.19	73.00 -30.81 QP
9	6.951	30.79	51.58	10.60	10.19	60.00 -8.42 Average
10	6.951	34.83	55.62	10.60	10.19	73.00 -17.38 QP
11	7.486	26.41	47.14	10.54	10.19	60.00 -12.86 Average
12	7.486	30.21	50.94	10.54	10.19	73.00 -22.06 QP

**AC 120V/60 Hz, Neutral**

Condition: Neutral

Project : 2501R01185E-EM


test Mode: Mode1

tester : Macy.shi Setting:RBW:9kHz

Freq	Read		LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV					
1	0.160	10.76	31.37	10.49	10.12	66.00	-34.63 Average
2	0.160	23.11	43.72	10.49	10.12	79.00	-35.28 QP
3	0.224	10.22	31.07	10.76	10.09	66.00	-34.93 Average
4	0.224	16.47	37.32	10.76	10.09	79.00	-41.68 QP
5	1.888	8.61	29.50	10.71	10.18	60.00	-30.50 Average
6	1.888	12.36	33.25	10.71	10.18	73.00	-39.75 QP
7	5.005	20.45	41.47	10.84	10.18	60.00	-18.53 Average
8	5.005	22.62	43.64	10.84	10.18	73.00	-29.36 QP
9	6.878	29.99	50.79	10.61	10.19	60.00	-9.21 Average
10	6.878	33.82	54.62	10.61	10.19	73.00	-18.38 QP
11	7.486	27.00	47.77	10.58	10.19	60.00	-12.23 Average
12	7.486	29.90	50.67	10.58	10.19	73.00	-22.33 QP

Test Mode 2

AC 120V/60 Hz, Line



Condition: Line


Project : 2501R01185E-EM

test Mode: Mode2

tester : Macy.shi Setting:RBW:9kHz

Freq	Read	LISN	Cable	Limit	Over	Remark
	Level	Level	Factor	Loss	Line	
MHz						
1	0.193	43.59	64.35	10.67	10.09	79.00 -14.65 QP
2	0.260	33.77	54.50	10.64	10.09	79.00 -24.50 QP
3	0.292	35.15	55.88	10.62	10.11	79.00 -23.12 QP
4	7.977	26.67	47.36	10.49	10.20	73.00 -25.64 QP
5	14.750	33.21	53.73	10.30	10.22	73.00 -19.27 QP
6	15.718	42.22	62.84	10.41	10.21	73.00 -10.16 QP
Read						
Freq	Level	LISN	Cable	Limit	Over	Remark
	Level	Level	Factor	Loss	Line	
MHz						
1	0.193	40.87	61.63	10.67	10.09	66.00 -4.37 Average
2	0.258	26.49	47.21	10.64	10.08	66.00 -18.79 Average
3	0.292	33.57	54.30	10.62	10.11	66.00 -11.70 Average
4	0.486	24.25	44.89	10.51	10.13	66.00 -21.11 Average
5	8.062	19.41	40.09	10.48	10.20	60.00 -19.91 Average
6	15.885	32.81	53.46	10.44	10.21	60.00 -6.54 Average

## AC 120V/60 Hz, Neutral



Trace: 1

Condition: Neutral

Project : 2501R01185E-EM


test Mode: Mode2

tester : Macy.shi Setting:RBW:9kHz

Freq	Read		LISN	Cable	Limit	Over	Remark
	MHz	dBuV					
1	0.193	43.41	64.25	10.75	10.09	79.00	-14.75 QP
2	0.258	32.70	53.50	10.72	10.08	79.00	-25.50 QP
3	0.292	35.49	56.28	10.68	10.11	79.00	-22.72 QP
4	0.486	29.50	50.14	10.51	10.13	79.00	-28.86 QP
5	7.893	26.39	47.16	10.57	10.20	73.00	-25.84 QP
6	16.055	39.60	60.30	10.49	10.21	73.00	-12.70 QP
Read		LISN	Cable	Limit	Over	Remark	
Freq	Level						
1	0.193	39.04	59.88	10.75	10.09	66.00	-6.12 Average
2	0.258	27.37	48.17	10.72	10.08	66.00	-17.83 Average
3	0.292	33.82	54.61	10.68	10.11	66.00	-11.39 Average
4	0.486	22.92	43.56	10.51	10.13	66.00	-22.44 Average
5	8.062	18.94	39.70	10.56	10.20	60.00	-20.30 Average
6	16.055	32.08	52.78	10.49	10.21	60.00	-7.22 Average


Test Mode 3

AC 120V/60 Hz, Line



Condition: Line  
Project : 2501R01185E-EM  
test Mode: Mode3  
tester : Macy.shi Setting:RBW:9kHz

Freq	Read	LISN	Cable	Limit	Over	Remark
	Level	Level	Factor	Loss	Line	
1	0.200	22.49	43.28	10.70	10.09	66.00 -22.72 Average
2	0.200	30.60	51.39	10.70	10.09	79.00 -27.61 QP
3	0.339	13.15	33.85	10.58	10.12	66.00 -32.15 Average
4	0.339	19.38	40.08	10.58	10.12	79.00 -38.92 QP
5	1.032	12.31	33.04	10.62	10.11	60.00 -26.96 Average
6	1.032	20.81	41.54	10.62	10.11	73.00 -31.46 QP
7	1.236	12.09	32.98	10.75	10.14	60.00 -27.02 Average
8	1.236	21.47	42.36	10.75	10.14	73.00 -30.64 QP
9	4.224	12.43	33.50	10.87	10.20	60.00 -26.50 Average
10	4.224	19.40	40.47	10.87	10.20	73.00 -32.53 QP
11	29.061	18.52	39.27	10.54	10.21	60.00 -20.73 Average
12	29.061	24.28	45.03	10.54	10.21	73.00 -27.97 QP

**AC 120V/60 Hz, Neutral**

Condition: Neutral

Project : 2501R01185E-EM

test Mode: Mode3

tester : Macy.shi Setting:RBW:9kHz

Freq	Read		LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV					
1	0.200	22.62	43.51	10.80	10.09	66.00	-22.49 Average
2	0.200	30.36	51.25	10.80	10.09	79.00	-27.75 QP
3	0.336	13.48	34.23	10.63	10.12	66.00	-31.77 Average
4	0.336	20.57	41.32	10.63	10.12	79.00	-37.68 QP
5	1.032	12.30	33.21	10.80	10.11	60.00	-26.79 Average
6	1.032	20.70	41.61	10.80	10.11	73.00	-31.39 QP
7	1.303	11.86	32.77	10.76	10.15	60.00	-27.23 Average
8	1.303	20.27	41.18	10.76	10.15	73.00	-31.82 QP
9	4.049	12.18	33.38	10.99	10.21	60.00	-26.62 Average
10	4.049	19.42	40.62	10.99	10.21	73.00	-32.38 QP
11	26.139	20.44	41.48	10.84	10.20	60.00	-18.52 Average
12	26.139	24.99	46.03	10.84	10.20	73.00	-26.97 QP


## FCC §15.109 - RADIATED EMISSIONS

### Applicable Standard


FCC §15.109

### EUT Setup


#### Below 1GHz for Radiated Emissions



#### Above 1GHz for Radiated Emissions



## Radiated Emissions Setup Configuration



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The related limit was specified in FCC Part 15B.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver and Spectrum analyzer Setup

During the radiated emission test, the EMI test receiver and spectrum analyzer setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	PK

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

If emission level of the EUT in Peak measurement mode is 20dB lower than peak limit line (that means the emission level in Peak measurement mode complies with both Peak and average limit lines) then only Peak measurement result is reported .Otherwise, Emission in average measurement mode shall be measured, and reported for frequency range above 1GHz.

## Level & Over Limit Calculation

The Level is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Read Level. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

$$\text{Level} = \text{Read Level} + \text{Factor}$$

The “Over limit” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -6 dB means the emission is 6dB below the limit for Class A. The equation for Over Limit calculation is as follows:


$$\text{Over limit} = \text{Level} - \text{Limit}$$

## Test Data

### Environmental Conditions

<b>Temperature:</b>	22.5~25 °C
<b>Relative Humidity:</b>	42~56%
<b>ATM Pressure:</b>	101.1~101.2 kPa


*The testing was performed by Alex Yan on 2025-04-15 for below 1GHz and Wing K Ji on 2025-04-18 for above 1GHz.*

*Test Mode 1***30 MHz~1 GHz****Horizontal**

Site : Chamber A  
Condition : 3m Horizontal  
Project Number : 2501R01185E-EM  
Test Mode : Mode1  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Alex Yan


Freq	Factor	Read	Limit	Over	Remark	
		Level	Level	Line		
1	70.86	-17.87	57.51	39.64	49.54	-9.90 Peak
2	103.85	-14.72	60.61	45.89	53.98	-8.09 QP
3	105.36	-14.32	60.39	46.07	53.98	-7.91 QP
4	107.18	-13.78	60.13	46.35	53.98	-7.63 QP
5	138.21	-11.72	58.45	46.73	53.98	-7.25 QP
6	500.08	-5.76	45.62	39.86	56.90	-17.04 Peak

## Vertical



Site : Chamber A  
Condition : 3m Vertical  
Project Number : 2501R01185E-EM  
Test Mode : Mode1  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Alex Yan


	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>	dB	
1	57.70	-18.25	61.36	43.11	49.54	-6.43	QP
2	61.83	-18.11	60.62	42.51	49.54	-7.03	QP
3	68.63	-17.88	63.70	45.82	49.54	-3.72	QP
4	69.08	-17.87	63.18	45.31	49.54	-4.23	QP
5	69.94	-17.87	63.62	45.75	49.54	-3.79	QP
6	105.36	-14.32	62.02	47.70	53.98	-6.28	QP

**1 ~ 9 GHz****Horizontal**

Site : chamber B  
Condition : Horizontal  
Project Number : 2501R01185E-EM  
Test mode : mode1  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	1748.094	-14.01	50.97	36.96	80.00	-43.04	Peak
2	2657.207	-11.03	54.75	43.72	80.00	-36.28	Peak
3	2975.247	-10.30	52.20	41.90	80.00	-38.10	Peak

## Vertical




Site : chamber B  
Condition : Vertical  
Project Number : 2501R01185E-EM  
Test mode : mode1  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Freq Factor	Read		Limit		Over	Remark
	MHz	dB/m	dBuV	dBuV/m		
1	1330.041	-14.34	60.18	45.84	80.00	-34.16 Peak
2	2656.207	-11.05	56.00	44.95	80.00	-35.05 Peak
3	3000.250	-10.12	52.69	42.57	80.00	-37.43 Peak

Test Mode 2

30 MHz~1 GHz


Horizontal



Site : Chamber A  
Condition : 3m Horizontal  
Project Number : 2501R01185E-EM  
Test Mode : Mode2  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Alex Yan


	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	51.53	-18.17	50.14	31.97	49.54	-17.57	Peak
2	108.27	-13.55	58.76	45.21	53.98	-8.77	Peak
3	111.01	-12.88	58.38	45.50	53.98	-8.48	Peak
4	145.86	-12.26	56.10	43.84	53.98	-10.14	Peak
5	250.08	-13.09	56.98	43.89	56.90	-13.01	Peak
6	600.11	-5.28	45.83	40.55	56.90	-16.35	Peak

## Vertical



Site : Chamber A  
Condition : 3m Vertical  
Project Number : 2501R01185E-EM  
Test Mode : Mode2  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Alex Yan


	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
			MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB
1	31.00	-6.47	46.08	39.61	49.54	-9.93	Peak
2	50.14	-17.94	56.60	38.66	49.54	-10.88	QP
3	51.17	-18.14	61.41	43.27	49.54	-6.27	Peak
4	147.27	-12.30	53.22	40.92	53.98	-13.06	Peak
5	231.01	-13.79	53.44	39.65	56.90	-17.25	Peak
6	500.08	-5.76	46.66	40.90	56.90	-16.00	Peak

**1 ~ 9 GHz****Horizontal**

Site : chamber B  
Condition : Horizontal  
Project Number : 2501R01185E-EM  
Test mode : mode2  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Freq	Factor	Read	Limit	Over	Remark			
		Level	Level	Line				
		MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1398.050	-14.03	55.44	41.41	80.00	-38.59	Peak	
2	1598.075	-14.33	58.50	44.17	80.00	-35.83	Peak	
3	3000.250	-10.12	54.14	44.02	80.00	-35.98	Peak	

## Vertical




Site : chamber B  
Condition : Vertical  
Project Number : 2501R01185E-EM  
Test mode : mode2  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Freq Factor	Read		Limit		Over	Remark
	MHz	dB/m	Level	dBuV/m	Line	
1	1600.075	-14.34	56.81	42.47	80.00	-37.53 Peak
2	2391.174	-10.98	54.22	43.24	80.00	-36.76 Peak
3	2999.250	-10.12	54.70	44.58	80.00	-35.42 Peak

Test Mode 3

30 MHz~1 GHz


Horizontal



Site : Chamber A  
Condition : 3m Horizontal  
Project Number : 2501R01185E-EM  
Test Mode : Mode3  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Alex Yan


Freq	Factor	Read	Limit	Over	Remark	
		Level	Level	Line		
1	61.59	-18.11	53.37	35.26	49.54	-14.28 Peak
2	106.20	-14.06	53.27	39.21	53.98	-14.77 Peak
3	138.45	-11.73	51.59	39.86	53.98	-14.12 Peak
4	275.04	-11.34	50.94	39.60	56.90	-17.30 Peak
5	375.12	-9.28	52.27	42.99	56.90	-13.91 Peak
6	500.08	-5.76	46.16	40.40	56.90	-16.50 Peak

## Vertical



Site : Chamber A  
Condition : 3m Vertical  
Project Number : 2501R01185E-EM  
Test Mode : Mode3  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Alex Yan


	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>	dB	
1	38.60	-11.40	54.45	43.05	49.54	-6.49	Peak
2	41.64	-13.58	56.15	42.57	49.54	-6.97	QP
3	45.96	-16.43	58.02	41.59	49.54	-7.95	QP
4	141.83	-11.96	47.40	35.44	53.98	-18.54	Peak
5	500.08	-5.76	45.97	40.21	56.90	-16.69	Peak
6	875.25	-1.52	34.00	32.48	56.90	-24.42	Peak

**1 ~ 9 GHz****Horizontal**

Site : chamber B  
Condition : Horizontal  
Project Number : 2501R01185E-EM  
Test mode : mode3  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	1403.050	-14.03	55.42	41.39	80.00	-38.61	Peak
2	1699.087	-13.90	56.55	42.65	80.00	-37.35	Peak
3	2976.247	-10.29	51.78	41.49	80.00	-38.51	Peak

## Vertical



Site : chamber B  
Condition : Vertical  
Project Number : 2501R01185E-EM  
Test mode : mode3  
Tester : Wing K Ji  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Freq Factor	Read		Limit		Over	Remark
	MHz	dB/m	dBuV	dBuV/m		
1	1598.075	-14.33	61.68	47.35	80.00	-32.65 Peak
2	2393.174	-10.99	56.13	45.14	80.00	-34.86 Peak
3	2999.250	-10.12	55.50	45.38	80.00	-34.62 Peak

## **EUT PHOTOGRAPHS**

Please refer to the attachment 2501R01185E-EM External photo and 2501R01185E-EM Internal photo.

## **TEST SETUP PHOTOGRAPHS**

Please refer to the attachment 2501R01185E-EM Test Setup photo.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***