



FCC TEST REPORT

Product Name: Ultra HD Multimedia Conferencing System
Trade Mark: GRANDSTREAM
Model No.: GVC3220
Report Number: 200512001RFC-4
Test Standards: FCC 47 CFR Part 15 Subpart E
FCC ID: YZZGVC3220
Test Result: PASS
Date of Issue: September 27, 2020

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor Boston, MA 02215, USA


Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park,
Qingxiang Road No.1, Longhua New District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:


Henry Lu
Team Leader

Reviewed by:


Kevin Liang
Assistant Manager

Approved by:


Billy Li
Technical Director

Date:

September 27, 2020

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

Version

Version No.	Date	Description
V1.0	September 27, 2020	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES.....	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	6
1.4 OTHER INFORMATION.....	8
1.5 DESCRIPTION OF SUPPORT UNITS	8
1.6 TEST LOCATION.....	8
1.7 TEST FACILITY.....	8
1.8 DEVIATION FROM STANDARDS.....	9
1.9 ABNORMALITIES FROM STANDARD CONDITIONS.....	9
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	9
1.11 MEASUREMENT UNCERTAINTY	9
2. TEST SUMMARY	10
3. EQUIPMENT LIST	11
4. TEST CONFIGURATION	12
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING.....	12
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	12
4.1.2 RECORD OF NORMAL ENVIRONMENT.....	12
4.2 TEST CHANNELS	13
4.3 EUT TEST STATUS	13
4.4 PRE-SCAN.....	14
4.5 TEST SETUP	15
4.5.1 FOR RADIATED EMISSIONS TEST SETUP	15
4.5.2 FOR CONDUCTED EMISSIONS TEST SETUP	16
4.5.3 FOR CONDUCTED RF TEST SETUP	17
4.6 SYSTEM TEST CONFIGURATION.....	18
4.7 DUTY CYCLE	19
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION	23
5.1 REFERENCE DOCUMENTS FOR TESTING	23
5.2 ANTENNA REQUIREMENT	23
5.3 26 DB BANDWIDTH	24
5.4 6 DB BANDWIDTH	43
5.5 MAXIMUM CONDUCTED OUTPUT POWER	49
5.6 PEAK POWER SPECTRAL DENSITY	53
5.7 RADIATED EMISSIONS AND BAND EDGE MEASUREMENT.....	78
5.8 DYNAMIC FREQUENCY SELECTION	119
5.9 AC POWER LINE CONDUCTED EMISSION	129
APPENDIX 1 PHOTOS OF TEST SETUP.....	132
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS.....	132

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	Ultra HD Multimedia Conferencing System		
Model No.:	GVC3220		
Trade Mark:	GRANDSTREAM		
DUT Stage:	Production Unit		
EUT Supports Function:	2.4 GHz ISM Band:	IEEE 802.11b/g/n	
		Bluetooth 5.0	
		2.4G Radio	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac
		5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac
Sample Received Date:	May 12, 2020		
Sample Tested Date:	May 12, 2020 to September 23, 2020		

1.2.2 Description of Accessories

Adapter 1	
Model No.:	EA10683ER-480
Input:	100-240 V~50/60 Hz 2.0 A
Output:	48 V = 1.25 A 60W
AC Cable:	1.2 Meter, Unshielded without ferrite
DC Cable:	2.0 Meter, Unshielded with one ferrite
Manufacturer:	EDACPOWER ELECTRONICS CO., LTD.

Adapter 2	
Model No.:	KPL-065S-VI
Input:	100-240 V~50/60 Hz 1.7 A
Output:	48 V = 1.35 A 65W
AC Cable:	1.2 Meter, Unshielded without ferrite
DC Cable:	2.0 Meter, Unshielded with one ferrite
Manufacturer:	Channel Well Technology Co., Ltd

Cable 1	
Connector:	HDMI
Cable Type:	Shielded with two ferrite
Length:	1.5 Meter, Shielded with two ferrite

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

Cable 2	
Connector:	HDMI
Cable Type:	Shielded with two ferrite
Length:	1.5 Meter, Shielded with two ferrite

Cable 3	
Connector:	HDMI
Cable Type:	Shielded with two ferrite
Length:	5.0 Meter, Shielded with two ferrite

Cable 4	
Connector:	Ethernet Cable
Cable Type:	Unshielded without ferrite
Length:	2.0 Meter, Unshielded without ferrite

Remote control	
Model No.:	GVC3210RMT

Microphone	
Model No.:	GMD1208

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Bands:	5150 MHz to 5250 MHz (U-NII-1)	
	5250 MHz to 5350 MHz (U-NII-2A)	
	5470 MHz to 5725 MHz (U-NII-2C)	
	5 725 MHz to 5 850 MHz (U-NII-3)	
Frequency Ranges:	5180 MHz to 5240 MHz	
	5260 MHz to 5320 MHz	
	5500 MHz to 5700 MHz	
	5 745 MHz to 5 825 MHz	
Support Standards:	IEEE 802.11a/n/ac	
TPC Function:	Not Support	
DFS Operational mode:	Slave without radar Interference detection function	
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)	
	IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)	
	IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)	
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20: 20 MHz	
	IEEE 802.11n-HT40/ac-VHT40: 40 MHz	
	IEEE 802.11ac-VHT80: 80 MHz	
Data Rate:	IEEE 802.11a: Up to 54 Mbps	
	IEEE 802.11n-HT20: Up to MCS15	
	IEEE 802.11n-HT40: Up to MCS15	
	IEEE 802.11ac-VHT20: Up to MCS8	
	IEEE 802.11ac-VHT40: Up to MCS9	
	IEEE 802.11ac-VHT80: Up to MCS9	
Number of Channels:	5150 MHz to 5250 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11acVHT80	
	5250 MHz to 5350 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11acVHT80	
	5470 MHz to 5725 MHz: 11 for IEEE 802.11a/n-HT20/ac-VHT20 5 for IEEE 802.11n-HT40/ac-VHT40 2 for IEEE 802.11ac-VHT80	
	5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11ac-VHT80	
Antenna Type:	Chain 0	Dipole Antenna
	Chain 1	Dipole Antenna
Antenna Gain:	Chain 0	5150 MHz to 5250 MHz: 5.0 dBi
		5250 MHz to 5350 MHz: 5.0 dBi
		5470 MHz to 5725 MHz: 5.0 dBi
		5725 MHz to 5850 MHz: 5.0 dBi
	Chain 1	5150 MHz to 5250 MHz: 5.0 dBi
		5250 MHz to 5350 MHz: 5.0 dBi

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

		5470 MHz to 5725 MHz: 5.0 dBi			
		5725 MHz to 5850 MHz: 5.0 dBi			
Maximum Power (dBm):	MIMO_Chain 0+1	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	19.23	19.36	13.18	18.17
	IEEE 802.11n-HT20:	13.29	14.79	10.95	16.76
	IEEE 802.11n-HT40:	9.80	10.34	7.42	17.30
	IEEE 802.11ac-VHT20:	14.96	16.88	13.13	18.05
	IEEE 802.11ac-VHT40:	9.87	10.42	7.54	17.34
	IEEE 802.11ac-VHT80:	9.28	9.50	14.73	17.52
Normal Test Voltage:	120 Vac				

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

1.4 OTHER INFORMATION

Operation Frequency Each of Channel				
	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
IEEE 802.11a, IEEE 802.11n-HT20, IEEE 802.11ac-VHT20	f = 5000 + 5k, k = 32 + 4n			f = 5000 + 5k, k = 145 + 4n
	n = 1,..., 4	n = 5,..., 8	n = 17,..., 27	n = 1,..., 5
IEEE 802.11n-HT40, IEEE 802.11ac-VHT40	f = 5000 + 5k, k = 30 + 8n			f = 5000 + 5k, k = 143 + 8n
	n = 1, 2	n = 1,..., 5	n = 9,..., 13	n = 1, 2
IEEE 802.11ac-VHT80	f = 5000 + 5k, k = 26 + 16n			f = 5000 + 5k, k = 155
	n = 1	n = 1, 2	n = 5, 6	
Note: f is the operating frequency (MHz); k is the operating channel.				

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	Lenovo	E450	SL10G10780	UnionTrust
Mouse	DELL	MS111	CN-011D3V-738	UnionTrust
USB flash disk	Kingston	DTSE9	N/A	UnionTrust
USB flash disk	Kingston	DTSE9G2	N/A	UnionTrust
SD card	Transcend	microSD	N/A	UnionTrust
Earphone	N/A	QTER01JY	N/A	UnionTrust
Monitor	DELL	P2416Db	N/A	UnionTrust
Monitor	HKC	M216AF	BOG20180003	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.30 Meter	UnionTrust
2	LAN Cable	Unshielded without ferrite	1.5 Meter	UnionTrust

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	± 3.2 dB
2	Conducted emission 150KHz-30MHz	± 2.7 dB
3	Radiated emission 9KHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.9 dB
5	Radiated emission 1GHz-18GHz	± 4.8 dB
6	Radiated emission 18GHz-26GHz	± 5.1 dB
7	Radiated emission 26GHz-40GHz	± 5.1 dB
8	Conducted spurious emissions	± 2.7 dB
9	RF Power, Conducted	± 0.9 dB
10	Occupied Bandwidth	± 1.86 %
11	Radio Frequency	2.4 GHz: $\pm 6.5 \times 10^{-8}$
12	Transmission Time	± 0.19 %

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart E Test Cases			
Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203 FCC 47 CFR Part 15 Subpart C Section 15.407(a)(1) (2)	N/A	PASS
26 dB emission bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(2)(5)	KDB 789033 D02 v02r01 Section C.1	PASS
6 dB bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (e)	KDB 789033 D02 v02r01 Section C.2	PASS
Maximum conducted output power	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3)	KDB 789033 D02 v02r01 Section E.3.a (Method PM)	PASS
Peak Power Spectral Density	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3)	KDB 789033 D02 v02r01 Section F	PASS
Radiated Emissions and Band Edge Measurement	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(1)(2)(3)(4)(6) FCC 47 CFR Part 15 Subpart C Section 15.209/205	KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6	PASS
Dynamic Frequency Selection	FCC 47 CFR Part 15 Subpart E Section 15.407 (h)	KDB 905462 D03 Client Without DFS New Rules v01r02	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(6) FCC 47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013, Section 6.2.	PASS
Note: 1) N/A: In this whole report not applicable.			

For Dynamic Frequency Selection

Test Case	Result
Channel Availability Check Time	N/A ¹
U-NII Detection Bandwidth	N/A ¹
Channel Closing Transmission Time	PASS
Channel Move Time	PASS
DFS Detection Threshold	N/A ¹
Non- Occupancy Period	N/A ¹
Note: 1) The EUT is slave, NA In this whole report not applicable.	

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	3M Chamber & Accessory Equipment	ETS-LINDGREN	3M	N/A	Dec. 03, 2018	Dec. 03, 2021
☒	Receiver	R&S	ESIB26	100114	Nov. 24, 2019	Nov. 23, 2020
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Nov. 24, 2019	Nov. 23, 2020
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	Nov. 16, 2019	Nov. 15, 2020
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Nov. 16, 2019	Nov. 15, 2020
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	Nov. 16, 2019	Nov. 15, 2020
☒	Preamplifier	HP	8447F	2805A02960	Nov. 24, 2019	Nov. 23, 2020
☐	Broadband Antenna (Pre-amplifier)	ETS-LINDGREN	3142E-PA	00201891	May. 30, 2020	May. 29, 2021
☐	6dB Attenuator	Talent	RA6A5-N-18	18103002	Nov. 24, 2019	Nov. 23, 2020
☐	Horn Antenna	ETS-LINDGREN	3117	00164202	Nov. 16, 2019	Nov. 15, 2020
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201874	May. 30, 2020	May. 29, 2021
☐	Horn Antenna	ETS-LINDGREN	3116C	00200180	Jun. 19, 2020	Jun. 18, 2021
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Nov. 16, 2019	Nov. 15, 2020
☒	Band Rejection Filter (5150MHz~5880MHz)	Micro-Tronics	BRM50716	G1868	Nov. 24, 2019	Nov. 23, 2020
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	Receiver	R&S	ESR7	1316.3003K07-101181-K3	Nov. 24, 2019	Nov. 23, 2020
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	Nov. 24, 2019	Nov. 23, 2020
☒	LISN	R&S	ESH2-Z5	860014/024	Nov. 24, 2019	Nov. 23, 2020
☐	LISN	ETS-Lindgren	3816/2SH	00201088	Nov. 24, 2019	Nov. 23, 2020
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted RF test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Nov. 24, 2019	Nov. 23, 2020
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	Nov. 24, 2019	Nov. 23, 2020
☐	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430023	Nov. 24, 2019	Nov. 23, 2020
☒	MXG X-Series RF Vector Signal Generator	KEYSIGHT	N5182B	MY51350267	Nov. 24, 2019	Nov. 23, 2020

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage	Relative Humidity (%)
NT/NV	+15 to +35	120	20 to 75
Remark:			
1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Tested by
AC Power Line Conducted Emission	23.9	39	99.17	Tripp Jiang
26 dB emission bandwidth	23.6	51	99.80	Swift Liu
Maximum conducted output power	23.6	51	99.80	Swift Liu
Peak Power Spectral Density	23.6	51	99.80	Swift Liu
6 dB bandwidth	23.6	51	99.80	Swift Liu
Dynamic Frequency Selection	23.6	51	99.80	Swift Liu
Radiated Emissions and Band Edge Measurement	25.5	57	100.62	Asia Yan

4.2 TEST CHANNELS

Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11a IEEE 802.11n-HT20 IEEE 802.11ac-VHT20	5150 MHz to 5250 MHz	Channel 36	Channel 44	Channel 48
		5180 MHz	5220 MHz	5240 MHz
	5250 MHz to 5350 MHz	Channel 52	Channel 60	Channel 64
		5260 MHz	5300 MHz	5320 MHz
	5470 MHz to 5725 MHz	Channel 100	Channel 116	Channel 140
		5500 MHz	5580 MHz	5700 MHz
	5725 MHz to 5850 MHz	Channel 149	Channel 157	Channel 165
		5745 MHz	5785 MHz	5825 MHz
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40	5150 MHz to 5250 MHz	Channel 38	--	Channel 46
		5190 MHz	--	5230 MHz
	5250 MHz to 5350 MHz	Channel 54	--	Channel 62
		5270 MHz	--	5310 MHz
	5470 MHz to 5725 MHz	Channel 102	Channel 110	Channel 134
		5510 MHz	5550 MHz	5670 MHz
	5725 MHz to 5850 MHz	Channel 151	--	Channel 159
		5755 MHz	--	5795 MHz
IEEE 802.11ac-VHT80	5150 MHz to 5250 MHz	--	Channel 42	--
		--	5210 MHz	--
	5250 MHz to 5350 MHz	--	Channel 58	--
		--	5290 MHz	--
	5470 MHz to 5725 MHz	Channel 106	--	Channel 122
		5530 MHz	--	5610 MHz
	5725 MHz to 5850 MHz	--	Channel 155	--
		--	5775 MHz	--

4.3 EUT TEST STATUS

Mode	Tx/Rx Function	Description
IEEE 802.11a/n/ac	2Tx/2Rx	1. Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

Power Setting								
Mode	U-NII-1		U-NII-2A		U-NII-2C		U-NII-3	
	Chain 0	Chain 1	Chain 0	Chain 1	Chain 0	Chain 1	Chain 0	Chain 1
IEEE 802.11a	16	16	16	16	10	10	16	16
IEEE 802.11n-HT20	12	12	13	13	10	10	16	16
IEEE 802.11n-HT40	8	8	8	8	6	6	15	15
IEEE 802.11ac-VHT20	12	12	13	13	10	10	16	16
IEEE 802.11ac-VHT40	8	8	8	8	6	6	15	15
IEEE 802.11ac-VHT80	7	7	7	7	6	6	15	15

Test Software
Test software name: Telnet device command;

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

4.4PRE-SCAN

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate. Following data rate was (were) selected for the final test as listed below

Mode	Worst-case data rates
IEEE 802.11a	6 Mbps
IEEE 802.11n-HT20	MCS8
IEEE 802.11n-HT40	MCS8
IEEE 802.11ac-VHT20	MCS0
IEEE 802.11ac-VHT40	MCS0
IEEE 802.11ac-VHT80	MCS0

4.5 TEST SETUP

4.5.1 For Radiated Emissions test setup




Figure 1. Below 30MHz







Figure 2. 30MHz to 1GHz



4.5.2 For Conducted Emissions test setup



4.5.3 For Conducted RF test setup



4.6 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by adapter. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in (see table below) orientation.

Frequency	Mode	Antenna Port	Worst-case axis positioning
Above 1GHz	2TX	Chain 0+1	Z axis

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.7 DUTY CYCLE

Test Procedure: ANSI C63.10-2013 Clause 12.2.


Test Results



Mode	Data rates (Mbps)	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)	Average Factor (dB)
IEEE 802.11a	6	0.1700	0.2200	0.77	77.27	1.12	5.88	-2.24
IEEE 802.11n-HT20	MCS8	0.1620	0.2060	0.79	78.64	1.04	6.17	-2.09
IEEE 802.11n-HT40	MCS8	0.0990	0.1410	0.70	70.21	1.54	10.10	-3.07
IEEE 802.11ac-VHT20	MCS0	0.1460	0.1920	0.76	76.04	1.19	6.85	-2.38
IEEE 802.11ac-VHT40	MCS0	0.0860	0.1290	0.67	66.67	1.76	11.63	-3.52
IEEE 802.11ac-VHT80	MCS0	0.0630	0.1060	0.59	59.43	2.26	15.87	-4.52



Remark:


- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor = $10 * \log(1/ \text{Duty cycle})$;
- 3) Average factor = $20 \log_{10} \text{Duty Cycle}$.

The test plots as follows









Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 789033 D02 General UNII Test Procedures New Rules v02r01	Guidelines for compliance testing of unlicensed national information infrastructure (U-NII) device part 15, subpart E
5	KDB 905462 D06 802.11 Channel Plans New Rules v02	Operation in U-NII bands -802.11 channel PLAN(\$15.407)
6	KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02	Compliance measurement procedures for Unlicensed –National Information Infrastructure devices operates in the frequency bands 5250 MHz to 5350 MHz and 5470 MHz to 5725 MHz bands incorporating dynamic frequency selection
7	KDB 905462 D03 Client Without DFS New Rules v01r02	U-NII client devices without radar detection capability
8	KDB 662911 D01 Multiple Transmitter Output v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.407(a)(1) (2) requirement: The conducted output power limit specified in paragraph (a) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (a) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power and the peak power spectral density shall be reduced by the by the amount in dB that the directional gain of the antenna exceeds 6 dBi. EUT Antenna: Both antenna in the interior of the equipment and no consideration of replacement. The transmit signals are correlated with each other and the antenna gain of both chains is completely no consistent, the best case directional gain of the antenna is 8.01 dBi (See section 5.5).

5.326 DB BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a) (2)(5)

Test Method: KDB 789033 D02 v02r01 Section C.1

Limit: None; for reporting purposes only.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum analyzer.

Spectrum analyzer according to the following Settings:

a) Set RBW = approximately 1 % of the emission bandwidth.

b) Set the VBW > RBW.

c) Detector = Peak.

d) Trace mode = max hold.

e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Mode	Channel	26 dB Bandwidth (MHz)		99% Bandwidth (MHz)	
		Chain 0	Chain 1	Chain 0	Chain 1
IEEE 802.11a	36 (5180)	21.12	21.50	16.686	16.987
	44 (5220)	21.23	21.39	16.643	16.967
	48 (5240)	21.24	21.88	16.701	17.083
	52 (5260)	21.13	21.78	16.682	17.064
	60 (5300)	21.05	21.98	16.619	17.103
	64 (5320)	21.28	21.74	16.692	17.075
	100 (5500)	21.08	21.55	16.660	16.857
	116 (5580)	21.16	21.35	16.613	16.815
	140 (5700)	20.95	21.32	16.678	16.901
IEEE 802.11n-HT20	36 (5180)	21.86	21.51	18.016	17.866
	44 (5220)	21.58	21.29	17.957	17.856
	48 (5240)	21.92	21.74	17.937	17.850
	52 (5260)	21.28	21.80	17.909	17.894
	60 (5300)	21.74	21.74	18.028	17.897
	64 (5320)	21.60	21.67	17.901	17.808
	100 (5500)	21.72	21.62	17.975	17.807
	116 (5580)	21.28	21.50	17.895	17.889
	140 (5700)	21.54	21.43	17.839	17.872
IEEE 802.11n-HT40	38 (5190)	40.63	39.55	36.454	36.466
	46 (5230)	39.94	39.49	36.447	36.264
	54 (5270)	39.99	40.47	36.266	36.382
	62 (5310)	40.20	41.21	36.312	36.478
	102 (5510)	40.61	42.97	36.352	36.471
	110 (5590)	40.05	39.58	36.441	36.390
	134 (5670)	40.09	39.72	36.282	36.392

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

IEEE 802.11ac-VHT20	36 (5180)	21.51	21.34	17.856	17.890
	44 (5220)	21.33	21.23	17.968	17.878
	48 (5240)	21.09	21.24	17.977	17.848
	52 (5260)	21.32	21.42	17.885	17.833
	60 (5300)	21.28	21.23	17.942	17.942
	64 (5320)	21.31	21.08	17.851	17.822
	100 (5500)	21.42	21.24	17.917	17.898
	116 (5580)	21.41	21.26	17.873	17.845
	140 (5700)	21.30	21.23	17.978	17.857
IEEE 802.11ac-VHT40	38 (5190)	40.38	39.63	36.449	36.379
	46 (5230)	40.47	39.92	36.546	36.365
	54 (5270)	40.52	40.11	36.484	36.357
	62 (5310)	40.48	39.85	36.497	36.364
	102 (5510)	40.08	40.87	36.542	36.307
	110 (5590)	40.85	41.51	36.458	36.430
	134 (5670)	40.13	39.36	36.509	36.282
IEEE 802.11ac-VHT80	42 (5210)	83.54	81.83	76.046	75.876
	58 (5290)	83.25	83.03	75.927	75.943
	106 (5530)	86.11	83.44	76.006	75.968
	122 (5610)	85.65	82.36	75.985	75.991


The test plots as follows:






















Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886


E-mail: info@uttlab.com


<http://www.uttlab.com>


UTTR-RF-FCCPART15.407-V1.0














Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0





Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

5.46 DB BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.407 (e)

Test Method: KDB 789033 D02 v02r01Section C.2

Limit: Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum Analyzer.

Spectrum analyzer according to the following Settings:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 * \text{RBW}$.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Mode	Channel/ Frequency (MHz)	6 dB Bandwidth (MHz)		99% Bandwidth (MHz)		6 dB Bandwidth Limit	Pass / Fail
		Chain 0	Chain 1	Chain 0	Chain 1		
IEEE 802.11a	149 (5745)	16.37	16.44	16.483	16.558	> 500 kHz	Pass
	157 (5785)	16.33	16.49	16.500	16.583	> 500 kHz	Pass
	165 (5825)	16.37	16.36	16.479	16.590	> 500 kHz	Pass
IEEE 802.11n-HT20	149 (5745)	17.58	17.52	17.842	17.893	> 500 kHz	Pass
	157 (5785)	17.52	17.69	17.842	17.875	> 500 kHz	Pass
	165 (5825)	17.00	17.65	17.864	17.861	> 500 kHz	Pass
IEEE 802.11n-HT40	151 (5755)	36.49	36.41	36.289	36.294	> 500 kHz	Pass
	159 (5795)	36.39	36.07	36.273	36.275	> 500 kHz	Pass
IEEE 802.11ac-VHT20	149 (5745)	17.65	17.65	17.698	17.705	> 500 kHz	Pass
	157 (5785)	17.64	17.68	17.688	17.703	> 500 kHz	Pass
	165 (5825)	17.58	17.68	17.722	17.737	> 500 kHz	Pass
IEEE 802.11ac-VHT40	151 (5755)	36.25	36.35	36.200	36.263	> 500 kHz	Pass
	159 (5795)	36.25	36.40	36.248	36.291	> 500 kHz	Pass
IEEE 802.11ac-VHT80	155 (5775)	75.71	76.05	75.748	75.636	> 500 kHz	Pass

The test plots as follows:



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886


E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0









5.5 MAXIMUM CONDUCTED OUTPUT POWER

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3)

Test Method: KDB 789033 D02 v02r01 Section E.3.a (Method PM)

Limits:

1. For the band 5.15-5.25 GHz.
 - (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
 - (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
 - (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
 - (iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure:

1. Connected the EUT's antenna port to measure device by 10dB attenuator.
2. Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of Tx on burst.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

For U-NII-2A, U-NII-2C Band:

For IEEE 802.11 a/n/ac, the minimum 26 dB emission bandwidth is 20.95MHz

$11 \text{ dBm} + 10\log_{10}(20.95) = 24.21 \text{ dBm} > 21.99 \text{ dBm} (200\text{mW})$

So the 21.99 dB limit applicable

Directional gain and the maximum output power limit.

Frequency Band	Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Correlated chains directional gain (dBi)	Peak Power Limits (dBm)
U-NII-1	5.00	5.00	8.01	21.99
U-NII-2A	5.00	5.00	8.01	21.99
U-NII-2C	5.00	5.00	8.01	21.99
U-NII-3	5.00	5.00	8.01	27.99

Basic methodology with N_{ANT} transmit antennas, each with the same directional gain G_{ANT} dBi, being driven by N_{ANT} transmitter outputs of equal power. Directional gain is to be computed as follows:

If any transmit signals are *correlated* with each other,

$$\text{Directional gain} = G_{ANT} + 10 \log(N_{ANT}) \text{ dBi}$$

Mode	Channel/ Frequency (MHz)	Maximum Conducted Output Power (dBm)						
		SISO				Total Power MIMO_ Chain 0+1	Limits (dBm)	Pass / Fail
		Chain 0		Chain 1				
		Meas Power	Corr'd Power	Meas Power	Corr'd Power			
IEEE 802.11a	36 (5180)	14.98	16.10	15.12	16.24	19.18	21.99	Pass
	44 (5220)	15.19	16.31	14.94	16.06	19.20	21.99	Pass
	48 (5240)	15.17	16.29	15.02	16.14	19.23	21.99	Pass
	52 (5260)	14.96	16.08	15.49	16.61	19.36	21.99	Pass
	60 (5300)	15.07	16.19	15.30	16.42	19.32	21.99	Pass
	64 (5320)	14.97	16.09	15.46	16.58	19.35	21.99	Pass
	100 (5500)	9.12	10.24	8.97	10.09	13.18	21.99	Pass
	116 (5580)	8.90	10.02	8.64	9.76	12.90	21.99	Pass
	140 (5700)	8.36	9.48	8.02	9.14	12.32	21.99	Pass
	149 (5745)	13.98	15.10	14.10	15.22	18.17	27.99	Pass
	157 (5785)	13.86	14.98	13.69	14.81	17.91	27.99	Pass
	165 (5825)	13.75	14.87	13.53	14.65	17.77	27.99	Pass

Mode	Channel/ Frequency (MHz)	Maximum Conducted Output Power (dBm)						
		MIMO				Total Power MIMO_ Chain 0+1	Limits (dBm)	Pass / Fail
		Chain 0		Chain 1				
		Meas Power	Corr'd Power	Meas Power	Corr'd Power			
IEEE 802.11n-HT20	36 (5180)	9.32	10.36	9.06	10.10	13.24	21.99	Pass
	44 (5220)	9.33	10.37	9.14	10.18	13.29	21.99	Pass
	48 (5240)	9.29	10.33	9.08	10.12	13.24	21.99	Pass
	52 (5260)	10.58	11.62	10.70	11.74	14.69	21.99	Pass
	60 (5300)	10.65	11.69	10.83	11.87	14.79	21.99	Pass
	64 (5320)	10.63	11.67	10.73	11.77	14.73	21.99	Pass
	100 (5500)	7.09	8.13	6.71	7.75	10.95	21.99	Pass
	116 (5580)	6.87	7.91	6.38	7.42	10.68	21.99	Pass
	140 (5700)	6.30	7.34	5.70	6.74	10.06	21.99	Pass
	149 (5745)	12.80	13.84	12.62	13.66	16.76	27.99	Pass
	157 (5785)	12.56	13.60	12.44	13.48	16.55	27.99	Pass
	165 (5825)	12.21	13.25	12.13	13.17	16.22	27.99	Pass

Mode	Channel/ Frequency (MHz)	Maximum Conducted Output Power (dBm)						
		MIMO				Total Power MIMO_ Chain 0+1	Limits (dBm)	Pass / Fail
		Chain 0		Chain 1				
		Meas Power	Corr'd Power	Meas Power	Corr'd Power			
IEEE 802.11n-HT40	38 (5190)	5.26	6.80	4.92	6.46	9.64	21.99	Pass
	46 (5230)	5.52	7.06	4.97	6.51	9.80	21.99	Pass
	54 (5270)	5.77	7.31	5.80	7.34	10.34	21.99	Pass
	62 (5310)	5.80	7.34	5.67	7.21	10.29	21.99	Pass
	102 (5510)	3.83	5.37	1.64	3.18	7.42	21.99	Pass
	118 (5590)	3.57	5.11	0.99	2.53	7.02	21.99	Pass
	134 (5670)	3.13	4.67	0.64	2.18	6.61	21.99	Pass
	151 (5755)	12.58	14.12	12.92	14.46	17.30	27.99	Pass
	159 (5795)	12.62	14.16	12.60	14.14	17.16	27.99	Pass

Mode	Channel/ Frequency (MHz)	Maximum Conducted Output Power (dBm)						
		MIMO				Total Power MIMO_ Chain 0+1	Limits (dBm)	Pass / Fail
		Chain 0		Chain 1				
		Meas Power	Corr'd Power	Meas Power	Corr'd Power			
IEEE 802.11ac- VHT20	36 (5180)	10.65	11.84	10.87	12.06	14.96	21.99	Pass
	44 (5220)	10.71	11.90	10.80	11.99	14.96	21.99	Pass
	48 (5240)	10.79	11.98	10.78	11.97	14.99	21.99	Pass
	52 (5260)	12.01	13.20	12.14	13.33	16.28	21.99	Pass
	60 (5300)	12.94	14.13	12.09	13.28	16.74	21.99	Pass
	64 (5320)	12.98	14.17	12.35	13.54	16.88	21.99	Pass
	100 (5500)	9.05	10.24	8.81	10.00	13.13	21.99	Pass
	116 (5580)	8.69	9.88	8.68	9.87	12.89	21.99	Pass
	140 (5700)	8.22	9.41	7.78	8.97	12.21	21.99	Pass
	149 (5745)	13.80	14.99	13.89	15.08	18.05	27.99	Pass
	157 (5785)	13.73	14.92	13.63	14.82	17.88	27.99	Pass
	165 (5825)	13.47	14.66	13.39	14.58	17.63	27.99	Pass

Mode	Channel/ Frequency (MHz)	Maximum Conducted Output Power (dBm)						
		MIMO				Total Power MIMO_ Chain 0+1	Limits (dBm)	Pass / Fail
		Chain 0		Chain 1				
		Meas Power	Corr'd Power	Meas Power	Corr'd Power			
IEEE 802.11ac- VHT40	38 (5190)	5.41	7.17	4.77	6.53	9.87	21.99	Pass
	46 (5230)	5.28	7.04	4.70	6.46	9.77	21.99	Pass
	54 (5270)	5.79	7.55	5.44	7.20	10.39	21.99	Pass
	62 (5310)	5.75	7.51	5.55	7.31	10.42	21.99	Pass
	102 (5510)	3.74	5.50	1.52	3.28	7.54	21.99	Pass
	118 (5590)	3.45	5.21	0.87	2.63	7.12	21.99	Pass
	134 (5670)	3.03	4.79	0.69	2.45	6.79	21.99	Pass
	151 (5755)	12.58	14.34	12.56	14.32	17.34	27.99	Pass
	159 (5795)	12.38	14.14	12.44	14.20	17.18	27.99	Pass

Mode	Channel/ Frequency (MHz)	Maximum Conducted Output Power (dBm)						
		MIMO				Total Power MIMO_ Chain 0+1	Limits (dBm)	Pass / Fail
		Chain 0		Chain 1				
		Meas Power	Corr'd Power	Meas Power	Corr'd Power			
IEEE 802.11ac- VHT80	42 (5210)	4.21	6.47	3.81	6.07	9.28	21.99	Pass
	58 (5290)	4.33	6.59	4.13	6.39	9.50	21.99	Pass
	106 (5530)	4.66	6.92	3.99	6.25	9.61	21.99	Pass
	122 (5610)	9.65	11.91	9.26	11.52	14.73	21.99	Pass
	155 (5775)	12.34	14.60	12.15	14.41	17.52	27.99	Pass

Remark:

1. Corr'd Power = Meas Power + Duty Cycle Factor
2. Total (Chain 0+1) = $10 \cdot \log[(10^{\text{Chain 0}/10}) + (10^{\text{Chain 1}/10})]$

5.6 PEAK POWER SPECTRAL DENSITY

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3)

Test Method: KDB 789033 D02 v02r01 Section F

Limits:

1. For the band 5.15-5.25 GHz.
 - (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
 - (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
 - (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
 - (iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum Analyzer.

Spectrum analyzer according to the following Settings:

1. For U-NII-1, U-NII-2A, U-NII-2C band:

Using method SA-2

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz, Set VBW $\geq$ 3 RBW, Detector = RMS
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value and add 10 log (1/duty cycle)

2. For U-NII-3 band:

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 500 kHz, Set VBW $\geq$ 3 RBW, Detector = RMS
- Use the peak marker function to determine the maximum power level in any 500 kHz band segment within the fundamental EBW.
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value and add 10 log (1/duty cycle)

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Directional gain and the maximum output power limit.

Frequency Band	Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Correlated chains directional gain (dBi)	PSD Limits (dBm/MHz or dBm/500kHz)
U-NII-1	5.00	5.00	8.01	8.99
U-NII-2A	5.00	5.00	8.01	8.99
U-NII-2C	5.00	5.00	8.01	8.99
U-NII-3	5.00	5.00	8.01	27.99

Basic methodology with N_{ANT} transmit antennas, each with the same directional gain G_{ANT} dBi, being driven by N_{ANT} transmitter outputs of equal power. Directional gain is to be computed as follows:

If any transmit signals are *correlated* with each other,

$$\text{Directional gain} = G_{ANT} + 10 \log(N_{ANT}) \text{ dBi}$$

For U-NII-1, U-NII-2A, U-NII-2C band

Mode	Channel/ Frequency (MHz)	Maximum Power Spectral Density (dBm/MHz)						
		SISO				Total PSD MIMO_ Chain 0+1	Limits	Pass / Fail
		Chain 0		Chain 1				
		Meas PSD	Corr'd PSD	Meas PSD	Corr'd PSD			
IEEE 802.11a	36 (5180)	5.01	6.13	4.67	5.78	8.97	8.99	Pass
	44 (5220)	5.12	6.24	4.52	5.64	8.96	8.99	Pass
	48 (5240)	4.72	5.84	4.89	6.01	8.94	8.99	Pass
	52 (5260)	4.52	5.63	5.11	6.23	8.95	8.99	Pass
	60 (5300)	4.08	5.20	4.42	5.53	8.38	8.99	Pass
	64 (5320)	4.03	5.15	4.57	5.69	8.44	8.99	Pass
	100 (5500)	-2.99	-1.87	-2.89	-1.77	1.19	8.99	Pass
	116 (5580)	-2.83	-1.71	-2.90	-1.78	1.26	8.99	Pass
	140 (5700)	-2.58	-1.46	-2.64	-1.52	1.52	8.99	Pass
Mode	Channel/ Frequency (MHz)	Maximum Power Spectral Density (dBm/MHz)						
		MIMO				Total PSD MIMO_ Chain 0+1	Limits	Pass / Fail
		Chain 0		Chain 1				
		Meas PSD	Corr'd PSD	Meas PSD	Corr'd PSD			
IEEE 802.11n-HT20	36 (5180)	-0.95	0.10	-0.86	0.18	3.15	8.99	Pass
	44 (5220)	-1.10	-0.06	-0.95	0.10	3.03	8.99	Pass
	48 (5240)	-1.33	-0.29	-1.54	-0.50	2.62	8.99	Pass
	52 (5260)	-0.16	0.89	-1.64	-0.60	3.22	8.99	Pass
	60 (5300)	-0.72	0.33	-0.52	0.52	3.44	8.99	Pass
	64 (5320)	-0.41	0.63	-0.67	0.37	3.51	8.99	Pass
	100 (5500)	-5.33	-4.29	-5.66	-4.61	-1.44	8.99	Pass
	116 (5580)	-5.37	-4.32	-5.72	-4.67	-1.48	8.99	Pass
	140 (5700)	-4.70	-3.65	-5.23	-4.19	-0.90	8.99	Pass
Mode	Channel/ Frequency (MHz)	Maximum Power Spectral Density (dBm/MHz)						
		MIMO				Total PSD MIMO_ Chain 0+1	Limits	Pass / Fail
		Chain 0		Chain 1				
		Meas PSD	Corr'd PSD	Meas PSD	Corr'd PSD			
IEEE 802.11n-HT40	38 (5190)	-7.82	-6.29	-7.79	-6.26	-3.26	8.99	Pass
	46 (5230)	-7.72	-6.19	-8.59	-7.06	-3.59	8.99	Pass
	54 (5270)	-8.25	-6.71	-8.01	-6.47	-3.58	8.99	Pass
	62 (5310)	-7.81	-6.27	-8.39	-6.86	-3.54	8.99	Pass
	102 (5510)	-12.65	-11.12	-14.47	-12.93	-8.92	8.99	Pass
	110 (5590)	-12.52	-10.98	-14.82	-13.28	-8.97	8.99	Pass
	134 (5670)	-11.83	-10.29	-13.98	-12.45	-8.23	8.99	Pass

Mode	Channel/ Frequency (MHz)	Maximum Power Spectral Density (dBm/MHz)						
		MIMO				Total PSD MIMO_ Chain 0+1	Limits	Pass / Fail
		Chain 0		Chain 1				
		Meas PSD	Corr'd PSD	Meas PSD	Corr'd PSD			
IEEE 802.11ac- VHT20	36 (5180)	0.52	1.71	0.82	2.01	4.87	8.99	Pass
	44 (5220)	0.68	1.87	0.99	2.18	5.04	8.99	Pass
	48 (5240)	0.12	1.31	0.45	1.64	4.48	8.99	Pass
	52 (5260)	1.06	2.25	1.41	2.60	5.44	8.99	Pass
	60 (5300)	0.79	1.98	1.28	2.47	5.24	8.99	Pass
	64 (5320)	0.64	1.83	1.21	2.40	5.13	8.99	Pass
	100 (5500)	-3.35	-2.16	-3.29	-2.10	0.88	8.99	Pass
	116 (5580)	-3.09	-1.90	-3.34	-2.15	0.99	8.99	Pass
	140 (5700)	-3.33	-2.14	-2.76	-1.57	1.16	8.99	Pass

Mode	Channel/ Frequency (MHz)	Maximum Power Spectral Density (dBm/MHz)						
		MIMO				Total PSD MIMO_ Chain 0+1	Limits	Pass / Fail
		Chain 0		Chain 1				
		Meas PSD	Corr'd PSD	Meas PSD	Corr'd PSD			
IEEE 802.11ac- VHT40	38 (5190)	-6.86	-5.10	-8.16	-6.40	-2.69	8.99	Pass
	46 (5230)	-7.84	-6.08	-8.36	-6.60	-3.32	8.99	Pass
	54 (5270)	-7.78	-6.02	-8.34	-6.58	-3.28	8.99	Pass
	62 (5310)	-8.52	-6.76	-8.76	-7.00	-3.87	8.99	Pass
	102 (5510)	-12.58	-10.82	-14.49	-12.73	-8.66	8.99	Pass
	110 (5590)	-12.24	-10.48	-14.68	-12.92	-8.52	8.99	Pass
	134 (5670)	-11.90	-10.14	-14.87	-13.11	-8.37	8.99	Pass

Mode	Channel/ Frequency (MHz)	Maximum Power Spectral Density (dBm/MHz)						
		MIMO				Total PSD MIMO_ Chain 0+1	Limits	Pass / Fail
		Chain 0		Chain 1				
		Meas PSD	Corr'd PSD	Meas PSD	Corr'd PSD			
IEEE 802.11ac- VHT80	42 (5210)	-11.99	-9.73	-11.91	-9.65	-6.68	8.99	Pass
	58 (5290)	-11.81	-9.55	-12.36	-10.10	-6.80	8.99	Pass
	106 (5530)	-12.83	-10.57	-13.78	-11.52	-8.01	8.99	Pass
	122 (5610)	-7.79	-5.53	-8.35	-6.09	-2.79	8.99	Pass

For U-NII-3 band


Mode	Channel/ Frequency (MHz)	Maximum Power Spectral Density (dBm/500kHz)						
		SISO				Total PSD MIMO_ Chain 0+1	Limit	Pass / Fail
		Chain 0		Chain 1				
		Meas PSD	Corr'd PSD	Meas PSD	Corr'd PSD			
IEEE 802.11a	149 (5745)	0.45	1.56	1.04	2.16	4.88	27.99	Pass
	157 (5785)	1.07	2.19	1.61	2.73	5.48	27.99	Pass
	165 (5825)	0.96	2.08	1.50	2.62	5.37	27.99	Pass
Mode	Channel/ Frequency (MHz)	Maximum Power Spectral Density (dBm/500kHz)						
		MIMO				Total PSD MIMO_ Chain 0+1	Limit	Pass / Fail
		Chain 0		Chain 1				
		Meas PSD	Corr'd PSD	Meas PSD	Corr'd PSD			
IEEE 802.11n-HT20	149 (5745)	-0.88	0.16	-0.66	0.39	3.29	27.99	Pass
	157 (5785)	-0.65	0.40	-0.15	0.89	3.66	27.99	Pass
	165 (5825)	-0.55	0.49	-0.18	0.87	3.69	27.99	Pass
IEEE 802.11n-HT40	151 (5755)	-4.23	-2.69	-4.03	-2.50	0.42	27.99	Pass
	159 (5795)	-3.65	-2.12	-3.09	-1.56	1.18	27.99	Pass
Mode	Channel/ Frequency (MHz)	Maximum Power Spectral Density (dBm/500kHz)						
		MIMO				Total PSD MIMO_ Chain 0+1	Limit	Pass / Fail
		Chain 0		Chain 1				
		Meas PSD	Corr'd PSD	Meas PSD	Corr'd PSD			
IEEE 802.11ac-VHT20	149 (5745)	0.38	1.57	0.75	1.94	4.77	27.99	Pass
	157 (5785)	0.74	1.92	0.80	1.99	4.97	27.99	Pass
	165 (5825)	1.07	2.26	0.72	1.91	5.10	27.99	Pass
IEEE 802.11ac-VHT40	151 (5755)	-4.64	-2.87	-4.05	-2.29	0.44	27.99	Pass
	159 (5795)	-3.65	-1.89	-3.55	-1.79	1.17	27.99	Pass
Mode	Channel/ Frequency (MHz)	Maximum Power Spectral Density (dBm/500kHz)						
		MIMO				Total PSD MIMO_ Chain 0+1	Limit	Pass / Fail
		Chain 0		Chain 1				
		Meas PSD	Corr'd PSD	Meas PSD	Corr'd PSD			
IEEE 802.11ac-VHT80	155 (5775)	-6.29	-4.03	-6.04	-3.78	-0.89	27.99	Pass

Remark:

1. Corr'd PSD = Meas PSD + Duty Cycle Factor

2. Total (Chain 0+1) = $10 \cdot \log[(10^{\text{Chain 0}/10}) + (10^{\text{Chain 1}/10})]$

The test plots as follows:



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0
















IEEE 802.11n-HT20


Channel 149




Channel 157



Channel 165





Shenzhen UnionTrust Quality and Technology Co., Ltd.


Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.0




IEEE 802.11n-HT40

Channel 134



Channel 151



Channel 159

