

## FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

#### Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

### Result

#### Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	6	3.98	26.0	398.11	20	0.315	1
5150-5250	7	5.01	22.5	177.83	20	0.177	1
5725-5850	7	5.01	22.5	177.83	20	0.177	1

Note: The 2.4G Wi-Fi and 5G Wi-Fi can transmit at the same time.  
 The antenna gain is 3dBi for 2.4GHz Wi-Fi and 4dBi for 5G Wi-Fi.  
 EUT support beamforming  
 Directional gain = G<sub>ANT</sub> + Array Gain  
 $Array\ Gain = 10 * \log(N_{ant}/N_{ss})\ dB$   
 For the worst case,  $N_{ss}=1$ , so:  
 For 2.4GHz Wi-Fi, Directional gain=3dBi+10\*log(2/1)dB=6dB  
 For 5GHz Wi-Fi, Directional gain=4dBi+10\*log(2/1)dB=7dB

Simultaneous transmitting consideration:

The ratio=MPE<sub>DTS</sub>/limit+MPE<sub>NII</sub>/limit =0.315/1+0.177/1=0.492<1.0

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

### Result: Compliance