

## 5. RF EXPOSURE EVALUATION

### 5.1 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

#### 5.1.1 Applicable Standard

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

#### 5.1.2 Result

##### Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Mode	Frequency (MHz)	Tune Up Conducted Power (dBm)	Antenna Gain (dBi) (Note 2)	Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
Bluetooth	2402-2480	14.5	4.45	32	0.006	1.0
BLE	2402-2480	14.0	4.45	32	0.005	1.0
2.4G Wi-Fi	2412-2462	25.0	7.15	32	0.128	1.0
5G Wi-Fi	5180-5240	27.6	8.26	32	0.300	1.0
	5260-5320	21.73	8.26	32	0.078	1.0
	5500-5700	21.73	8.26	32	0.078	1.0
	5745-5825	27.2	8.26	32	0.273	1.0
6G Wi-Fi	5955-6145	16.0	7.55	32	0.018	1.0
	6435-6515	16.0	7.55	32	0.018	1.0
	6535-6855	16.0	7.55	32	0.018	1.0
	6875-7115	16.0	7.55	32	0.018	1.0

Note:

- 1) The tune up conducted power was declared by the applicant.
- 2) For the Wi-Fi mode, the antenna gain would be the directional gain.
- 3) The Bluetooth, 2.4G Wi-Fi, 5G Wi-Fi and 6G Wi-Fi can transmit simultaneously.

The ratio= $\text{MPE}_{\text{Bluetooth}}/\text{limit} + \text{MPE}_{\text{2.4G Wi-Fi}}/\text{limit} + \text{MPE}_{\text{5G Wi-Fi}}/\text{limit} + \text{MPE}_{\text{6G Wi-Fi}}/\text{limit}$   
 $= 0.006 + 0.128 + 0.300 + 0.018 = 0.452 < 1.0$ , simultaneous exposure is not required.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 32cm from nearby persons.

**Result: Compliance**