



MRT Technology (Suzhou) Co., Ltd
Phone: +86-512-66308358
Fax: +86-512-66308368
Web: www.mrt-cert.com

Report No.: 1601RSU00601
Report Version: V02
Issue Date: 01-20-2016

MEASUREMENT REPORT

FCC PART 15.247 Bluetooth v2.1 + EDR

FCC ID: YZZGXP2130V2

APPLICANT: Grandstream Networks, Inc.

Application Type: Certification

Product: IP Phone

Model No.: GXP2130

Brand Name: Grandstream

FCC Classification: FCC Part 15 Spread Spectrum Transmitter(DSS)

FCC Rule Part(s): Part 15.247

Test Procedure(s): ANSI C63.10-2013, DA 00-705

Test Date: January 12 ~ 16, 2016

Reviewed By :

(Robin Wu)

Approved By :

(Marlin Chen)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and DA 00-705. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date
1601RSU00601	Rev. 01	Initial report	01-18-2016
1601RSU00601	Rev. 02	Update the test date	01-20-2016

Note: The EUT has been got the FCC certificate (FCC ID: YZZGXP2130V2). The EUT adds two new adapters now and we have shown the conducted emission data and radiated emission data (below 1GHz) in this DSS report.

CONTENTS

Description	Page
1. INTRODUCTION	5
1.1. Scope	5
1.2. MRT Test Location	5
2. PRODUCT INFORMATION	6
2.1. Equipment Description.....	6
2.2. Product Specification Subjective to this Standard	7
2.3. Operation Frequency / Channel List	8
2.4. Test Configuration	9
2.5. EMI Suppression Device(s)/Modifications.....	9
3. DESCRIPTION of TEST.....	10
3.1. Evaluation Procedure	10
3.2. AC Line Conducted Emissions	10
3.3. Radiated Emissions	11
4. ANTENNA REQUIREMENTS.....	12
5. TEST EQUIPMENT CALIBRATION DATE	13
6. MEASUREMENT UNCERTAINTY.....	14
7. TEST RESULT	15
7.1. Summary	15
7.2. Radiated Spurious Emission Measurement	16
7.2.1. Test Limit	16
7.2.2. Test Procedure Used	16
7.2.3. Test Setting.....	16
7.2.4. Test Setup.....	17
7.2.5. Test Result.....	18
7.3. AC Conducted Emissions Measurement.....	22
7.3.1. Test Limit	22
7.3.2. Test Setup.....	22
7.3.3. Test Result.....	23
8. CONCLUSION.....	27

§2.1033 General Information

Applicant:	Grandstream Networks, Inc.
Applicant Address:	4th Floor, Rainbow Technology Building #16 New West Rd, Nanshan Science & Technology Park (North District), Shenzhen, China 518057
Manufacturer:	Grandstream Networks, Inc.
Manufacturer Address:	4th Floor, Rainbow Technology Building #16 New West Rd, Nanshan Science & Technology Park (North District), Shenzhen, China 518057
Test Site:	MRT Technology (Suzhou) Co., Ltd
Test Site Address:	D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
MRT Registration No.:	809388
FCC Rule Part(s):	Part 15.247
Model No.	GXP2130
FCC ID:	YZZGXP2130V2
Test Device Serial No.:	N/A <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering
FCC Classification:	FCC Part 15 Spread Spectrum Transmitter (DSS)

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC registered (MRT Reg. No. 809388) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-4179, G-814, C-4664, T-2206) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications and Radio testing for FCC, Industry Canada, EU and TELEC Rules.



1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on September 30, 2013.



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name	IP Phone
Model No.	GXP2130
Brand Name	Grandstream
BT Specification	v2.1+EDR
Antenna Type	PCB Antenna
Antenna Gain	2dBi
Components	
Adapter #1	M/N: NBS05B120050VU Input: AC 100-240V ~ 50/60Hz, 0.15A OUTPUT: 12Vdc, 0.5A
Adapter #2	M/N: F06US1200050A Input: AC 100-240V ~ 50/60Hz, 0.2A max OUTPUT: 12Vdc, 0.5A

2.2. Product Specification Subjective to this Standard

Product Specification Subjective to this Standard	
Transmitter / Receiver Frequency Range	2402~2480MHz
Number of Channels	79
Channel Spacing	1MHz
Type of Modulation	FHSS
Data Rate	1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK)

Note: For other features of this EUT, test report will be issued separately.

The equipment under test (EUT) is the **IP Phone FCC ID: YZZGXP2130V2**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

2.3. Operation Frequency / Channel List

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz
03	2405 MHz	04	2406 MHz	05	2407 MHz
06	2408 MHz	07	2409 MHz	08	2410 MHz
09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz
15	2417 MHz	16	2418 MHz	17	2419 MHz
18	2420 MHz	19	2421 MHz	20	2422 MHz
21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz
27	2429 MHz	28	2430 MHz	29	2431 MHz
30	2432 MHz	31	2433 MHz	32	2434 MHz
33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz
39	2441 MHz	40	2442 MHz	41	2443 MHz
42	2444 MHz	43	2445 MHz	44	2446 MHz
45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz
51	2453 MHz	52	2454 MHz	53	2455 MHz
54	2456 MHz	55	2457 MHz	56	2458 MHz
57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz
63	2465 MHz	64	2466 MHz	65	2467 MHz
66	2468 MHz	67	2469 MHz	68	2470 MHz
69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz
75	2477 MHz	76	2478 MHz	77	2479 MHz
78	2480 MHz	N/A	N/A	N/A	N/A

2.4. Test Configuration

The **IP Phone FCC ID: YZZGXP2130V2** was tested per the guidance of ANSI C63.10-2013 and DA 00-705. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.5. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

3. DESCRIPTION of TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems" (DA 00-705) were used in the measurement of the **IP Phone FCC ID: YZZGXP2130V2**.

Deviation from measurement procedure.....**None**

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions were used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

Line conducted emissions test results are shown in Section 6.3.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beamwidth of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the **IP Phone** is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The **IP Phone** FCC ID: **YZZGXP2130V2** unit complies with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions - SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2016/11/03
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2016/11/03
Two-Line V-Network	R&S	ENV216	MRTSUE06003	1 year	2016/11/03
Temperature/ Meter Humidity	Yuhuaze	N/A	MRTSUE06180	1 year	2016/12/20

Radiated Emissions - AC2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9010A	MRTSUE06124	1 year	2016/06/23
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2016/11/03
TRILOG Antenna	Schwarzbeck	VULB9168	MRTSUE06172	1 year	2016/12/10
Temperature/ Meter Humidity	Mingao	ETH529	MRTSUE06170	1 year	2016/11/29

Software	Version	Function
e3	V 8.3.5	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 150kHz~30MHz: 3.46dB
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz ~ 1GHz: 4.18dB

7. TEST RESULT

7.1. Summary

Product Name: IP Phone
FCC ID: YZZGXP2130V2
Method/System: Frequency Hopping Spread Spectrum (FHSS)
Number of Channels: 79

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.209	General Field Strength Limits (Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Radiated	PASS	Section 7.2
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.3

Notes: All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.

7.2. Radiated Spurious Emission Measurement

7.2.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [V/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 – 30	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

7.2.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.12.1

7.2.3. Test Setting

Peak Field Strength Measurements


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in Table 1
3. VBW = 3 * RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

7.2.4. Test Setup


30MHz ~ 1GHz Test Setup:



7.2.5. Test Result

The worst case of Radiated Emission 30MHz ~ 1GHz:

Site: AC2	Time: 2016/01/13 - 11:31
Limit: FCC_Part15.209_RE(3m)_Class B	Engineer: Lewis Huang
Probe: VULB9162_0.03-8GHz	Polarity: Horizontal
EUT: IP Phone	Power: AC 120V/60Hz
Worst Case Mode: Transmit at channel 2402MHz by DH5 (Adapter #1)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			158.040	28.412	18.640	-15.088	43.500	9.772	QP
2			250.190	30.036	16.340	-15.964	46.000	13.696	QP
3			338.460	32.483	16.840	-13.517	46.000	15.643	QP
4			374.835	31.638	15.420	-14.362	46.000	16.218	QP
5			515.485	32.033	13.480	-13.967	46.000	18.553	QP
6		*	750.225	38.602	16.340	-7.398	46.000	22.262	QP

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2016/01/13 - 11:33
Limit: FCC_Part15.209_RE(3m)_Class B	Engineer: Lewis Huang
Probe: VULB9162_0.03-8GHz	Polarity: Vertical
EUT: IP Phone	Power: AC 120V/60Hz
Worst Case Mode: Transmit at channel 2402MHz by DH5 (Adapter #1)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Over Limit (dB)	Limit (dB μ V/m)	Factor (dB)	Type
1			30.970	31.904	19.674	-8.096	40.000	12.230	QP
2	*		67.830	31.915	20.310	-8.085	40.000	11.606	QP
3			140.580	34.423	24.940	-9.077	43.500	9.482	QP
4			374.835	30.248	14.030	-15.752	46.000	16.218	QP
5			549.920	30.171	11.020	-15.829	46.000	19.151	QP
6			750.225	35.902	13.640	-10.098	46.000	22.262	QP

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2016/01/13 - 11:46
Limit: FCC_Part15.209_RE(3m)_Class B	Engineer: Lewis Huang
Probe: VULB9162_0.03-8GHz	Polarity: Horizontal
EUT: IP Phone	Power: AC 120V/60Hz
Worst Case Mode: Transmit at channel 2402MHz by DH5 (Adapter #2)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Over Limit (dB)	Limit (dB μ V/m)	Factor (dB)	Type
1			134.760	25.701	15.970	-17.799	43.500	9.731	QP
2			250.190	28.556	14.860	-17.444	46.000	13.696	QP
3			300.145	30.449	15.870	-15.551	46.000	14.579	QP
4			374.835	31.468	15.250	-14.532	46.000	16.218	QP
5			649.830	30.861	10.140	-15.139	46.000	20.722	QP
6	*		750.225	38.572	16.310	-7.428	46.000	22.262	QP

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2016/01/13 - 11:48
Limit: FCC_Part15.209_RE(3m)_Class B	Engineer: Lewis Huang
Probe: VULB9162_0.03-8GHz	Polarity: Vertical
EUT: IP Phone	Power: AC 120V/60Hz
Worst Case Mode: Transmit at channel 2402MHz by DH5 (Adapter #2)	



No	Flag	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			31.270	32.496	20.220	-7.504	40.000	12.276	QP
2	*		66.375	36.962	24.870	-3.038	40.000	12.092	QP
3			98.870	28.676	15.840	-14.824	43.500	12.836	QP
4			134.760	34.121	24.390	-9.379	43.500	9.731	QP
5			374.835	27.676	11.458	-18.324	46.000	16.218	QP
6			649.830	31.751	11.030	-14.249	46.000	20.722	QP

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

7.3. AC Conducted Emissions Measurement


7.3.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

7.3.2. Test Setup



7.3.3. Test Result

Site: SR2	Time: 2016/01/12 - 11:23
Limit: FCC_Part15.207_CE_AC Power_Class B	Engineer: Vince Yu
Probe: ENV216_101683_Filter On	Polarity: Line
EUT: IP Phone	Power: AC 120V/60Hz
Test Mode: Transmit at Channel 2402MHz by DH5 (Adapter #1)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.154	40.065	29.325	-25.716	65.781	10.740	QP
2			0.154	24.538	13.799	-31.243	55.781	10.740	AV
3			0.514	37.402	27.246	-18.598	56.000	10.156	QP
4		*	0.514	31.520	21.364	-14.480	46.000	10.156	AV
5			0.690	29.151	19.083	-26.849	56.000	10.068	QP
6			0.690	21.621	11.553	-24.379	46.000	10.068	AV
7			0.990	29.284	19.370	-26.716	56.000	9.914	QP
8			0.990	20.808	10.894	-25.192	46.000	9.914	AV
9			1.246	27.066	17.166	-28.934	56.000	9.900	QP
10			1.246	19.257	9.357	-26.743	46.000	9.900	AV
11			13.734	32.113	22.060	-27.887	60.000	10.053	QP
12			13.734	25.261	15.208	-24.739	50.000	10.053	AV

Note: Measure Level (dB μ V) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB).

Site: SR2	Time: 2016/01/12 - 11:28
Limit: FCC_Part15.207_CE_AC Power_Class B	Engineer: Vince Yu
Probe: ENV216_101683_Filter On	Polarity: Neutral
EUT: IP Phone	Power: AC 120V/60Hz
Test Mode: Transmit at Channel 2402MHz by DH5 (Adapter #1)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.150	40.820	29.678	-25.180	66.000	11.142	QP
2			0.150	25.099	13.957	-30.901	56.000	11.142	AV
3			0.162	36.519	26.441	-28.842	65.361	10.078	QP
4			0.162	17.975	7.897	-37.386	55.361	10.078	AV
5			0.826	35.102	25.097	-20.898	56.000	10.004	QP
6			0.826	25.045	15.041	-20.955	46.000	10.004	AV
7			0.994	36.161	26.249	-19.839	56.000	9.912	QP
8	*		0.994	26.891	16.978	-19.109	46.000	9.912	AV
9			1.110	34.418	24.514	-21.582	56.000	9.904	QP
10			1.110	24.510	14.605	-21.490	46.000	9.904	AV
11			14.450	39.995	29.903	-20.005	60.000	10.091	QP
12			14.450	30.147	20.056	-19.853	50.000	10.091	AV

Note: Measure Level (dB μ V) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB).

Site: SR2	Time: 2016/01/12 - 11:54
Limit: FCC_Part15.207_CE_AC Power_Class B	Engineer: Vince Yu
Probe: ENV216_101683_Filter On	Polarity: Line
EUT: IP Phone	Power: AC 120V/60Hz
Test Mode: Transmit at Channel 2402MHz by DH5 (Adapter #2)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dB μ V)	Reading Level (dB μ V)	Over Limit (dB)	Limit (dB μ V)	Factor (dB)	Type
1			0.150	42.540	31.372	-23.460	66.000	11.168	QP
2			0.150	24.420	13.251	-31.580	56.000	11.168	AV
3			0.170	40.094	30.017	-24.866	64.960	10.078	QP
4			0.170	20.808	10.730	-34.152	54.960	10.078	AV
5			0.478	36.484	26.336	-19.889	56.374	10.149	QP
6			0.478	23.784	13.636	-22.589	46.374	10.149	AV
7	*	*	0.550	37.107	26.966	-18.893	56.000	10.141	QP
8			0.550	24.066	13.925	-21.934	46.000	10.141	AV
9			9.366	39.326	29.176	-20.674	60.000	10.150	QP
10			9.366	26.616	16.466	-23.384	50.000	10.150	AV
11			11.106	40.299	30.197	-19.701	60.000	10.102	QP
12			11.106	27.288	17.186	-22.712	50.000	10.102	AV

Note: Measure Level (dB μ V) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB).

Site: SR2	Time: 2016/01/12 - 11:58
Limit: FCC_Part15.207_CE_AC Power_Class B	Engineer: Vince Yu
Probe: ENV216_101683_Filter On	Polarity: Neutral
EUT: IP Phone	Power: AC 120V/60Hz
Test Mode: Transmit at Channel 2402MHz by DH5 (Adapter #2)	



No	Flag	Mark	Frequency (MHz)	Measure Level (dB μ V)	Reading Level (dB μ V)	Over Limit (dB)	Limit (dB μ V)	Factor (dB)	Type
1			0.150	41.941	30.799	-24.059	66.000	11.142	QP
2			0.150	25.993	14.851	-30.007	56.000	11.142	AV
3			0.158	41.196	30.907	-24.372	65.568	10.290	QP
4			0.158	24.887	14.597	-30.682	55.568	10.290	AV
5			0.550	35.177	25.018	-20.823	56.000	10.159	QP
6			0.550	25.404	15.245	-20.596	46.000	10.159	AV
7			1.134	34.958	25.054	-21.042	56.000	9.905	QP
8			1.134	25.551	15.647	-20.449	46.000	9.905	AV
9			8.994	39.485	29.314	-20.515	60.000	10.171	QP
10			8.994	29.584	19.413	-20.416	50.000	10.171	AV
11			9.546	39.651	29.473	-20.349	60.000	10.178	QP
12	*		9.546	29.929	19.751	-20.071	50.000	10.178	AV

Note: Measure Level (dB μ V) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB).

8. CONCLUSION

The data collected relate only the item(s) tested and show that the **IP Phone FCC ID: YZZGXP2130V2** is in compliance with Part 15C of the FCC Rules.

The End