



www.ecmg-global.net

EMI TEST REPORT

On Model Name: VoIP Gateway

Model Number: GXW4004, GXW4008

Brand Name: Grandstream

Prepared for Grandstream Networks, INC

FCC ID Number: YZZGXW400X

According to FCC 47 CFR Part 15, Subpart B


Test Report #: SHE-1108-10683-FCC

Prepared by: Sewen Guo

Reviewed by: Jawen Yin

QC Manager: Swall Zhang

Test Report Released by:



Swall Zhang

September 2, 2011

Date

Test Location

Tests performed in a Certified ANSI Semi-Anechoic Chamber and Shielded Room.

Test Site Location : Galanz

*25 South Ronggui Rd., Shunde, Foshan,
Guangdong, China*

Tel : 86-757-23612785

Fax : 86-757-23612537

Test Facility

The test facility was recognized, certified, or accredited by the following organizations:

- *CNAL - LAB Code: L2244*

Galanz EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- *FCC - Registration No.: 580210*

Galanz EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC was maintained in our files.

Table of Contents

GOVERNMENT DISCLAIMER NOTICE	2
REPRODUCTION CLAUSE	2
OPINIONS AND INTERPRETATIONS	2
STATEMENT OF MEASUREMENT UNCERTAINTY	2
ADMINISTRATIVE DATA	3
EUT DESCRIPTION	4
EUT MODEL DERIVED	5
TEST SUMMARY	6
TEST MODE JUSTIFICATION	7
EUT EXERCISE SOFTWARE	7
EQUIPMENT MODIFICATION	7
EUT SAMPLE PHOTOS	8
TEST SYSTEM DETAILS	13
CONFIGURATION OF TESTED SYSTEM	15
ATTACHMENT 1 - CONDUCTED EMISSION TEST RESULTS	16
ATTACHMENT 2 - RADIATED EMISSION MEASUREMENT	20

List Attached Files

Exhibit Type	File Description	File Name
<i>Test Report</i>	<i>Test Report</i>	<i>YZZGXW400X _Test report.pdf</i>
<i>Operation Description</i>	<i>Technical Description</i>	<i>YZZGXW400X_operation description.pdf</i>
<i>External Photos</i>	<i>External Photos</i>	<i>YZZGXW400X_External Photos</i>
<i>Internal Photos</i>	<i>Internal Photos</i>	<i>YZZGXW400X_Internal Photos</i>
<i>Block Diagram</i>	<i>Block Diagram</i>	<i>YZZGXW400X_Block Diagram.pdf</i>
<i>Schematics</i>	<i>Circuit Diagram</i>	<i>YZZGXW400X _Schematics.pdf</i>
<i>ID Label/Location</i>	<i>Label and Location</i>	<i>YZZGXW400X _Label & Location.pdf</i>
<i>User Manual</i>	<i>User Manual</i>	<i>YZZGXW400X _User Manual.pdf</i>
<i>Test setup photos</i>	<i>Test set-up photos</i>	<i>YZZGXW400X _Test Set-up Photos</i>

Government Disclaimer Notice

When government drawing, specification, or other data are used for any purpose other than in connection with a definitely related government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawing, specifications, or other data, is not to be regarded by implication or otherwise in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell patented invention that may in any way be related thereto. This report must not be used to claim product endorsement by NVLAP or any agency of the U.S. Government.

Reproduction Clause

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from EMC Compliance Management Group.

Opinions and Interpretations

This test report relates to the abovementioned equipment under test (EUT). Without the permission of EMC Compliance Management Group Test Lab this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark on this or similar products. The manufacturer has sole responsibility of continued compliance of the device.

Statement of Measurement Uncertainty

The data and results referenced in the document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities that can account for a nominal measurement error. Furthermore, component and process variability of devices similar to that tested may result in additional deviation.

Administrative Data

Test Sample : *VoIP Gateway*
Model Numbers : *GXW4004, GXW4008*
Model Tested : *GXW4008*
Receipt Date : *August 26, 2011*
Date Tested : *August 29, 2011 to August 30, 2011*
Applicant : *Grandstream Networks, INC*
Address : *5F, Bldg #1, No.2 Kefa Rd., Science & Technology Park, Shenzhen, China*
Telephone : *86-755-26014600*
Fax : *86-755-26014601*
Manufacturer : *Grandstream Networks, INC*
Address : *5F, Bldg #1, No.2 Kefa Rd., Science & Technology Park, Shenzhen, China*
Telephone : *86-755-26014600*
Fax : *86-755-26014601*
Factory : *Grandstream Networks, INC*
Address : *5F, Bldg #1, No.2 Kefa Rd., Science & Technology Park, Shenzhen, China*
Telephone : *86-755-26014600*
Fax : *86-755-26014601*

EUT Description

Grandstream Networks, INC., model tested GXW4008 (referred to as the EUT in this report) is an VoIP Gateway.

The EUT is an VoIP Gateway and technical specifications of EUT as below:

Parameter		Range
<i>Basic parameters</i>	<i>Rated voltage</i>	12VDC
	<i>Rated Current</i>	1.5A
<i>I/O Ports</i>	<i>LAN Port</i>	<i>Connect the LAN port with an Ethernet cable to your PC</i>
	<i>WAN Port</i>	<i>Connect to the internal LAN network or router</i>
	<i>RESET</i>	<i>Factory Reset button. Press for 7 seconds to reset factory default settings</i>
	<i>DC 12V</i>	<i>Power adapter connection</i>
	<i>CONSOLE</i>	<i>Console connection for a PC.</i>
	<i>LINE</i>	<i>When the unit loses power or unit became unregistered, FXS port 1 will be able to make/receive calls from the PSTN line connected to this port.</i>
	<i>FXS1 - FXS8</i>	<i>FXS port to be connected to analog phones / fax machines.</i>
<i>Adapter informations</i>	<i>Input</i>	<i>100-240VAC, 50/60Hz ,0.4A</i>
	<i>Output</i>	<i>12VDC, 1.5A</i>
	<i>Model</i>	<i>SFF1200150A1BB</i>
	<i>Brand name</i>	<i>Mass power</i>

NOTE: For more detailed informations or features please refer to user's manual of EUT.

EUT Model Derived

Model of GXW4004 and GXW4008 are the same series of the products, they have the same circuit function, the difference between them is only FXS port's number and anything else are the same. for more details please see the following FXS's port photo.

GXW4004 I/O ports view:



Model of GXW4004
has four FXS ports.

GXW4008 I/O ports view:



Model of GXW4008
has eight FXS ports.

The worst-case model of GXW4008 was chosen for the final testing.

Test Summary

The Electromagnetic Compatibility requirements on model GXW4008 for this test are stated below. All results listed in this report relate exclusively to this above-mentioned model as the Equipment under Test. This report confers no approval or endorsement upon any other component, host or subsystem used in the test set-up.

Emission Tests				
Specifications	Description	Test Results	Test Point	Remark
<i>FCC Part 15.107 ANSI C63.4 -2003</i>	<i>Conducted Emission</i>	<i>Passed</i>	<i>AC Input Port</i>	<i>Attachment 1</i>
<i>FCC Part 15.109 ANSI C63.4 -2003</i>	<i>Radiated Emission</i>	<i>Passed</i>	<i>Enclosure</i>	<i>Attachment 2</i>

Test Mode Justification

The EUT was tested in the most representative operating mode as normal use. The following mode was chosen for final test as described below:

Connected a PC to LAN port of EUT by an RJ-45 cable and ping 192.168.2.1 -t to EUT. then, connected an IP phone to WAN port by another an RJ-45 cable and connected an analog phone to FXS1 port by an RJ-11 cable and established a call communication between them and measured it.

EUT Exercise Software

No test software support this test.

Equipment Modification

Any modifications installed previous to testing by Grandstream Networks, INC., will be incorporated in each production model sold or leased in United States.

There were no modifications installed by EMC Compliance Management Group test personnel.

EUT Sample Photos

EUT Model: GXW4008



EUT- Top View



EUT- Bottom View



EUT- Front View



EUT- Rear View




EUT -Side View




RJ-45 Cable View




Power Adaptor View (Manufacturer: Mass Power)



Uncovered View



Mainboard Top View



Mainboard Bottom View

Test System Details


EUT			
Model Number:	<i>GXW4004, GXW4008</i>		
Model Tested:	<i>GXW4008</i>		
Description:	<i>VoIP Gateway</i>		
Input:	<i>AC 120V/60Hz</i>		
Manufacturer:	<i>Grandstream Networks, INC</i>		
Support Equipment			
Description	Model Number	Serial Number	Manufacturer
<i>Notebook PC</i>	<i>NC4000</i>	<i>CNU4122BCL</i>	<i>HP</i>
<i>AC Adapter Of Notebook PC</i>	<i>PPP009H</i>	<i>239427-003</i>	<i>HP</i>
<i>Mouse</i>	<i>MO32B0</i>	<i>23-033131</i>	<i>HP</i>
<i>Keyboard</i>	<i>SK-1788</i>	<i>N/A</i>	<i>LENOVO</i>
<i>Monitor</i>	<i>177V+</i>	<i>N/A</i>	<i>AOC</i>
<i>IP Phone</i>	<i>GXP 2100</i>	<i>N/A</i>	<i>Grandstream Networks, INC</i>
<i>Analog Phone</i>	<i>2957E</i>	<i>N/A</i>	<i>Shenzhen Daerxun Technology Co., Ltd</i>

Cable Description					
Description	From	To	Length (Meters)	Shielded (Y/N)	Ferrite (Y/N)
<i>AC Adaptor Cord Of Notebook PC</i>	<i>AC Adaptor</i>	<i>Notebook PC</i>	<i>1.6</i>	<i>N</i>	<i>Y</i>
	<i>AC Plug</i>	<i>AC Adaptor</i>	<i>1.2</i>	<i>N</i>	<i>Y</i>
<i>Mouse Cord</i>	<i>Mouse</i>	<i>Notebook PC</i>	<i>1.2</i>	<i>N</i>	<i>Y</i>
<i>Keyboard Cord</i>	<i>Keyboard</i>	<i>Notebook PC</i>	<i>1.2</i>	<i>N</i>	<i>Y</i>
<i>VGA Cord</i>	<i>Notebook PC</i>	<i>Monitor</i>	<i>1.2</i>	<i>Y</i>	<i>Y</i>
<i>RJ-45 Cable #1</i>	<i>EUT</i>	<i>Notebook PC</i>	<i>1.5</i>	<i>N</i>	<i>N</i>
<i>RJ-45 Cable #2</i>	<i>EUT</i>	<i>GXP 2100</i>	<i>>3.0</i>	<i>N</i>	<i>Y</i>
<i>AC Adaptor Cord of EUT</i>	<i>EUT</i>	<i>Plug</i>	<i>2.4</i>	<i>N</i>	<i>N</i>
<i>Note: The "EUT" means "VoIP Gateway".</i>					

NOTE:


The EUT has been tested as an independent unit together with other necessary accessories or support units. The above support units or accessories were used to form a representative test configuration during the test tests.


Configuration of Tested System




Note :The “EUT” means “VoIP Gateway”.

ATTACHMENT 1 - CONDUCTED EMISSION TEST RESULTS

CLIENT:	Grandstream Networks, INC	TEST STANDERD:	FCC Part 15, Subpart B, Section 15.107
MODEL NUMBERS:	GXW4004,GXW4008	PRODUCT:	VoIP Gateway
MODEL TESTED:	GXW4008	EUT DESIGNATION:	Home or Office Use
TEMPERATURE:	23°C	HUMIDITY:	47%RH
ATM PRESSURE:	103kPa	GROUNDING:	None
TESTED BY:	Sewen Guo	DATE OF TEST:	August 29, 2011
TEST REFERENCE:	ANSI C63.4- 2003		
TEST PROCEDURE:	The EUT was set up according to the guidelines of ANSI C63.4-2003 for conducted emissions. The measurement was using a AMN on each line and an EMI receiver peak scan was made at the frequency measurement range. The six highest significant peaks were then marked, and these signals were then quasi-peaked and averaged. The frequency range investigated was from 150KHz to 30MHz.		
DESCRIPTION OF TEST MODE	Please refer to test mode justification.		
TEST SET UP			
TESTED RANGE:	150kHz to 30MHz		
TEST VOLTAGE:	AC 120V/60Hz		
RESULTS:	The EUT meets the requirements of test reference for Conducted Emissions. The test results relate only to the equipment under test provided by client.		
Changes or Modifications:	There were no modifications installed by EMC Compliance Management Group test personnel.		
M. UNCERTAINTY:	Freq. $\pm 2 \times 10^{-7} \times$ Center Freq., Amp ± 2.6 dB		



Line L Conducted Emission Graph Of AC Mains



Line N Conducted Emission Graph Of AC Mains

Test Data:

Lines (L/N)	Frequency (MHz)	Corrected QP Level (dBuV)	Limits QP (dBuV)	Margin QP(dB)	Frequency (MHz)	Corrected AV Level (dBuV)	Limits AV (dBuV)	Margin QP(dB)
L	0.155	54.7	65.6	-10.9	0.155	35.2	55.6	-20.4
L	0.300	46.9	60.2	-13.3	0.300	36.5	50.2	-13.7
L	2.670	43.9	56.0	-12.1	2.670	32.9	46.0	-13.1
N	0.150	57.6	65.9	-8.3	0.150	39.3	55.9	-16.6
N	0.200	47.3	63.5	-16.2	0.200	27.3	53.5	-26.2
N	0.295	43.5	60.3	-16.8	0.295	32.6	50.3	-17.7

Note :


- 1) All readings are using a bandwidth of 9 kHz, with a 500 ms sweep time. A video filter was not use.
- 2) "QP" means "Quasi-Peak" values, "AV" means "Average" values.
- 3) The other reading are too low against official limits that are not be recorded.

Test Equipment List:

Test Equipment	Model No.	Manufacturer	Serial No.	Last Cal.	Cal. Interval
Receiver	SMR4503	SCHAFFNER	11725	2011.07.08	2012.07.08
Line impedance stabilization network	4825/2	ETS	1161	2011.07.08	2012.07.08


Note: All testing were performed using internationally recognized standards. All test instruments were calibrated.

SIGNED BY:


ENGINEER

REVIEWED BY:


SENIOR ENGINEER




Conducted Emission Test Set-up

ATTACHMENT 2 – RADIATED EMISSION MEASUREMENT


CLIENT:	Grandstream Networks, INC	TEST STANDERD:	FCC Part 15,Subpart B, Section 15.109
MODEL NUMBERS:	GXW4004,GXW4008	PRODUCT:	VoIP Gateway
EUT MODEL:	GXW4008	EUT DESIGNATION:	Home or Office Use
TEMPERATURE:	23°C	HUMIDITY:	47%RH
ATM PRESSURE:	103.0kPa	GROUNDING:	None
TESTED BY:	Sewen Guo	DATE OF TEST:	August 30, 2011
TEST REFERENCE:	ANSI C63.4- 2003		
TEST PROCEDURE:	<p>The EUT was set up according to the guidelines of ANSI C63.4- 2003 for radiated emissions. An EMI receiver peak scan was made at the frequency measurement range (pre-scan) in an Anechoic chamber.signal discrimination was then performed and the significant peaks marked.these peaks were then quasi-peaked in the frequency range of 30 MHz to 1GHz and average and peak in the frequency range of 1GHz to 3GHz at an anechoic chamber.</p> <p>The following data lists the significant emission frequencies, measured levels, correction factors (including cable and antenna correction factors), and the corrected readings against the limits. Explanation of the Correction Factor are given as follows:</p> <p>FS= RA + AF + CF - AG</p> <p>Where: FS = Field Strength</p> <p>RA = Receiver Amplitude</p> <p>AF = Antenna Factor</p> <p>CF = Cable Attenuation Factor</p> <p>AG = Amplifier Gain</p>		
TESTED RANGE:	30MHz to 3.0GHz		
TEST VOLTAGE:	AC 120V/60Hz		
RESULTS:	The EUT meet the requirements of test reference for radiated emissions.The test results relate only to the equipment under test provided by client.		

Continue on to next page...

	<p>Figure 1 : Frequencies measured below 1 GHz configuration</p>
TEST SET-UP	
	<p>Figure 2 : Frequencies measured above 1 GHz configuration</p>
CHANGES OR MODIFICATIONS:	There were no modifications installed by EMC Compliance Management Group. test personnel.
M. UNCERTAINTY:	Freq. $\pm 2 \times 10^{-7} \times$ Center Freq., Amp ± 2.6 dB



Horizontal Radiated Emission Test



Vertical Radiated Emission Test

Test Data:**Below 1GHz:**

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Preamp Factor (dB)	Reading Level QP (dBuV/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
Horizontal							
172.800	0.02	9.4	/	24.88	34.3	43.5	-9.2
175.040	0.02	7.8	/	27.68	35.5	43.5	-8.0
375.040	0.16	13.9	/	30.04	44.1	46.0	-1.9
584.720	0.30	18.7	/	21.9	40.9	46.0	-5.1
799.920	0.39	22.2	/	15.31	37.9	46.0	-8.1
844.560	0.42	22.5	/	13.78	36.7	46.0	-9.3
Vertical							
41.600	0.02	15.4	/	17.18	32.6	40.0	-7.4
51.840	0.02	6.2	/	28.18	34.4	40.0	-5.6
106.720	0.02	7.7	/	31.38	39.1	43.5	-4.4
454.800	0.2	16.8	/	24.8	41.8	46.0	-4.2
584.720	0.3	18.7	/	23.7	42.7	46.0	-3.3
844.560	0.42	22.5	/	14.58	37.5	46.0	-8.5

Note:

- All readings are quasi-peak unless stated otherwise, using a QPA bandwidth of 120kHz, with a 60 s sweep time. A video filter was not used.
- The field strength is calculated by adding the antenna factor, cable factor & preamplifier. The basic equation with a sample calculation is as follows: Emission Level =Reading Level + Antenna Factor + Cable Loss -Preamplifier Factor.
- The other emission levels are 20dB below the official limits that are not reported.

Above 1GHz:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Preamp Factor (dB)	Reading Level (dBuV/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization (H/V)
Peak Measurement								
1.064	1.40	23.9	-33.6	-5.81	53.09	74	-20.91	H
1.192	1.48	24.2	-33.6	-8.07	51.21	74	-22.79	H
1.584	1.79	26.7	-33.6	-11.44	50.65	74	-23.35	H
1.064	1.40	23.9	-33.6	-5.64	53.26	74	-20.74	V
1.192	1.48	24.2	-33.6	-8.35	50.93	74	-23.07	V
1.584	1.79	26.7	-33.6	-10.87	51.22	74	-22.78	V
Average Measurement								
1.056	1.39	23.9	-33.6	-19.99	38.90	54	-15.1	H
1.192	1.48	24.2	-33.6	-22.38	36.90	54	-17.1	H
1.328	1.57	25.3	-33.6	-23.98	36.49	54	-17.51	H
1.056	1.39	23.9	-33.6	-11.15	47.74	54	-6.26	V
1.192	1.48	24.2	-33.6	-20.42	38.86	54	-15.14	V
1.392	1.60	25.7	-33.6	-23.91	36.99	54	-17.01	V

Note:

- a) The field strength is calculated by adding the antenna factor, cable factor & preamplifier. The basic equation with a sample calculation is as follows: Emission Level =Reading Level + Antenna Factor + Cable Loss -Preamplifier Factor.
- b) The limits shown are based on peak value and average value detector above 1GHz, the bandwidth of test receiver was set at 1MHz above 1GHz.
- c) The other emission levels are 20dB below the official limits that are not reported.

Test Equipment List:

Test Equipment	Model No.	Manufacturer	Serial No.	Last Cal.	Cal. Due
Receiver	SMR4503	SCHAFFNER	11725	2011.07.08	2012.07.07
Double-ridged Wave guide horn	3115	ETS	6587	2011.08.02	2012.08.01
Microwave system amplifier	83017A	Agilent	MY39500438	2011.07.11	2012.07.10
Biconilog Antenna	3142C	ETS	00042672	2010.09.28	2011.09.27
Band-pass Filter	BRM50702	Micro-Tronic	S/N-030	2010.11.30	2011.11.29
Spectrum Analyzer	FSP30	R&S	100755	2010.11.30	2011.11.29
<i>Note: All testing were performed using internationally recognized standards. All test instruments were calibrated.</i>					

SIGNED BY:



ENGINEER


REVIEWED BY:



SENIOR ENGINEER



Radiated Emission Test Set-up(Below 1GHz)



Radiated Emission Test Set-up(Above 1GHz)