

EMI TEST REPORT

On Model Name: Analog Telephone Adapter

Model Number: HT503

Brand Name: Grandstream

Prepared for Grandstream Networks, INC

FCC ID Number: YZZHT503V2

According to FCC 47 CFR Part 15, Subpart B

Test Report #: SHE-1308-11040-FCC

Tested by: Daomen Galanz
Daomen /Engineer Company Name

Reviewed by: Jawen Yin ECMG
Jawen Yin/ Senior Engineer Company Name

QC Manager: Swall Zhang ECMG
Swall Zhang/QC Manager Company Name

Test Report Released by: Swall Zhang September 13, 2013
Swall Zhang Date

Test Location

Tests performed in a Certified ANSI Semi-Anechoic Chamber and Shielded Room.

<i>Test Site Location</i>	<i>: Galanz</i>
	<i>25 South Ronggui Rd., Shunde, Foshan, Guangdong, China</i>
<i>Tel</i>	<i>: (86)-757-23612785</i>
<i>Fax</i>	<i>: (86)-757-23612537</i>

Test Facility

The test facility was recognized, certified, or accredited by the following organizations:

- CNAL - LAB Code: L2244***

Galanz EMC Laboratory has been assessed and in compliance with CN AL/AC01:2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- FCC - Registration No.: 580210***

Galanz EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC was maintained in our files.

Table of Contents

GOVERNMENT DISCLAIMER NOTICE	2
REPRODUCTION CLAUSE	2
OPINIONS AND INTERPRETATIONS	2
STATEMENT OF MEASUREMENT UNCERTAINTY	2
ADMINISTRATIVE DATA	3
EUT DESCRIPTION	4
TEST SUMMARY	5
TEST MODE JUSTIFICATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATION	6
EUT SAMPLE PHOTOS FOR MODEL HT503	7
TEST SYSTEM DETAILS	11
ATTACHMENT 1 - CONDUCTED EMISSION TEST RESULTS	14
ATTACHMENT 2 - RADIATED EMISSION MEASUREMENT	20

List Attached Files

Exhibit Type	File Description	File Name
<i>Test Report</i>	<i>Test Report</i>	<i>YZZHT503V2_Test report.pdf</i>
<i>Operation Description</i>	<i>Technical Description</i>	<i>YZZHT503V2_operation description.pdf</i>
<i>External Photos</i>	<i>External Photos</i>	<i>YZZHT503V2_External Photos</i>
<i>Internal Photos</i>	<i>Internal Photos</i>	<i>YZZHT503V2_Internal Photos</i>
<i>Block Diagram</i>	<i>Block Diagram</i>	<i>YZZHT503V2_Block Diagram.pdf</i>
<i>Schematics</i>	<i>Circuit Diagram</i>	<i>YZZHT503V2_Schematics.pdf</i>
<i>ID Label/Location</i>	<i>Label and Location</i>	<i>YZZHT503V2_Label & Location.pdf</i>
<i>User Manual</i>	<i>User Manual</i>	<i>YZZHT503V2 _User Manual.pdf</i>
<i>Test set-up photos</i>	<i>Test set-up photos</i>	<i>YZZHT503V2 _Test Set-up Photos</i>

Government Disclaimer Notice

When government drawing, specification, or other data are used for any purpose other than in connection with a definitely related government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawing, specifications, or other data, is not to be regarded by implication or otherwise in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell patented invention that may in any way be related thereto. This report must not be used to claim product endorsement by NVLAP or any agency of the U.S. Government.

Reproduction Clause

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from ECMG Electronic Technical Testing Corp (Shenzhen).

Opinions and Interpretations

This test report relates to the abovementioned equipment under test (EUT). Without the permission of ECMG Electronic Technical Testing Corp (Shenzhen) Test Lab this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark on this or similar products. The manufacturer has sole responsibility of continued compliance of the device.

Statement of Measurement Uncertainty

The data and results referenced in the document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities that can account for a nominal measurement error. Furthermore, component and process variability of devices similar to that tested may result in additional deviation.

Administrative Data

Test Sample : *Analog Telephone Adapter*

Model Numbers : *HT503*

Model Tested : *HT503*

Receipt Date : *September 6th, 2013*

Date Tested : *September 11st, 2013*

Applicant : *Grandstream Networks, INC*

Address : *5F, Bldg #1, No.2 Kefa Rd., Science & Technology Park, Shenzhen, China*

Telephone : *(86)-755-26014600*

Fax : *(86)-755-26014601*

Manufacturer : *Grandstream Networks, INC*

Address : *5F, Bldg #1, No.2 Kefa Rd., Science & Technology Park, Shenzhen, China*

Telephone : *(86)-755-26014600*

Fax : *(86)-755-26014601*

Factory : *Grandstream Networks, INC*

Address : *5F, Bldg #1, No.2 Kefa Rd., Science & Technology Park, Shenzhen, China*

Telephone : *(86)-755-26014600*

Fax : *(86)-755-26014601*

EUT Description

Grandstream Networks, INC., model tested HT503 (referred to as the EUT in this report) is an Analog Telephone Adapter.

Technical specifications of the EUT are as below:

Parameter		Range
<i>Basic parameters</i>	<i>Rated voltage</i>	12VDC
	<i>Rated Current</i>	0.5A
<i>I/O Ports</i>	<i>Power Cable</i>	<i>Power adapter connection</i>
	<i>WAN Port (RJ-45)</i>	<i>Connect the WAN port to the internal LAN network or router.</i>
	<i>LAN Port (RJ-45)</i>	<i>Connect the LAN port with an Ethernet cable to your PC.</i>
	<i>RESET</i>	<i>Factory Reset button. Press for 7 seconds to reset factory default settings.</i>
	<i>PHONE (RJ-11)</i>	<i>FXS port to be connected to analog phones / fax machines.</i>
	<i>LINE (RJ-11)</i>	<i>FXO port should be connected to the PSTN line.</i>
<i>Power Adapter #1</i>	<i>Input</i>	100-240VAC 50/60Hz 0.15A
	<i>Output</i>	12VDC, 0.5A,
	<i>Model</i>	WCF1200050A1BA
	<i>Brand name</i>	Mass power
<i>Power Adapter #2</i>	<i>Input</i>	100-240VAC 50/60Hz 0.2A
	<i>Output</i>	12VDC, 0.5A
	<i>Model</i>	UE06L8-120050SPAU
	<i>Brand name</i>	UE

NOTE: For more detailed informations or features please refer to user's manual of EUT.

Test Summary

The Electromagnetic Compatibility requirements on model HT503 for this test are stated below. All results listed in this report relate exclusively to this above-mentioned model as the Equipment under Test. This report confers no approval or endorsement upon any other component, host or subsystem used in the test set-up.

Emission Tests				
Specifications	Description	Test Results	Test Point	Remark
<i>FCC Part 15.107 ANSI C63.4 -2003</i>	<i>Conducted Emission</i>	<i>Passed</i>	<i>AC Input Port</i>	<i>Attachment 1</i>
<i>FCC Part 15.109 ANSI C63.4 -2003</i>	<i>Radiated Emission</i>	<i>Passed</i>	<i>Enclosure</i>	<i>Attachment 2</i>

Test Mode Justification

Pre-scan has been conducted to determine the worst-case modes from all possible combinations between available operation modes. IP call modes was chosen for the final test as described below.

IP Call mode:

Connected LAN port and FXS port of the EUT to an IP phone and a telephone by an RJ-45 cord and RJ-11 cord and established an call link between them, then connected PC port of the EUT to a notebook PC and ping “192.168.0.160 -t” to EUT and measured it.

EUT Exercise Software

No test software support this test.

Equipment Modification

Any modifications installed previous to testing by Grandstream Networks, INC., will be incorporated in each production model sold or leased in United States.

There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen). Test personnel.

EUT Sample Photos for model HT503




EUT- Front View




EUT- Rear View




EUT -I/O Ports View



EUT-Uncovered View



Main board- Top View



Main board- Bottom View



Power Adaptor #1 View (Manufacturer: Mass Power)



Power Adaptor #2 View (Manufacturer: UE power)

Test System Details


EUT			
Model Number:	<i>HT503</i>		
Model Tested:	<i>HT503</i>		
Description:	<i>Analog Telephone Adapter</i>		
Input:	<i>AC 120V/60Hz</i>		
Manufacturer:	<i>Grandstream Networks, INC</i>		
Support Equipment			
Description	Model Number	Serial Number	Manufacturer
<i>Notebook PC</i>	<i>ThinkPad X121e</i>	---	<i>Lenovo</i>
<i>Adapter Of Notebook PC</i>	<i>ThinkPad 57Y4614</i>	---	<i>Lenovo</i>
<i>Mouse</i>	<i>MO32B0</i>	<i>23-033131</i>	<i>IBM</i>
<i>Keyboard</i>	<i>SK-1788</i>	---	<i>Lenovo</i>
<i>Monitor</i>	<i>TFT1780PS</i>	<i>B8879HA021638</i>	<i>AOC</i>
<i>IP phone</i>	<i>GXP2100</i>	---	<i>Grandstream</i>
<i>Telephone</i>	<i>HCD129P/TSDL 2953</i>	---	<i>DAERXUN</i>

Continue on to next page...


<i>Cable Description</i>					
<i>Description</i>	<i>From</i>	<i>To</i>	<i>Length (Meters)</i>	<i>Shielded (Y/N)</i>	<i>Ferrite (Y/N)</i>
<i>Power Cord Of Notebook PC</i>	<i>Adapter</i>	<i>Notebook PC</i>	<i>1.6</i>	<i>N</i>	<i>Y</i>
	<i>Adapter</i>	<i>Plug</i>	<i>1.2</i>	<i>N</i>	<i>Y</i>
<i>Mouse cord</i>	<i>Mouse</i>	<i>Plug</i>	<i>1.2</i>	<i>N</i>	<i>Y</i>
<i>Keyboard cord</i>	<i>Keyboard</i>	<i>Plug</i>	<i>1.2</i>	<i>N</i>	<i>Y</i>
<i>VGA Cord</i>	<i>Monitor</i>	<i>PC</i>	<i>1.2</i>	<i>Y</i>	<i>Y</i>
<i>RJ-45 Cord #1</i>	<i>EUT</i>	<i>Notebook PC</i>	<i>1.5</i>	<i>N</i>	<i>N</i>
<i>RJ-45 Cord #2</i>	<i>EUT</i>	<i>IP Phone</i>	<i>>3.0</i>	<i>N</i>	<i>N</i>
<i>Power Adapter #1 cord of EUT</i>	<i>EUT</i>	<i>Plug</i>	<i>1.8</i>	<i>N</i>	<i>N</i>
<i>Power Adapter #2 cord of EUT</i>	<i>EUT</i>	<i>Plug</i>	<i>1.8</i>	<i>N</i>	<i>N</i>
<i>Note: The "EUT" means "Analog Telephone Adapter".</i>					

NOTE: The EUT has been tested as an independent unit together with other necessary accessories or support units. The above support units or accessories were used to form a representative test configuration during the test tests.


Configuration of Tested System




ATTACHMENT 1 - CONDUCTED EMISSION TEST RESULTS

CLIENT:	Grandstream Networks, INC	TEST STANDERD:	FCC Part 15, Subpart B, Section 15.107
MODEL NUMBERS:	HT503	PRODUCT:	Analog Telephone Adapter
MODEL TESTED:	HT503	EUT DESIGNATION:	Home or Office
TEMPERATURE:	23°C	HUMIDITY:	51%
ATM PRESSURE:	103kPa	GROUNDING:	None
TESTED BY:	Daomen	DATE OF TEST:	September 11 st , 2013
TEST REFERENCE:	ANSI C63.4 -2003		
TEST PROCEDURE:	The EUT was set up according to the guidelines of ANSI C63.4 -2003 for conducted emissions. The measurement was using a AMN on each line and an EMI receiver peak scan was made at the frequency measurement range. The six highest significant peaks were then marked, and these signals were then quasi-peaked and averaged. The frequency range investigated was from 150KHz to 30MHz.		
DESCRIPTION OF TEST MODE	IP Call mode		
TEST SET UP	<p>EUT & Support stand</p> 		
TESTED RANGE:	150kHz to 30MHz		
TEST VOLTAGE:	AC 120V/60Hz		
RESULTS:	The EUT meets the requirements of test reference for Conducted Emissions. The test results relate only to the equipment under test provided by client.		
Changes or Modifications:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen). test personnel.		
M. UNCERTAINTY:	Freq. $\pm 2 \times 10^{-7} \times$ Center Freq., Amp ± 2.6 dB		

Power Adaptor #1:(Mass power)




Line L Conducted Emission Graph




Line N Conducted Emission Graph

Power Adaptor #2:(UE power)



Line L Conducted Emission Graph



Line N Conducted Emission Graph

Test Data:**Power Adaptor #1(Mass power)**

Lines (L/N)	Frequency (MHz)	Corrected QP Level (dBuV)	Limits QP (dBuV)	Margin QP (dB)	Frequency (MHz)	Corrected AV Level (dBuV)	Limits AV (dBuV)	Margin QP (dB)
L	0.395	41.9	58	-16.1	0.395	34.3	48	-13.7
L	0.560	34.4	56	-21.6	0.560	22.3	46	-23.7
L	1.950	32.9	56	-23.1	1.950	18.7	46	-27.3
N	0.390	43.5	58.1	-14.6	0.390	38.6	48.1	-9.5
N	0.545	34.6	56	-21.4	0.545	22.5	46	-23.5
N	1.150	31.6	56	-24.4	1.150	17.4	46	-28.6

Note :

- 1) All readings are using a bandwidth of 9 kHz, with a 500 ms sweep time. A video filter was not use.
- 2) "QP" means "Quasi-Peak" values, "AV" means "Average" values.
- 3) The other reading are too low against official limits that are not be recorded.

Power Adaptor #2(UE power)

Lines (L/N)	Frequency (MHz)	Corrected QP Level (dBuV)	Limits QP (dBuV)	Margin QP (dB)	Frequency (MHz)	Corrected AV Level (dBuV)	Limits AV (dBuV)	Margin QP (dB)
L	0.150	43.6	66	-22.4	0.150	27.3	56	-28.7
L	0.360	37.3	58.7	-21.4	0.360	26.6	48.7	-22.1
L	0.730	30.0	56	-26	0.730	17.1	46	-28.9
N	0.160	45.7	65.5	-19.8	0.160	31.3	55.5	-24.2
N	0.355	45.3	58.8	-13.5	0.355	42.3	48.8	-6.5
N	0.485	35.3	56.3	-21	0.485	29.4	46.3	-16.9

Note :


- 1) All readings are using a bandwidth of 9 kHz, with a 500 ms sweep time. A video filter was not use.
- 2) "QP" means "Quasi-Peak" values, "AV" means "Average" values.
- 3) The other reading are too low against official limits that are not be recorded.

Test Equipment List:

<i>Test Equipment</i>	<i>Model No.</i>	<i>Manufacturer</i>	<i>Serial No.</i>	<i>Last Cal.</i>	<i>Cal. Interval</i>
Receiver	SMR4503	SCHAFFNER	11725	2013.07.08	2014.07.08
Line impedance stabilization network	4825/2	ETS	1161	2013.07.08	2014.07.08
<i>Note: All testing were performed using internationally recognized standards. All test instruments were calibrated.</i>					

TESTED BY: Saomen **GALANZ**
ENGINEER COMPANY NAME

REVIEWED BY: Jameym **ECMG**
SENIOR ENGINEER COMPANY NAME



Conducted Emission Test Set-up -front view



Conducted Emission Test Set-up -rear view

ATTACHMENT 2 – RADIATED EMISSION MEASUREMENT

CLIENT:	Grandstream Networks, INC	TEST STANDERD:	FCC Part 15,Subpart B, Section 15.109
MODEL NUMBERS:	HT503	PRODUCT:	Analog Telephone Adapter
EUT MODEL:	HT503	EUT DESIGNATION:	Home or Office
TEMPERATURE:	23°C	HUMIDITY:	49%RH
ATM PRESSURE:	103.0kPa	GROUNDING:	None
TESTED BY:	Daomen	DATE OF TEST:	September 11 st , 2013
TEST REFERENCE:	ANSI C63.4 -2003		
TEST PROCEDURE:	<p>The EUT was set up according to the guidelines of ANSI C63.4 -2003 for radiated emissions. An EMI receiver peak scan was made at the frequency measurement range (pre-scan) in an Anechoic chamber. signal discrimination was then performed and the significant peaks marked. these peaks were then quasi-peaked in the frequency range of 30 MHz to 1GHz and average and peak in the frequency range of 1 GHz to 5GHz at an anechoic chamber.</p> <p>The following data lists the significant emission frequencies, measured levels, correction factors (including cable and antenna correction factors), and the corrected readings against the limits. Explanation of the Correction Factor are given as follows:</p> <p>FS= RA + AF + CF - AG</p> <p>Where: FS = Field Strength</p> <p>RA = Receiver Amplitude</p> <p>AF = Antenna Factor</p> <p>CF = Cable Attenuation Factor</p> <p>AG = Amplifier Gain</p>		
TEST MODE	IP Call Mode		
TESTED RANGE:	9K-30MHz and 30MHz to 5GHz		
TEST VOLTAGE:	AC 120V/60Hz		
RESULTS:	The EUT meet the requirements of test reference for radiated emissions. The test results relate only to the equipment under test provided by client.		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen). Test personnel.		
M. UNCERTAINTY:	Freq. $\pm 2 \times 10^{-7}$ x Center Freq., Amp ± 2.6 dB		

Continue on to next page...

Frequency measured at 9KHz to 30MHz:




Figure 1 : Frequencies measured below 1 GHz configuration

TEST SET-UP:






Figure 2 : Frequencies measured above 1 GHz configuration




Power Adaptor #1(Mass power)




Radiated Filed Strength Emission Test Plot(9KHz-30MHz)

Power Adaptor #1(Mass power)




Horizontal: Radiated Emission Test Plot (30MHz-1000MHz)




Vertical: Radiated Emission Test Plot (30MHz-1000MHz)

Power Adaptor #2(UE power)



Horizontal: Radiated Emission Test Plot (30MHz-1000MHz)



Test Data:
IP Call mode/9KHz to 30MHz:

Test No. #:	Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Level QP (dBuV/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	/	/	/	/	/	/	/
2	/	/	/	/	/	/	/
3	/	/	/	/	/	/	/
4	/	/	/	/	/	/	/
5	/	/	/	/	/	/	/
6	/	/	/	/	/	/	/

Note:

1. The field strength is calculated by adding the antenna factor, cable factor. The basic equation with a sample calculation is as follows: Emission Level =Reading Level + Antenna Factor + Cable Loss.
2. For band in 9KHz to 30MHz, Pre-scan has been conducted to determine the worst-case from power apaptor #1 and apaptor #2. Apaptor #1 was selected for the final testing.
3. The limits shown are based on quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. the bandwidth of Test Receiver was set at 200Hz in frequency range of 9KHz to 150KHz, 9kHz in the frequency range of 150KHz to 30MHz.
4. All emission levels in the frequency range of 9KHz to 30MHz are 20dB below the official limits that are not reported.

FCC Test Report #: SHE-1308-11040-FCC

Prepared for Grandstream Networks, INC

Prepared by ECMG Electronic Technical Testing Corp (Shenzhen)

Page 24 of 31

Test Data:**Power Adaptor #1(Mass power):****IP Call Mode/Below 1GHz:**

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Preamp Factor (dB)	Reading Level QP (dBuV/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
Horizontal							
124.980	0.02	6.3	/	27.18	33.5	43.5	-10.0
175.020	0.02	7.8	/	23.68	31.5	43.5	-12.0
249.960	0.12	11.8	/	24.08	36.0	46	-10.0
375.000	0.16	13.8	/	28.74	42.7	46	-3.3
700.020	0.36	20.4	/	11.54	32.3	46	-13.7
750.000	0.39	21.1	/	12.51	34.0	46	-12.0
Vertical							
34.080	0.02	17.9	/	18.48	36.4	40	-3.6
77.220	0.02	5.3	/	26.08	31.4	40	-8.6
138.420	0.02	7.8	/	21.08	28.9	43.5	-14.6
375.000	0.16	13.8	/	26.14	40.1	46	-5.9
700.020	0.36	20.4	/	12.44	33.2	46	-12.8
951.240	0.44	24	/	-1.54	22.9	46	-23.1

Note:

1. All readings are quasi-peak unless stated otherwise, using a QPA bandwidth of 120kHz, with a 60 s sweep time. A video filter was not used.
2. The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Emission Level =Reading Level + Antenna Factor + Cable Loss -Preamplifier Factor.
3. The other emission levels are 20dB below the official limits that are not reported.

IP Call Mode/Above 1GHz:

Frequency (GHz)	Cable Loss (dB)	Antenna Factor (dB)	Preamp Factor (dB)	Reading Level (dBuV/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization (H/V)
Peak Measurement								
1.000	1.39	23.9	33.6	-3.63	55.26	74	-18.74	H
1.330	1.58	24.7	33.6	-6.72	53.16	74	-20.84	H
1.520	1.71	26.8	33.6	-11.39	50.72	74	-23.28	H
1.326	1.58	24.7	33.6	-8.76	51.12	74	-22.88	V
2.400	2.3	29.3	33	-15.89	48.71	74	-25.29	V
1.858	1.93	27.5	33.6	-7.4	55.63	74	-18.37	V
Average Measurement								
1.329	1.58	24.7	33.6	-22.68	37.20	54	-16.80	H
1.331	1.58	24.7	33.6	-24.75	35.13	54	-18.87	H
1.855	1.93	27.5	33.6	-26.03	37.00	54	-17.00	H
1.326	1.58	24.7	33.6	-21.59	38.29	54	-15.71	V
2.400	2.3	29.3	33	-31.5	33.10	54	-20.90	V
1.858	1.93	27.5	33.6	-30.92	32.11	54	-21.89	V

Note:

1. The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Emission Level =Reading Level + Antenna Factor + Cable Loss -Preamplifier Factor.
2. The limits shown are based on Peak value and Average value detector above 1GHz, the bandwidth of Test Receiver was set at 1MHz above 1GHz.
3. The other emission levels are 20dB below the official limits that are not reported.

Power Adaptor #2(UE power):

IP Call Mode/Below 1GHz:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Preamp Factor (dB)	Reading Level QP (dBuV/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
Horizontal							
30.720	0.02	16.7	/	12.48	29.2	40	-10.8
125.040	0.02	6.9	/	28.38	35.3	43.5	-8.2
175.040	0.02	7.8	/	22.58	30.4	43.5	-13.1
250.000	0.12	11.8	/	24.78	36.7	46	-9.3
374.960	0.16	13.7	/	26.04	39.9	46	-6.1
954.240	0.44	24	/	9.16	33.6	46	-12.4
Vertical							
34.080	0.02	17.9	/	19.58	37.5	40	-2.5
43.520	0.02	13.9	/	12.78	26.7	40	-13.3
77.200	0.02	5.3	/	26.28	31.6	40	-8.4
250.000	0.12	11.8	/	18.18	30.1	46	-15.9
374.960	0.16	13.7	/	26.34	40.2	46	-5.8
750.000	0.39	21.1	/	15.91	37.4	46	-8.6

Note:

1. All readings are quasi-peak unless stated otherwise, using a QPA bandwidth of 120kHz, with a 60 s sweep time. A video filter was not used.
2. The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Emission Level =Reading Level + Antenna Factor + Cable Loss -Preamplifier Factor.
3. The other emission levels are 20dB below the official limits that are not reported.

IP Call Mode/Above 1GHz:

Frequency (GHz)	Cable Loss (dB)	Antenna Factor (dB)	Preamp Factor (dB)	Reading Level (dBuV/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization (H/V)
Peak Measurement								
1.000	1.39	23.9	33.6	-2.09	56.80	74	-17.20	H
1.330	1.58	24.7	33.6	-4.67	55.21	74	-18.79	H
1.520	1.71	26.8	33.6	-4.94	57.17	74	-16.83	H
1.326	1.58	24.7	33.6	-5.99	53.89	74	-20.11	V
2.400	2.3	29.3	33	-14.47	50.13	74	-23.87	V
1.858	1.93	27.5	33.6	-10.26	52.77	74	-21.23	V
Average Measurement								
1.329	1.58	24.7	33.6	-24.19	35.69	54	-18.31	H
1.331	1.58	24.7	33.6	-23.16	36.72	54	-17.28	H
1.855	1.93	27.5	33.6	-29.82	33.21	54	-20.79	H
1.326	1.58	24.7	33.6	-24.22	35.66	54	-18.34	V
2.400	2.3	29.3	33	-31.85	32.75	54	-21.25	V
1.858	1.93	27.5	33.6	-26.93	36.10	54	-17.90	V

Note:

1. The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Emission Level =Reading Level + Antenna Factor + Cable Loss -Preamplifier Factor.
2. The limits shown are based on Peak value and Average value detector above 1GHz, the bandwidth of Test Receiver was set at 1MHz above 1GHz.
3. The other emission levels are 20dB below the official limits that are not reported.

Test Equipment List:

Test Equipment	Model No.	Manufacturer	Serial No.	Last Cal.	Cal. Due
Receiver	SMR4503	SCHAFFNER	11725	2013.07.08	2014.07.07
HF Loop Antenna	HLA6120	TESEQ	26348	2013.09.27	2014.09.26
Double-ridged Wave guide horn	3115	ETS	6587	2013.08.02	2014.08.01
Microwave system amplifier	83017A	Agilent	MY39500438	2013.07.11	2014.07.10
Biconilog Antenna	3142C	ETS	00042672	2013.09.28	2014.09.27
Band-pass Filter	BRM50702	Micro-Tronic	S/N-030	2012.11.30	2013.11.29
Spectrum Analyzer	FSP30	R&S	100755	2012.11.30	2013.11.29
<i>Note: All testing were performed using internationally recognized standards. All test instruments were calibrated.</i>					

TESTED BY: Daomen GALANZ
COMPANY NAME
ENGINEER

REVIEWED BY: Jameymm ECMG
COMPANY NAME
SENIOR ENGINEER



Radiated Emission Test Set-up (9KHz-30MHz)



Radiated Emission Test Set-up (Below 1GHz)



Radiated Emission Test Set-up (Above 1GHz)