



TEST REPORT

Certificate #4312.01

Product Name: Cordless Wi-Fi IP Phone
Trade Mark: GRANDSTREAM
Model No. / HVIN: WP825
Report Number: 210913008RFC-4
Test Standards: FCC 47 CFR Part 15 Subpart E
 RSS-247 Issue 2
 RSS-Gen Issue 5
FCC ID: YZZWP825
IC: 11964A-WP825
Test Result: PASS
Date of Issue: November 12, 2021

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and
technology park, Longhua district, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:



Henry Lu
 Team Leader

Reviewed by:



Kevin Liang
 Assistant Manager

Approved by:



Billy Li
 Technical Director

Date:

November 12, 2021

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Version

Version No.	Date	Description
V1.0	November 12, 2021	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	5
1.4 OTHER INFORMATION	6
1.5 DESCRIPTION OF SUPPORT UNITS	6
1.6 TEST LOCATION	7
1.7 TEST FACILITY	7
1.8 DEVIATION FROM STANDARDS	7
1.9 ABNORMALITIES FROM STANDARD CONDITIONS	7
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
1.11 MEASUREMENT UNCERTAINTY	8
2. TEST SUMMARY	9
3. EQUIPMENT LIST	10
4. TEST CONFIGURATION	11
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	11
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	11
4.1.2 RECORD OF NORMAL ENVIRONMENT	11
4.2 TEST CHANNELS	12
4.3 EUT TEST STATUS	12
4.4 PRE-SCAN	13
4.5 TEST SETUP	14
4.5.1 FOR RADIATED EMISSIONS TEST SETUP	14
4.5.2 FOR CONDUCTED EMISSIONS TEST SETUP	15
4.5.3 FOR CONDUCTED RF TEST SETUP	16
4.6 SYSTEM TEST CONFIGURATION	17
4.7 DUTY CYCLE	18
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION	22
5.1 REFERENCE DOCUMENTS FOR TESTING	22
5.2 ANTENNA REQUIREMENT	22
5.3 26 dB BANDWIDTH & OCCUPIED BANDWIDTH	23
5.4 6 dB BANDWIDTH & OCCUPIED BANDWIDTH	34
5.5 MAXIMUM CONDUCTED OUTPUT POWER OR E.I.R.P	42
5.6 PEAK POWER SPECTRAL DENSITY	50
5.7 RADIATED EMISSIONS AND BAND EDGE MEASUREMENT	67
5.8 DYNAMIC FREQUENCY SELECTION	107
5.9 AC POWER LINE CONDUCTED EMISSION	117
APPENDIX 1 PHOTOS OF TEST SETUP	120
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	120

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	Cordless Wi-Fi IP Phone		
Model No. / HVIN:	WP825		
Trade Mark:	GRANDSTREAM		
DUT Stage:	Identical Prototype		
EUT Supports Function:	2.4 GHz ISM Band:	IEEE 802.11b/g/n	
		Bluetooth 5.0	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac
		5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac
Sample Received Date:	September 14, 2021		
Sample Tested Date:	September 14, 2021 to October 20, 2021		

1.2.2 Description of Accessories

Adapter(1)	
Model No.:	DSA-6PFG-05 FUS 050100
Input:	100-240 V~50/60 Hz 0.2 A
Output:	5.0 V $\equiv$ 1.0 A 5.0W
DC Cable:	1.5 Meter, Unshielded without ferrite

Adapter(2)	
Model No.:	GQ06-050100-ZU
Input:	100-240 V~50/60 Hz 0.3 A Max
Output:	5.0 V $\equiv$ 1.0 A
DC Cable:	1.5 Meter, Unshielded without ferrite

Adapter(3)	
Model No.:	NBS05B050100VU
Input:	100-240 V~50/60 Hz 0.2 A
Output:	5.0 V $\equiv$ 1.0 A
DC Cable:	1.5 Meter, Unshielded without ferrite

Battery	
Model No.:	GS-02
Battery Type:	Lithium-ion
Rated Voltage:	3.7 Vdc
Limited Charge Voltage:	4.2 Vdc

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Rated Capacity:	2000 mAh
------------------------	----------

Others
Charging base+ Back Scaffold

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Bands:	5150 MHz to 5250 MHz (U-NII-1)
	5250 MHz to 5350 MHz (U-NII-2A)
	5470 MHz to 5725 MHz (U-NII-2C)
	5 725 MHz to 5 850 MHz (U-NII-3)
Frequency Ranges:	5180 MHz to 5240 MHz
	5260 MHz to 5320 MHz
	5500 MHz to 5700 MHz
	5 745 MHz to 5 825 MHz
Support Standards:	IEEE 802.11a/n/ac
TPC Function:	Not Support
DFS Operational mode:	Slave without radar Interference detection function
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20: 20 MHz
	IEEE 802.11n-HT40/ac-VHT40: 40 MHz
	IEEE 802.11ac-VHT80: 80 MHz
Data Rate:	IEEE 802.11a: Up to 54 Mbps
	IEEE 802.11n-HT20: Up to MCS7
	IEEE 802.11n-HT40: Up to MCS7
	IEEE 802.11ac-VHT20: Up to MCS8
	IEEE 802.11ac-VHT40: Up to MCS9
	IEEE 802.11ac-VHT80: Up to MCS9
Number of Channels:	5150 MHz to 5250 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11acVHT80
	5250 MHz to 5350 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11acVHT80
	5470 MHz to 5725 MHz: 11 for IEEE 802.11a/n-HT20/ac-VHT20 5 for IEEE 802.11n-HT40/ac-VHT40 2 for IEEE 802.11ac-VHT80
	5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11ac-VHT80
Antenna Type:	Dipole Antenna
Antenna Gain:	5150 MHz to 5250 MHz: 4.0 dBi
	5250 MHz to 5350 MHz: 4.0 dBi

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Maximum EIRP (dBm):	5470 MHz to 5725 MHz: 4.0 dBi				
	5725 MHz to 5850 MHz: 4.0 dBi				
	Chain 0	U-NII-1			
	IEEE 802.11a:	18.37			
	IEEE 802.11n-HT20:	18.07			
	IEEE 802.11n-HT40:	17.75			
	IEEE 802.11ac-VHT20:	18.14			
	IEEE 802.11ac-VHT40:	17.76			
Maximum conducted output power (dBm):		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	14.37	13.96	14.15	13.32
	IEEE 802.11n-HT20:	14.07	13.82	14.23	13.54
	IEEE 802.11n-HT40:	13.75	14.26	12.96	12.81
	IEEE 802.11ac-VHT20	14.14	13.82	12.93	13.33
	IEEE 802.11ac-VHT40	13.76	13.58	13.04	13.10
	IEEE 802.11ac-VHT80:	13.23	13.23	12.62	14.58
Normal Test Voltage:		3.7Vdc			

1.4 OTHER INFORMATION

Operation Frequency Each of Channel				
	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
IEEE 802.11a, IEEE 802.11n-HT20, IEEE 802.11ac-VHT20	$f = 5000 + 5k, k = 32 + 4n$			$f = 5000 + 5k,$ $k = 145 + 4n$
	$n = 1, \dots, 4$	$n = 5, \dots, 8$	$n = 17, \dots, 27$	$n = 1, \dots, 5$
IEEE 802.11n-HT40, IEEE 802.11ac-VHT40	$f = 5000 + 5k, k = 30 + 8n$			$f = 5000 + 5k,$ $k = 143 + 8n$
	$n = 1, 2$	$n = 1, \dots, 5$	$n = 9, \dots, 13$	$n = 1, 2$
IEEE 802.11ac-VHT80	$f = 5000 + 5k, k = 26 + 16n$			$f = 5000 + 5k,$ $k = 155$
	$n = 1$	$n = 1, 2$	$n = 5, 6$	
Note: f is the operating frequency (MHz); k is the operating channel.				

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	FCC ID	Supplied by
Notebook	Lenovo	B40-80	MP12NEQ6	N/A	UnionTrust
Mouse	DELL	MS111	CN-011D3V-738	N/A	UnionTrust
Wireless Home Router	SAGEMCOM	FAST5280	N/A	VW3FAST5280	UnionTrust
Key-Press Attenuator	Huaxin	KT2.5-90/1S-2S	N/A	N/A	UnionTrust
4 Way Divider	WOKEN	0120A040560002D	N/A	N/A	UnionTrust

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.1Meter	Applicant

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.9 dB
5	Radiated emission 1GHz-18GHz	± 4.8 dB
6	Radiated emission 18GHz-26GHz	± 5.1 dB
7	Radiated emission 26GHz-40GHz	± 5.1 dB
8	Conducted spurious emissions	± 2.7 dB
9	RF Power, Conducted	± 0.9 dB
10	Occupied Bandwidth	± 1.86 %
11	Radio Frequency	2.4 GHz: ± 6.5 x 10 ⁻⁸
12	Transmission Time	± 0.19 %

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart E Test Cases			
Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203 FCC 47 CFR Part 15 Subpart E Section 15.407(a)(1) (2) RSS-Gen Issue 5, Section 6.8	N/A	PASS
26 dB emission bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(2)(5) RSS-247 Issue 2 Section 6.2.1.2	KDB 789033 D02 v02r01 Section C.1	PASS
6 dB bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (e) RSS-247 Issue 2 Section 6.2.4.1	KDB 789033 D02 v02r01 Section C.2	PASS
Occupied Bandwidth	RSS-Gen Issue 5, Section 6.7	RSS-Gen Issue 5, section 6.7	PASS
Maximum conducted output power	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3) RSS-247 Issue 2 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1	KDB 789033 D02 v02r01 Section E.3.a (Method PM)	PASS
Peak Power Spectral Density	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3) RSS-247 Issue 2 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1	KDB 789033 D02 v02r01 Section F	PASS
Radiated Emissions and Band Edge Measurement	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(1)(2)(3)(4)(6) FCC 47 CFR Part 15 Subpart C Section 15.209/205 RSS-247 Issue 2 Section 6.2.1.2/6.2.2.2/6.2.3.2/6.2.4.2	KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6	PASS
Dynamic Frequency Selection	FCC 47 CFR Part 15 Subpart E Section 15.407 (h) RSS-247 Issue 2 Section 6.3	KDB 905462 D03 Client Without DFS New Rules v01r02	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(6) FCC 47 CFR Part 15 Subpart C Section 15.207 RSS-Gen Issue 5, Section 8.8	ANSI C63.10-2013, Section 6.2.	PASS
Note: 1) N/A: In this whole report not applicable.			

For Dynamic Frequency Selection

Test Case	Result
Channel Availability Check Time	N/A ¹
U-NII Detection Bandwidth	N/A ¹
Channel Closing Transmission Time	PASS
Channel Move Time	PASS
DFS Detection Threshold	N/A ¹
Non- Occupancy Period	N/A ¹
Note: 1) The EUT is slave, NA In this whole report not applicable.	

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	3m SAC	ETS-LINDGREN	3m	N/A	Jan. 22, 2021	Jan. 21, 2024
☒	Receiver	R&S	ESIB26	100114	Nov. 18, 2020	Nov. 17, 2021
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Apr. 22, 2021	Apr. 21, 2022
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	Nov. 14, 2020	Nov. 13, 2021
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Nov. 14, 2020	Nov. 13, 2021
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	Nov. 14, 2020	Nov.13, 2021
☒	Preamplifier	HP	8447F	2805A02960	Nov. 10, 2020	Nov. 9, 2021
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201541	Apr. 30, 2021	Apr. 29, 2023
☒	Pre-amplifier	ETS-Lindgren	00118385	00201874	Nov. 10, 2020	Nov. 9, 2021
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Nov. 14, 2020	Nov. 13, 2022
☒	Pre-amplifier	ETS-Lindgren	00118384	00202652	Nov. 17, 2020	Nov. 16, 2022
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☐	Band Rejection Filter (2400MHz~2500MHz)	Micro-Tronics	BRM50702	G248	Nov. 16, 2020	Nov. 15, 2021
☒	Band Rejection Filter (5150MHz~5880MHz)	Micro-Tronics	BRM50716	G186	Nov. 16, 2020	Nov. 15, 2021
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	Receiver	R&S	ESR7	1316.3003K07-101181-K3	Nov. 18, 2020	Nov.17, 2021
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	Nov. 18, 2020	Nov.17, 2021
☒	LISN	R&S	ESH2-Z5	860014/024	Nov. 18, 2020	Nov.17, 2021
☒	LISN	ETS-Lindgren	3816/2SH	00201088	Nov. 18, 2020	Nov.17, 2021
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted RF test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Apr. 22, 2021	Apr. 21, 2022
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	Nov. 10, 2020	Nov. 9, 2021
☐	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430023	Nov. 10, 2020	Nov. 9, 2021
☒	MXG X-Series RF Vector Signal Generator	KEYSIGHT	N5182B	MY51350267	Nov. 10, 2020	Nov. 9, 2021

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	3.7	20 to 75
Remark:			
1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Tested by
26 dB emission bandwidth	23.4	51	99.80	Bert Xiong
6 dB bandwidth				
Occupied Bandwidth				
Maximum conducted output power				
Peak Power Spectral Density				
Dynamic Frequency Selection	24.5	46	100.02	Fire Huo
Radiated Emissions and Band Edge Measurement				
AC Power Line Conducted Emission	22.6	53	101.2	Niko Su

4.2 TEST CHANNELS

Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11a IEEE 802.11n-HT20 IEEE 802.11ac-VHT20	5150 MHz to 5250 MHz	Channel 36	Channel 44	Channel 48
		5180 MHz	5220 MHz	5240 MHz
	5250 MHz to 5350 MHz	Channel 52	Channel 60	Channel 64
		5260 MHz	5300 MHz	5320 MHz
	5470 MHz to 5725 MHz	Channel 100	Channel 116	Channel 140
		5500 MHz	5580 MHz	5700 MHz
	5725 MHz to 5850 MHz	Channel 149	Channel 157	Channel 165
		5745 MHz	5785 MHz	5825 MHz
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40	5150 MHz to 5250 MHz	Channel 38	--	Channel 46
		5190 MHz	--	5230 MHz
	5250 MHz to 5350 MHz	Channel 54	--	Channel 62
		5270 MHz	--	5310 MHz
	5470 MHz to 5725 MHz	Channel 102	Channel 110	Channel 134
		5510 MHz	5550 MHz	5670 MHz
	5725 MHz to 5850 MHz	Channel 151	--	Channel 159
		5755 MHz	--	5795 MHz
IEEE 802.11ac-VHT80	5150 MHz to 5250 MHz	--	Channel 42	--
		--	5210 MHz	--
	5250 MHz to 5350 MHz	--	Channel 58	--
		--	5290 MHz	--
	5470 MHz to 5725 MHz	Channel 106	--	--
		5530 MHz	--	--
	5725 MHz to 5850 MHz	--	Channel 155	--
		--	5775 MHz	--

4.3 EUT TEST STATUS

Mode	Tx/Rx Function	Description
IEEE 802.11a/n/ac	1Tx/1Rx	1. Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

Power Setting				
	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
IEEE 802.11a	13	13	13	13
IEEE 802.11n-HT20	13	13	13	13
IEEE 802.11n-HT40	13	13	13	13
IEEE 802.11ac-VHT20	13	13	13	13
IEEE 802.11ac-VHT40	13	13	13	13
IEEE 802.11ac-VHT80	13	13	12	13

Test Software
Test software name: Putty commands;

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

4.4 PRE-SCAN

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate. Following data rate was (were) selected for the final test as listed below

Mode	Worst-case data rates
IEEE 802.11a	6 Mbps
IEEE 802.11n-HT20	MCS0
IEEE 802.11n-HT40	MCS0
IEEE 802.11ac-VHT20	MCS0
IEEE 802.11ac-VHT40	MCS0
IEEE 802.11ac-VHT80	MCS0

4.5 TEST SETUP

4.5.1 For Radiated Emissions test setup

Figure 1. Below 30MHz







Figure 2. 30MHz to 1GHz






4.5.2 For Conducted Emissions test setup



4.5.3 For Conducted RF test setup



4.6 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.7 DUTY CYCLE

Test Procedure: ANSI C63.10-2013 Clause 12.2.


Test Results

Mode	Data rates (Mbps)	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)	Average Factor (dB)
IEEE 802.11a	6	1.395	1.435	0.97	97.21	0.12	0.72	-0.25
IEEE 802.11n-HT20	MCS0	1.310	1.350	0.97	97.04	0.13	0.76	-0.26
IEEE 802.11n-HT40	MCS0	0.657	0.699	0.94	93.99	0.27	1.52	-0.54
IEEE 802.11ac-VHT20	MCS0	1.315	1.360	0.97	96.69	0.15	0.76	-0.29
IEEE 802.11ac-VHT40	MCS0	0.654	0.696	0.94	93.97	0.27	1.53	-0.54
IEEE 802.11ac-VHT80	MCS0	0.324	0.366	0.89	88.52	0.53	3.09	-1.06

Remark:

- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor = $10 * \log(1/ \text{Duty cycle})$;
- 3) Average factor = $20 \log_{10} \text{Duty Cycle}$.

The test plots as follows



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China



Tel: +86-755-28230888



Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1







Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	RSS-247 Issue 2	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
4	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
5	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
6	KDB 789033 D02 General UNII Test Procedures New Rules v02r01	Guidelines for compliance testing of unlicensed national information infrastructure (U-NII) device part 15, subpart E
7	KDB 905462 D06 802.11 Channel Plans New Rules v02	Operation in U-NII bands -802.11 channel PLAN(\$15.407)
8	KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02	Compliance measurement procedures for Unlicensed –National Information Infrastructure devices operates in the frequency bands 5250 MHz to 5350 MHz and 5470 MHz to 5725 MHz bands incorporating dynamic frequency selection
9	KDB 905462 D03 Client Without DFS New Rules v01r02	U-NII client devices without radar detection capability
10	KDB 662911 D01 Multiple Transmitter Output v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.407(a)(1) (2) requirement: The conducted output power limit specified in paragraph (a) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (a) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power and the peak power spectral density shall be reduced by the by the amount in dB that the directional gain of the antenna exceeds 6 dBi. RSS-Gen Issue 5, Section 6.8 requirement: According to RSS-Gen Issue 5, Section 6.8, a transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns. EUT Antenna: Antenna in the interior of the equipment and no consideration of replacement. The gain of the antenna is 4.0 dBi.

5.326 DB BANDWIDTH & OCCUPIED BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(2)(5)
RSS-247 Issue 2 Section 6.2.1.2

Test Method: KDB 789033 D02 v02r01 Section C.1

Limit: None; for reporting purposes only.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum analyzer.

Spectrum analyzer according to the following Settings:

- Set RBW = approximately 1 % of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Results: Pass

Mode	Channel	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)
IEEE 802.11a	36 (5180)	20.94	16.733
	44 (5220)	20.89	16.680
	48 (5240)	21.08	16.664
	52 (5260)	21.17	16.862
	60 (5300)	20.88	16.737
	64 (5320)	21.16	16.762
	100 (5500)	21.05	16.715
	116 (5580)	21.20	16.764
	140 (5700)	21.03	16.722
IEEE 802.11n-HT20	36 (5180)	21.42	17.875
	44 (5220)	21.49	17.796
	48 (5240)	21.36	17.833
	52 (5260)	21.24	17.769
	60 (5300)	20.87	17.760
	64 (5320)	21.45	17.843
	100 (5500)	21.27	17.752
	116 (5580)	21.62	17.828
	140 (5700)	21.21	17.778
IEEE 802.11n-HT40	38 (5190)	45.69	36.128
	46 (5230)	40.46	36.107
	54 (5270)	39.70	36.089
	62 (5310)	48.54	36.120
	102 (5510)	39.37	36.100
	110 (5550)	38.59	36.048
	134 (5670)	39.29	36.153

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>


UTTR-RF-RSS247-V1.1



Mode	Channel	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)
IEEE 802.11ac-VHT20	36 (5180)	21.31	17.792
	44 (5220)	21.19	17.806
	48 (5240)	21.38	17.775
	52 (5260)	21.26	17.850
	60 (5300)	22.37	17.800
	64 (5320)	21.19	17.746
	100 (5500)	21.26	17.865
	116 (5580)	21.17	17.811
	140 (5700)	21.49	17.883
IEEE 802.11ac-VHT40	38 (5190)	39.30	36.073
	46 (5230)	46.31	36.149
	54 (5270)	41.92	36.124
	62 (5310)	44.74	36.105
	102 (5510)	39.90	36.172
	110 (5550)	38.30	35.972
	134 (5670)	39.52	36.068
	42 (5230)	80.69	75.127
IEEE 802.11ac-VHT80	58 (5290)	81.47	75.350
	106 (5530)	81.11	75.315

The test plots as follows:






















5.46 DB BANDWIDTH & OCCUPIED BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (e)
RSS-247 Issue 2 Section 6.2.4.1

Test Method: KDB 789033 D02 v02r01 Section C.2

Limit: Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum Analyzer.

Spectrum analyzer according to the following Settings:

6dB Bandwidth

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 * \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

- a) Set RBW = 1% to 5% of the occupied bandwidth
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode


Test Results: Pass


Test Data:



Mode	Channel/ Frequency (MHz)	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limit	Pass / Fail
IEEE 802.11a	149 (5745)	15.79	16.708	> 500 kHz	Pass
	157 (5785)	16.33	16.800	> 500 kHz	Pass
	165 (5825)	15.79	16.864	> 500 kHz	Pass
IEEE 802.11n-HT20	149 (5745)	15.82	17.821	> 500 kHz	Pass
	157 (5785)	15.55	17.866	> 500 kHz	Pass
	165 (5825)	14.89	17.825	> 500 kHz	Pass
IEEE 802.11n-HT40	151 (5755)	35.08	36.169	> 500 kHz	Pass
	159 (5795)	34.32	36.299	> 500 kHz	Pass
IEEE 802.11ac-VHT20	149 (5745)	15.14	17.875	> 500 kHz	Pass
	157 (5785)	15.23	17.830	> 500 kHz	Pass
	165 (5825)	14.98	17.896	> 500 kHz	Pass
IEEE 802.11ac-VHT40	151 (5755)	35.30	36.246	> 500 kHz	Pass
	159 (5795)	35.25	36.330	> 500 kHz	Pass
IEEE 802.11ac-VHT80	155 (5775)	75.43	75.517	> 500 kHz	Pass

The test plots as follows:


6 dB Bandwidth










Occupied Bandwidth







5.5 MAXIMUM CONDUCTED OUTPUT POWER OR E.I.R.P

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3)
RSS-247 Issue 2 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1

Test Method: KDB 789033 D02 v02r01 Section E.3.a (Method PM)

Limits: FCC 47 CFR Part 15 Subpart E

1. For the band 5.15-5.25 GHz.
 - (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
 - (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
 - (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
 - (iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Limits: RSS-247 Issue 2

1. Frequency band 5150-5250 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

2. Frequency band 5250-5350 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

- a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;
- b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less, B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

Additional requirements

In addition to the above requirements, devices shall comply with the following, where applicable:

- a) Outdoor fixed devices with a maximum e.i.r.p. greater than 200 mW shall comply with the following e.i.r.p. at different elevations, where θ is the angle above the local horizontal plane (of the Earth) as shown below:

i. -13 dBW/MHz	for $0^\circ \leq \theta < 8^\circ$
ii. $-13 - 0.716 (\theta - 8)$ dBW/MHz	for $8^\circ \leq \theta < 40^\circ$
iii. $-35.9 - 1.22 (\theta - 40)$ dBW/MHz	for $40^\circ \leq \theta \leq 45^\circ$
iv. -42 dBW/MHz	for $\theta > 45^\circ$

The measurement procedure defined in Annex A of this document shall be used to verify the compliance to the e.i.r.p. at different elevations.

- b) Devices, other than outdoor fixed devices, having an e.i.r.p. greater than 200 mW shall comply with either i. or ii. below:
 - i. devices shall comply with the e.i.r.p. elevation mask in 6.2.2.3(a); or
 - ii. devices shall implement a method to permanently reduce their e.i.r.p. via a firmware feature in the event that the Department requires it. The test report must demonstrate how the device's power table can be updated to meet this firmware requirement. The manufacturer shall provide this firmware to update all systems automatically in compliance with the directions received from the Department.

3. Frequency bands 5470-5600 MHz and 5650-5725 MHz

The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

4. Frequency band 5725-5850 MHz

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices

operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint³ systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

Test Procedure:

1. Connected the EUT's antenna port to measure device by 10dB attenuator.
2. Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of Tx on burst.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Directional gain and the maximum output power limit.
RSS-247 Issue 2

Frequency Band	Antenna Gain (dBi)	Power Limits (dBm)
U-NII-1	4.0	23.00
U-NII-2A	4.0	24.00
U-NII-2C	4.0	24.00
U-NII-3	4.0	30.00

FCC 47 CFR Part 15 Subpart E

Frequency Band	Antenna Gain (dBi)	Power Limits (dBm)
U-NII-1	4.0	24.00
U-NII-2A	4.0	24.00
U-NII-2C	4.0	24.00
U-NII-3	4.0	30.00

Frequency band 5150-5250 MHz

RSS-247 Issue 2:

For IEEE 802.11a, the minimum 99% emission bandwidth is 16.664MHz

$10 \text{ dBm} + 10\log_{10}(16.664) = 22.22 \text{ dBm} < 23 \text{ dBm}$

So the 22.22 dB limit applicable

For IEEE 802.11n-HT20/ ac-VHT20, the minimum 99% emission bandwidth is 17.775 MHz

$10 \text{ dBm} + 10\log_{10}(17.775) = 22.50 \text{ dBm} < 23 \text{ dBm}$

So the 22.50 dB limit applicable

For IEEE 802.11n-HT40/ ac-VHT40/ ac-VHT80, the minimum 99% emission bandwidth is 36.073 MHz

$10 \text{ dBm} + 10\log_{10}(36.073) = 25.57 \text{ dBm} > 23 \text{ dBm}$

So the 23 dB limit applicable

Mode	Channel/ Frequency (MHz)	Maximum e.i.r.p (dBm)	Limit (dBm)	Pass / Fail
IEEE 802.11a	36 (5180)	18.37	22.22	Pass
	44 (5220)	18.31	22.22	Pass
	48 (5240)	18.29	22.22	Pass
IEEE 802.11n-HT20	36 (5180)	18.07	22.50	Pass
	44 (5220)	17.84	22.50	Pass
	48 (5240)	17.89	22.50	Pass
IEEE 802.11n-HT40	38 (5190)	17.75	23	Pass
	46 (5230)	17.40	23	Pass
IEEE 802.11ac-VHT20	36 (5180)	18.14	22.50	Pass
	44 (5220)	18.01	22.50	Pass
	48 (5240)	17.83	22.50	Pass
IEEE 802.11ac-VHT40	38 (5190)	17.76	23	Pass
	46 (5230)	17.39	23	Pass
IEEE 802.11ac-VHT80	42 (5210)	17.23	23	Pass

Remark:

- Maximum e.i.r.p = Maximum conducted output power + Antenna Gain

FCC 47 CFR Part 15 Subpart E:

Mode	Channel/ Frequency (MHz)	Maximum conducted output power (dBm)		Limit (dBm)	Pass / Fail
		Meas Power	Corr'd Power		
IEEE 802.11a	36 (5180)	14.25	14.37	24	Pass
	44 (5220)	14.19	14.31	24	Pass
	48 (5240)	14.17	14.29	24	Pass
IEEE 802.11n-HT20	36 (5180)	13.94	14.07	24	Pass
	44 (5220)	13.71	13.84	24	Pass
	48 (5240)	13.76	13.89	24	Pass
IEEE 802.11n-HT40	38 (5190)	13.48	13.75	24	Pass
	46 (5230)	13.13	13.40	24	Pass
IEEE 802.11ac-VHT20	36 (5180)	13.99	14.14	24	Pass
	44 (5220)	13.86	14.01	24	Pass
	48 (5240)	13.68	13.83	24	Pass
IEEE 802.11ac-VHT40	38 (5190)	13.49	13.76	24	Pass
	46 (5230)	13.12	13.39	24	Pass
IEEE 802.11ac-VHT80	42 (5210)	12.70	13.23	24	Pass

Remark:

1. Corr'd Power = Meas Power + Duty Cycle Factor

Frequency band 5250-5350 MHz

RSS-247 Issue 2:

For IEEE 802.11 a, the minimum 99% emission bandwidth is 16.737 MHz

$$11 \text{ dBm} + 10\log_{10}(16.737) = 23.24 \text{ dBm} < 24\text{dBm}$$

So the 23.24 dB limit applicable

For IEEE 802.11n-HT20/ ac-VHT20, the minimum 99% emission bandwidth is 17.746 MHz

$$11 \text{ dBm} + 10\log_{10}(17.746) = 23.49 \text{ dBm} < 24\text{dBm}$$

So the 23.49 dB limit applicable

For IEEE 802.11 n-HT40/ac-VHT40/ac-VHT80, the minimum 99% emission bandwidth is 36.089 MHz

$$11 \text{ dBm} + 10\log_{10}(36.089) = 26.57 \text{ dBm} > 24 \text{ dBm (200mW)}$$

So the 24 dB limit applicable

FCC 47 CFR Part 15 Subpart E:

For IEEE 802.11 a/n/ac, the minimum 26 dB emission bandwidth is 20.87 MHz

$$11 \text{ dBm} + 10\log_{10}(20.87) = 24.20 \text{ dBm} > 24 \text{ dBm (200mW)}$$

So the 24 dB limit applicable

Mode	Channel/ Frequency (MHz)	Maximum conducted output power (dBm)		Limit (dBm)		Pass / Fail
		Meas Power	Corr'd Power	FCC Part 15E	RSS-247	
IEEE 802.11a	52 (5260)	13.84	13.96	24	23.24	Pass
	60 (5300)	13.78	13.90	24	23.24	Pass
	64 (5320)	13.81	13.93	24	23.24	Pass
IEEE 802.11n-HT20	52 (5260)	13.69	13.82	24	23.49	Pass
	60 (5300)	13.50	13.63	24	23.49	Pass
	64 (5320)	13.64	13.77	24	23.49	Pass
IEEE 802.11n-HT40	54 (5270)	13.99	14.26	24	24	Pass
	62 (5310)	13.13	13.40	24	24	Pass
IEEE 802.11ac-VHT20	52 (5260)	13.52	13.67	24	23.49	Pass
	60 (5300)	13.58	13.73	24	23.49	Pass
	64 (5320)	13.67	13.82	24	23.49	Pass
IEEE 802.11ac-VHT40	54 (5270)	13.31	13.58	24	24	Pass
	62 (5310)	13.06	13.33	24	24	Pass
IEEE 802.11ac-VHT80	58 (5290)	12.73	13.26	24	24	Pass

Remark:

- Maximum conducted output power = Conducted output power + Duty Cycle Factor

Frequency bands 5470-5725 MHz (RSS-247 Issue 2 Not including 5600-5650 MHz)

RSS-247 Issue 2:

For IEEE 802.11 a, the minimum 99% emission bandwidth is 16.715 MHz

$$11 \text{ dBm} + 10\log_{10}(16.715) = 23.23 \text{ dBm} < 24 \text{ dBm}$$

So the 23.23 dB limit applicable

For IEEE 802.11n-HT20/ac-VHT20, the minimum 99% emission bandwidth is 17.752 MHz

$$11 \text{ dBm} + 10\log_{10}(17.752) = 23.49 \text{ dBm} < 24 \text{ dBm}$$

So the 23.49 dB limit applicable

For IEEE 802.11 n-HT40/ac-VHT40/ac-VHT80, the minimum 99% emission bandwidth is 35.972 MHz

$$11 \text{ dBm} + 10\log_{10}(35.972) = 26.56 \text{ dBm} > 24 \text{ dBm}$$

So the 24 dB limit applicable

FCC 47 CFR Part 15 Subpart E:

For IEEE 802.11 a/n/ac, the minimum 26 dB emission bandwidth is 21.03 MHz

$$11 \text{ dBm} + 10\log_{10}(21.03) = 24.23 \text{ dBm} > 24 \text{ dBm}$$

So the 24 dB limit applicable

Mode	Channel/ Frequency (MHz)	Maximum conducted output power (dBm)		Limit (dBm)		Pass / Fail
		SISO		FCC Part 15E	RSS-247	
		Meas Power	Corr'd Power			
IEEE 802.11a	100 (5500)	13.14	13.26	24	23.23	Pass
	116 (5580)	13.31	13.43	24	23.23	Pass
	140 (5700)	14.03	14.15	24	23.23	Pass
IEEE 802.11n-HT20	100 (5500)	13.23	13.36	24	23.49	Pass
	116 (5580)	13.35	13.48	24	23.49	Pass
	140 (5700)	14.10	14.23	24	23.49	Pass
IEEE 802.11n-HT40	102 (5510)	12.64	12.91	24	24	Pass
	110 (5550)	12.69	12.96	24	24	Pass
	134 (5670)	12.64	12.91	24	24	Pass
IEEE 802.11ac-VHT20	100 (5500)	12.78	12.93	24	23.49	Pass
	116 (5580)	12.71	12.86	24	23.49	Pass
	140 (5700)	12.39	12.54	24	23.49	Pass
IEEE 802.11ac-VHT40	102 (5510)	12.64	12.91	24	24	Pass
	110 (5550)	12.68	12.95	24	24	Pass
	134 (5670)	12.77	13.04	24	24	Pass
IEEE 802.11ac-VHT80	106 (5530)	12.09	12.62	24	24	Pass

Remark:

- Maximum conducted output power = Conducted output power + Duty Cycle Factor

Frequency band 5725-5850 MHz

Mode	Channel/ Frequency (MHz)	Maximum conducted output power (dBm)		Limit (dBm)	Pass / Fail
		Meas Power	Corr'd Power		
IEEE 802.11a	149 (5745)	12.67	12.79	30	Pass
	157 (5785)	13.20	13.32	30	Pass
	165 (5825)	13.06	13.18	30	Pass
IEEE 802.11n-HT20	149 (5745)	12.87	13.00	30	Pass
	157 (5785)	13.41	13.54	30	Pass
	165 (5825)	13.21	13.34	30	Pass
IEEE 802.11n-HT40	151 (5755)	12.36	12.63	30	Pass
	159 (5795)	12.54	12.81	30	Pass
IEEE 802.11ac-VHT20	149 (5745)	13.18	13.33	30	Pass
	157 (5785)	12.73	12.88	30	Pass
	165 (5825)	12.69	12.84	30	Pass
IEEE 802.11ac-VHT40	151 (5755)	12.82	13.09	30	Pass
	159 (5795)	12.83	13.10	30	Pass
IEEE 802.11ac-VHT80	155 (5775)	14.05	14.58	30	Pass

Remark:

- Maximum conducted output power = Conducted output power + Duty Cycle Factor

5.6 PEAK POWER SPECTRAL DENSITY

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3)
RSS-247 Issue 2 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1

Test Method: KDB 789033 D02 v02r01 Section F

Limits: FCC 47 CFR Part 15 Subpart E

1. For the band 5.15-5.25 GHz.
 - (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
 - (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
 - (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
 - (iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Limits: RSS-247 Issue 2

1. Frequency band 5150-5250 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

2. Frequency band 5250-5350 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

- a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;
- b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less, B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

Additional requirements

In addition to the above requirements, devices shall comply with the following, where applicable:

- a) Outdoor fixed devices with a maximum e.i.r.p. greater than 200 mW shall comply with the following e.i.r.p. at different elevations, where θ is the angle above the local horizontal plane (of the Earth) as shown below:

i. -13 dBW/MHz	for $0^\circ \leq \theta < 8^\circ$
ii. $-13 - 0.716 (\theta - 8)$ dBW/MHz	for $8^\circ \leq \theta < 40^\circ$
iii. $-35.9 - 1.22 (\theta - 40)$ dBW/MHz	for $40^\circ \leq \theta \leq 45^\circ$
iv. -42 dBW/MHz	for $\theta > 45^\circ$

The measurement procedure defined in Annex A of this document shall be used to verify the compliance to the e.i.r.p. at different elevations.

- b) Devices, other than outdoor fixed devices, having an e.i.r.p. greater than 200 mW shall comply with either i. or ii. below:
 - iii. devices shall comply with the e.i.r.p. elevation mask in 6.2.2.3(a); or
 - iv. devices shall implement a method to permanently reduce their e.i.r.p. via a firmware feature in the event that the Department requires it. The test report must demonstrate how the device's power table can be updated to meet this firmware requirement. The manufacturer shall provide this firmware to update all systems automatically in compliance with the directions received from the Department.

3. Frequency bands 5470-5600 MHz and 5650-5725 MHz

The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

4. Frequency band 5725-5850 MHz

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices

operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint³ systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum Analyzer.

Spectrum analyzer according to the following Settings:

1. For U-NII-1, U-NII-2A, U-NII-2C band:

Using method SA-2

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz, Set VBW $\geq$ 3 RBW, Detector = RMS
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value and add 10 log (1/duty cycle)

2. For U-NII-3 band:

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 500 kHz, Set VBW $\geq$ 3 RBW, Detector = RMS
- Use the peak marker function to determine the maximum power level in any 500 kHz band segment within the fundamental EBW.
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value and add 10 log (1/duty cycle)

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Directional gain and the maximum output power limit.

RSS-247 Issue 2:

Frequency Band	Antenna Gain (dBi))	PSD Limits (dBm/MHz or dBm/500kHz)
U-NII-1	4.0	10.00
U-NII-2A	4.0	11.00
U-NII-2C	4.0	11.00
U-NII-3	4.0	30.00

FCC 47 CFR Part 15 Subpart E:

Frequency Band	Antenna Gain (dBi))	PSD Limits (dBm/MHz or dBm/500kHz)
U-NII-1	4.0	11.00
U-NII-2A	4.0	11.00
U-NII-2C	4.0	11.00
U-NII-3	4.0	30.00

Frequency band 5150-5250 MHz
RSS-247 Issue 2

Mode	Channel/ Frequency (MHz)	e.i.r.p. spectral density (dBm/MHz)	Limit (dBm/MHz)	Pass / Fail
IEEE 802.11a	36 (5180)	9.316	10	Pass
	44 (5220)	9.447	10	Pass
	48 (5240)	9.130	10	Pass
IEEE 802.11n-HT20	36 (5180)	8.747	10	Pass
	44 (5220)	8.426	10	Pass
	48 (5240)	8.431	10	Pass
IEEE 802.11n-HT40	38 (5190)	6.463	10	Pass
	46 (5230)	5.673	10	Pass
IEEE 802.11ac-VHT20	36 (5180)	8.882	10	Pass
	44 (5220)	8.989	10	Pass
	48 (5240)	8.504	10	Pass
IEEE 802.11ac-VHT40	38 (5190)	6.439	10	Pass
	46 (5230)	6.186	10	Pass
IEEE 802.11ac-VHT80	42 (5210)	2.927	10	Pass

Remark:

- e.i.r.p. spectral density = Power spectral density + Duty Cycle Factor + Antenna Gain

FCC 47 CFR Part 15 Subpart E

Mode	Channel/ Frequency (MHz)	Power spectral density (dBm/MHz)		Limit (dBm/MHz)	Pass / Fail
		Meas PSD	Corr'd PSD		
IEEE 802.11a	36 (5180)	5.144	5.316	11	Pass
	44 (5220)	5.275	5.447	11	Pass
	48 (5240)	4.958	5.130	11	Pass
IEEE 802.11n-HT20	36 (5180)	4.586	4.747	11	Pass
	44 (5220)	4.265	4.426	11	Pass
	48 (5240)	4.270	4.431	11	Pass
IEEE 802.11n-HT40	38 (5190)	2.090	2.463	11	Pass
	46 (5230)	1.300	1.673	11	Pass
IEEE 802.11ac-VHT20	36 (5180)	4.698	4.882	11	Pass
	44 (5220)	4.805	4.989	11	Pass
	48 (5240)	4.320	4.504	11	Pass
IEEE 802.11ac-VHT40	38 (5190)	2.106	2.439	11	Pass
	46 (5230)	1.853	2.186	11	Pass
IEEE 802.11ac-VHT80	42 (5210)	-1.746	-1.073	11	Pass

Remark:

- Power spectral density = Conducted power spectral density + Duty Cycle Factor

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Frequency band 5250-5350 MHz

Mode	Channel/ Frequency (MHz)	Power spectral density (dBm/MHz)		Limit (dBm/MHz)	Pass / Fail
		Meas PSD	Corr'd PSD		
IEEE 802.11a	52 (5260)	4.956	5.128	11	Pass
	60 (5300)	4.653	4.825	11	Pass
	64 (5320)	4.618	4.790	11	Pass
IEEE 802.11n-HT20	52 (5260)	4.131	4.292	11	Pass
	60 (5300)	4.021	4.182	11	Pass
	64 (5320)	4.129	4.290	11	Pass
IEEE 802.11n-HT40	54 (5270)	1.171	1.544	11	Pass
	62 (5310)	1.032	1.405	11	Pass
IEEE 802.11ac-VHT20	52 (5260)	4.335	4.519	11	Pass
	60 (5300)	3.888	4.072	11	Pass
	64 (5320)	3.984	4.168	11	Pass
IEEE 802.11ac-VHT40	54 (5270)	1.375	1.708	11	Pass
	62 (5310)	1.169	1.502	11	Pass
IEEE 802.11ac-VHT80	58 (5290)	-2.413	-1.740	11	Pass

Remark:

- Power spectral density = Conducted power spectral density + Duty Cycle Factor

Frequency bands 5470-5725 MHz (RSS-247 Issue 2 Not including 5600-5650 MHz)

Mode	Channel/ Frequency (MHz)	Power spectral density (dBm/MHz)		Limit (dBm/MHz)	Pass / Fail
		Meas PSD	Corr'd PSD		
IEEE 802.11a	100 (5500)	4.300	4.472	11	Pass
	116 (5580)	4.176	4.348	11	Pass
	140 (5700)	3.739	3.911	11	Pass
IEEE 802.11n-HT20	100 (5500)	3.865	4.026	11	Pass
	116 (5580)	3.589	3.750	11	Pass
	140 (5700)	3.185	3.346	11	Pass
IEEE 802.11n-HT40	102 (5510)	0.346	0.719	11	Pass
	110 (5550)	0.574	0.947	11	Pass
	134 (5670)	0.295	0.668	11	Pass
IEEE 802.11ac-VHT20	100 (5500)	3.699	3.883	11	Pass
	116 (5580)	3.418	3.602	11	Pass
	140 (5700)	3.509	3.693	11	Pass
IEEE 802.11ac-VHT40	102 (5510)	-0.064	0.269	11	Pass
	110 (5550)	0.365	0.698	11	Pass
	134 (5670)	0.622	0.955	11	Pass
IEEE 802.11ac-VHT80	106 (5530)	-2.890	-2.217	11	Pass

Remark:

- Power spectral density = Conducted power spectral density + Duty Cycle Factor

Frequency band 5725-5850 MHz

Mode	Channel/ Frequency (MHz)	Power spectral density (dBm/500kHz)		Limit (dBm/500KHz)	Pass / Fail
		Meas PSD	Corr'd PSD		
IEEE 802.11a	149 (5745)	2.163	2.335	30	Pass
	157 (5785)	1.437	1.609	30	Pass
	165 (5825)	1.208	1.380	30	Pass
IEEE 802.11n-HT20	149 (5745)	1.776	1.937	30	Pass
	157 (5785)	0.691	0.852	30	Pass
	165 (5825)	0.035	0.196	30	Pass
IEEE 802.11n-HT40	151 (5755)	-1.215	-0.842	30	Pass
	159 (5795)	-1.975	-1.602	30	Pass
IEEE 802.11ac-VHT20	149 (5745)	1.387	1.571	30	Pass
	157 (5785)	0.909	1.093	30	Pass
	165 (5825)	0.301	0.485	30	Pass
IEEE 802.11ac-VHT40	151 (5755)	-1.353	-1.020	30	Pass
	159 (5795)	-1.694	-1.361	30	Pass
IEEE 802.11ac-VHT80	155 (5775)	-4.933	-4.260	30	Pass

Remark:

1. Power spectral density = Conducted power spectral density + Duty Cycle Factor

The test plots as follows:



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1





**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886


E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

















5.7 RADIATED EMISSIONS AND BAND EDGE MEASUREMENT

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(1)(2)(3)(4)(6)
FCC 47 CFR Part 15 Subpart C Section 15.209/205
RSS-247 Issue 2 Section 6.2.1.2/6.2.2.2/6.2.3.2/6.2.4.2

Test Method: KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

1. Limits of Radiated Emission and Band edge Measurement

Radiated emissions that fall in the restricted bands must comply with the general emissions limits in 15.209(a) as below table. Other emissions shall be at least 20 dB below the highest level of the desired power.

Frequency	Field strength (microvolt/meter)	Limit (dB μ V/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

- The lower limit shall apply at the transition frequencies.
- Emission level (dB μ V/m) = 20 log Emission level (uV/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

2. Limits of Unwanted Emission Out of the Restricted Bands

Applicable To	Limit	
789033 D02 General U-NII Test Procedures New Rules v01r04	Field Strength at 3 m	
	PK: 74 (dBμV/m)	AV: 54 (dBμV/m)
Applicable To	EIRP Limit	Equivalent Field Strength at 3 m
RSS-247 Issue 2 Section 6.2.1.2	PK: -27 (dBm/MHz)	PK: 74 (dBμV/m)
RSS-247 Issue 2 Section 6.2.2.2	PK: -27 (dBm/MHz)	PK: 74 (dBμV/m)
RSS-247 Issue 2 Section 6.2.3.2	PK: -27 (dBm/MHz)	PK: 68.2 (dBμV/m)
RSS-247 Issue 2 Section 6.2.4.2	27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;	PK: 68.2 (dBμV/m)
	15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;	
	10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges;	
	-27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.	

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

- The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Remark:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for RMS Average (Duty cycle < 98 %) for Average detection (AV) at frequency above 1 GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz (Duty cycle $\geq 98 \%$) or $\geq 1/T$ (duty cycle is < 98%) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.


Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

Radiated Emission Test Data (9 KHz ~ 30 MHz):

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Radiated Emission Test Data (30 MHz ~ 1 GHz Worst Case):
Worst-Case Configuration
Horizontal


No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	43.845	31.82	-10.52	21.30	40.00	-18.70	QP
2	53.756	36.84	-16.79	20.05	40.00	-19.95	QP
3	178.770	31.00	-9.91	21.09	43.50	-22.41	QP
4	270.616	30.45	-7.77	22.68	46.00	-23.32	QP
5	703.731	26.15	1.34	27.49	46.00	-18.51	QP
6	893.656	25.42	4.23	29.65	46.00	-16.35	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Vertical



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	32.870	26.03	-4.75	21.28	40.00	-18.72	QP
2	128.486	33.91	-15.97	17.94	43.50	-25.56	QP
3	177.518	34.04	-10.22	23.82	43.50	-19.68	QP
4	488.326	29.34	-3.31	26.03	46.00	-19.97	QP
5	674.677	26.72	0.53	27.25	46.00	-18.75	QP
6	893.656	25.10	4.23	29.33	46.00	-16.67	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Radiated Emission Test Data (Above 1GHz):
IEEE 802.11a_Channel 36

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10360.00	38.80	6.24	45.04	74.00	-28.96	Peak	Horizontal
2	10360.00	28.26	6.24	34.50	54.00	-19.50	Average	Horizontal
3	15540.00	35.83	11.27	47.10	74.00	-26.90	Peak	Horizontal
4	15540.00	24.89	11.27	36.16	54.00	-17.84	Average	Horizontal
5	10360.00	39.10	6.24	45.34	74.00	-28.66	Peak	Vertical
6	10360.00	28.31	6.24	34.55	54.00	-19.45	Average	Vertical
7	15540.00	37.05	11.27	48.32	74.00	-25.68	Peak	Vertical
8	15540.00	24.81	11.27	36.08	54.00	-17.92	Average	Vertical

IEEE 802.11a_Channel 44

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10440.00	40.04	6.30	46.34	74.00	-27.66	Peak	Horizontal
2	10440.00	28.35	6.30	34.65	54.00	-19.35	Average	Horizontal
3	15660.00	36.00	11.40	47.40	74.00	-26.60	Peak	Horizontal
4	15660.00	24.95	11.40	36.35	54.00	-17.65	Average	Horizontal
5	10440.00	39.66	6.30	45.96	74.00	-28.04	Peak	Vertical
6	10440.00	28.41	6.30	34.71	54.00	-19.29	Average	Vertical
7	15660.00	35.72	11.40	47.12	74.00	-26.88	Peak	Vertical
8	15660.00	24.87	11.40	36.27	54.00	-17.73	Average	Vertical

IEEE 802.11a_Channel 48

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10480.00	39.57	6.33	45.90	74.00	-28.10	Peak	Horizontal
2	10480.00	27.86	6.33	34.19	54.00	-19.81	Average	Horizontal
3	15720.00	35.89	11.48	47.37	74.00	-26.63	Peak	Horizontal
4	15720.00	24.74	11.48	36.22	54.00	-17.78	Average	Horizontal
5	10480.00	39.45	6.33	45.78	74.00	-28.22	Peak	Vertical
6	10480.00	27.92	6.33	34.25	54.00	-19.75	Average	Vertical
7	15720.00	36.76	11.48	48.24	74.00	-25.76	Peak	Vertical
8	15720.00	24.82	11.48	36.30	54.00	-17.70	Average	Vertical

IEEE 802.11a_Channel 52

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10520.00	39.11	6.39	45.50	74.00	-28.50	Peak	Horizontal
2	10520.00	27.92	6.39	34.31	54.00	-19.69	Average	Horizontal
3	15780.00	36.20	11.56	47.76	74.00	-26.24	Peak	Horizontal
4	15780.00	24.82	11.56	36.38	54.00	-17.62	Average	Horizontal
5	10520.00	40.02	6.39	46.41	74.00	-27.59	Peak	Vertical
6	10520.00	27.80	6.39	34.19	54.00	-19.81	Average	Vertical
7	15780.00	36.40	11.56	47.96	74.00	-26.04	Peak	Vertical
8	15780.00	24.74	11.56	36.30	54.00	-17.70	Average	Vertical

IEEE 802.11a_Channel 60

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10600.00	40.68	6.53	47.21	74.00	-26.79	Peak	Horizontal
2	10600.00	27.19	6.53	33.72	54.00	-20.28	Average	Horizontal
3	15900.00	36.76	11.71	48.47	74.00	-25.53	Peak	Horizontal
4	15900.00	24.65	11.71	36.36	54.00	-17.64	Average	Horizontal
5	10600.00	38.88	6.56	45.44	74.00	-28.56	Peak	Vertical
6	10600.00	27.35	6.56	33.91	54.00	-20.09	Average	Vertical
7	15900.00	37.17	11.71	48.88	74.00	-25.12	Peak	Vertical
8	15900.00	24.90	11.71	36.61	54.00	-17.39	Average	Vertical

IEEE 802.11a_Channel 64

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10640.00	39.54	6.64	46.18	74.00	-27.82	Peak	Horizontal
2	10640.00	27.27	6.64	33.91	54.00	-20.09	Average	Horizontal
3	15960.00	37.46	11.77	49.23	74.00	-24.77	Peak	Horizontal
4	15960.00	24.84	11.77	36.61	54.00	-17.39	Average	Horizontal
5	10640.00	40.14	6.64	46.78	74.00	-27.22	Peak	Vertical
6	10640.00	27.14	6.64	33.78	54.00	-20.22	Average	Vertical
7	15960.00	37.03	11.77	48.80	74.00	-25.20	Peak	Vertical
8	15960.00	24.84	11.77	36.61	54.00	-17.39	Average	Vertical

IEEE 802.11a_Channel 100

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11000.00	39.19	7.42	46.61	74.00	-27.39	Peak	Horizontal
2	11000.00	27.72	7.42	35.14	54.00	-18.86	Average	Horizontal
3	16500.00	37.23	12.35	49.58	74.00	-24.42	Peak	Horizontal
4	16500.00	24.61	12.35	36.96	54.00	-17.04	Average	Horizontal
5	11000.00	40.48	7.42	47.90	74.00	-26.10	Peak	Vertical
6	11000.00	27.60	7.42	35.02	54.00	-18.98	Average	Vertical
7	16500.00	35.85	12.35	48.20	74.00	-25.80	Peak	Vertical
8	16500.00	24.53	12.35	36.88	54.00	-17.12	Average	Vertical

IEEE 802.11a_Channel 116

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11160.00	40.32	7.32	47.64	74.00	-26.36	Peak	Horizontal
2	11160.00	26.86	7.32	34.18	54.00	-19.82	Average	Horizontal
3	16740.00	36.18	12.55	48.73	74.00	-25.27	Peak	Horizontal
4	16740.00	24.91	12.55	37.46	54.00	-16.54	Average	Horizontal
5	11160.00	39.49	7.32	46.81	74.00	-27.19	Peak	Vertical
6	11160.00	26.66	7.32	33.98	54.00	-20.02	Average	Vertical
7	16740.00	38.00	12.55	50.55	74.00	-23.45	Peak	Vertical
8	16740.00	24.66	12.55	37.21	54.00	-16.79	Average	Vertical

IEEE 802.11a_Channel 140

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11400.00	41.32	7.15	48.47	74.00	-25.53	Peak	Horizontal
2	11400.00	26.38	7.15	33.53	54.00	-20.47	Average	Horizontal
3	17100.00	37.52	12.92	50.44	74.00	-23.56	Peak	Horizontal
4	17100.00	23.69	12.92	36.61	54.00	-17.39	Average	Horizontal
5	11400.00	36.72	7.15	43.87	74.00	-30.13	Peak	Vertical
6	11400.00	26.38	7.15	33.53	54.00	-20.47	Average	Vertical
7	17100.00	34.44	12.92	47.36	74.00	-26.64	Peak	Vertical
8	17100.00	23.60	12.92	36.52	54.00	-17.48	Average	Vertical

IEEE 802.11a_Channel 149

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11490.00	38.90	7.09	45.99	74.00	-28.01	Peak	Horizontal
2	11490.00	27.14	7.09	34.23	54.00	-19.77	Average	Horizontal
3	17235.00	35.36	13.12	48.48	74.00	-25.52	Peak	Horizontal
4	17235.00	24.06	13.12	37.18	54.00	-16.82	Average	Horizontal
5	11490.00	39.80	7.09	46.89	74.00	-27.11	Peak	Vertical
6	11490.00	27.14	7.09	34.23	54.00	-19.77	Average	Vertical
7	17235.00	35.11	13.12	48.23	74.00	-25.77	Peak	Vertical
8	17235.00	24.06	13.12	37.18	54.00	-16.82	Average	Vertical

IEEE 802.11a_Channel 157

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11570.00	39.42	7.19	46.61	74.00	-27.39	Peak	Horizontal
2	11570.00	26.47	7.19	33.66	54.00	-20.34	Average	Horizontal
3	17355.00	36.52	13.29	49.81	74.00	-24.19	Peak	Horizontal
4	17355.00	24.65	13.29	37.94	54.00	-16.06	Average	Horizontal
5	11570.00	40.06	7.19	47.25	74.00	-26.75	Peak	Vertical
6	11570.00	26.41	7.19	33.60	54.00	-20.40	Average	Vertical
7	17355.00	35.58	13.29	48.87	74.00	-25.13	Peak	Vertical
8	17355.00	24.56	13.29	37.85	54.00	-16.15	Average	Vertical

IEEE 802.11a_Channel 165

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11650.00	40.31	7.31	47.62	74.00	-26.38	Peak	Horizontal
2	11650.00	26.46	7.31	33.77	54.00	-20.23	Average	Horizontal
3	17475.00	35.50	13.46	48.96	74.00	-25.04	Peak	Horizontal
4	17475.00	24.10	13.46	37.56	54.00	-16.44	Average	Horizontal
5	11650.00	40.13	7.31	47.44	74.00	-26.56	Peak	Vertical
6	11650.00	26.39	7.31	33.70	54.00	-20.30	Average	Vertical
7	17475.00	35.10	13.46	48.56	74.00	-25.44	Peak	Vertical
8	17475.00	24.00	13.46	37.46	54.00	-16.54	Average	Vertical

IEEE 802.11n-HT20_Channel 36

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10360.00	40.37	6.24	46.61	74.00	-27.39	Peak	Horizontal
2	10360.00	28.59	6.24	34.83	54.00	-19.17	Average	Horizontal
3	15540.00	38.13	11.27	49.40	74.00	-24.60	Peak	Horizontal
4	15540.00	25.05	11.27	36.32	54.00	-17.68	Average	Horizontal
5	10360.00	41.13	6.24	47.37	74.00	-26.63	Peak	Vertical
6	10360.00	28.75	6.24	34.99	54.00	-19.01	Average	Vertical
7	15540.00	35.78	11.27	47.05	74.00	-26.95	Peak	Vertical
8	15540.00	25.05	11.27	36.32	54.00	-17.68	Average	Vertical

IEEE 802.11n-HT20_Channel 44

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10440.00	42.03	6.30	48.33	74.00	-25.67	Peak	Horizontal
2	10440.00	28.52	6.30	34.82	54.00	-19.18	Average	Horizontal
3	15660.00	36.02	11.40	47.42	74.00	-26.58	Peak	Horizontal
4	15660.00	25.28	11.40	36.68	54.00	-17.32	Average	Horizontal
5	10440.00	40.19	6.30	46.49	74.00	-27.51	Peak	Vertical
6	10440.00	28.63	6.30	34.93	54.00	-19.07	Average	Vertical
7	15660.00	35.72	11.40	47.12	74.00	-26.88	Peak	Vertical
8	15660.00	25.12	11.40	36.52	54.00	-17.48	Average	Vertical

IEEE 802.11n-HT20_Channel 48

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10480.00	43.06	6.33	49.39	74.00	-24.61	Peak	Horizontal
2	10480.00	28.21	6.33	34.54	54.00	-19.46	Average	Horizontal
3	15720.00	35.96	11.48	47.44	74.00	-26.56	Peak	Horizontal
4	15720.00	25.07	11.48	36.55	54.00	-17.45	Average	Horizontal
5	10480.00	42.51	6.33	48.84	74.00	-25.16	Peak	Vertical
6	10480.00	28.43	6.33	34.76	54.00	-19.24	Average	Vertical
7	15720.00	39.12	11.48	50.60	74.00	-23.40	Peak	Vertical
8	15720.00	25.07	11.48	36.55	54.00	-17.45	Average	Vertical

IEEE 802.11n-HT20_Channel 52

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10520.00	41.08	6.39	47.47	74.00	-26.53	Peak	Horizontal
2	10520.00	27.86	6.39	34.25	54.00	-19.75	Average	Horizontal
3	15780.00	36.13	11.56	47.69	74.00	-26.31	Peak	Horizontal
4	15780.00	24.74	11.56	36.30	54.00	-17.70	Average	Horizontal
5	10520.00	39.14	6.39	45.53	74.00	-28.47	Peak	Vertical
6	10520.00	27.92	6.39	34.31	54.00	-19.69	Average	Vertical
7	15780.00	36.09	11.57	47.66	74.00	-26.34	Peak	Vertical
8	15780.00	24.65	11.57	36.22	54.00	-17.78	Average	Vertical

IEEE 802.11n-HT20_Channel 60

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10600.00	38.31	6.56	44.87	74.00	-29.13	Peak	Horizontal
2	10600.00	27.35	6.56	33.91	54.00	-20.09	Average	Horizontal
3	15900.00	36.73	11.71	48.44	74.00	-25.56	Peak	Horizontal
4	15900.00	24.82	11.71	36.53	54.00	-17.47	Average	Horizontal
5	10600.00	38.64	6.56	45.20	74.00	-28.80	Peak	Vertical
6	10600.00	27.22	6.56	33.78	54.00	-20.22	Average	Vertical
7	15900.00	36.69	11.71	48.40	74.00	-25.60	Peak	Vertical
8	15900.00	24.82	11.71	36.53	54.00	-17.47	Average	Vertical

IEEE 802.11n-HT20_Channel 64

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10640.00	38.65	6.64	45.29	74.00	-28.71	Peak	Horizontal
2	10640.00	27.02	6.64	33.66	54.00	-20.34	Average	Horizontal
3	15960.00	37.39	11.77	49.16	74.00	-24.84	Peak	Horizontal
4	15960.00	24.76	11.77	36.53	54.00	-17.47	Average	Horizontal
5	10640.00	39.45	6.64	46.09	74.00	-27.91	Peak	Vertical
6	10640.00	27.14	6.64	33.78	54.00	-20.22	Average	Vertical
7	15960.00	36.22	11.77	47.99	74.00	-26.01	Peak	Vertical
8	15960.00	24.76	11.77	36.53	54.00	-17.47	Average	Vertical

IEEE 802.11n-HT20_Channel 100

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11000.00	38.41	7.42	45.83	74.00	-28.17	Peak	Horizontal
2	11000.00	27.66	7.42	35.08	54.00	-18.92	Average	Horizontal
3	16500.00	38.57	12.35	50.92	74.00	-23.08	Peak	Horizontal
4	16500.00	24.53	12.35	36.88	54.00	-17.12	Average	Horizontal
5	11000.00	39.80	7.42	47.22	74.00	-26.78	Peak	Vertical
6	11000.00	27.66	7.42	35.08	54.00	-18.92	Average	Vertical
7	16500.00	37.46	12.35	49.81	74.00	-24.19	Peak	Vertical
8	16500.00	24.53	12.35	36.88	54.00	-17.12	Average	Vertical

IEEE 802.11n-HT20_Channel 116

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11160.00	37.83	7.32	45.15	74.00	-28.85	Peak	Horizontal
2	11160.00	26.59	7.32	33.91	54.00	-20.09	Average	Horizontal
3	16740.00	37.42	12.55	49.97	74.00	-24.03	Peak	Horizontal
4	16740.00	24.75	12.55	37.30	54.00	-16.70	Average	Horizontal
5	11160.00	37.93	7.32	45.25	74.00	-28.75	Peak	Vertical
6	11160.00	26.73	7.32	34.05	54.00	-19.95	Average	Vertical
7	16740.00	35.91	12.55	48.46	74.00	-25.54	Peak	Vertical
8	16740.00	24.75	12.55	37.30	54.00	-16.70	Average	Vertical

IEEE 802.11n-HT20_Channel 140

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11400.00	39.99	7.15	47.14	74.00	-26.86	Peak	Horizontal
2	11400.00	26.45	7.15	33.60	54.00	-20.40	Average	Horizontal
3	17100.00	35.10	12.92	48.02	74.00	-25.98	Peak	Horizontal
4	17100.00	23.60	12.92	36.52	54.00	-17.48	Average	Horizontal
5	11400.00	39.75	7.15	46.90	74.00	-27.10	Peak	Vertical
6	11400.00	26.31	7.15	33.46	54.00	-20.54	Average	Vertical
7	17100.00	37.65	12.92	50.57	74.00	-23.43	Peak	Vertical
8	17100.00	23.60	12.92	36.52	54.00	-17.48	Average	Vertical

IEEE 802.11n-HT20_Channel 149

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11490.00	37.94	7.09	45.03	74.00	-28.97	Peak	Horizontal
2	11490.00	27.14	7.09	34.23	54.00	-19.77	Average	Horizontal
3	17235.00	36.03	13.12	49.15	74.00	-24.85	Peak	Horizontal
4	17235.00	24.06	13.12	37.18	54.00	-16.82	Average	Horizontal
5	11490.00	39.59	7.09	46.68	74.00	-27.32	Peak	Vertical
6	11490.00	27.07	7.09	34.16	54.00	-19.84	Average	Vertical
7	17235.00	38.13	13.12	51.25	74.00	-22.75	Peak	Vertical
8	17235.00	23.96	13.12	37.08	54.00	-16.92	Average	Vertical

IEEE 802.11n-HT20_Channel 157

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11570.00	39.49	7.19	46.68	74.00	-27.32	Peak	Horizontal
2	11570.00	26.41	7.19	33.60	54.00	-20.40	Average	Horizontal
3	17355.00	35.72	13.29	49.01	74.00	-24.99	Peak	Horizontal
4	17355.00	24.65	13.29	37.94	54.00	-16.06	Average	Horizontal
5	11570.00	39.68	7.19	46.87	74.00	-27.13	Peak	Vertical
6	11570.00	26.47	7.19	33.66	54.00	-20.34	Average	Vertical
7	17355.00	35.67	13.29	48.96	74.00	-25.04	Peak	Vertical
8	17355.00	24.65	13.29	37.94	54.00	-16.06	Average	Vertical

IEEE 802.11n-HT20_Channel 165

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11650.00	38.98	7.31	46.29	74.00	-27.71	Peak	Horizontal
2	11650.00	26.46	7.31	33.77	54.00	-20.23	Average	Horizontal
3	17475.00	35.99	13.46	49.45	74.00	-24.55	Peak	Horizontal
4	17475.00	24.00	13.46	37.46	54.00	-16.54	Average	Horizontal
5	11650.00	40.31	7.31	47.62	74.00	-26.38	Peak	Vertical
6	11650.00	26.59	7.31	33.90	54.00	-20.10	Average	Vertical
7	17475.00	35.03	13.46	48.49	74.00	-25.51	Peak	Vertical
8	17475.00	23.91	13.46	37.37	54.00	-16.63	Average	Vertical

IEEE 802.11n-HT40_Channel 38

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10380.00	39.45	6.25	45.70	74.00	-28.30	Peak	Horizontal
2	10380.00	28.69	6.25	34.94	54.00	-19.06	Average	Horizontal
3	15570.00	35.93	11.29	47.22	74.00	-26.78	Peak	Horizontal
4	15570.00	25.11	11.29	36.40	54.00	-17.60	Average	Horizontal
5	10380.00	40.88	6.25	47.13	74.00	-26.87	Peak	Vertical
6	10380.00	28.63	6.25	34.88	54.00	-19.12	Average	Vertical
7	15570.00	38.02	11.29	49.31	74.00	-24.69	Peak	Vertical
8	15570.00	24.95	11.29	36.24	54.00	-17.76	Average	Vertical

IEEE 802.11n-HT40_Channel 46

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10460.00	42.04	6.32	48.36	74.00	-25.64	Peak	Horizontal
2	10460.00	28.33	6.32	34.65	54.00	-19.35	Average	Horizontal
3	15690.00	36.15	11.45	47.60	74.00	-26.40	Peak	Horizontal
4	15690.00	25.07	11.45	36.52	54.00	-17.48	Average	Horizontal
5	10460.00	43.14	6.32	49.46	74.00	-24.54	Peak	Vertical
6	10460.00	28.44	6.32	34.76	54.00	-19.24	Average	Vertical
7	15690.00	38.08	11.45	49.53	74.00	-24.47	Peak	Vertical
8	15690.00	25.15	11.45	36.60	54.00	-17.40	Average	Vertical

IEEE 802.11n-HT40_Channel 54

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10540.00	41.05	6.32	47.37	74.00	-26.63	Peak	Horizontal
2	10540.00	28.18	6.32	34.50	54.00	-19.50	Average	Horizontal
3	15810.00	35.33	11.45	46.78	74.00	-27.22	Peak	Horizontal
4	15810.00	24.96	11.45	36.41	54.00	-17.59	Average	Horizontal
5	10540.00	39.77	6.42	46.19	74.00	-27.81	Peak	Vertical
6	10540.00	28.13	6.42	34.55	54.00	-19.45	Average	Vertical
7	15810.00	38.75	11.59	50.34	74.00	-23.66	Peak	Vertical
8	15810.00	24.82	11.59	36.41	54.00	-17.59	Average	Vertical

IEEE 802.11n-HT40_Channel 62

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10620.00	41.56	6.61	48.17	74.00	-25.83	Peak	Horizontal
2	10620.00	27.49	6.61	34.10	54.00	-19.90	Average	Horizontal
3	15930.00	36.52	11.75	48.27	74.00	-25.73	Peak	Horizontal
4	15930.00	25.03	11.75	36.78	54.00	-17.22	Average	Horizontal
5	10620.00	42.07	6.61	48.68	74.00	-25.32	Peak	Vertical
6	10620.00	27.49	6.61	34.10	54.00	-19.90	Average	Vertical
7	15930.00	36.21	11.75	47.96	74.00	-26.04	Peak	Vertical
8	15930.00	25.03	11.75	36.78	54.00	-17.22	Average	Vertical

IEEE 802.11n-HT40_Channel 102

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11020.00	40.51	7.41	47.92	74.00	-26.08	Peak	Horizontal
2	11020.00	27.85	7.41	35.26	54.00	-18.74	Average	Horizontal
3	16530.00	38.29	12.38	50.67	74.00	-23.33	Peak	Horizontal
4	16530.00	24.67	12.38	37.05	54.00	-16.95	Average	Horizontal
5	11020.00	38.98	7.41	46.39	74.00	-27.61	Peak	Vertical
6	11020.00	27.85	7.41	35.26	54.00	-18.74	Average	Vertical
7	16530.00	35.56	12.38	47.94	74.00	-26.06	Peak	Vertical
8	16530.00	24.75	12.38	37.13	54.00	-16.87	Average	Vertical

IEEE 802.11n-HT40_Channel 110

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11100.00	41.27	7.35	48.62	74.00	-25.38	Peak	Horizontal
2	11100.00	26.96	7.35	34.31	54.00	-19.69	Average	Horizontal
3	16650.00	35.96	12.48	48.44	74.00	-25.56	Peak	Horizontal
4	16650.00	24.90	12.48	37.38	54.00	-16.62	Average	Horizontal
5	11100.00	40.65	7.35	48.00	74.00	-26.00	Peak	Vertical
6	11100.00	28.96	7.35	36.31	54.00	-17.69	Average	Vertical
7	16650.00	35.89	12.48	48.37	74.00	-25.63	Peak	Vertical
8	16650.00	24.98	12.48	37.46	54.00	-16.54	Average	Vertical