

RF Exposure Evaluation Report

Product : reTerminal E1001 ePaper Display/
reTerminal E1002 ePaper Display

Trade mark : Seeed Studio

Model/Type reference : E1001, E1002

Serial Number : N/A

Report Number : EED32R81447603

FCC ID : Z4T-E100X

Date of Issue : Sep. 05, 2025

Test Standards : 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB 447498 D04 Interim General RF
Exposure Guidance v01

Test result : PASS

Prepared for:

Seeed Technology Co.,Ltd
9F,Building G3,TCL International E city,Shuguang Community,Xili
street,Nanshan,Shenzhen, Guangdong Province, P.R.C

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Park, Zone 70, Bao'an District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Keven Tan

Keven Tan

Reviewed by:

Frazer Li

Frazer Li

Approved by:

Aaron Ma

Aaron Ma

Date:

Sep. 05, 2025



Check No.:4050120825

1 Contents

	Page
1 CONTENTS	2
2 GENERAL INFORMATION	3
2.1 CLIENT INFORMATION	3
2.2 GENERAL DESCRIPTION OF EUT	3
2.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	3
2.4 TEST LOCATION	5
2.5 DEVIATION FROM STANDARDS	5
2.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
2.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
3 SAR EVALUATION	6
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
3.1.1 Limits	6
3.1.2 Test Procedure	6
3.1.3 EUT RF Exposure Evaluation	7

Page 3 of 8

Applicant:	Seed Technology Co.,Ltd
Address of Applicant:	9F,Building G3,TCL International E city,Shuguang Community,Xili street,Nanshan,Shenzhen, Guangdong Province, P.R.C
Manufacturer:	Seed Technology Co.,Ltd
Address of Manufacturer:	9F,Building G3,TCL International E city,Shuguang Community,Xili street,Nanshan,Shenzhen, Guangdong Province, P.R.C
Factory:	Shenzhen Xinxian Technology Co.,Limited.
Address of Factory:	5th Floor,102 first Floor,Building B17,HengfengIndustrial town No.739 Zhoushi Road,Hangcheng Street,Bao'an District,Shenzhen

Product Name:	reTerminal E1001 ePaper Display/reTerminal E1002 ePaper Display
Model No.(EUT):	E1001, E1002
Trade Mark:	Seeed Studio

Frequency Range:	BLE: 2402MHz~2480MHz 2.4G Wi-Fi: IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz	
Modulation Type:	BLE: GFSK BT: GFSK, $\pi/4$ DQPSK, 8DPSK 2.4G Wi-Fi: IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g :OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM,QPSK,BPSK)	
Test Power Grade:	Default	
Test Software of EUT:	Esp32.exe	
Antenna Type:	FPC antenna	
Antenna Gain:	2.39dBi	
Power Supply:	USB Port:	DC 5V
Sample Received Date:	Aug. 12, 2025	
Sample tested Date:	Aug. 12, 2025 to Aug. 31, 2025	

Remark:
Model No.: E1001, E1002
Only the model E1001 was tested, the electrical circuit design, layout, components used, and internal wiring are identical,The difference is that the two use different sereens.

Feature	reTerminal E1001 ePaper Display	reTerminal E1002 ePaper Display
FPC Connector	24 pin	50 pin
Screen	7.5" Monochrome Display	7.3" Full color Display
Other Components	Identical	Identical

2.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Hongwei Industrial Park, Zone 70, Bao'an District, Shenzhen, Guangdong, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

2.5 Deviation from Standards

None.

2.6 Abnormalities from Standard Conditions

None.

2.7 Other Information Requested by the Customer

None.

3 SAR Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.1.3 EUT RF Exposure Evaluation**For Stand alone:****BLE:**

Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio
@2.4GHz	20	7.73	2.39	7.97	6.2661	3060	0.0020

2.4G Wi-Fi:

Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio
@2.4GHz	20	18.38	2.39	18.62	72.7780	3060	0.0238

Note:

- ① EIRP=conducted power+antenna gain;
- ② $ERP = EIRP - 2.15$;
- ③ $EIRP(dBm) = \text{Field strength of the fundamental signal}(dBuV/m@3m) - 95.23$;
- ④ $ERP(mW) = 10^{(ERP(dBm)/10)}$;
- ⑤ The estimation distance is 20cm;
- ⑥ The test data please refer to the report of EED32R81447601 and EED32R81447602 only the worst case data was recorded in the report.

For Simultaneous Transmission:

As MPE ratio (BLE+2.4G Wi-Fi)=0.0020+0.0238=0.0258 < 1, it's deemed to fulfil the RF exposure requirement.

Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;
2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;
3. The result(s) shown in this report refer(s) only to the sample(s) tested;
4. Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;
5. Without written approval of CTI, this report can't be reproduced except in full;

*** End of Report ***