

RF exposure report

For

Joyplus International Enterprise Limited

805 TECHNOLOGY BUILDING,DUOLI INDUSTRIAL PARK,SHANGMEILIN,
MEIHUA ROAD,FUTIAN DISTRICT,SHENZHEN ,CHINA

FCC ID: Z4UA2313785

Test Model Number: A23-78A

This Report Concerns:	Equipment Type:
Original Report	Tablet PC
Test Engineer:	Lisa Chen <i>Lisa Chen</i>
Report No.:	BSL13121029Y-1ER-6
Receive EUT	November 25 /
Date/Test Date:	November 25 - December 16, 2013
Reviewed By:	Sky Zhang <i>Sky Zhang</i>
Prepared By:	BSL Testing Co.,LTD. NO. 24, ZH Park, Nantou, Shenzhen, 518000 China Tel: 86- 755-26508703 Fax: 86- 755-26508703

FCC §15.247 (i) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance v05

Result

According to FCC KDB 447498 D01 General RF Exposure Guidance v05 generic portable criteria

The distance between antenna and test point is 5 mm
The max output power:9.39 dBm8.6896 mW)

According to the Appendix A of KDB 447498, the exclusion thresholds for 2450 MHz is 10 mW.

Conclusion:

The peak output power is 8.6896 mW <the exclusion thresholds 10 mW, so stand-alone SAR evaluation is not required.