

REACH Tech (Xiamen) Co., Ltd.

Hac Cover Letter

FCC ID: Z5JREACH-Q882

Date: Dec 10, 2013

Federal Communications Commission
Authorization and Evaluation Division
7435 Oakland Mills Road
Columbia, MD 21046


To whom it may concern:

a. This device (FCC ID: Z5JREACH-Q882) with Hearing Aid Compatibility Requirement is going to be certified under ANSI C6219.-2011 version per Part 20.19. For Radio Frequency interference, Speag's Audio Interference Analyzer (AIA) or other indirect or direct measurement was not used to determine the M rating. The M rating was determined by measuring the maximum steady state average E-field values in dB(V/m) as documented in HAC test report exhibit and adding the MIF values in dB(V/m) using pre-determined values provided by Speag.

UID	Communcation System	MIF
10021	GSM-FDD(TDMA,GMSK)	3.63
10011	UMTS-FCC(WCDMA)	-27.23

The Speag Reference Documentation for supporting the pre-determined MIF value is Schmid & Partner Engineering AG, DASY5 Manual V5.2, December 2012. We are confirming that the Speag Simulation provided represents all the air interface modes applicable for a HAC rating on this handset.

Sincerely,



Xiaowen Tang / Quality Manager
REACH Tech (Xiamen) Co., Ltd.