



Nemko Canada Inc
303 River Road
Ottawa, Ontario, Canada
K1V 1H2

Attn: Director of Certification

Re: Request Limited Modular Authority for FCC ID#: ZHX-370-00012-01

We hereby request Limited Modular Approval based on the numbered requirements identified below as we address them to be included in our application for equipment authorization.

1. The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with Part 15 limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation.

Our equipment meets this by completely enclosing the module in an aluminum case. Noise filters are also utilized on certain signals to limit unintentional radiation.

2. The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with Part 15 requirements under conditions of excessive data rates or over-modulation.

Our equipment meets this by exercising complete control of the rate at which data is transmitted. That is, the data rate or modulation cannot be modified by changing any inputs to the module.

3. The modular transmitter must have its own power supply regulation. This is intended to ensure that the module will comply with Part 15 requirements regardless of the design of the power supplying circuitry in the device into which the module is installed.

Our equipment meets this by utilizing its own internal power supply regulation circuits. Module operation is consistent with input voltage ranging from 4-8 Volts.

4. The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). Any

antenna used with the module must be approved with the module, either at the time of initial authorization or through a Class II permissive change. The “professional installation” provision of Section 15.203 may not be applied to modules.

Our module will not be offered for sale as a stand-alone product, and will always be integrated into MicroPower products only. Those products will either satisfy the unique connector requirement, or be professionally installed. Requirements for installing the module into a MircoPower product are described in the Mono Camera Module Installation Guide.

5. The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)).

Our equipment is tested in a typical final product system. The module will not be offered for sale, and only be integrated into MicroPower products, according to the Mono Camera Module Installation Guide.

6. The modular transmitter must be labeled with its own FCC ID number, and, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: “Contains Transmitter Module FCC ID: XYZMODEL1” or “Contains FCC ID: XYZMODEL1.” Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.

Our equipment meets this by affixing compliant labels to both the module, and the exterior of the final product(s).

7. The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured.

The operational levels and timing of our equipment is completely self-contained, and can not be adjusted by and end user. The equipment will operate as tested.

8. The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance.

Our module is used in fixed surveillance equipment, mounted on walls, poles, eaves, etc. It will not be installed into equipment used as mobile devices. As such, a separation of at least 20cm to any persons in the vicinity of the equipment is guaranteed. This separation satisfies the RF exposure requirements.

Sincerely,

A handwritten signature in blue ink, appearing to read "Mark Sapper".

Mark Sapper
Director of Engineering