



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. 410.290.6652 / Fax 410.290.6654
http://www.pctestlab.com



MEASUREMENT REPORT FCC Part 15.225 NFC

Applicant Name:
LG Electronics MobileComm U.S.A
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:
12/17/2013
Test Site/Location:
PCTEST Lab, Columbia, MD, USA
Test Report Serial No.:
0Y1312022320.A3L


FCC ID:	ZNFD950
APPLICANT:	LG Electronics MobileComm U.S.A

Application Type: Class II Permissive Change
Model(s): LG-D950, D950, LGD950
EUT Type: Portable Handset
Frequency: 13.56MHz
FCC Classification: Low Power Communications Device Transmitter (DXX)
FCC Rule Part(s): FCC Part 15 Subpart C (15.225)
Test Procedure(s): ANSI C63.10-2009
Class II Permissive Change: Please see FCC change documents.
Original Grant Date: 11/22/2013

The device bearing the FCC Identifier specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in ANSI C63.10-2009 (See Test Report). These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

NVLAP accreditation does not constitute any product endorsement by NVLAP or any agency of the United States Government. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Randy Ortanez
President








FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 1 of 15	

TABLE OF CONTENTS

FCC Part 15.225 MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 SCOPE	4
1.2 PCTEST TEST LOCATION	4
2.0 PRODUCT INFORMATION.....	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 DEVICE CAPABILITIES	5
2.3 TEST CONFIGURATION	5
2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
2.5 LABELING REQUIREMENTS	5
3.0 DESCRIPTION OF TEST	6
3.1 EVALUATION PROCEDURE	6
3.2 RADIATED EMISSIONS.....	6
4.0 ANTENNA REQUIREMENTS	7
5.0 SAMPLE CALCULATIONS	8
5.1 RADIATED EMISSION MEASUREMENT SAMPLE CALCULATION.....	8
6.0 TEST EQUIPMENT CALIBRATION DATA	9
7.0 ENVIRONMENTAL CONDITIONS	10
8.0 TEST DATA.....	11
8.1 SUMMARY	11
8.2 IN-BAND RADIATED SPURIOUS EMISSION MEASUREMENTS.....	12
8.3 RADIATED SPURIOUS EMISSION MEASUREMENTS, OUT-OF-BAND	13
9.0 CONCLUSION.....	15

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 2 of 15	



MEASUREMENT REPORT

FCC Part 15.225





§ 2.1033 General Information



APPLICANT: LG Electronics MobileComm U.S.A
APPLICANT ADDRESS: 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632
 United States
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA
FCC RULE PART(S): Part 15 Subpart C (15.225)
IC SPECIFICATION(S): RSS-210 Issue 8
MODEL: LG-D950
FCC ID: ZNFD950
Test Device Serial No.: WLAN Production Pre-Production Engineering
FCC CLASSIFICATION: Low Power Communications Device Transmitter (DXX)
DATE(S) OF TEST: 12/17/2013
TEST REPORT S/N: 0Y1312022320.A3L

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 3 of 15

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on February 15, 2012.






Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 4 of 15

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFD950**. The test data contained in this report pertains only to the emissions due to the NFC transmitter of the EUT.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Band 2, 4, 5, 17 (5/10MHz BW), 7 (5/10/15/20MHz BW) LTE, 802.11a/b/g/n/ac WLAN (DTS/NII), Bluetooth (1x,EDR, LE), NFC

2.3 Test Configuration

The LG Portable Handset FCC ID: ZNFD950 was set to continuously transmit at 13.56MHz. This was performed using manufacturer software loaded on the phone and a passive RFID tag to allow for continuous transmission. This device was tested in accordance with the guidance of ANSI C63.10-2009. See Section 3.2 of this test report for a description of the radiated emissions test setup.



2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

2.5 Labeling Requirements

Per 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 5 of 15	

3.0 DESCRIPTION OF TEST

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2009) was used in the measurement of the **LG Portable Handset FCC ID: ZNFD950**.



Deviation from measurement procedure.....None

3.2 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. For the EUT positioning, "H" is defined with the EUT lying flat on the test surface, "H2" is defined with the EUT standing up on its side, and "V" is defined with the EUT standing upright.

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 6 of 15	

4.0 ANTENNA REQUIREMENTS



Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the LG Portable Handset are **permanently attached**.
- There are no provisions for connection to an external antenna.
- The NFC antenna is embedded in the battery used for testing.

Conclusion:

The **LG Portable Handset FCC ID: ZNFD950** unit complies with the requirement of §15.203.

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 7 of 15	

5.0 SAMPLE CALCULATIONS

5.1 Radiated Emission Measurement Sample Calculation



@ 66.7 MHz

Class B limit		= 100 $\mu\text{V}/\text{m}$ = 40.0 dB $\mu\text{V}/\text{m}$
Reading		= - 76.0 dBm (calibrated level)
Convert to dB μV		= - 76.0 + 107 = 31.0 dB μV
Antenna Factor + Cable Loss		= 5.8 dB/m
	Total	= 36.8 dB $\mu\text{V}/\text{m}$
Margin		= 36.8 - 40.0 = - 3.2 dB
		= 3.2 dB below limit

Note:

Level [dB μV] = 20 log₁₀ (Level [$\mu\text{V}/\text{m}$])

Level [dB μV] = Level [dBm] + 107

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 8 of 15	

6.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	3/29/2013	Annual	3/29/2014	N/A
Agilent	8447D	Broadband Amplifier	5/31/2013	Annual	5/31/2014	1937A03348
Agilent	N9020A	MXA Signal Analyzer	10/29/2013	Annual	10/29/2014	US46470561
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	6/26/2013	Annual	6/26/2014	121034
Emco	3816/2	LISN	2/12/2013	Biennial	2/12/2015	9707-1079
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	7/24/2013	Biennial	7/24/2015	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	5/30/2012	Biennial	5/30/2014	135427
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	5/31/2013	Annual	5/31/2014	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	5/31/2013	Annual	5/31/2014	100040
Rohde & Schwarz	ESU26	EMI Test Receiver	2/25/2013	Annual	2/25/2014	100342
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/26/2012	Biennial	1/26/2014	A051107

Table 6-1. Annual Test Equipment Calibration Schedule

Note:

In the table above, if the equipment calibration due date falls within the test dates, care was taken to ensure that the equipment was utilized prior to the calibration due date.



FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 9 of 15	

7.0 ENVIRONMENTAL CONDITIONS

The temperature is controlled within range of 15°C to 35°C.

The relative humidity is controlled within range of 10% to 75%.

The atmospheric pressure is controlled within the range 86-106kPa (860-1060mbar).

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 10 of 15	

8.0 TEST DATA

8.1 Summary



Company Name: LG Electronics MobileComm U.S.A
 FCC ID: ZNFD950
 Frequencies Examined: 13.56MHz

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (Tx)						
15.225 (a)(b)(c)	RSS-210 [A2.6]	In-Band Emissions	15,848 μ V/m @ 30m 13.553 – 13.567 MHz 334 μ V/m @ 30m 13.410 – 13.553 MHz 13.567 – 13.710 MHz 106 μ V/m @ 30m 13.110 – 13.410 MHz 13.710 – 14.010 MHz		PASS	Section 8.2
15.225 (d) 15.209	RSS-210 [A2.6]	Out-of-Band Emissions	Emissions outside of the specified band (13.110 – 14.010 MHz) must meet the radiated limits detailed in 15.209		PASS	Section 8.3

Table 8-1. Summary of Test Results

Note:

This unit was tested with its standard battery.

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 11 of 15	

8.2 In-Band Radiated Spurious Emission Measurements

§15.225(a), (b), (c); RSS-210 [A2.6]

Radiated emission testing was performed in the band 13.110 – 14.010 MHz.

Frequency: 13.56MHz



Measurement Distance: 3 Meters

Frequency [MHz]	Level [dBm]	AFCL [dB/m]	Antenna Position	EUT Pol. [H/V]	3m Field Strength [dBμV/m]	30m Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13.282	-94.06	14.57	X	V	27.51	-12.49	40.51	-53.00
13.379	-93.42	14.56	X	V	28.14	-11.86	40.51	-52.36
13.487	-93.01	14.56	X	V	28.55	-11.45	50.47	-61.93
13.560	-73.23	14.56	X	V	48.33	8.33	84.00	-75.67
13.668	-94.58	14.55	X	V	26.97	-13.03	50.47	-63.50
13.811	-94.13	14.55	X	V	27.42	-12.58	40.51	-53.09
13.979	-93.86	14.54	X	V	27.68	-12.32	40.51	-52.82

Table 8-2. In-Band Radiated Measurements

NOTES:

- All measurements were performed using a loop antenna. The antenna was positioned in three orthogonal positions (X front, Y side, Z top) and the position with the highest emission level was recorded.
- The EUT was positioned in three orthogonal planes to determine the orientation resulting in the worst case emissions.
- Measurements were performed at 3m and the data was extrapolated to the specified measurement distance of 30m using the square of an inverse linear distance extrapolation factor (40 dB/decade) as specified in §15.31(f)(2). Extrapolation Factor = $20 \log_{10}(30/3)^2 = 40\text{dB}$.
- The spectrum was investigated from 9kHz up to 30MHz using the loop antenna. Only the emissions shown in the table above were found to be significant.
- All measurements were recorded using a spectrum analyzer employing a quasi-peak detector.
- Field Strength Level $_{[\text{dB}\mu\text{V}/\text{m}]}$ = Analyzer Level $_{[\text{dBm}]}$ + 107 + AFCL $_{[\text{dB}/\text{m}]}$
- AFCL $_{[\text{dB}/\text{m}]}$ = Antenna Factor $_{[\text{dB}/\text{m}]}$ + Cable Loss $_{[\text{dB}]}$
- Margin $_{[\text{dB}]}$ = Field Strength Level $_{[\text{dB}\mu\text{V}/\text{m}]}$ – Limit $_{[\text{dB}\mu\text{V}/\text{m}]}$

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 12 of 15	

8.3 Radiated Spurious Emission Measurements, Out-of-Band §15.209, §15.225(d); RSS-210 [A2.6]



The EUT was tested from 9kHz up to the 1GHz excluding the band 13.110 – 14.010 MHz. All measurements up to 960MHz were recorded with a spectrum analyzer employing a quasi-peak detector. All out-of-band emissions must not exceed the limits shown in Table 8-3 per Section 15.209. A loop antenna was used to investigate emissions below 30MHz.

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 8-3. Radiated Limits – Out of band

Sample Calculation

- Field Strength Level [dBμV/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dBμV/m] – Limit [dBμV/m]

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 13 of 15	

Radiated Spurious Emission Measurements, Out-of-Band (Cont'd)
§15.209, §15.225(d); RSS-210 [A2.6]

Tx Frequency 13.56MHz



Measurement Distance: 3 Meters

Frequency [MHz]	Level [dBm]	AFCL [dB/m]	Pol [H/V]	3m Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
40.68	-102.00	14.38	V	19.38	40.00	-20.62
54.24	-101.46	9.62	V	15.16	40.00	-24.84
67.80	-103.27	10.18	V	13.91	40.00	-26.09
81.36	-102.63	10.65	V	15.03	40.00	-24.97
94.92	-100.99	11.05	V	17.06	43.52	-26.46
108.05	-102.24	11.63	V	16.39	43.52	-27.13

Table 8-4. Radiated Measurements



NOTES:

1. All measurements were recorded using a spectrum analyzer employing a quasi-peak detector for emissions below 960MHz.
2. Both Vertical and Horizontal polarities of the receive antenna were evaluated with the worst case emissions being reported. Below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. The EUT was positioned in three orthogonal planes to determine the orientation resulting in the worst case emissions.
4. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No emissions were found at the seconds harmonic.
5. No spurious emissions levels were found to be greater than the level of the fundamental.

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset	Page 14 of 15	

9.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFD950** has been tested to show compliance with the requirements specified in §15.225 of the FCC Rules.

FCC ID: ZNFD950		FCC Pt. 15.225 MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Reviewed by: Quality Manager
Test Report S/N: 0Y1312022320.A3L	Test Date(s): 12/17/2013	EUT Type: Portable Handset		Page 15 of 15