

Installation (!) Instructions

TPMS PSG E type Uni Sensor

After you have programmed the Uni-Sensor, follow installation procedures below.

Important:

Each time the TPMS sensor is changed or disassembled, it is MANDATORY to replace the TPMS sensor washer, nut, screw, and valve core accessories (use only CUB service component kits designed for TPMS sensor) to ensure proper sealing.

For Clamp-In Metal Valve Sensors:

1. Take the valve cap, valve nut away from the valve stem and keep grommet on the valve stem. Insert the sensor with valve stem into the rim valve hole, put on the valve stem nut.
2. While holding the sensor down against the wheel bottom, hand tighten the nut. With the torque wrench, tighten the nut to 4.0 Nm.
3. Place the plastic cap on.

For Snap-In Rubber Valve Sensors:

1. Apply tire soap or lubricant to rubber valve stem.
2. Line sensor up with rim hole and attach a standard TTV (Tubeless Tire Valve) pull tool to the end of the valve.
3. Pull the valve stem straight through the valve hole. Refer to your TTV tool manual for proper installation. The force to make it sit shall not exceed 40 kg (90 lb). Finally place the plastic cap.
4. In case of the valve stem replacing, tighten the screw by 1.35 Nm.

Caution:

It is recommended to seek the service of a qualified technician. Pay special attention and follow all instructions to all cautions and warnings included in the shop manual. Failure to do so could result in failure of the vehicle's Tire Pressure Monitor System (TPMS) Sensors to function properly, or result in damage to the TPMS Sensor.

The PUR-sensor(Uni-Sensor)is blank software inside, be sure to program the sensor by CUB's sensor-AID or compatible tool for your specific motor vehicle make, model and year before installation. Only install programmed TPMS sensors to the application listed in the tool. Improper TPMS installation or the use of unauthorized TPMS Sensors will cause the failure of TPM system. Upon completion of installation, test the TPMS System following the original manufacturer's service guide to confirm proper installation. Check all installation procedures to ensure proper installation and retest. If the System continues to fail consult with CUB support or an authorized motor vehicle dealership.

These TPMS sensor assemblies are designed and manufactured to be operated in Original Equipment wheels and tires only. While using non-OE wheels/tires, the vehicle owner has responsibility to ensure that the TPMS is working correctly. Failure to ensure that the TPMS is working correctly can result in severe injury or death.

For snap-in sensors, refer to your tire changing equipment manuals for proper instructions for mounting tire to rim when snap-in TPMS sensors are used. Avoid wet and extreme temperatures and never install a used screw or used snap-in valve. It is prohibited to use for racing and beyond 180 km/h (112.5 mph).

FCC Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 cm between the radiator and a human body.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

—Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

ISED Statement:

This equipment complies with ISED radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 cm between the radiator and a human body.

Cet équipement est conforme aux limites d'exposition aux rayonnements ISED établies pour un environnement non contrôlé. Cet équipement doit être installé et utilisé avec une distance minimale de 20 cm entre le radiateur et un corps humain.

This device contains licence-exempt transmitter(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

- (1) this device may not cause interference,
- (2) this device must accept any interference, including interference that may cause undesired operation of the device.

L'émetteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

- (1) L'appareil ne doit pas produire de brouillage;
- (2) L'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Warranty:

CUB warrants that the TPMS sensor shall be free from defects in workmanship and material during warranty period. CUB does not assume any liability in case of faulty, incorrect installation of the product, or by using other products causing TPMS sensor malfunction on the part of customer or user.

Always check our website for detail installation procedures, safety information and warranty policy.

