



Test Report (Class II Permissive Change)

Product Name	JukeBlox Networked Media Module
Model No	CX870-3BB
FCC ID.	ZQO-CX8703B

Applicant	STANDARD MICROSYSTEMS CORPORATION
Address	3930, EAST RAY ROAD SUITE 200, PHOENIX, ARIZONA, 85044-7176, UNITED STATES

Date of Receipt	Dec. 13, 2012
Issue Date	Dec. 24, 2012
Report No.	12C252R-RFUSP42V01
Report Version	V1.0

**0914**

The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Test Report Certification

Issue Date: Dec. 24, 2012

Report No.: 12C252R-RFUSP42V01



Accredited by NIST (NVLAP)
NVLAP Lab Code: 200533-0

Product Name	JukeBlox Networked Media Module
Applicant	STANDARD MICROSYSTEMS CORPORATION
Address	3930, EAST RAY ROAD SUITE 200, PHOENIX, ARIZONA, 85044-7176, UNITED STATES
Manufacturer	DONG GUAN G-COM COMPUTER CO., LTD
Model No.	CX870-3BB
FCC ID.	ZQO-CX8703B
EUT Rated Voltage	DC 3.3V
EUT Test Voltage	AC 120V/60Hz
Trade Name	PICO Module
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2010 ANSI C63.4: 2003, ANSI C63.10: 2009
Test Result	Complied

The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By :

A handwritten signature in blue ink that appears to read "Rita Huang".

(Senior Adm. Specialist / Rita Huang)

Tested By :

A handwritten signature in blue ink that appears to read "Alan Chen".

(Engineer / Alan Chen)

Approved By :

A handwritten signature in blue ink that appears to read "Vincent Lin".

(Manager / Vincent Lin)

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	4
1.1. EUT Description.....	4
1.2. Operational Description	6
1.3. Tested System Details.....	7
1.4. Configuration of Tested System	7
1.5. EUT Exercise Software	7
1.6. Test Facility	8
2. Peak Power Output	9
2.1. Test Equipment.....	9
2.2. Test Setup	9
2.3. Limits	9
2.4. Test Procedure	9
2.5. Uncertainty	9
2.6. Test Result of Peak Power Output.....	10
3. Radiated Emission.....	12
3.1. Test Equipment.....	12
3.2. Test Setup	13
3.3. Limits	14
3.4. Test Procedure	15
3.5. Uncertainty	15
3.6. Test Result of Radiated Emission.....	16
4. Band Edge	26
4.1. Test Equipment.....	26
4.2. Test Setup	27
4.3. Limits	27
4.4. Test Procedure	28
4.5. Uncertainty	28
4.6. Test Result of Band Edge	29
5. EMI Reduction Method During Compliance Testing	37

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	JukeBlox Networked Media Module
Trade Name	PICO Module
Model No.	CX870-3BB
FCC ID.	ZQO-CX8703B
Frequency Range	2412-2462MHz for 802.11b/g
Number of Channels	802.11b/g: 11
Data Speed	802.11b: 1-11Mbps, 802.11g: 6-54Mbps
Type of Modulation	802.11b:DSSS (DBPSK, DQPSK, CCK) 802.11g:OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type	Dipole
Antenna Gain	Refer to the table "Antenna List"
Channel Control	Auto

Antenna List

No.	Manufacturer	Model No.	Peak Gain
1	INPAQ	DAM-L0-B-N0-000-04-02	5.03 dBi for 2.4GHz

Note: The antenna of EUT is conform to FCC 15.203

802.11b/g Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 01:	2412 MHz	Channel 02:	2417 MHz	Channel 03:	2422 MHz	Channel 04:	2427 MHz
Channel 05:	2432 MHz	Channel 06:	2437 MHz	Channel 07:	2442 MHz	Channel 08:	2447 MHz
Channel 09:	2452 MHz	Channel 10:	2457 MHz	Channel 11:	2462 MHz		

Note:

1. The EUT is a JukeBlox Networked Media Module with a built-in 2.4GHz WLAN transceiver.
2. The antenna of EUT is conforming to FCC 15.203.
3. This is requesting a Class II permissive change for FCC ID: ZQO-CX8703B. Originally granted on 07/12/2011.

The major change filed under this application is:

Change #1: Addition new antenna, antenna gain: 5.03dBi (Dipole).

Change #2: Addition model number: CX870-3BB

Change #3: Remove one RF output connector.

Change #4: Addition shielding case.

Change #5: Change SDRAM manufacturers (ESMT and Winbond)

4. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
5. Lowest and highest data rates are tested in each mode. Only worst case is shown in the report. (802.11b is 1Mbps 、 802.11g is 6Mbps)
6. These tests are conducted on a sample for the purpose of demonstrating compliance of 802.11b/g transmitter with Part 15 Subpart C Paragraph 15.247 of spread spectrum devices.


1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	FCC ID	Power Cord
1 Notebook PC	DELL	PPT	N/A	DoC	Non-Shielded, 0.8m
2 Test Fixture	Lite-on	N/A	N/A	N/A	N/A

Signal Cable Type	Signal cable Description
A RS-232 Cable	Non-Shielded, 1.0m

1.4. Configuration of Tested System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown in section 1.4
- (2) Execute command on the notebook.
- (3) Configure the test mode, the test channel, and the data rate.
- (4) Start the continuous transmission.
- (5) Verify that the EUT works properly.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from

QuiTek Corporation's Web Site: <http://www.quietek.com/tw/ctg/cts/accreditations.htm>

The address and introduction of QuiTek Corporation's laboratories can be founded in our Web site:

<http://www.quietek.com/>

Site Description: File on
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Registration Number: 92195

Accreditation on NVLAP
NVLAP Lab Code: 200533-0

Site Name: Quietek Corporation
Site Address: No.5-22, Ruishukeng,
Linkou Dist. New Taipei City 24451,
Taiwan, R.O.C.
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
E-Mail : service@quietek.com

FCC Accreditation Number: TW1014

2. Peak Power Output

2.1. Test Equipment


Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X Power Meter	Anritsu	ML2495A/6K00003357	May, 2012
X Power Sensor	Anritsu	MA2411B/0738448	Jun, 2012

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

2.2. Test Setup

Conducted Measurement



2.3. Limits

The maximum peak power shall be less 1 Watt.

2.4. Test Procedure

The EUT was tested according to DTS test procedure of ANSI C63.10: 2009 for compliance to FCC 47CFR 15.247 requirements.

2.5. Uncertainty

± 1.27 dB

2.6. Test Result of Peak Power Output

Product : JukeBlox Networked Media Module
 Test Item : Peak Power Output Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)				Peak Power	Required Limit	Result
		1	2	5.5	11			
		Measurement Level (dBm)						
01	2412	17.42	--	--	--	19.44	<30dBm	Pass
06	2437	17.61	17.58	17.55	17.50	20.05	<30dBm	Pass
11	2462	17.77	--	--	--	19.53	<30dBm	Pass

Note: Peak Power Output Value =Reading value on peak power meter + cable loss

Product : JukeBlox Networked Media Module
 Test Item : Peak Power Output Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit	Result
		6	9	12	18	24	36	48	54			
		Measurement Level (dBm)										
01	2412	13.90	--	--	--	--	--	--	--	22.95	<30dBm	Pass
06	2437	13.92	13.89	13.85	13.83	13.81	13.79	13.78	13.76	23.05	<30dBm	Pass
11	2462	13.8	--	--	--	--	--	--	--	22.31	<30dBm	Pass

Note: Peak Power Output Value =Reading value on peak power meter + cable loss

3. Radiated Emission

3.1. Test Equipment


The following test equipment are used during the radiated emission test:

Test Site	Equipment		Manufacturer	Model No./Serial No.	Last Cal.
☒Site # 3	X	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2012
	X	Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2012
	X	Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2012
	X	Pre-Amplifier	Agilent	8447D/2944A09549	Sep., 2012
	X	Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2012
	X	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2012
	X	Coaxial Cable	QuiTek	QTK-CABLE/ CAB5	Feb., 2012
	X	Controller	QuiTek	QTK-CONTROLLER/ CTRL3	N/A
	X	Coaxial Switch	Anritsu	MP59B/6200265729	N/A


Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

3.2. Test Setup

Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



3.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209(a) Limits		
Frequency MHz	uV/m @3m	dBuV/m@3m
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Remarks: E field strength (dBuV/m) = 20 log E field strength (uV/m)

3.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2003 and tested according to DTS test procedure of ANSI C63.10: 2009 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2003 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

Radiated emission measurements below 1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The worst radiated emission is measured in the Open Area Test Site on the Final Measurement.

The frequency range from 30MHz to 10th harmonics is checked.

3.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

3.6. Test Result of Radiated Emission

Product : JukeBlox Networked Media Module
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
Peak Detector:					
4824.000	2.428	42.250	44.679	-29.321	74.000
7236.000	9.177	38.690	47.867	-26.133	74.000
9648.000	10.019	38.290	48.310	-25.690	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4824.000	2.836	43.910	46.747	-27.253	74.000
7236.000	9.676	39.450	49.126	-24.874	74.000
9648.000	10.556	40.400	50.957	-23.043	74.000

Average Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : JukeBlox Networked Media Module
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2437 MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV/m	dB	dBuV/m

Horizontal

Peak Detector:

4874.000	2.076	41.150	43.227	-30.773	74.000
7311.000	9.512	38.190	47.702	-26.298	74.000
9748.000	9.630	38.190	47.820	-26.180	74.000

Average Detector:

--

Vertical

Peak Detector:

4874.000	2.532	44.150	46.682	-27.318	74.000
7311.000	10.089	38.780	48.869	-25.131	74.000
9748.000	10.266	39.190	49.457	-24.543	74.000

Average Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : JukeBlox Networked Media Module
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
------------------	-------------------------	--------------------------	--------------------------------	--------------	-----------------

Horizontal

Peak Detector:

4924.000	2.191	40.460	42.651	-31.349	74.000
7386.000	10.373	39.210	49.584	-24.416	74.000
9848.000	9.964	39.050	49.014	-24.986	74.000

Average Detector:

--

Vertical

Peak Detector:

4924.000	2.805	43.450	46.255	-27.745	74.000
7386.000	11.180	38.290	49.470	-24.530	74.000
9848.000	10.801	38.640	49.441	-24.559	74.000

Average Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : JukeBlox Networked Media Module
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
------------------	-------------------------	--------------------------	--------------------------------	--------------	-----------------

Horizontal

Peak Detector:

4824.000	2.428	41.260	43.689	-30.311	74.000
7236.000	9.177	39.150	48.327	-25.673	74.000
9648.000	10.019	39.420	49.440	-24.560	74.000

Average Detector:

--

Vertical

Peak Detector:

4824.000	2.836	42.110	44.947	-29.053	74.000
7236.000	9.676	39.350	49.026	-24.974	74.000
9648.000	10.556	39.260	49.817	-24.183	74.000

Average Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : JukeBlox Networked Media Module
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2437 MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV/m	dB	dBuV/m

Horizontal

Peak Detector:

4874.000	2.076	41.230	43.307	-30.693	74.000
7311.000	9.512	38.180	47.692	-26.308	74.000
9748.000	9.630	38.090	47.720	-26.280	74.000

Average Detector:

--

Peak Detector:

4874.000	2.532	42.560	45.092	-28.908	74.000
7311.000	10.089	38.220	48.309	-25.691	74.000
9748.000	10.266	38.510	48.777	-25.223	74.000

Average Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : JukeBlox Networked Media Module
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
------------------	-------------------------	--------------------------	--------------------------------	--------------	-----------------

Horizontal

Peak Detector:

4924.000	2.191	42.090	44.281	-29.719	74.000
7386.000	10.373	39.050	49.424	-24.576	74.000
9848.000	9.964	38.640	48.604	-25.396	74.000

Average Detector:

--

Vertical

Peak Detector:

4924.000	2.805	41.500	44.305	-29.695	74.000
7386.000	11.180	39.160	50.340	-23.660	74.000
9848.000	10.801	39.170	49.971	-24.029	74.000

Average Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : JukeBlox Networked Media Module
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)(2437 MHz) (Winbond SDRAM)

Frequency MHz	Correct Factor	Reading dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
59.100	-11.901	48.309	36.408	-3.592	40.000
179.380	-11.904	49.326	37.422	-6.078	43.500
398.600	0.879	41.661	42.540	-3.460	46.000
610.060	3.657	30.909	34.566	-11.434	46.000
745.860	3.906	32.557	36.463	-9.537	46.000
926.280	6.832	27.894	34.726	-11.274	46.000
Vertical					
61.040	-11.587	46.726	35.139	-4.861	40.000
183.260	-3.735	42.387	38.652	-4.848	43.500
396.660	-2.039	40.084	38.045	-7.955	46.000
610.060	2.087	34.004	36.091	-9.909	46.000
790.480	2.693	30.397	33.090	-12.910	46.000
972.840	0.179	29.707	29.886	-24.114	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : JukeBlox Networked Media Module
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)(2437 MHz) (ESMT SDRAM)

Frequency MHz	Correct Factor	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
	dB				
Horizontal					
128.940	-7.390	36.525	29.135	-14.365	43.500
377.260	1.107	29.311	30.418	-15.582	46.000
507.240	2.529	32.242	34.771	-11.229	46.000
800.180	6.417	29.494	35.911	-10.089	46.000
875.840	5.816	28.709	34.525	-11.475	46.000
961.200	6.810	34.617	41.427	-12.573	54.000
Vertical					
45.520	-10.625	40.789	30.164	-9.836	40.000
507.240	0.429	29.731	30.160	-15.840	46.000
749.740	2.023	31.793	33.816	-12.184	46.000
800.180	2.637	31.075	33.712	-12.288	46.000
875.840	0.516	31.096	31.612	-14.388	46.000
961.200	3.310	37.772	41.082	-12.918	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : JukeBlox Networked Media Module
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)(2437 MHz) (Winbond SDRAM)

Frequency MHz	Correct Factor	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
	dB				
Horizontal					
111.480	-7.489	45.734	38.246	-5.254	43.500
177.440	-10.838	50.945	40.107	-3.393	43.500
414.120	-0.195	36.278	36.083	-9.917	46.000
610.060	3.657	34.004	37.661	-8.339	46.000
745.860	3.906	35.442	39.348	-6.652	46.000
920.460	6.792	29.165	35.957	-10.043	46.000
Vertical					
105.660	-4.576	42.827	38.250	-5.250	43.500
202.660	-5.573	43.431	37.859	-5.641	43.500
383.080	0.195	34.526	34.721	-11.279	46.000
610.060	2.087	34.004	36.091	-9.909	46.000
790.480	2.693	30.397	33.090	-12.910	46.000
932.100	3.430	28.174	31.604	-14.396	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : JukeBlox Networked Media Module
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)(2437 MHz) (ESMT SDRAM)

Frequency MHz	Correct Factor	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
	dB				
Horizontal					
128.940	-7.390	36.327	28.937	-14.563	43.500
253.100	-5.669	40.051	34.382	-11.618	46.000
507.240	2.529	32.746	35.275	-10.725	46.000
800.180	6.417	28.604	35.021	-10.979	46.000
875.840	5.816	28.358	34.174	-11.826	46.000
961.200	6.810	34.702	41.512	-12.488	54.000
Vertical					
127.000	-3.712	35.763	32.051	-11.449	43.500
507.240	0.429	30.048	30.477	-15.523	46.000
749.740	2.023	30.959	32.982	-13.018	46.000
800.180	2.637	30.239	32.876	-13.124	46.000
875.840	0.516	30.876	31.392	-14.608	46.000
961.200	3.310	37.223	40.533	-13.467	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

4. Band Edge

4.1. Test Equipment

RF Conducted Measurement

The following test equipments are used during the band edge tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2012
Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2012
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2012

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with "X" are used to measure the final test results.

RF Radiated Measurement:

The following test equipments are used during the band edge tests:


Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X Site # 3	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2012
	X Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2012
	Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2012
	X Pre-Amplifier	Agilent	8447D/2944A09549	Sep., 2012
	X Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2012
	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2012
	X Coaxial Cable	QuiTek	QTK-CABLE/ CAB5	Feb., 2012
	X Controller	QuiTek	QTK-CONTROLLER/ CTRL3	N/A
	X Coaxial Switch	Anritsu	MP59B/6200265729	N/A

Note:


1. All instruments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

4.2. Test Setup

RF Conducted Measurement



RF Radiated Measurement:



4.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

4.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2003 and tested according to DTS test procedure of ANSI C63.10: 2009 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2003 on radiated measurement.

4.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

4.6. Test Result of Band Edge

Product : JukeBlox Networked Media Module
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2380.800	33.732	24.466	58.197	74.000	54.000	Pass
01 (Peak)	2390.000	33.739	22.176	55.915	74.000	54.000	Pass
01 (Peak)	2413.000	33.775	63.153	96.927	--	--	--
01 (Average)	2390.000	33.739	11.756	45.495	74.000	54.000	Pass
01 (Average)	2414.800	33.778	59.340	93.119	--	--	--

Figure Channel 01:

Horizontal (Peak)





Figure Channel 01:

Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : JukeBlox Networked Media Module
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2386.200	32.293	28.670	60.963	74.000	54.000	Pass
01 (Peak)	2390.000	32.267	25.055	57.322	74.000	54.000	Pass
01 (Peak)	2413.000	32.254	77.947	110.200	--	--	--
01 (Average)	2386.400	32.292	20.498	52.790	74.000	54.000	Pass
01 (Average)	2390.000	32.267	16.254	48.521	74.000	54.000	Pass
01 (Average)	2411.200	32.245	74.249	106.494	--	--	--

Figure Channel 01:

Vertical (Peak)





Figure Channel 01:

Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : JukeBlox Networked Media Module
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2462.900	33.895	63.089	96.984	--	--	--
11 (Peak)	2483.500	33.951	21.622	55.572	74.000	54.000	Pass
11 (Peak)	2487.500	33.961	23.670	57.630	74.000	54.000	Pass
11 (Average)	2461.100	33.890	59.384	93.274	--	--	--
11 (Average)	2483.500	33.951	11.827	45.777	74.000	54.000	Pass
11 (Average)	2486.900	33.959	12.299	46.258	74.000	54.000	Pass

Figure Channel 11:

Horizontal (Peak)





Figure Channel 11:

Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : JukeBlox Networked Media Module
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2462.900	32.485	76.216	108.701	--	--	--
11 (Peak)	2483.500	32.586	24.277	56.862	74.000	54.000	Pass
11 (Peak)	2487.900	32.607	28.960	61.566	74.000	54.000	Pass
11 (Average)	2461.100	32.476	72.631	105.107	--	--	--
11 (Average)	2483.500	32.586	15.725	48.310	74.000	54.000	Pass
11 (Average)	2487.100	32.602	19.845	52.447	74.000	54.000	Pass

Figure Channel 11:

Vertical (Peak)





Figure Channel 11:

Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : JukeBlox Networked Media Module
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2390.000	33.739	28.053	61.792	74.000	54.000	Pass
01 (Peak)	2409.400	33.767	66.416	100.183	--	--	--
01 (Average)	2390.000	33.739	12.464	46.203	74.000	54.000	Pass
01 (Average)	2413.800	33.776	53.776	87.552	--	--	--

Figure Channel 01:

Horizontal (Peak)





Figure Channel 01:

Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : JukeBlox Networked Media Module
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2389.400	32.271	40.113	72.384	74.000	54.000	Pass
01 (Peak)	2390.000	32.267	39.101	71.368	74.000	54.000	Pass
01 (Peak)	2415.200	32.263	78.711	110.974	--	--	--
01 (Average)	2390.000	32.267	18.676	50.943	74.000	54.000	Pass
01 (Average)	2410.000	32.244	65.675	97.919	--	--	--

Figure Channel 01:

Vertical (Peak)





Figure Channel 01:

Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : JukeBlox Networked Media Module
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2460.073	33.887	66.023	99.911	--	--	--
11 (Peak)	2483.500	33.951	27.859	61.809	74.000	54.000	Pass
11 (Average)	2464.069	33.898	53.225	87.123	--	--	--
11 (Average)	2483.500	33.951	12.856	46.806	74.000	54.000	Pass

Figure Channel 11:

Horizontal (Peak)





Figure Channel 11:

Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : JukeBlox Networked Media Module
 Test Item : Band Edge Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2463.470	32.487	79.325	111.812	--	--	--
11 (Peak)	2483.500	32.586	38.463	71.048	74.000	54.000	Pass
11 (Average)	2459.474	32.468	66.357	98.825	--	--	--
11 (Average)	2483.500	32.586	19.495	52.080	74.000	54.000	Pass

Figure Channel 11:

Vertical (Peak)





Figure Channel 11:

Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

5. EMI Reduction Method During Compliance Testing

No modification was made during testing.

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs