

# RF EXPOSURE REPORT



Report No.: 15050057-FCC-H2

Supersede Report No.: N/A

Applicant	b mobile HK Limited	
Product Name	Mobile phone	
Model No.	AX605	
Serial No.	N/A	
Test Standard	FCC 2.1093:2014	
Test Date	December 12 to December 31, 2015	
Issue Date	December 31, 2015	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
Winnie Zhang	David Huang	
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15050057-FCC-H2
Page	3 of 9

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.8	
5.1 RF EXPOSURE.....	8
5.2 TEST RESULT .....	9

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
15050057-FCC-H2	NONE	Original	December 31, 2015

## 2. Customer information

Applicant Name	b mobile HK Limited
Applicant Add	Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong
Manufacturer	b mobile HK Limited
Manufacturer Add	Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

#### 4. Equipment under Test (EUT) Information

Description of EUT: Mobile phone

Main Model: AX605

Serial Model: N/A

Date EUT received: December 11, 2015

Test Date(s): December 12 to December 31, 2015

GSM850: -1dBi

PCS1900: 0dBi

UMTS-FDD Band V: 0dBi

Antenna Gain: UMTS-FDD Band II: 0dBi

Bluetooth: 0.5dBi

WIFI: 0.5dBi

GPS: -2dBi

GSM / GPRS: GMSK

EGPRS: GMSK, 8PSK

UMTS-FDD: QPSK, 16QAM

Type of Modulation: 802.11b/g/n: DSSS, OFDM

Bluetooth: GFSK,  $\pi/4$ DQPSK, 8DPSK

GPS:BPSK

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz

PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz

UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz

UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz;

RF Operating Frequency (ies): RX: 1932.4 ~ 1987.6 MHz

WIFI: 802.11b/g/n(20M): 2412-2472 MHz

WIFI: 802.11n(40M): 2422-2462 MHz

Bluetooth: 2402-2480 MHz

GPS RX: 1575.42 MHz

Test Report	15050057-FCC-H2
Page	7 of 9

GSM 850: 124CH  
PCS1900: 299CH  
UMTS-FDD Band V : 102CH  
UMTS-FDD Band II : 277CH  
WIFI :802.11b/g/n(20M): 13CH  
WIFI :802.11n(40M): 9CH  
Bluetooth: 79CH  
GPS:1CH

Battery:  
Model:A3506  
Standard Voltage:DC3.7V

Input Power:  
Rated Capacity:1300mAh,4.81Wh  
Adapter:  
Model:N/A  
Input: AC100-240V; 50/60Hz; 0.15A  
Output: DC 5.0V,500mA

Port: Power Port, Earphone Port, USB Port

Trade Name : Bmobile

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: ZSW-30-022

## 5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

### 5.1 RF Exposure

#### **Standard Requirement:**

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16}$  where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

## 5.2 Test Result

### Bluetooth Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	3.773	4±1	5	3.162	0.98	3
	Mid	2441	4.168	4±1	5	3.162	0.99	3
	High	2480	<b>4.522</b>	4±1	5	3.162	1.00	3
π / 4 DQPSK	Low	2402	3.693	4±1	5	3.162	0.98	3
	Mid	2441	4.048	4±1	5	3.162	0.99	3
	High	2480	4.359	4±1	5	3.162	1.00	3
8-DPSK	Low	2402	3.738	4±1	5	3.162	0.98	3
	Mid	2441	4.149	4±1	5	3.162	0.99	3
	High	2480	4.475	4±1	5	3.162	1.00	3

### WIFI Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
802.11b	Low	2412	8.99	8.5±1	9.5	8.913	2.77	3
	Mid	2442	8.90	8.5±1	9.5	8.913	2.79	3
	High	2472	<b>9.70</b>	8.7±1	9.7	9.333	2.93	3
802.11g	Low	2412	9.13	8.5±1	9.5	8.913	2.77	3
	Mid	2442	9.20	8.5±1	9.5	8.913	2.79	3
	High	2472	<b>9.35</b>	8.5±1	9.5	8.913	2.80	3
802.11n (20M)	Low	2412	8.92	8.5±1	9.5	8.913	2.77	3
	Mid	2442	9.02	8.5±1	9.5	8.913	2.79	3
	High	2472	<b>9.26</b>	8.5±1	9.5	8.913	2.80	3
802.11n (40M)	Low	2422	8.83	8.5±1	9.5	8.913	2.77	3
	Mid	2442	<b>9.25</b>	8.5±1	9.5	8.913	2.79	3
	High	2462	9.08	8.5±1	9.5	8.913	2.80	3

**Result:** Compliance

No SAR measurement is required.