

TEST REPORT

FCC ID:ZSW-30-029

Product: Mobile Phone

Model No.: AX705

Additional Model No.: N/A

Trade Mark: Bmobile

Report No.: TCT160519E035

Issued Date: May 26, 2016

Issued for:

b mobile HK Limited

**Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak
Street; Kwai Chung; New Territories; Hong Kong, China.**

Issued By:

Shenzhen Tongce Testing Lab.

1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

TEL: +86-755-27673339

FAX: +86-755-27673332

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. Test Certification.....	3
2. Test Result Summary	4
3. EUT Description	5
4. Genera Information.....	8
4.1. Test environment and mode.....	8
4.2. Description of Support Units.....	10
5. Facilities and Accreditations	11
5.1. Facilities	11
5.2. Location	11
5.3. Measurement Uncertainty.....	11
6. Test Results and Measurement Data	12
6.1. Antenna requirement	12
6.2. Conducted Emission.....	13
6.3. Emission Bandwidth	18
6.4. Power Spectral Density.....	19
6.5. Conducted Band Edge and Spurious Emission Measurement	20
6.6. Radiated Spurious Emission Measurement	22

Appendix A: Test Result of Conducted Test

Appendix B: Photographs of Test Setup

Appendix C: Photographs of EUT

1. Test Certification

Product:	Mobile Phone
Model No.:	AX705
Additional Model No.:	N/A
Applicant:	b mobile HK Limited
Address:	Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong, China.
Manufacturer:	b mobile HK Limited
Address:	Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong, China.
Date of Test:	May 19 –May 24, 2016
Applicable Standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247 KDB 558074 D01 DTS Meas Guidance v03r05

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:

 Sky Luo


Date: May 24, 2016

Reviewed By:

 Joe Zhou

Date: May 26, 2016

Approved By:

 Tomsin

Date: May 26, 2016

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3) §2.1046	PASS
6dB Emission Bandwidth	§15.247 (a)(2) §2.1049	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	1§5.247(d) §2.1051, §2.1057	PASS
Spurious Emission	§15.205/§15.209 §2.1053, §2.1057	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. EUT Description

Product Name:	Mobile Phone
Model :	AX705
Additional Model:	N/A
Trade Mark:	Bmobile
Hardware Version:	G3729_02
Software Version:	MOLY.WR8.W1449.MD.WG.MP.V5.P7
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)) 2422MHz~2452MHz (802.11n(HT40))
Channel Separation:	5MHz
Number of Channel:	11 for 802.11b/802.11g/802.11n(HT20) 7 for 802.11n(HT40)
Modulation Technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum (DSSS)
Modulation Technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Data speed (IEEE 802.11n):	Up to 135Mbps
Antenna Type:	Internal antenna
Antenna Gain:	-0.82dBi
Power Supply:	DC 3.8V from rechargeable lithium battery. Adapter information Input: AC 100-240V, 50/60Hz, 0.2A Output: DC 5V, 1A

Operation Frequency each of channel For 802.11b/g/n(HT20)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Operation Frequency each of channel For 802.11n (HT40)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
--	--	4	2427MHz	7	2442MHz	--	--
--	--	5	2432MHz	8	2447MHz	--	--
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

802.11b/802.11g/802.11n (HT20)

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The Highest channel	2462MHz

802.11n (HT40)

Channel	Frequency
The lowest channel	2422MHz
The middle channel	2437MHz
The Highest channel	2452MHz

TX output power setting

Mode	Power setting (dBm)
802.11b for all channel setting	19
802.11g for Lowest channel setting	15
802.11g for Middle channel setting	16
802.11g for Highest channel setting	15
802.11n(HT20) for Lowest channel setting	15
802.11n(HT20) for Middle channel setting	16
802.11n(HT20) for Highest channel setting	15
802.11n(HT40) for Lowest channel setting	13
802.11n(HT40) for Lowest channel setting	16
802.11n(HT40) for Highest channel setting	13

4. General Information

4.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 98.46%)
<p>The sample was placed 0.8m & 1.5m for the measurement below & above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. For the full battery state and The output power to the maximum state.</p>	
Test software:	
<p>Enter the mobile phone engineering mode by *###3646633#* Set fixed test channel, data rate, duty cycle and power setting under engineering mode.</p>	
<p>We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:</p>	
Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	6.5Mbps
802.11n(HT40)	13.5Mbps
Final Test Mode:	

Operation mode:	Keep the EUT in continuous transmitting with modulation
1. For WIFI function, the engineering test program was provided and enabled to make EUT continuous transmit/receive. 2. According to ANSI C63.10 standards, the test results are both the “worst case” and “worst setup” 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(HT20). 13.5Mbps for 802.11n(HT40) Duty cycle setting during the transmission is 98.5% with maximum power setting for all modulations.	

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

5. Facilities and Accreditations

5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 572331

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

- CNAS - Registration No.: CNAS L6165

Shenzhen TCT Testing Technology Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6165.

5.2. Location

Shenzhen Tongce Testing Lab

Address: 1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

Tel: 86-755-36638142

5.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^\circ\text{C}$
7	Humidity	$\pm 1.0\%$

6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
-----------------------	-------------------------------------

15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

E.U.T Antenna:

The WIFI antenna is a internal antenna which permanently attached, and the best case gain of the antenna is -0.82dBi.



6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	<p>Reference Plane</p> <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test Mode:	Charging + transmitting with modulation														
Test Procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 														
Test Result:	PASS														

6.2.2. Test Instruments


Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCS30	100139	Sep. 11, 2016
LISN	Schwarzbeck	NSLK 8126	8126453	Sep. 16, 2016
Coax cable	TCT	CE-05	N/A	Sep. 11, 2016
EMI Test Software	Shurples Technology	EZ-EMC	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site Chamber #2 Phase: **L1** Temperature: 25 (C)
Limit: FCC Part 15B Class B Conduction(QP) Power: AC 120V/60Hz Humidity: 54 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1734	38.25	11.48	49.73	64.79	-15.06	QP	
2		0.1734	24.29	11.48	35.77	54.79	-19.02	AVG	
3		0.2320	33.56	11.44	45.00	62.37	-17.37	QP	
4		0.2320	20.68	11.44	32.12	52.37	-20.25	AVG	
5		0.2945	30.38	11.41	41.79	60.39	-18.60	QP	
6		0.2945	15.97	11.41	27.38	50.39	-23.01	AVG	
7		0.5641	29.55	11.27	40.82	56.00	-15.18	QP	
8		0.5641	16.80	11.27	28.07	46.00	-17.93	AVG	
9		0.9742	29.61	11.17	40.78	56.00	-15.22	QP	
10		0.9742	17.45	11.17	28.62	46.00	-17.38	AVG	
11		2.9742	20.03	11.33	31.36	56.00	-24.64	QP	
12		2.9742	8.64	11.33	19.97	46.00	-26.03	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)

Limit (dB μ V) = Limit stated in standard


Margin (dB) = Measurement (dB μ V) – Limits (dB μ V)

Q.P. = Quasi-Peak

AVG = average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site Chamber #2				Phase:	N	Temperature:	25 (C)
Limit: FCC Part 15B Class B Conduction(QP)				Power:	AC 120V/60Hz	Humidity:	54 %
No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dB μ V	dB	dB μ V	dB	Detector
1	*	0.1773	39.85	11.48	51.33	64.61	-13.28
2		0.1773	24.13	11.48	35.61	54.61	-19.00
3		0.2281	33.06	11.45	44.51	62.52	-18.01
4		0.2281	17.52	11.45	28.97	52.52	-23.55
5		0.2867	29.70	11.42	41.12	60.62	-19.50
6		0.2867	13.95	11.42	25.37	50.62	-25.25
7		0.5250	27.28	11.29	38.57	56.00	-17.43
8		0.5250	17.20	11.29	28.49	46.00	-17.51
9		1.1109	24.88	11.22	36.10	56.00	-19.90
10		1.1109	11.53	11.22	22.75	46.00	-23.25
11		4.1563	22.18	10.91	33.09	56.00	-22.91
12		4.1563	10.58	10.91	21.49	46.00	-24.51

Note1:

Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)

Limit (dB μ V) = Limit stated in standard

Margin (dB) = Measurement (dB μ V) - Limits (dB μ V)

Q.P. = Quasi-Peak

AVG = average

is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Note2: Measurements were conducted in all three channels (high, middle, low) and all modulations (802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)), and the worst case Mode (lowest channel and 802.11b) was submitted only.

6.2.4. Maximum Conducted (Average) Output Power

6.2.5. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB 558074 D01 DTS Meas Guidance v03r05
Limit:	30dBm
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r05. 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Measure the conducted output power and record the results in the test report.
Test Result:	PASS


6.2.6. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 12, 2016
RF cable	TCT	RE-06	N/A	Sep. 12, 2016
Antenna Connector	TCT	RFC-01	N/A	Sep. 12, 2016

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.3. Emission Bandwidth

6.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB 558074 D01 DTS Meas Guidance v03r05
Limit:	>500kHz
Test Setup:	 <p>Spectrum Analyzer EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r05. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS


6.3.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 12, 2016
RF cable	TCT	RE-06	N/A	Sep. 12, 2016
Antenna Connector	TCT	RFC-01	N/A	Sep. 12, 2016

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.4. Power Spectral Density

6.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB 558074 D01 DTS Meas Guidance v03r05
Limit:	The average power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
Test Setup:	 <p>Spectrum Analyzer EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows Measurement Procedure 10.3 Method AVGPSD of FCC KDB Publication No.558074 D01 DTS Meas. Guidance v03r05 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. Video bandwidth VBW $\geq 3 \times \text{RBW}$. Set the span to at least 1.5 times the OBW. 5. Detector = RMS, Sweep time = auto couple. 6. Employ trace averaging (RMS) mode over a minimum of 100 traces. Use the peak marker function to determine the maximum power level. 7. Measure and record the results in the test report.
Test Result:	PASS

6.4.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 12, 2016
RF cable	TCT	RE-06	N/A	Sep. 12, 2016
Antenna Connector	TCT	RFC-01	N/A	Sep. 12, 2016

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.5. Conducted Band Edge and Spurious Emission Measurement

6.5.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Limit:	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
Test Setup:	 <p>Spectrum Analyzer EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05. 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d). 5. Measure and record the results in the test report. 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS


6.5.2. Test Instruments


RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 12, 2016
RF cable	TCT	RE-06	N/A	Sep. 12, 2016
Antenna Connector	TCT	RFC-01	N/A	Sep. 12, 2016

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).


6.6. Radiated Spurious Emission Measurement

6.6.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209																																															
Test Method:	ANSI C63.10: 2013																																															
Frequency Range:	9 kHz to 25 GHz																																															
Measurement Distance:	3 m																																															
Antenna Polarization:	Horizontal & Vertical																																															
Operation mode:	Transmitting mode with modulation																																															
Receiver Setup:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Detector</th> <th>RBW</th> <th>VBW</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>9kHz- 150kHz</td> <td>Quasi-peak</td> <td>200Hz</td> <td>1kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td>150kHz- 30MHz</td> <td>Quasi-peak</td> <td>9kHz</td> <td>30kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td>30MHz-1GHz</td> <td>Quasi-peak</td> <td>100KHz</td> <td>300KHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td rowspan="2">Above 1GHz</td><td>Peak</td> <td>1MHz</td> <td>3MHz</td> <td>Peak Value</td> </tr> <tr> <td>Peak</td> <td>1MHz</td> <td>10Hz</td> <td>Average Value</td> </tr> </tbody> </table>					Frequency	Detector	RBW	VBW	Remark	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	Peak	1MHz	10Hz	Average Value														
Frequency	Detector	RBW	VBW	Remark																																												
9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value																																												
150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value																																												
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																																												
Above 1GHz	Peak	1MHz	3MHz	Peak Value																																												
	Peak	1MHz	10Hz	Average Value																																												
Limit:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Field Strength (microvolts/meter)</th> <th>Measurement Distance (meters)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>0.009-0.490</td> <td>2400/F(KHz)</td> <td>300</td> <td></td> </tr> <tr> <td>0.490-1.705</td> <td>24000/F(KHz)</td> <td>30</td> <td></td> </tr> <tr> <td>1.705-30</td> <td>30</td> <td>30</td> <td></td> </tr> <tr> <td>30-88</td> <td>100</td> <td>3</td> <td></td> </tr> <tr> <td>88-216</td> <td>150</td> <td>3</td> <td></td> </tr> <tr> <td>216-960</td> <td>200</td> <td>3</td> <td></td> </tr> <tr> <td>Above 960</td> <td>500</td> <td>3</td> <td></td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Frequency</th> <th>Field Strength (microvolts/meter)</th> <th>Measurement Distance (meters)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Above 1GHz</td><td>500</td> <td>3</td> <td>Average</td> </tr> <tr> <td>5000</td> <td>3</td> <td>Peak</td> </tr> </tbody> </table>					Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector	0.009-0.490	2400/F(KHz)	300		0.490-1.705	24000/F(KHz)	30		1.705-30	30	30		30-88	100	3		88-216	150	3		216-960	200	3		Above 960	500	3		Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector	Above 1GHz	500	3	Average	5000	3	Peak
Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector																																													
0.009-0.490	2400/F(KHz)	300																																														
0.490-1.705	24000/F(KHz)	30																																														
1.705-30	30	30																																														
30-88	100	3																																														
88-216	150	3																																														
216-960	200	3																																														
Above 960	500	3																																														
Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector																																													
Above 1GHz	500	3	Average																																													
	5000	3	Peak																																													
Test setup:	<p>For radiated emissions below 30MHz</p>  <p>Distance = 3m</p> <p>Turn table</p> <p>EUT</p> <p>Ground Plane</p> <p>30MHz to 1GHz</p>																																															



Above 1GHz



1. For the radiated emission test below 1GHz:
 The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.

For the radiated emission test above 1GHz:

Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for

Test Procedure:

	<p>receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</p> <p>4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>5. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none">(1) Span shall wide enough to fully capture the emission being measured;(2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;(3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement. <p>For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p>
Test results:	PASS

6.6.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
ESPI Test Receiver	ROHDE&SCHW ARZ	ESVD	100008	Sep. 11, 2016
Spectrum Analyzer	ROHDE&SCHW ARZ	FSEM	848597/001	Sep. 11, 2016
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 12, 2016
Pre-amplifier	EM Electronics Corporation CO.,LTD	EM30265	07032613	Sep. 11, 2016
Pre-amplifier	HP	8447D	2727A05017	Sep. 11, 2016
Loop antenna	ZHINAN	ZN30900A	12024	Sep. 13, 2016
Broadband Antenna	Schwarzbeck	VULB9163	340	Sep. 13, 2016
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Sep. 13, 2016
Horn Antenna	Schwarzbeck	BBHA 9170	373	Sep. 13, 2016
Coax cable	TCT	RE-low-01	N/A	Sep. 11, 2016
Coax cable	TCT	RE-high-02	N/A	Sep. 11, 2016
Coax cable	TCT	RE-low-03	N/A	Sep. 11, 2016
Coax cable	TCT	RE-High-04	N/A	Sep. 11, 2016
Antenna Mast	CCS	CC-A-4M	N/A	Sep. 12, 2016
EMI Test Software	Shurples Technology	EZ-EMC	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.6.3. Test Data

Please refer to following diagram for individual


Below 1GHz

Horizontal:



Site				Polarization: Horizontal				Temperature: 25		
Limit: FCC Part 15B Class B RE_3 m				Power: DC 3.8V				Humidity: 54 %		
No.	Mk.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	Degree	Comment
		Level	Factor	ment	dBuV/m	dB	Detector	cm	degree	
		MHz	dBuV	dB	dBuV/m	dB				
1	*	30.0000	36.71	-13.72	22.99	40.00	-17.01	peak	0	
2		55.0423	28.99	-12.42	16.57	40.00	-23.43	peak	0	
3		99.3002	26.84	-11.54	15.30	43.50	-28.20	peak	0	
4		214.4372	26.11	-11.18	14.93	43.50	-28.57	peak	0	
5		455.3323	26.98	-4.41	22.57	46.00	-23.43	peak	0	
6		1000.000	26.04	6.06	32.10	54.00	-21.90	peak	0	

Vertical:



Site	Polarization: Vertical	Temperature: 25
Limit: FCC Part 15B Class B RE_3 m	Power: DC 3.8V	Humidity: 54 %

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1 *	30.5100	38.94	-13.65	25.29	40.00	-14.71	peak	0	
2	49.1911	35.04	-12.08	22.96	40.00	-17.04	peak	0	
3	54.1221	30.09	-12.35	17.74	40.00	-22.26	peak	0	
4	79.3103	32.42	-16.35	16.07	40.00	-23.93	peak	0	
5	432.8764	27.23	-5.13	22.10	46.00	-23.90	peak	0	
6	730.0143	26.93	0.52	27.45	46.00	-18.55	peak	0	

Note: 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low) and all modulations (802.11b, 802.11g, 802.11n(HT20)), and the worst case Mode (lowest channel and 802.11b) was submitted only.

Test Result of Radiated Spurious at Band edges

Modulation Type: 802.11b

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB μ V/m)	AV limit (dB μ V/m)
2310	H	45.11	-4.20	40.91	74.00	54.00
2377.38	H	47.76	-4.10	43.66	74.00	54.00
2390	H	52.92	-3.94	48.98	74.00	54.00
2310	V	43.57	-4.20	39.37	74.00	54.00
2377.38	V	53.33	-4.10	49.23	74.00	54.00
2390	V	55.39	-3.94	51.45	74.00	54.00

Modulation Type: 802.11b

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB μ V/m)	AV limit (dB μ V/m)
2483.5	H	49.89	-3.60	46.29	74.00	54.00
2487.09	H	47.42	-3.50	43.92	74.00	54.00
2500	H	44.26	-3.34	40.92	74.00	54.00
2483.5	V	53.65	-3.60	50.05	74.00	54.00
2487.09	V	46.72	-3.50	43.22	74.00	54.00
2500	V	42.18	-3.34	38.84	74.00	54.00

Modulation Type: 802.11g

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB μ V/m)	AV limit (dB μ V/m)
2310	H	45.28	-4.20	41.08	74.00	54.00
2388.96	H	47.75	-4.10	43.65	74.00	54.00
2390	H	52.68	-3.94	48.74	74.00	54.00
2310	V	43.61	-4.20	39.41	74.00	54.00
2388.96	V	53.42	-4.10	49.32	74.00	54.00
2390	V	55.59	-3.94	51.65	74.00	54.00

Modulation Type: 802.11g

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB μ V/m)	AV limit (dB μ V/m)
2483.5	H	50.17	-3.60	46.57	74.00	54.00
2487.59	H	47.42	-3.50	43.92	74.00	54.00
2500	H	44.56	-3.34	41.22	74.00	54.00
2483.5	V	53.94	-3.60	50.34	74.00	54.00
2487.59	V	46.76	-3.50	43.26	74.00	54.00
2500	V	41.57	-3.34	38.23	74.00	54.00

Modulation Type: 802.11n(20MHz)

Low channel: 2412 MHz						
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB μ V/m)	AV limit (dB μ V/m)
2310	H	44.92	-4.20	40.72	74.00	54.00
2388.01	H	47.88	-4.10	43.78	74.00	54.00
2390	H	52.69	-3.94	48.75	74.00	54.00
2310	V	43.63	-4.20	39.43	74.00	54.00
2388.01	V	53.82	-4.10	49.72	74.00	54.00
2390	V	55.15	-3.94	51.21	74.00	54.00

Modulation Type: 802.11n(20MHz)

High channel: 2462 MHz						
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB μ V/m)	AV limit (dB μ V/m)
2483.5	H	50.17	-3.60	46.57	74.00	54.00
2392.55	H	47.42	-3.50	43.92	74.00	54.00
2500	H	44.37	-3.34	41.03	74.00	54.00
2483.5	V	54.14	-3.60	50.54	74.00	54.00
2392.55	V	46.75	-3.50	43.25	74.00	54.00
2500	V	42.02	-3.34	38.68	74.00	54.00

Modulation Type: 802.11n(40MHz)

Low channel: 2422 MHz						
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB μ V/m)	AV limit (dB μ V/m)
2310	H	45.14	-4.20	40.94	74.00	54.00
2354.01	H	47.88	-4.10	43.78	74.00	54.00
2390	H	52.79	-3.94	48.85	74.00	54.00
2310	V	43.69	-4.20	39.49	74.00	54.00
2354.01	V	53.58	-4.10	49.48	74.00	54.00
2390	V	55.12	-3.94	51.18	74.00	54.00

Modulation Type: 802.11n(40MHz)

High channel: 2452 MHz						
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB μ V/m)	AV limit (dB μ V/m)
2483.5	H	50.85	-3.60	47.25	74.00	54.00
2496.0	H	47.27	-3.50	43.77	74.00	54.00
2500	H	44.32	-3.34	40.98	74.00	54.00
2483.5	V	54.38	-3.60	50.78	74.00	54.00
2496.0	V	46.57	-3.50	43.07	74.00	54.00
2500	V	41.99	-3.34	38.65	74.00	54.00

Note:

1. Peak Final Emission Level=Peak Reading + Correction Factor;
2. Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

Above 1GHz

Modulation Type: 802.11b

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
4824	H	50.21	---	0.75	50.96	---	74	54	-3.04
7236	H	41.81	---	9.87	51.68	---	74	54	-2.32
---	H	---	---	---	---	---	---	---	---
4824	V	49.51	---	0.75	50.26	---	74	54	-3.74
7236	V	42.56	---	9.87	52.43	---	74	54	-1.57
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
4874	H	49.16	---	0.97	50.13	---	74	54	-3.87
7311	H	41.48	---	9.83	51.31	---	74	54	-2.69
---	H	---	---	---	---	---	---	---	---
4874	V	48.86	---	0.97	49.83	---	74	54	-4.17
7311	V	41.39	---	9.83	51.22	---	74	54	-2.78
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
4924	H	49.34	---	1.18	50.52	---	74	54	-3.48
7386	H	40.32	---	10.07	50.39	---	74	54	-3.61
---	H	---	---	---	---	---	---	---	---
4924	V	47.61	---	1.18	48.79	---	74	54	-5.21
7386	V	41.74	---	10.07	51.81	---	74	54	-2.19
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB μ V/m)-Average limit (dB μ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---”in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: 802.11g

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
4824	H	50.13	---	0.75	50.88	---	74	54	-3.12
7236	H	41.93	---	9.87	51.80	---	74	54	-2.20
---	H	---	---	---	---	---	---	---	---
4824	V	49.55	---	0.75	50.3	---	74	54	-3.70
7236	V	42.79	---	9.87	52.66	---	74	54	-1.34
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
4874	H	49.16	---	0.97	50.13	---	74	54	-3.87
7311	H	41.47	---	9.83	51.30	---	74	54	-2.70
---	H	---	---	---	---	---	---	---	---
4874	V	48.88	---	0.97	49.85	---	74	54	-4.15
7311	V	41.42	---	9.83	51.25	---	74	54	-2.75
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
4924	H	49.34	---	1.18	50.52	---	74	54	-3.48
7386	H	40.32	---	10.07	50.39	---	74	54	-3.61
---	H	---	---	---	---	---	---	---	---
4924	V	47.27	---	1.18	48.45	---	74	54	-5.55
7386	V	41.46	---	10.07	51.53	---	74	54	-2.47
---	V	---	---	---	---	---	---	---	---

Note:

3. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
4. Margin (dB) = Emission Level (Peak) (dB μ V/m)-Average limit (dB μ V/m)
5. The emission levels of other frequencies are very lower than the limit and not show in test report.
6. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
7. Data of measurement shown “---” in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: 802.11n (HT20)

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
4824	H	50.26	---	0.75	51.01	---	74	54	-2.99
7236	H	41.92	---	9.87	51.79	---	74	54	-2.21
---	H	---	---	---	---	---	---	---	---
4824	V	49.42	---	0.75	50.17	---	74	54	-3.83
7236	V	42.59	---	9.87	52.46	---	74	54	-1.54
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
4874	H	49.12	---	0.97	50.09	---	74	54	-3.91
7311	H	41.48	---	9.83	51.31	---	74	54	-2.69
---	H	---	---	---	---	---	---	---	---
4874	V	49.08	---	0.97	50.05	---	74	54	-3.95
7311	V	41.39	---	9.83	51.22	---	74	54	-2.78
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
4924	H	49.31	---	1.18	50.49	---	74	54	-3.51
7386	H	40.38	---	10.07	50.45	---	74	54	-3.55
---	H	---	---	---	---	---	---	---	---
4924	V	48.78	---	1.18	49.96	---	74	54	-4.04
7386	V	41.64	---	10.07	51.71	---	74	54	-2.29
---	V	---	---	---	---	---	---	---	---

Modulation Type: 802.11n(HT40)

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
4844	H	48.73	---	0.75	49.48	---	74	54	-4.52
7266	H	40.84	---	9.87	50.71	---	74	54	-3.29
---	H	---	---	---	---	---	---	---	---
4844	V	49.39	---	0.75	50.14	---	74	54	-3.86
7266	V	39.33	---	9.87	49.2	---	74	54	-4.8
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
4874	H	49.25	---	0.97	50.22	---	74	54	-3.78
7311	H	39.12	---	9.83	48.95	---	74	54	-5.05
---	H	---	---	---	---	---	---	---	---
4874	V	48.14	---	0.97	49.11	---	74	54	-4.89
7311	V	39.83	---	9.83	49.66	---	74	54	-4.34
---	V	---	---	---	---	---	---	---	---

High channel: 2452 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
4904	H	48.89	---	1.18	50.07	---	74	54	-3.93
7356	H	38.20	---	10.17	48.37	---	74	54	-5.63
---	H	---	---	---	---	---	---	---	---
4904	V	48.96	---	1.18	50.14	---	74	54	-3.86
7356	V	37.63	---	10.17	47.8	---	74	54	-6.2
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB μ V/m)-Average limit (dB μ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---”in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

*****END OF REPORT*****


Appendix A: Test Result of Conducted Test

Conducted Average Output Power

Result Table



Mode	Channel	Meas.Level [dBm]	Av.Power [dBm]	Verdict
11B	LCH	18.64	18.64	PASS
11B	MCH	18.38	18.38	PASS
11B	HCH	18.33	18.33	PASS
11G	LCH	14.87	14.87	PASS
11G	MCH	15.30	15.30	PASS
11G	HCH	14.72	14.72	PASS
11N20SISO	LCH	14.91	14.91	PASS
11N20SISO	MCH	15.42	15.42	PASS
11N20SISO	HCH	14.73	14.73	PASS
11N40SISO	LCH	12.31	12.31	PASS
11N40SISO	MCH	15.11	15.11	PASS
11N40SISO	HCH	12.25	12.25	PASS


Test Graph



11B/HCH	 <p>Agilent Spectrum Analyzer Channel Power</p> <p>Center Freq 2.462000000 GHz</p> <p>Ref Offset 8.49 dB</p> <p>Ref 30.00 dBm</p> <p>10 dB/div</p> <p>Log</p> <p>Center 2.462 GHz</p> <p>#Res BW 1 MHz</p> <p>#VBW 3 MHz</p> <p>Span 25.75 MHz</p> <p>#Sweep 100 ms</p> <p>CF Step 2.574800 MHz</p> <p>Frequency</p> <p>Center Freq 2.462000000 GHz</p> <p>CF Step 2.574800 MHz</p> <p>Auto Man</p> <p>Freq Offset 0 Hz</p> <p>Channel Power: 18.33 dBm / 12.87 MHz</p> <p>Power Spectral Density: -52.77 dBm / Hz</p>
11G/LCH	 <p>Agilent Spectrum Analyzer Channel Power</p> <p>Center Freq 2.412000000 GHz</p> <p>Ref Offset 8.49 dB</p> <p>Ref 30.00 dBm</p> <p>10 dB/div</p> <p>Log</p> <p>Center 2.412 GHz</p> <p>#Res BW 1 MHz</p> <p>#VBW 3 MHz</p> <p>Span 32.72 MHz</p> <p>#Sweep 100 ms</p> <p>CF Step 3.272400 MHz</p> <p>Frequency</p> <p>Center Freq 2.412000000 GHz</p> <p>CF Step 3.272400 MHz</p> <p>Auto Man</p> <p>Freq Offset 0 Hz</p> <p>Channel Power: 14.87 dBm / 16.36 MHz</p> <p>Power Spectral Density: -57.27 dBm / Hz</p>
11G/MCH	 <p>Agilent Spectrum Analyzer Channel Power</p> <p>Center Freq 2.437000000 GHz</p> <p>Ref Offset 8.49 dB</p> <p>Ref 30.00 dBm</p> <p>10 dB/div</p> <p>Log</p> <p>Center 2.437 GHz</p> <p>#Res BW 1 MHz</p> <p>#VBW 3 MHz</p> <p>Span 32.91 MHz</p> <p>#Sweep 100 ms</p> <p>CF Step 3.291200 MHz</p> <p>Frequency</p> <p>Center Freq 2.437000000 GHz</p> <p>CF Step 3.291200 MHz</p> <p>Auto Man</p> <p>Freq Offset 0 Hz</p> <p>Channel Power: 15.30 dBm / 16.46 MHz</p> <p>Power Spectral Density: -56.87 dBm / Hz</p>

11G/HCH	 <p>Agilent Spectrum Analyzer Channel Power</p> <p>Center Freq 2.462000000 GHz</p> <p>Ref Offset 8.49 dB</p> <p>Ref 30.00 dBm</p> <p>10 dB/div</p> <p>Log</p> <p>Center 2.462 GHz</p> <p>#Res BW 1 MHz</p> <p>#VBW 3 MHz</p> <p>Span 32.72 MHz</p> <p>#Sweep 100 ms</p> <p>Channel Power: 14.72 dBm / 16.36 MHz</p> <p>Power Spectral Density: -57.41 dBm / Hz</p> <p>Frequency: 2.462000000 GHz</p> <p>CF Step: 3.271600 MHz</p> <p>Auto</p> <p>Man</p> <p>Freq Offset: 0 Hz</p>
11N20SISO/LCH	 <p>Agilent Spectrum Analyzer Channel Power</p> <p>Center Freq 2.412000000 GHz</p> <p>Ref Offset 8.49 dB</p> <p>Ref 30.00 dBm</p> <p>10 dB/div</p> <p>Log</p> <p>Center 2.412 GHz</p> <p>#Res BW 1 MHz</p> <p>#VBW 3 MHz</p> <p>Span 35.04 MHz</p> <p>#Sweep 100 ms</p> <p>Channel Power: 14.91 dBm / 17.52 MHz</p> <p>Power Spectral Density: -57.52 dBm / Hz</p> <p>Frequency: 2.412000000 GHz</p> <p>CF Step: 3.504200 MHz</p> <p>Auto</p> <p>Man</p> <p>Freq Offset: 0 Hz</p>
11N20SISO/MCH	 <p>Agilent Spectrum Analyzer Channel Power</p> <p>Center Freq 2.437000000 GHz</p> <p>Ref Offset 8.49 dB</p> <p>Ref 20.00 dBm</p> <p>10 dB/div</p> <p>Log</p> <p>Center 2.437 GHz</p> <p>#Res BW 1 MHz</p> <p>#VBW 3 MHz</p> <p>Span 35.24 MHz</p> <p>#Sweep 100 ms</p> <p>Channel Power: 15.42 dBm / 17.62 MHz</p> <p>Power Spectral Density: -57.04 dBm / Hz</p> <p>Frequency: 2.437000000 GHz</p> <p>CF Step: 3.524200 MHz</p> <p>Auto</p> <p>Man</p> <p>Freq Offset: 0 Hz</p>

11N20SISO/HCH	 <p>Agilent Spectrum Analyzer Channel Power</p> <p>Center Freq: 2.462000000 GHz Trig: Free Run Avg Hold: 10/10 Radio Std: None Radio Device: BTS</p> <p>Ref Offset 8.49 dB Ref 30.00 dBm 10 dB/div Log</p> <p>Center: 2.462 GHz #Res BW: 1 MHz #VBW: 3 MHz Span: 35.09 MHz #Sweep: 100 ms</p> <p>Channel Power: 14.73 dBm / 17.55 MHz Power Spectral Density: -57.71 dBm /Hz</p>
11N40SISO/LCH	 <p>Agilent Spectrum Analyzer Channel Power</p> <p>Center Freq: 2.422000000 GHz Trig: Free Run Avg Hold: 10/10 Radio Std: None Radio Device: BTS</p> <p>Ref Offset 8.49 dB Ref 30.00 dBm 10 dB/div Log</p> <p>Center: 2.422 GHz #Res BW: 1 MHz #VBW: 3 MHz Span: 71.45 MHz #Sweep: 100 ms</p> <p>Channel Power: 12.31 dBm / 35.72 MHz Power Spectral Density: -63.22 dBm /Hz</p>
11N40SISO/MCH	 <p>Agilent Spectrum Analyzer Channel Power</p> <p>Center Freq: 2.437000000 GHz Trig: Free Run Avg Hold: 10/10 Radio Std: None Radio Device: BTS</p> <p>Ref Offset 8.49 dB Ref 30.00 dBm 10 dB/div Log</p> <p>Center: 2.437 GHz #Res BW: 1 MHz #VBW: 3 MHz Span: 72.01 MHz #Sweep: 100 ms</p> <p>Channel Power: 15.11 dBm / 36 MHz Power Spectral Density: -60.45 dBm /Hz</p>







6dB Occupied Bandwidth

Result Table


Mode	Channel	6dB Bandwidth [MHz]	99% OBW [MHz]	Verdict
11B	LCH	9.542	12.551	PASS
11B	MCH	10.05	12.930	PASS
11B	HCH	10.05	12.874	PASS
11G	LCH	15.08	16.362	PASS
11G	MCH	16.30	16.456	PASS
11G	HCH	14.44	16.358	PASS
11N20SISO	LCH	15.08	17.521	PASS
11N20SISO	MCH	17.20	17.621	PASS
11N20SISO	HCH	15.00	17.545	PASS
11N40SISO	LCH	33.85	35.724	PASS
11N40SISO	MCH	35.50	36.004	PASS
11N40SISO	HCH	35.09	35.746	PASS

Test Graph




11B/HCH	 <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.462000000 GHz</p> <p>Ref Offset 8.49 dB</p> <p>Ref 30.00 dBm</p> <p>10 dB/div</p> <p>Log</p> <p>Center 2.462 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 40 MHz</p> <p>Sweep 4.267 ms</p> <p>Occupied Bandwidth 12.874 MHz</p> <p>Total Power 24.9 dBm</p> <p>Transmit Freq Error 8.996 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 10.05 MHz</p> <p>x dB -6.00 dB</p> <p>MSG</p> <p>Frequency</p> <p>Center Freq 2.462000000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Auto Man</p> <p>Freq Offset 0 Hz</p>
11G/LCH	 <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.412000000 GHz</p> <p>Ref Offset 8.49 dB</p> <p>Ref 30.00 dBm</p> <p>10 dB/div</p> <p>Log</p> <p>Center 2.412 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 40 MHz</p> <p>Sweep 4.267 ms</p> <p>Occupied Bandwidth 16.362 MHz</p> <p>Total Power 20.6 dBm</p> <p>Transmit Freq Error -8.108 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 15.08 MHz</p> <p>x dB -6.00 dB</p> <p>MSG</p> <p>Frequency</p> <p>Center Freq 2.412000000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Auto Man</p> <p>Freq Offset 0 Hz</p>
11G/MCH	 <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.437000000 GHz</p> <p>Ref Offset 8.49 dB</p> <p>Ref 30.00 dBm</p> <p>10 dB/div</p> <p>Log</p> <p>Center 2.437 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 40 MHz</p> <p>Sweep 4.267 ms</p> <p>Occupied Bandwidth 16.456 MHz</p> <p>Total Power 20.9 dBm</p> <p>Transmit Freq Error -10.135 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 16.30 MHz</p> <p>x dB -6.00 dB</p> <p>MSG</p> <p>Frequency</p> <p>Center Freq 2.437000000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Auto Man</p> <p>Freq Offset 0 Hz</p>


11G/HCH





11N20SISO/LCH



11N20SISO/MCH



11N20SISO/HCH	 <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.462000000 GHz</p> <p>Ref Offset: 8.49 dB</p> <p>Ref: 30.00 dBm</p> <p>10 dB/div</p> <p>Log</p> <p>Center 2.462 GHz</p> <p>#Res BW: 100 kHz</p> <p>#VBW: 300 kHz</p> <p>Span: 40 MHz</p> <p>Sweep: 4.267 ms</p> <p>Occupied Bandwidth: 17.545 MHz</p> <p>Total Power: 20.5 dBm</p> <p>Transmit Freq Error: -5.118 kHz</p> <p>OBW Power: 99.00 %</p> <p>x dB Bandwidth: 15.00 MHz</p> <p>x dB: -6.00 dB</p> <p>CF Step: 4.000000 MHz</p> <p>Auto</p> <p>Man</p> <p>Freq Offset: 0 Hz</p> <p>MSG: </p> <p>Frequency: Center Freq 2.462000000 GHz</p>
11N40SISO/LCH	 <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.422000000 GHz</p> <p>Ref Offset: 8.49 dB</p> <p>Ref: 30.00 dBm</p> <p>10 dB/div</p> <p>Log</p> <p>Center 2.422 GHz</p> <p>#Res BW: 100 kHz</p> <p>#VBW: 300 kHz</p> <p>Span: 80 MHz</p> <p>Sweep: 8 ms</p> <p>Occupied Bandwidth: 35.724 MHz</p> <p>Total Power: 18.2 dBm</p> <p>Transmit Freq Error: -96.207 kHz</p> <p>OBW Power: 99.00 %</p> <p>x dB Bandwidth: 33.85 MHz</p> <p>x dB: -6.00 dB</p> <p>CF Step: 8.000000 MHz</p> <p>Auto</p> <p>Man</p> <p>Freq Offset: 0 Hz</p> <p>MSG: </p> <p>Frequency: Center Freq 2.422000000 GHz</p>
11N40SISO/MCH	 <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.437000000 GHz</p> <p>Ref Offset: 8.49 dB</p> <p>Ref: 30.00 dBm</p> <p>10 dB/div</p> <p>Log</p> <p>Center 2.437 GHz</p> <p>#Res BW: 100 kHz</p> <p>#VBW: 300 kHz</p> <p>Span: 80 MHz</p> <p>Sweep: 8 ms</p> <p>Occupied Bandwidth: 36.004 MHz</p> <p>Total Power: 21.1 dBm</p> <p>Transmit Freq Error: -50.149 kHz</p> <p>OBW Power: 99.00 %</p> <p>x dB Bandwidth: 35.50 MHz</p> <p>x dB: -6.00 dB</p> <p>CF Step: 8.000000 MHz</p> <p>Auto</p> <p>Man</p> <p>Freq Offset: 0 Hz</p> <p>MSG: </p> <p>Frequency: Center Freq 2.437000000 GHz</p>

11N40SISO/HCH

