


FCC PART 27
FCC PART 22H, PART 24E
TEST REPORT

For

b mobile HK Limited

Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong.

FCC ID: ZSW-30-032

Report Type: Original Report	Product Type: Mobile Phone
Report Number: RSZ161012001-00D	
Report Date: 2016-12-19	
Jesse Huang	
Reviewed By: Manager	
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
TEST EQUIPMENT LIST	7
FCC §1.1307 & §2.1093 - RF EXPOSURE.....	8
APPLICABLE STANDARD	8
TEST RESULT	8
FCC §2.1047 - MODULATION CHARACTERISTIC	9
FCC § 2.1046, § 22.913 (A) & § 24.232 (C); §27.50 (D) (H) - RF OUTPUT POWER	10
APPLICABLE STANDARD	10
TEST PROCEDURE	10
TEST DATA	10
FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH.....	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34
FCC §2.1051, §22.917(A) & §24.238(A); §27.53 (H) (M) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	65
APPLICABLE STANDARD	65
TEST PROCEDURE	65
TEST DATA	65
FCC § 2.1053; § 22.917 (A);§ 24.238 (A); §27.53 (H)(M) SPURIOUS RADIATED EMISSIONS.....	99
APPLICABLE STANDARD	99
TEST PROCEDURE	99
TEST DATA	99
FCC § 22.917 (A);§ 24.238 (A); §27.53 (H)(M) - BAND EDGES	102
APPLICABLE STANDARD	102
TEST PROCEDURE	102
TEST DATA	102
FCC § 2.1055; § 22.355; § 24.235; §27.54; - FREQUENCY STABILITY.....	153
APPLICABLE STANDARD	153
TEST PROCEDURE	153
TEST DATA	154

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *b mobile HK Limited's* product, model number: *AX1085 (FCC ID: ZSW-30-032)* in this report is a *Mobile Phone*, which was measured approximately: 15.5 cm (L) × 8.6 cm (W) × 0.9 cm (H), rated with input voltage: DC 3.8 V battery or DC 5.0V from adapter.

Adapter information

Input: AC 100-240V~50/60Hz 0.4A

Output: DC5.0V, 1.0A

Notes: This series products model: AX1085 and AX1080 are identical; they have the same or similar appearance, structure, PCB, Material and function to the testing products, and only different is model number. Model AX1085 was selected for fully testing, the detailed information can be referred to the attached declaration which was stated and guaranteed by the applicant.

** All measurement and test data in this report was gathered from production sample serial number: 1603416 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2016-10-12.*

Objective

This test report is prepared on behalf of *b mobile HK Limited* in accordance with Part 2-Subpart J, Part 22-Subpart H and Part 24-Subpart E and Part 27 of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS & DSS and Part 15B JBP submissions with FCC ID: ZSW-30-032.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2-Subpart J as well as the following parts:

Part 22 Subpart H - Public Mobile Services
Part 24 Subpart E - Personal Communication Services
Part 27 – Miscellaneous wireless communications services

Applicable Standards: TIA/EIA 603-D, ANSI C63.4-2014.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		± 3.26 dB
RF conducted test with spectrum		± 0.9 dB
RF Output Power with Power meter		± 0.5 dB
Radiated emission	30MHz~1GHz	± 5.91 dB
	Above 1G	± 4.92 dB
Occupied Bandwidth		± 0.5 kHz
Temperature		± 1.0 °C
Humidity		$\pm 6\%$

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the Chenghu Lake Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.

The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.0002K50-116218-UY

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance*
§2.1046; § 22.913 (a); § 24.232 (c); §27.50 (c) (d) (h)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905; § 22.917; § 24.238; §27.53	Occupied Bandwidth	Compliance
§ 2.1051; § 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; §27.54;	Frequency stability	Compliance

Note: * Please refer to SAR report released by BACL, report number: RSZ161012001-20.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Sonoma Instrument	Amplifier	330	171377	2015-12-12	2016-12-12
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-25	2017-11-25
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2016-01-09	2019-01-08
Narda	Pre-amplifier	AFS42-00101800	2001270	2016-09-08	2017-09-08
EMCO	Horn Antenna	3116	9510-2384	2015-11-07	2018-11-06
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-25	2017-11-25
ETS	Horn Antenna	3115	6229	2016-01-11	2017-01-10
ETS	Horn Antenna	3115	9311-4159	2016-01-11	2017-01-10
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-12-15	2016-12-15
Ducommun technologies	RF Cable	104PEA	218124002	2016-04-22	2017-04-22
HP	Signal Generator	83172A	3339A00199	2016-11-11	2017-11-10
RF Conducted test					
BACL	TS 8997 Cable-01	T-KS-EMC086	T-KS-EMC086	2015-12-10	2016-12-09
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-12-16	2016-12-15
WEINSCHL	3dB Attenuator	5326	N/A	2016-06-18	2017-06-18
Rohde & Schwarz	OSP120 BASE UNIT	OSP120	101247	2016-07-04	2017-07-03
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2016-09-21	2017-09-21
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605	2016-11-25	2017-11-25
R&S	Wideband Radio Communication tester	CMW500	1201.002K50-116218-UY	2016-10-08	2017-10-08
HONOVA	Power Splitter	ZFRSC-14-S+	019411452	2016-06-12	2017-06-12
WEINSCHL	10dB Attenuator	5328	N/A	2016-06-18	2017-06-18

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ161012001-20.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H, 24E & Part 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c); §27.50 (d) (h) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.


According to §27.50(d), the maximum EIRP must not exceed 1Watts (30dBm) for 1710-1755MHz. The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB.

According to §27.50(h), the maximum EIRP must not exceed 2Watts (33dBm) for 2500-2570MHz.

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the CMW500/CMU200 through sufficient attenuation.



Radiated method:

TIA 603-D section 2.2.17

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100.0 kPa

The testing was performed by Alisa.Gao on 2016-11-29.

Conducted Power**Cellular Band (Part 22H)**

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	128	824.2	32.40	38.45
	190	836.6	32.41	38.45
	251	848.8	32.41	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	128	824.2	32.39	31.63	29.84	28.84	38.45
	190	836.6	32.42	31.72	29.91	29.00	38.45
	251	848.8	32.40	31.62	30.05	29.11	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	128	824.2	25.70	24.74	22.77	21.72	38.45
	190	836.6	25.96	24.98	23.02	21.95	38.45
	251	848.8	26.08	25.10	23.09	22.04	38.45

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band V)	Normal	RMC12.2k		21.79	21.96	21.97
		HSDPA	1	20.52	21.46	20.90
			2	21.04	20.87	21.07
			3	21.06	21.15	21.03
			4	20.89	20.89	21.07
		HSUPA	1	20.80	20.94	20.93
			2	20.48	20.73	20.51
			3	20.27	20.67	20.43
			4	20.54	20.88	20.49
			5	20.48	20.56	20.57
		HSPA+	1	21.03	20.86	21.09

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	512	1850.2	29.29	33
	661	1880.0	29.30	33
	810	1909.8	29.22	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	512	1850.2	29.30	28.37	26.43	25.32	33
	661	1880.0	29.33	28.48	26.56	25.51	33
	810	1909.8	29.25	28.46	26.66	25.62	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	512	1850.2	23.64	23.57	22.49	21.42	33
	661	1880.0	23.79	23.71	22.68	21.63	33
	810	1909.8	24.10	23.99	22.87	21.87	33

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band II)	Normal	RMC12.2k		21.34	21.18	21.26
		HSDPA	1	20.18	20.04	20.16
			2	20.61	20.35	20.52
			3	20.56	20.41	20.36
			4	20.74	20.38	20.39
		HSUPA	1	20.21	20.01	20.20
			2	20.42	20.24	20.24
			3	20.31	20.47	20.37
			4	20.46	20.33	20.49
			5	20.54	20.54	20.59
		HSPA+	1	20.09	20.48	20.28

Peak-to-average ratio (PAR)**Cellular Band**

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.14	13
	Middle	0.17	13
	High	0.16	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	0.22	13
	Middle	0.24	13
	High	0.25	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	2.75	13
	Middle	3.08	13
	High	3.30	13
HSDPA (16QAM)	Low	3.27	13
	Middle	3.32	13
	High	3.04	13
HSUPA (BPSK)	Low	3.08	13
	Middle	3.71	13
	High	3.40	13

PCS Band

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.17	13
	Middle	0.19	13
	High	0.16	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	0.27	13
	Middle	0.26	13
	High	0.25	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	2.75	13
	Middle	3.08	13
	High	3.30	13
HSDPA (16QAM)	Low	4.43	13
	Middle	3.23	13
	High	4.10	13
HSUPA (BPSK)	Low	3.75	13
	Middle	5.07	13
	High	4.95	13

Radiated Power**GSM Mode:**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable loss (dB)	Antenna Gain (dB)			
ERP for Cellular Band (Part 22H), Middle Channel										
836.6	97.08	354	1.4	H	26.1	0.46	4.75	30.39	38.45	8.06
836.6	88.83	176	2.3	V	17.8	0.46	4.75	22.09	38.45	16.36
EIRP for PCS Band (Part 24E), Middle Channel										
1880.00	77.94	168	1.8	H	17.1	0.31	10.4	27.19	33	5.81
1880.00	74.37	329	2.0	V	10.1	0.31	10.4	20.19	33	12.81

EDGE Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable loss (dB)	Antenna Gain (dB)			
ERP, Cellular Band (Part 22H), Middle Channel										
836.6	82.36	214	1.3	H	11.3	0.46	4.75	15.59	38.45	22.86
836.6	91.48	329	1.3	V	20.5	0.46	4.75	24.79	38.45	13.66
EIRP, PCS Band (Part 24E), Middle Channel										
1880.00	73.43	19	1.8	H	12.6	0.31	10.4	22.69	33	10.31
1880.00	72.56	307	1.1	V	8.3	0.31	10.4	18.39	33	14.61

WCDMA Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable loss (dB)	Antenna Gain (dB)			
ERP for WCDMA Band V (Part 22H), Middle Channel										
836.6	87.91	78	1.8	H	16.9	0.46	4.75	21.19	38.45	17.26
836.6	82.75	250	1.5	V	11.7	0.46	4.75	15.99	38.45	22.46
EIRP for WCDMA Band II (Part 24E), Middle Channel										
1880.00	71.73	76	1.4	H	10.9	0.31	10.4	20.99	33	12.01
1880.00	74.77	18	1.5	V	7.2	0.31	10.4	17.29	33	15.71

Note:

All above data were tested with no amplifier.

Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

LTE Band 2**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	22.94	22.88	23.10
		RB Size=1, RB Offset=2	22.83	22.99	22.99
		RB Size=1, RB Offset=5	22.84	23.01	22.83
		RB Size=3, RB Offset=0	22.97	22.99	23.20
		RB Size=3, RB Offset=1	22.87	22.91	23.06
		RB Size=3, RB Offset=2	22.86	23.24	23.21
		RB Size=6, RB Offset=0	21.46	21.84	22.02
	16QAM	RB Size=1, RB Offset=0	22.02	21.96	21.88
		RB Size=1, RB Offset=2	21.87	22.00	21.68
		RB Size=1, RB Offset=5	21.74	22.00	21.65
		RB Size=3, RB Offset=0	21.88	21.87	21.62
		RB Size=3, RB Offset=1	21.78	21.74	21.42
		RB Size=3, RB Offset=2	21.67	21.76	21.39
		RB Size=6, RB Offset=0	21.08	21.08	21.02
3.0	QPSK	RB Size=1, RB Offset=0	22.85	22.86	22.92
		RB Size=1, RB Offset=7	22.73	22.79	22.77
		RB Size=1, RB Offset=14	22.57	22.75	22.70
		RB Size=8, RB Offset=0	21.94	21.92	21.91
		RB Size=8, RB Offset=4	21.88	21.82	21.84
		RB Size=8, RB Offset=7	21.67	21.60	21.83
		RB Size=15, RB Offset=0	22.02	21.95	21.99
	16QAM	RB Size=1, RB Offset=0	22.43	22.37	22.39
		RB Size=1, RB Offset=7	22.35	22.24	22.28
		RB Size=1, RB Offset=14	22.13	21.99	22.32
		RB Size=8, RB Offset=0	21.03	21.05	21.05
		RB Size=8, RB Offset=4	21.00	20.90	20.89
		RB Size=8, RB Offset=7	20.84	20.89	20.79
		RB Size=15, RB Offset=0	21.01	21.01	21.06

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	23.02	23.01	23.06
		RB Size=1, RB Offset=12	22.90	22.86	23.11
		RB Size=1, RB Offset=24	22.74	22.94	23.09
		RB Size=12, RB Offset=0	22.01	21.99	21.99
		RB Size=12, RB Offset=6	21.92	22.00	21.85
		RB Size=12, RB Offset=11	21.68	22.05	21.76
		RB Size=25, RB Offset=0	21.98	21.94	21.97
	16QAM	RB Size=1, RB Offset=0	21.98	21.98	21.97
		RB Size=1, RB Offset=12	21.92	21.97	21.98
		RB Size=1, RB Offset=24	21.88	21.85	21.86
		RB Size=12, RB Offset=0	21.06	21.02	21.02
		RB Size=12, RB Offset=6	21.02	21.03	20.93
		RB Size=12, RB Offset=11	21.06	21.07	20.77
		RB Size=25, RB Offset=0	21.10	21.05	21.03
10.0	QPSK	RB Size=1, RB Offset=0	23.04	23.01	23.04
		RB Size=1, RB Offset=24	22.89	23.04	22.93
		RB Size=1, RB Offset=49	22.84	22.93	22.76
		RB Size=25, RB Offset=0	21.96	21.95	22.00
		RB Size=25, RB Offset=12	22.02	21.76	21.88
		RB Size=25, RB Offset=24	22.03	21.75	21.77
		RB Size=50, RB Offset=0	21.99	21.99	22.05
	16QAM	RB Size=1, RB Offset=0	22.57	22.58	22.66
		RB Size=1, RB Offset=24	22.48	22.43	22.61
		RB Size=1, RB Offset=49	22.42	22.18	22.39
		RB Size=25, RB Offset=0	22.61	20.95	20.95
		RB Size=25, RB Offset=12	22.50	20.75	20.83
		RB Size=25, RB Offset=24	22.42	20.80	20.67
		RB Size=50, RB Offset=0	20.76	20.75	20.75

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	22.98	22.98	22.34
		RB Size=1, RB Offset=37	22.90	22.88	22.17
		RB Size=1, RB Offset=74	22.82	22.79	21.89
		RB Size=36, RB Offset=0	21.97	21.98	22.01
		RB Size=36, RB Offset=18	21.82	21.76	21.97
		RB Size=36, RB Offset=37	21.82	21.55	22.05
		RB Size=75, RB Offset=0	22.04	22.02	21.99
	16QAM	RB Size=1, RB Offset=0	22.55	22.48	21.70
		RB Size=1, RB Offset=37	22.42	22.34	21.51
		RB Size=1, RB Offset=74	22.15	22.19	21.39
		RB Size=36, RB Offset=0	20.99	20.95	22.02
		RB Size=36, RB Offset=18	20.83	20.88	21.98
		RB Size=36, RB Offset=37	20.91	20.70	22.06
		RB Size=75, RB Offset=0	21.04	21.01	20.97
20.0	QPSK	RB Size=1, RB Offset=0	23.05	23.05	22.95
		RB Size=1, RB Offset=49	22.98	22.97	22.94
		RB Size=1, RB Offset=99	22.81	22.98	22.96
		RB Size=50, RB Offset=0	22.02	22.01	21.93
		RB Size=50, RB Offset=24	21.83	21.97	21.94
		RB Size=50, RB Offset=49	21.83	21.93	21.86
		RB Size=100, RB Offset=0	21.06	21.01	21.83
	16QAM	RB Size=1, RB Offset=0	22.27	22.29	22.04
		RB Size=1, RB Offset=49	22.11	22.23	21.98
		RB Size=1, RB Offset=99	21.90	22.05	21.75
		RB Size=50, RB Offset=0	21.04	21.05	20.98
		RB Size=50, RB Offset=24	21.10	20.99	20.90
		RB Size=50, RB Offset=49	21.14	21.03	20.90
		RB Size=100, RB Offset=0	21.04	21.01	20.91

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	3.72	13	Pass
QPSK (100%RB Size)	4.15	13	Pass
16QAM (1RB Size)	3.85	13	Pass
16QAM (100%RB Size)	4.47	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1880.00	72.43	356	2.2	H	11.6	0.31	10.4	21.69	33
1880.00	71.55	109	1.0	V	7.3	0.31	10.4	17.39	33
3 MHz Bandwidth									
1880.00	72.11	196	1.8	H	11.3	0.31	10.4	21.39	33
1880.00	71.16	261	1.2	V	6.9	0.31	10.4	16.99	33
5 MHz Bandwidth									
1880.00	71.77	334	1.3	H	10.9	0.31	10.4	20.99	33
1880.00	70.62	38	1.4	V	6.4	0.31	10.4	16.49	33
10 MHz Bandwidth									
1880.00	71.51	68	2.2	H	10.7	0.31	10.4	20.79	33
1880.00	70.42	78	1.7	V	6.2	0.31	10.4	16.29	33
15 MHz Bandwidth									
1880.00	71.04	87	1.4	H	10.2	0.31	10.4	20.29	33
1880.00	70.26	141	1.2	V	6.0	0.31	10.4	16.09	33
20 MHz Bandwidth									
1880.00	70.24	150	2.3	H	9.4	0.31	10.4	19.49	33
1880.00	70.16	248	1.1	V	5.9	0.31	10.4	15.99	33

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1880.00	71.81	20	1.1	H	11.0	0.31	10.4	21.09	33
1880.00	72.22	116	1.6	V	8.0	0.31	10.4	18.09	33
3 MHz Bandwidth									
1880.00	71.75	196	1.8	H	10.9	0.31	10.4	20.99	33
1880.00	72.16	261	1.2	V	7.9	0.31	10.4	17.99	33
5 MHz Bandwidth									
1880.00	71.44	85	2.4	H	10.6	0.31	10.4	20.69	33
1880.00	72.09	222	1.9	V	7.8	0.31	10.4	17.89	33
10 MHz Bandwidth									
1880.00	71.31	68	2.2	H	10.5	0.31	10.4	20.59	33
1880.00	71.42	78	1.7	V	7.2	0.31	10.4	17.29	33
15 MHz Bandwidth									
1880.00	71.04	87	1.4	H	10.2	0.31	10.4	20.29	33
1880.00	70.66	141	1.2	V	6.4	0.31	10.4	16.49	33
20 MHz Bandwidth									
1880.00	70.78	101	2.1	H	9.9	0.31	10.4	19.99	33
1880.00	70.47	123	2.5	V	6.2	0.31	10.4	16.29	33

LTE Band 4:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	22.44	22.44	22.42
		RB Size=1, RB Offset=2	22.29	22.30	22.31
		RB Size=1, RB Offset=5	22.24	22.01	22.29
		RB Size=3, RB Offset=0	22.54	22.49	22.50
		RB Size=3, RB Offset=1	22.41	22.42	22.38
		RB Size=3, RB Offset=2	22.35	22.21	22.10
		RB Size=6, RB Offset=0	21.43	21.4	21.42
	16QAM	RB Size=1, RB Offset=0	21.45	21.42	21.40
		RB Size=1, RB Offset=2	21.36	21.45	21.37
		RB Size=1, RB Offset=5	21.18	21.46	21.18
		RB Size=3, RB Offset=0	22.78	21.52	21.47
		RB Size=3, RB Offset=1	22.63	21.48	21.35
		RB Size=3, RB Offset=2	22.37	21.27	21.19
		RB Size=6, RB Offset=0	20.47	20.47	20.53
3.0	QPSK	RB Size=1, RB Offset=0	21.92	21.92	21.90
		RB Size=1, RB Offset=7	21.91	21.78	21.92
		RB Size=1, RB Offset=14	21.97	21.74	21.82
		RB Size=8, RB Offset=0	21.52	21.47	21.51
		RB Size=8, RB Offset=4	21.45	21.32	21.41
		RB Size=8, RB Offset=7	21.37	21.20	21.12
		RB Size=15, RB Offset=0	21.49	21.44	21.49
	16QAM	RB Size=1, RB Offset=0	21.97	21.93	21.96
		RB Size=1, RB Offset=7	21.90	21.84	21.89
		RB Size=1, RB Offset=14	21.82	21.90	21.64
		RB Size=8, RB Offset=0	20.57	20.53	20.56
		RB Size=8, RB Offset=4	20.48	20.39	20.48
		RB Size=8, RB Offset=7	20.21	20.43	20.23
		RB Size=15, RB Offset=0	20.58	20.58	20.61

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	22.66	22.49	22.46
		RB Size=1, RB Offset=12	22.52	22.46	22.39
		RB Size=1, RB Offset=24	22.49	21.51	22.38
		RB Size=12, RB Offset=0	21.75	21.58	21.61
		RB Size=12, RB Offset=6	21.74	21.59	21.56
		RB Size=12, RB Offset=11	21.47	21.39	21.40
		RB Size=25, RB Offset=0	21.71	21.45	21.44
	16QAM	RB Size=1, RB Offset=0	21.90	21.50	21.51
		RB Size=1, RB Offset=12	21.82	21.31	21.42
		RB Size=1, RB Offset=24	21.66	21.38	21.38
		RB Size=12, RB Offset=0	20.87	20.50	20.46
		RB Size=12, RB Offset=6	20.83	20.34	20.37
		RB Size=12, RB Offset=11	20.80	20.05	20.10
		RB Size=25, RB Offset=0	20.80	20.52	20.57
10.0	QPSK	RB Size=1, RB Offset=0	22.51	22.48	22.48
		RB Size=1, RB Offset=24	22.42	22.36	22.44
		RB Size=1, RB Offset=49	22.48	22.38	22.33
		RB Size=25, RB Offset=0	22.55	22.50	22.54
		RB Size=25, RB Offset=12	22.41	22.48	22.55
		RB Size=25, RB Offset=24	22.42	22.31	22.56
		RB Size=50, RB Offset=0	21.53	21.48	21.48
	16QAM	RB Size=1, RB Offset=0	22.07	21.99	21.93
		RB Size=1, RB Offset=24	21.89	21.86	21.83
		RB Size=1, RB Offset=49	21.95	21.82	21.61
		RB Size=25, RB Offset=0	20.51	20.50	20.55
		RB Size=25, RB Offset=12	20.34	20.30	20.33
		RB Size=25, RB Offset=24	20.37	20.28	20.22
		RB Size=50, RB Offset=0	20.54	20.51	20.50

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	22.64	22.43	22.52
		RB Size=1, RB Offset=37	22.60	22.29	22.50
		RB Size=1, RB Offset=74	22.40	22.01	22.50
		RB Size=36, RB Offset=0	21.95	21.52	21.49
		RB Size=36, RB Offset=18	21.76	21.51	21.53
		RB Size=36, RB Offset=37	21.76	21.59	21.26
		RB Size=75, RB Offset=0	21.69	21.55	21.59
	16QAM	RB Size=1, RB Offset=0	21.67	21.96	21.89
		RB Size=1, RB Offset=37	21.55	21.84	21.74
		RB Size=1, RB Offset=74	21.36	21.73	21.78
		RB Size=36, RB Offset=0	20.80	20.51	20.49
		RB Size=36, RB Offset=18	20.70	20.51	20.49
		RB Size=36, RB Offset=37	20.57	20.27	20.35
		RB Size=75, RB Offset=0	20.71	20.56	20.61
20.0	QPSK	RB Size=1, RB Offset=0	22.65	22.52	22.48
		RB Size=1, RB Offset=49	22.51	22.51	22.36
		RB Size=1, RB Offset=99	22.44	22.30	22.21
		RB Size=50, RB Offset=0	21.79	21.46	21.37
		RB Size=50, RB Offset=24	21.73	21.40	21.29
		RB Size=50, RB Offset=49	21.62	21.39	21.33
		RB Size=100, RB Offset=0	21.74	21.47	21.50
	16QAM	RB Size=1, RB Offset=0	22.27	21.81	21.87
		RB Size=1, RB Offset=49	22.13	21.76	21.74
		RB Size=1, RB Offset=99	22.00	21.79	21.76
		RB Size=50, RB Offset=0	21.01	20.53	20.53
		RB Size=50, RB Offset=24	21.02	20.57	20.60
		RB Size=50, RB Offset=49	20.92	20.34	20.64
		RB Size=100, RB Offset=0	20.84	20.52	20.51

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	4.41	13	Pass
QPSK (100%RB Size)	5.13	13	Pass
16QAM (1RB Size)	4.68	13	Pass
16QAM (100%RB Size)	5.33	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1732.50	74.58	204	1.7	H	12.2	0.30	9.90	21.80	30
1732.50	72.44	334	1.9	V	7.6	0.30	9.90	17.20	30
3 MHz Bandwidth									
1732.50	74.28	160	2.0	H	11.9	0.30	9.90	21.50	30
1732.50	72.21	55	1.9	V	7.4	0.30	9.90	17.00	30
5 MHz Bandwidth									
1732.50	73.85	235	1.0	H	11.5	0.30	9.90	21.10	30
1732.50	72.17	127	1.3	V	7.3	0.30	9.90	16.90	30
10 MHz Bandwidth									
1732.50	73.61	274	2.3	H	11.3	0.30	9.90	20.90	30
1732.50	71.81	341	1.1	V	7.0	0.30	9.90	16.60	30
15 MHz Bandwidth									
1732.50	73.49	241	2.3	H	11.1	0.30	9.90	20.70	30
1732.50	71.54	276	2.2	V	6.7	0.30	9.90	16.30	30
20 MHz Bandwidth									
1732.50	73.07	345	1.0	H	10.7	0.30	9.90	20.30	30
1732.50	70.91	181	1.0	V	6.1	0.30	9.90	15.70	30

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1732.50	74.37	204	1.7	H	12.0	0.30	9.90	21.60	30
1732.50	72.53	334	1.9	V	7.7	0.30	9.90	17.30	30
3 MHz Bandwidth									
1732.50	73.88	160	2.0	H	11.5	0.30	9.90	21.10	30
1732.50	72.01	55	1.9	V	7.2	0.30	9.90	16.80	30
5 MHz Bandwidth									
1732.50	73.46	354	1.8	H	11.1	0.30	9.90	20.70	30
1732.50	71.94	36	2.4	V	7.1	0.30	9.90	16.70	30
10 MHz Bandwidth									
1732.50	73.11	274	2.3	H	10.8	0.30	9.90	20.40	30
1732.50	71.71	341	1.1	V	6.9	0.30	9.90	16.50	30
15 MHz Bandwidth									
1732.50	72.56	177	2.3	H	10.2	0.30	9.90	19.80	30
1732.50	71.34	96	2.3	V	6.5	0.30	9.90	16.10	30
20 MHz Bandwidth									
1732.50	72.07	345	1.0	H	9.7	0.30	9.90	19.30	30
1732.50	70.91	181	1.0	V	6.1	0.30	9.90	15.70	30

LTE Band 5:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	23.05	23.02	23.02
		RB Size=1, RB Offset=2	22.86	22.90	23.08
		RB Size=1, RB Offset=5	22.69	22.89	22.83
		RB Size=3, RB Offset=0	23.16	23.14	23.09
		RB Size=3, RB Offset=1	23.08	23.08	23.00
		RB Size=3, RB Offset=2	22.90	23.13	23.08
		RB Size=6, RB Offset=0	22.09	22.05	22.05
	16QAM	RB Size=1, RB Offset=0	22.06	22.07	22.03
		RB Size=1, RB Offset=2	22.08	21.98	21.87
		RB Size=1, RB Offset=5	22.10	21.96	21.64
		RB Size=3, RB Offset=0	22.20	22.16	22.13
		RB Size=3, RB Offset=1	22.07	21.96	22.03
		RB Size=3, RB Offset=2	21.90	21.94	22.00
		RB Size=6, RB Offset=0	21.09	21.08	21.08
3.0	QPSK	RB Size=1, RB Offset=0	22.99	22.96	23.02
		RB Size=1, RB Offset=7	23.02	22.97	22.84
		RB Size=1, RB Offset=14	23.03	22.92	22.64
		RB Size=8, RB Offset=0	22.17	22.10	22.03
		RB Size=8, RB Offset=4	22.11	22.02	22.01
		RB Size=8, RB Offset=7	22.03	22.09	21.85
		RB Size=15, RB Offset=0	22.11	22.11	22.15
	16QAM	RB Size=1, RB Offset=0	22.58	22.53	22.53
		RB Size=1, RB Offset=7	22.60	22.41	22.41
		RB Size=1, RB Offset=14	22.45	22.21	22.41
		RB Size=8, RB Offset=0	21.28	21.23	21.14
		RB Size=8, RB Offset=4	21.12	21.09	21.03
		RB Size=8, RB Offset=7	20.90	21.11	21.04
		RB Size=15, RB Offset=0	21.24	21.19	21.22

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	23.14	23.09	23.08
		RB Size=1, RB Offset=12	23.02	23.02	23.04
		RB Size=1, RB Offset=24	22.78	23.00	23.11
		RB Size=12, RB Offset=0	22.23	22.18	22.19
		RB Size=12, RB Offset=6	22.10	22.03	22.11
		RB Size=12, RB Offset=11	22.12	22.12	22.07
		RB Size=25, RB Offset=0	22.09	22.09	22.12
	16QAM	RB Size=1, RB Offset=0	22.15	22.15	22.20
		RB Size=1, RB Offset=12	22.11	22.02	22.14
		RB Size=1, RB Offset=24	22.04	22.03	22.02
		RB Size=12, RB Offset=0	21.18	21.21	21.29
		RB Size=12, RB Offset=6	21.02	21.04	21.13
		RB Size=12, RB Offset=11	21.03	20.85	21.00
		RB Size=25, RB Offset=0	21.24	21.23	21.25
10.0	QPSK	RB Size=1, RB Offset=0	23.09	23.06	23.12
		RB Size=1, RB Offset=24	23.09	23.02	23.18
		RB Size=1, RB Offset=49	22.86	23.06	23.05
		RB Size=25, RB Offset=0	22.15	22.15	22.14
		RB Size=25, RB Offset=12	22.14	22.02	22.12
		RB Size=25, RB Offset=24	22.19	21.95	22.07
		RB Size=50, RB Offset=0	22.16	22.14	22.17
	16QAM	RB Size=1, RB Offset=0	22.70	22.67	22.64
		RB Size=1, RB Offset=24	22.73	22.67	22.59
		RB Size=1, RB Offset=49	22.47	22.72	22.39
		RB Size=25, RB Offset=0	21.15	21.17	21.08
		RB Size=25, RB Offset=12	21.05	21.12	20.97
		RB Size=25, RB Offset=24	20.83	20.94	20.83
		RB Size=50, RB Offset=0	21.15	21.15	21.18

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	4.41	13	Pass
QPSK (100%RB Size)	5.57	13	Pass
16QAM (1RB Size)	4.82	13	Pass
16QAM (100%RB Size)	5.24	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
836.5	88.37	250	1.8	H	17.4	0.46	4.75	21.69	38.45
836.5	84.22	343	1.7	V	13.2	0.46	4.75	17.49	38.45
3 MHz Bandwidth									
836.5	88.18	108	2.2	H	17.2	0.46	4.75	21.49	38.45
836.5	83.73	29	1.1	V	12.7	0.46	4.75	16.99	38.45
5 MHz Bandwidth									
836.5	87.78	19	2.3	H	16.8	0.46	4.75	21.09	38.45
836.5	83.54	302	1.3	V	12.5	0.46	4.75	16.79	38.45
10 MHz Bandwidth									
836.5	87.35	330	1.7	H	16.3	0.46	4.75	20.59	38.45
836.5	83.21	292	1.2	V	12.2	0.46	4.75	16.49	38.45

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
836.5	88.36	205	2.3	H	17.3	0.46	4.75	21.59	38.45
836.5	84.11	47	1.2	V	13.1	0.46	4.75	17.39	38.45
3 MHz Bandwidth									
836.5	87.88	282	1.2	H	16.8	0.46	4.75	21.09	96.18
836.5	83.74	196	2.4	V	12.7	0.46	4.75	16.99	88.74
5 MHz Bandwidth									
836.5	87.54	202	1.3	H	16.5	0.46	4.75	20.79	38.45
836.5	83.21	162	1.5	V	12.2	0.46	4.75	16.49	38.45
10 MHz Bandwidth									
836.5	87.07	4	2.2	H	16.0	0.46	4.75	20.29	38.45
836.5	82.61	240	1.5	V	11.6	0.46	4.75	15.89	38.45

LTE Band 7

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	23.14	23.09	23.17
		RB Size=1, RB Offset=12	23.02	23.03	23.08
		RB Size=1, RB Offset=24	23.01	22.86	22.79
		RB Size=12, RB Offset=0	22.15	22.16	22.20
		RB Size=12, RB Offset=6	22.05	22.17	22.02
		RB Size=12, RB Offset=11	21.91	22.23	21.95
		RB Size=25, RB Offset=0	22.14	22.09	22.16
	16QAM	RB Size=1, RB Offset=0	22.19	22.15	22.17
		RB Size=1, RB Offset=12	22.05	22.20	22.04
		RB Size=1, RB Offset=24	21.88	22.18	21.95
		RB Size=12, RB Offset=0	21.19	21.20	21.18
		RB Size=12, RB Offset=6	21.07	21.06	21.03
		RB Size=12, RB Offset=11	20.97	21.16	20.81
		RB Size=25, RB Offset=0	21.23	21.19	21.18
10.0	QPSK	RB Size=1, RB Offset=0	23.08	23.06	23.15
		RB Size=1, RB Offset=24	22.98	22.94	23.15
		RB Size=1, RB Offset=49	23.06	22.97	22.91
		RB Size=25, RB Offset=0	22.14	22.15	22.13
		RB Size=25, RB Offset=12	22.00	22.00	22.05
		RB Size=25, RB Offset=24	21.99	21.89	21.85
		RB Size=50, RB Offset=0	22.18	22.14	22.19
	16QAM	RB Size=1, RB Offset=0	22.66	22.65	22.57
		RB Size=1, RB Offset=24	22.71	22.65	22.50
		RB Size=1, RB Offset=49	22.48	22.48	22.43
		RB Size=25, RB Offset=0	21.21	21.17	21.13
		RB Size=25, RB Offset=12	21.19	21.17	20.91
		RB Size=25, RB Offset=24	20.99	21.02	20.71
		RB Size=50, RB Offset=0	21.20	21.14	21.14

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	23.04	23.01	23.08
		RB Size=1, RB Offset=37	22.94	23.02	22.92
		RB Size=1, RB Offset=74	22.78	23.05	22.78
		RB Size=36, RB Offset=0	22.07	22.06	22.07
		RB Size=36, RB Offset=18	21.94	21.97	21.97
		RB Size=36, RB Offset=37	21.76	22.06	22.05
		RB Size=75, RB Offset=0	22.09	22.09	22.15
	16QAM	RB Size=1, RB Offset=0	22.66	22.64	22.62
		RB Size=1, RB Offset=37	22.63	22.65	22.67
		RB Size=1, RB Offset=74	22.50	22.56	22.57
		RB Size=36, RB Offset=0	21.17	21.11	21.12
		RB Size=36, RB Offset=18	20.98	21.00	20.97
		RB Size=36, RB Offset=37	20.87	20.78	20.94
		RB Size=75, RB Offset=0	21.14	21.13	21.16
20.0	QPSK	RB Size=1, RB Offset=0	23.09	23.09	23.16
		RB Size=1, RB Offset=49	22.92	22.97	23.06
		RB Size=1, RB Offset=99	22.69	22.87	22.99
		RB Size=50, RB Offset=0	22.16	22.14	22.22
		RB Size=50, RB Offset=24	22.01	22.17	22.06
		RB Size=50, RB Offset=49	22.02	22.07	21.99
		RB Size=100, RB Offset=0	22.24	22.19	22.19
	16QAM	RB Size=1, RB Offset=0	22.43	22.38	22.49
		RB Size=1, RB Offset=49	22.42	22.39	22.50
		RB Size=1, RB Offset=99	22.18	22.31	22.50
		RB Size=50, RB Offset=0	22.13	22.14	22.14
		RB Size=50, RB Offset=24	22.15	22.02	22.01
		RB Size=50, RB Offset=49	21.95	21.83	21.75
		RB Size=100, RB Offset=0	22.26	22.19	22.24

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	3.46	13	Pass
QPSK (100%RB Size)	4.11	13	Pass
16QAM (1RB Size)	4.42	13	Pass
16QAM (100%RB Size)	5.59	13	Pass

EIRP:**QPSK:**

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
2535.00	68.32	93	1.4	H	10.9	0.43	10.60	21.07	33
2535.00	65.72	143	2.0	V	6.6	0.43	10.60	16.77	33
10 MHz Bandwidth									
2535.00	68.07	117	1.7	H	10.6	0.43	10.60	20.77	33
2535.00	65.73	290	1.0	V	6.6	0.43	10.60	16.77	33
15 MHz Bandwidth									
2535.00	67.57	347	1.2	H	10.1	0.43	10.60	20.27	33
2535.00	65.23	57	1.8	V	6.1	0.43	10.60	16.27	33
20 MHz Bandwidth									
2535.00	67.39	8	1.2	H	9.9	0.43	10.60	20.07	33
2535.00	65.11	26	1.5	V	6.0	0.43	10.60	16.17	33

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
2535.00	68.58	48	2.2	H	11.1	0.43	10.60	21.27	33
2535.00	65.64	190	1.2	V	6.5	0.43	10.60	16.67	33
10 MHz Bandwidth									
2535.00	68.13	322	2.2	H	10.7	0.43	10.60	20.87	33
2535.00	65.22	340	2.0	V	6.1	0.43	10.60	16.27	33
15 MHz Bandwidth									
2535.00	67.59	131	1.8	H	10.1	0.43	10.60	20.27	33
2535.00	64.67	245	1.9	V	5.5	0.43	10.60	15.67	33
20 MHz Bandwidth									
2535.00	67.01	350	1.0	H	9.6	0.43	10.60	19.77	33
2535.00	64.39	226	1.7	V	5.2	0.43	10.60	15.37	33

Note:

All above data were tested with no amplifier

Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH


Applicable Standard

FCC 47 §2.1049, §22.917, §22.905, §24.238 and §27.53.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 1% to 5% of the anticipated emission bandwidth and the 26 dB & 99% bandwidth was recorded.



Test Data

Environmental Conditions

Temperature:	23~25 °C
Relative Humidity:	49~50 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Alisa.Gao from 2016-11-29 to 2016-12-02.

EUT operation mode: transmitting

Test Result: Compliance. Please refer to the following plots.

Cellular Band (Part 22H)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	836.6	244.5	316.6
EGPRS(8PSK)	836.6	244.5	320.6

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	836.6	4.208	4.890
HSUPA (BPSK)	836.6	4.208	4.910
HSDPA (16QAM)	836.6	4.208	4.890


PCS Band (Part 24E)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	1880.0	244.5	320.6
EGPRS(8PSK)	1880.0	252.5	320.6


Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	1880.0	4.208	4.910
HSUPA (BPSK)	1880.0	4.228	4.890
HSDPA (16QAM)	1880.0	4.228	4.910



Cellular Band (Part 22H)



26 dB Emissions & 99% Occupied Bandwidth for GSM (GMSK) Mode







26 dB Emissions & 99% Occupied Bandwidth for EDGE Mode



26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode**26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode**



26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode**PCS Band (Part 24E)****26 dB Emissions & 99% Occupied Bandwidth for GSM (GMSK) Mode**



26 dB Emissions & 99% Occupied Bandwidth for EDGE Mode**26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode**



26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode**26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode**



LTE Band 2: (Middle Channel)



Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.111	1.285
	16QAM	1.117	1.285
3.0	QPSK	2.705	2.922
	16QAM	2.693	2.958
5.0	QPSK	4.549	5.070
	16QAM	4.549	5.070
10.0	QPSK	9.018	9.860
	16QAM	8.978	9.780
15.0	QPSK	13.587	15.210
	16QAM	13.527	14.970
20.0	QPSK	18.036	19.639
	16QAM	18.036	19.559



QPSK (1.4 MHz) - 99% Occupied Bandwidth & 26 dB Bandwidth, Middle channel**16-QAM (1.4 MHz) - 99% Occupied Bandwidth & 26 dB Bandwidth, Middle channel**

QPSK (3.0 MHz) - 99% Occupied Bandwidth & 26 dB Bandwidth, Middle channel**16-QAM (3.0 MHz) - 99% Occupied Bandwidth & 26 dB Bandwidth, Middle channel**

QPSK (5.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**16-QAM (5.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**

QPSK (10.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**16-QAM (10.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel****QPSK (15.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**

**16-QAM (15.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**

QPSK (20.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**16-QAM (20.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**

LTE Band 4: (Middle Channel)

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.111	1.291
	16QAM	1.117	1.291
3.0	QPSK	2.693	2.934
	16QAM	2.693	2.958
5.0	QPSK	4.549	5.090
	16QAM	4.529	5.110
10.0	QPSK	8.978	9.860
	16QAM	8.978	9.820
15.0	QPSK	13.527	15.090
	16QAM	13.527	15.030
20.0	QPSK	18.036	19.639
	16QAM	18.036	19.639

Delta 1 [T1] -0.32 dB

Ref Lvl 34.5 dBm 1.29058116 MHz

RBW 30 kHz RF Att 40 dB

VBW 100 kHz

SWT 8 ms Unit dBm

4.5 dB Offset

D1 16 dBm

D2 10 dBm

1MAX

1 [T1] -16.05 dBm

1 [T1] 1.73186313 GHz

1 [T1] -0.32 dB

1.29058116 MHz

1 [T1] 1.1102204 MHz

1 [T1] 9.93 dBm

1 [T1] 1.73194729 GHz

1 [T1] 7.84 dBm

1 [T1] 1.73305832 GHz

1MAX

Center 1.7325 GHz 280 kHz/ Span 2.8 MHz

Date: 30.NOV.2016 07:44:40

Delta 1 [T1] -0.24 dB RBW 30 kHz RF Att 40 dB

Ref Lvl 34.5 dBm 1.29058116 MHz SWT 8 ms Unit dBm

4.5 dB Offset

D1 16.6 dBm

D2 -9.4 dBm

1MAX

1 [T1] -5.60 dBm

1 [T1] 1.73185752 GHz

1 [T1] -0.24 dB

1 [T1] 1.29058116 MHz

1 [T1] 1.11663327 MHz

1 [T1] 5.60 dBm

1 [T1] 1.73194168 GHz



1 [T1] 6.98 dBm



1 [T1] 1.73305832 GHz



1MAX



Center 1.7325 GHz 280 kHz/ Span 2.8 MHz



Date: 30. NOV. 2016 07:42:26

QPSK (3.0 MHz) - 99% Occupied Bandwidth & 26 dB Bandwidth, Middle channel**16-QAM (3.0 MHz) - 99% Occupied Bandwidth & 26 dB Bandwidth, Middle channel**

QPSK (5.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**16-QAM (5.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**



QPSK (10.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**16-QAM (10.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel****QPSK (15.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**



**16-QAM (15.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**

QPSK (20.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**16-QAM (20.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**


LTE Band 5: (Middle Channel)

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.111	1.291
	16QAM	1.100	1.279
3.0	QPSK	2.693	2.946
	16QAM	2.693	2.958
5.0	QPSK	4.549	5.070
	16QAM	4.549	5.090
10.0	QPSK	8.978	9.900
	16QAM	8.978	9.739


QPSK (1.4 MHz) - 99% Occupied Bandwidth & 26 dB Bandwidth, Middle channel**16-QAM (1.4 MHz) - 99% Occupied Bandwidth & 26 dB Bandwidth, Middle channel**



QPSK (3.0 MHz) - 99% Occupied Bandwidth & 26 dB Bandwidth, Middle channel**16-QAM (3.0 MHz) - 99% Occupied Bandwidth & 26 dB Bandwidth, Middle channel**

QPSK (5.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel





16-QAM (5.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel






QPSK (10.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**16-QAM (10.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**

LTE BAND 7:


Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
5.0	QPSK	4.549	5.090
	16QAM	4.549	5.030
10.0	QPSK	8.978	9.780
	16QAM	8.978	9.780
15.0	QPSK	13.587	15.210
	16QAM	13.587	15.090
20.0	QPSK	17.956	19.559
	16QAM	18.036	19.719



QPSK (5.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**16-QAM (5.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**

QPSK (10.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**16-QAM (10.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel****QPSK (15.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**



16-QAM (15.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel



QPSK (20.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**16-QAM (20.0 MHz) - 99% Occupied & 26 dB Emissions Bandwidth, Middle channel**

FCC §2.1051, §22.917(a) & §24.238(a); §27.53 (h) (m) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a) and §27.53(h) (m).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Data

Environmental Conditions

Temperature:	24~26 °C
Relative Humidity:	50~52 %
ATM Pressure:	100.0~101.0 kPa


The testing was performed by Alisa.Gao from 2016-11-29 to 2016-12-09.

EUT operation mode: transmitting

Test result: Compliance, please refer to the following plots.


Cellular Band (Part 22H)

30 MHz – 1 GHz (GSM Mode)




Fundamental test


1 GHz – 10 GHz (GSM Mode)



30 MHz – 1 GHz (WCDMA Mode)




1 GHz – 10 GHz (WCDMA Mode)






PCS Band (Part 24E)

30 MHz – 1 GHz (GSM Mode)




1 GHz – 2 GHz (GSM Mode)




2 GHz – 20 GHz (GSM Mode)**30 MHz – 1 GHz (WCDMA Mode)**

1 GHz – 2 GHz (WCDMA Mode)




2 GHz – 20 GHz (WCDMA Mode)




LTE Band 2:


30 MHz - 1 GHz (1.4 MHz, Middle Channel)




1 GHz - 2 GHz (1.4 MHz, Middle Channel)




2 GHz – 20 GHz (1.4 MHz, Middle Channel)




30 MHz - 1 GHz (3.0 MHz, Middle Channel)




1 GHz – 2 GHz (3.0 MHz, Middle Channel)




2 GHz – 20 GHz (3.0 MHz, Middle Channel)




30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz - 2 GHz (5.0 MHz, Middle Channel)




2 GHz – 20 GHz (5.0 MHz, Middle Channel)




30 MHz - 1 GHz (10.0 MHz, Middle Channel)




1 GHz – 2 GHz (10.0 MHz, Middle Channel)




2 GHz – 20 GHz (10.0 MHz, Middle Channel)




30 MHz - 1 GHz (15.0 MHz, Middle Channel)




1 GHz - 2 GHz (15.0 MHz, Middle Channel)




2 GHz – 20 GHz (15.0 MHz, Middle Channel)




30 MHz - 1 GHz (20.0 MHz, Middle Channel)



1 GHz – 2 GHz (20.0 MHz, Middle Channel)




2 GHz – 20 GHz (20.0 MHz, Middle Channel)




LTE Band 4:


30 MHz - 1 GHz (1.4 MHz, Middle Channel)




1 GHz - 2 GHz (1.4 MHz, Middle Channel)




2 GHz – 20 GHz (1.4 MHz, Middle Channel)




30 MHz - 1 GHz (3.0 MHz, Middle Channel)




1 GHz – 2 GHz (3.0 MHz, Middle Channel)




2 GHz – 20 GHz (3.0 MHz, Middle Channel)




30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz - 2 GHz (5.0 MHz, Middle Channel)




2 GHz – 20 GHz (5.0 MHz, Middle Channel)




30 MHz - 1 GHz (10.0 MHz, Middle Channel)




1 GHz – 2 GHz (10.0 MHz, Middle Channel)




2 GHz – 20 GHz (10.0 MHz, Middle Channel)




30 MHz - 1 GHz (15.0 MHz, Middle Channel)




1 GHz - 2 GHz (15.0 MHz, Middle Channel)




2 GHz – 20 GHz (15.0 MHz, Middle Channel)




30 MHz - 1 GHz (20.0 MHz, Middle Channel)



1 GHz – 2 GHz (20.0 MHz, Middle Channel)




2 GHz – 20 GHz (20.0 MHz, Middle Channel)




LTE Band 5:


30 MHz - 1 GHz (1.4 MHz, Middle Channel)




1 GHz – 10 GHz (1.4 MHz, Middle Channel)




30 MHz - 1 GHz (3.0 MHz, Middle Channel)



1 GHz – 10 GHz (3.0 MHz, Middle Channel)




30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz – 10 GHz (5.0 MHz, Middle Channel)



30 MHz - 1 GHz (10.0 MHz, Middle Channel)




1 GHz – 10 GHz (10.0 MHz, Middle Channel)




LTE Band 7:


30 MHz – 1 GHz (5.0 MHz, Middle Channel)




1 GHz – 3.0 GHz (5.0 MHz, Middle Channel)




3.0 GHz – 26 GHz (5.0 MHz, Middle Channel)




30 MHz – 1.0 GHz (10.0 MHz, Middle Channel)




1 GHz – 3 GHz (10.0 MHz, Middle Channel)




3 GHz – 26 GHz (10.0 MHz, Middle Channel)





30 MHz – 1 GHz (15.0 MHz, Middle Channel)




1 GHz – 3 GHz (15.0 MHz, Middle Channel)




3 GHz – 26 GHz (15.0 MHz, Middle Channel)**30 MHz – 1 GHz (20.0 MHz, Middle Channel)**

1 GHz – 3 GHz (20.0 MHz, Middle Channel)



3 GHz – 26 GHz (20.0 MHz, Middle Channel)



FCC § 2.1053; § 22.917 (a); § 24.238 (a); § 27.53 (h)(m) SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, § 22.917(a) and § 24.238(a) and § 27.53(h)(m)

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TX pwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$

Spurious attenuation limit in dB = $55 + 10 \log_{10} (\text{power out in Watts})$

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Layne Li on 2016-11-28.

EUT operation mode: transmitting

Pre-scan with Low, Middle and High channel, the worst case as below:

30 MHz ~ 10 GHz:

Cellular Band (Part 22H)

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
GSM Mode, Middle channel										
151.94	27.91	131	1.1	H	-69.1	0.27	0	-69.37	-13	56.37
151.94	28.63	26	2.0	V	-68.4	0.27	0	-68.67	-13	55.67
1673.20	54.93	127	1.2	H	-49.0	0.30	9.40	-39.90	-13	26.90
1673.20	54.02	174	1.7	V	-51.4	0.30	9.40	-42.30	-13	29.30
WCDMA Mode, Middle channel										
151.94	27.73	355	1.5	H	-69.3	0.27	0	-69.57	-13	56.57
151.94	29.04	63	2.3	V	-68.0	0.27	0	-68.27	-13	55.27
1673.20	43.63	353	1.5	H	-60.3	0.30	9.40	-51.20	-13	38.20
1673.20	44.62	16	2.1	V	-60.8	0.30	9.40	-51.70	-13	38.70

30 MHz ~ 20 GHz:

PCS Band (Part 24E)

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
GSM Mode, Middle channel										
151.94	28.67	20	1.0	H	-68.3	0.27	0	-68.57	-13	55.57
151.94	28.17	280	2.0	V	-68.8	0.27	0	-69.07	-13	56.07
3760.00	41.83	151	2.2	H	-51.9	2.42	12.60	-41.72	-13	28.72
3760.00	39.23	109	2.2	V	-53.5	2.42	12.60	-43.32	-13	30.32
WCDMA Mode, Middle channel										
151.94	28.22	35	1.9	H	-68.8	0.27	0	-69.07	-13	56.07
151.94	29.84	14	1.0	V	-67.2	0.27	0	-67.47	-13	54.47
3760.00	40.73	187	1.8	H	-53.0	2.42	12.60	-42.82	-13	29.82
3760.00	40.43	187	2.2	V	-52.3	2.42	12.60	-42.12	-13	29.12

LTE Band:*Test mode: Transmitting (Pre-scan with all the bandwidth, and worse case as below)*

Frequency	Receiver	Turntable	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
(MHz)	Reading (dBμV)	Angle Degree	Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
Band 2										
Test frequency range:30 MHz ~ 20 GHz										
151.94	28.35	98	2.2	H	-68.6	0.27	0	-68.87	-13	55.87
151.94	28.76	133	2.3	V	-68.2	0.27	0	-68.47	-13	55.47
3760.00	40.83	220	2.3	H	-52.9	2.42	12.60	-42.72	-13	29.72
3760.00	40.63	227	1.6	V	-52.1	2.42	12.60	-41.92	-13	28.92
Band 4										
Test frequency range:30 MHz ~ 20 GHz										
151.94	28.21	84	2.3	H	-68.8	0.27	0	-69.07	-13	56.07
151.94	28.49	59	2.3	V	-68.5	0.27	0	-68.77	-13	55.77
3465.00	41.97	292	1.2	H	-52.6	2.34	12.40	-42.54	-13	29.54
3465.00	39.51	197	2.2	V	-53.0	2.34	12.40	-42.94	-13	29.94
Band 5										
Test frequency range:30 MHz ~ 10 GHz										
151.94	28.42	141	1.7	H	-68.6	0.27	0	-68.87	-13	55.87
151.94	28.13	269	2.2	V	-68.9	0.27	0	-69.17	-13	56.17
1673.00	41.83	332	1.6	H	-62.1	0.30	9.40	-53.00	-13	40.00
1673.00	43.92	355	1.1	V	-61.5	0.30	9.40	-52.40	-13	39.40
Band 7										
Test frequency range: 30 MHz ~ 26 GHz										
151.94	27.73	20	1.2	H	-69.3	0.27	0	-69.57	-25	44.57
151.94	27.78	109	2.5	V	-69.2	0.27	0	-69.47	-25	44.47
5070.00	34.76	280	1.7	H	-53.9	2.57	12.70	-43.77	-25	18.77
5070.00	33.47	146	1.0	V	-56.0	2.57	12.70	-45.87	-25	20.87

Note:

- 1) Absolute Level = SG Level - Cable loss + Antenna Gain
- 2) Margin = Limit- Absolute Level

FCC § 22.917 (a); § 24.238 (a); § 27.53 (h)(m) - BAND EDGES**Applicable Standard**

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to § 24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to FCC § 27.53 (h)(m), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency

**Test Data****Environmental Conditions**

Temperature:	23~25 °C
Relative Humidity:	49~50 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Alisa.Gao from 2016-11-29 to 2016-12-02.

EUT operation mode: transmitting

Test Result: Compliance. Please refer to the following plots.

Ref Lvl 27.5 dBm

Marker 1 [T1] -14.44 dBm

RBW 5 kHz

VBW 10 kHz

SWT 200 ms

RF Att 40 dB

Unit dBm

4.5 dB Offset

1MAX

D1 -13 dBm

1 [T1] -14.44 dBm

823.97795591 MHz

Center 824 MHz

200 kHz/

Span 2 MHz

Date: 2.DEC.2016 13:41:35


Ref Lvl 27.5 dBm
 Marker 1 [T1] 849.02605210 MHz -14.70 dBm
 RBW 5 kHz RF Att 40 dB
 VBW 10 kHz
 SWT 200 ms Unit dBm

4.5 dB Offset
 1MAX
 D1 -13 dBm
 1A


Center 849 MHz
 200 kHz/
 Span 2 MHz



Date: 2.DEC.2016 13:43:57



Cellular Band, Left Band Edge for EDGE Mode





Cellular Band, Right Band Edge for EDGE Mode




Cellular Band, Left Band Edge for WCDMA (BPSK) Mode**Cellular Band, Right Band Edge for WCDMA (BPSK) Mode**


Cellular Band, Left Band Edge for HSDPA (16QAM) Mode**Cellular Band, Right Band Edge for HSDPA (16QAM) Mode**

Cellular Band, Left Band Edge for HSUPA (BPSK) Mode**Cellular Band, Right Band Edge for HSUPA (BPSK) Mode**


PCS Band, Left Band Edge for GSM (GMSK) Mode




PCS Band, Right Band Edge for GSM (GMSK) Mode




PCS Band, Left Band Edge for EDGE Mode




PCS Band, Right Band Edge for EDGE Mode




PCS Band, Left Band Edge for WCDMA (BPSK) Mode




PCS Band, Right Band Edge for WCDMA (BPSK) Mode




PCS Band, Left Band Edge for HSDPA (16QAM) Mode




PCS Band, Right Band Edge for HSDPA (16QAM) Mode



PCS Band, Left Band Edge for HSUPA (BPSK) Mode




PCS Band, Right Band Edge for HSUPA (BPSK) Mode




LTE Band 2:


QPSK (1.4 MHz, FULL RB) - Left Band Edge




QPSK (1.4 MHz, FULL RB) - Right Band Edge




16-QAM (1.4 MHz, FULL RB) - Left Band Edge




16-QAM (1.4 MHz, FULL RB) - Right Band Edge




QPSK (3.0 MHz, FULL RB) - Left Band Edge




QPSK (3.0 MHz, FULL RB) - Right Band Edge





16-QAM (3.0 MHz, FULL RB) - Left Band Edge




16-QAM (3.0 MHz, FULL RB) - Right Band Edge




QPSK (5.0 MHz, FULL RB) - Left Band Edge**QPSK (5.0 MHz, FULL RB) - Right Band Edge**


16-QAM (5.0 MHz, FULL RB) - Left Band Edge




16-QAM (5.0 MHz, FULL RB) - Right Band Edge




QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge




16-QAM (10.0 MHz, FULL RB) - Left Band Edge




16-QAM (10.0 MHz, FULL RB) - Right Band Edge



QPSK (15.0 MHz, FULL RB) - Left Band Edge



QPSK (15.0 MHz, FULL RB) - Right Band Edge



Ref Lvl 34.5 dBm

Marker 1 [T1] -22.38 dBm

RBW 200 kHz RF Att 40 dB

VBW 500 kHz

SWT 5 ms Unit dBm

4.5 dB Offset

1.84997996 GHz

1.84997996 GHz

-22.38 dBm

-13 dBm

Center 1.85 GHz



3 MHz/

Span 30 MHz


Date: 1.DEC.2016 11:34:07

Marker 1 [T1]
 Ref Lvl -23.00 dBm
 34.5 dBm 1.91003006 GHz
 RBW 200 kHz RF Att 40 dB
 VBW 500 kHz
 SWT 5 ms Unit dBm


4.5 dB Offset
 MAX
 D1 -13 dBm
 A
 1RM
 Center 1.91 GHz 3 MHz/
 Span 30 MHz
 Date: 1.DEC.2016 12:05:57

QPSK (20.0 MHz, FULL RB) - Left Band Edge**QPSK (20.0 MHz, FULL RB) - Right Band Edge**

16-QAM (20.0 MHz, FULL RB) - Left Band Edge




16-QAM (20.0 MHz, FULL RB) - Right Band Edge




LTE Band 4:


QPSK (1.4 MHz, FULL RB) - Left Band Edge




QPSK (1.4 MHz, FULL RB) - Right Band Edge




16-QAM (1.4 MHz, FULL RB) - Left Band Edge




16-QAM (1.4 MHz, FULL RB) - Right Band Edge




QPSK (3.0 MHz, FULL RB) - Left Band Edge




QPSK (3.0 MHz, FULL RB) - Right Band Edge




16-QAM (3.0 MHz, FULL RB) - Left Band Edge




16-QAM (3.0 MHz, FULL RB) - Right Band Edge




QPSK (5.0 MHz, FULL RB) - Left Band Edge




QPSK (5.0 MHz, FULL RB) - Right Band Edge




16-QAM (5.0 MHz, FULL RB) - Left Band Edge




16-QAM (5.0 MHz, FULL RB) - Right Band Edge




QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge





16-QAM (10.0 MHz, FULL RB) - Left Band Edge




16-QAM (10.0 MHz, FULL RB) - Right Band Edge




QPSK (15.0 MHz, FULL RB) - Left Band Edge**QPSK (15.0 MHz, FULL RB) - Right Band Edge**


16-QAM (15.0 MHz, FULL RB) - Left Band Edge




16-QAM (15.0 MHz, FULL RB) - Right Band Edge




QPSK (20.0 MHz, FULL RB) - Left Band Edge




QPSK (20.0 MHz, FULL RB) - Right Band Edge



16-QAM (20.0 MHz, FULL RB) - Left Band Edge




16-QAM (20.0 MHz, FULL RB) - Right Band Edge






LTE Band 5:



QPSK (1.4 MHz, FULL RB) - Left Band Edge




QPSK (1.4 MHz, FULL RB) - Right Band Edge




16-QAM (1.4 MHz, FULL RB) - Left Band Edge**16-QAM (1.4 MHz, FULL RB) - Right Band Edge**



QPSK (3.0 MHz, FULL RB) - Left Band Edge**QPSK (3.0 MHz, FULL RB) - Right Band Edge**

16-QAM (3.0 MHz, FULL RB) - Left Band Edge




16-QAM (3.0 MHz, FULL RB) - Right Band Edge




QPSK (5.0 MHz, FULL RB) - Left Band Edge**QPSK (5.0 MHz, FULL RB) - Right Band Edge**

16-QAM (5.0 MHz, FULL RB) - Left Band Edge



16-QAM (5.0 MHz, FULL RB) - Right Band Edge



Ref Lvl 34.5 dBm
 Marker 1 [T1] -21.79 dBm
 823.9795992 MHz
 RBW 100 kHz
 VBW 300 kHz
 SWT 5 ms
 RF Att 40 dB
 Unit dBm

4.5 dB Offset

1MAX

D1 -13 dBm

1RM

Center 824 MHz

2 MHz/

Span 20 MHz

Date: 1.DEC.2016 14:50:45

Ref Lvl 34.5 dBm

Marker 1 [T1] -20.16 dBm

849.02004008 MHz

RBW 100 kHz

VBW 300 kHz

SWT 5 ms

RF Att 40 dB

Unit dBm

4.5 dB Offset

1MAX

D1 -13 dBm



1RM

Center 849 MHz

2 MHz/


Span 20 MHz

Date: 1.DEC.2016 14:51:39


16-QAM (10.0 MHz, FULL RB) - Left Band Edge**16-QAM (10.0 MHz, FULL RB) - Right Band Edge**

LTE Band 7:


QPSK (5.0 MHz, FULL RB) - Left Band Edge




QPSK (5.0 MHz, FULL RB) - Right Band Edge




16-QAM (5.0 MHz, FULL RB) - Left Band Edge




16-QAM (5.0 MHz, FULL RB) - Right Band Edge




QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge




16-QAM (10.0 MHz, FULL RB) - Left Band Edge




16-QAM (10.0 MHz, FULL RB) - Right Band Edge




QPSK (15 MHz, FULL RB) - Left Band Edge




QPSK (15 MHz, FULL RB) - Right Band Edge





16-QAM (15 MHz, FULL RB) - Left Band Edge




16-QAM (15 MHz, FULL RB) - Right Band Edge




QPSK (20 MHz, FULL RB) - Left Band Edge**QPSK (20 MHz, FULL RB) - Right Band Edge**

16-QAM (20 MHz, FULL RB) - Left Band Edge



16-QAM (20 MHz, FULL RB) - Right Band Edge



FCC § 2.1055; § 22.355; § 24.235; §27.54; - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055, §22.355, §24.235 and §27.54.

According to FCC §2.1055, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile > 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100.0 kPa

The testing was performed by Alisa.Gao on 2016-11-29.

EUT operation mode: transmitting

Test Result: Compliance. Please refer to the following plots.

Cellular Band (Part 22H)**GSM Mode**

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	-7	-0.00837	2.5
-20		9	0.01076	2.5
-10		5	0.00598	2.5
0		5	0.00598	2.5
10		-1	-0.00120	2.5
20		6	0.00717	2.5
30		12	0.01434	2.5
40		6	0.00717	2.5
50		8	0.00956	2.5
25	V _{min.} = 3.6	-1	-0.00120	2.5
25	V _{max.} = 4.2	9	0.01076	2.5

EDGE Mode

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	8	0.00956	2.5
-20		13	0.01554	2.5
-10		2	0.00239	2.5
0		12	0.01434	2.5
10		10	0.01195	2.5
20		8	0.00956	2.5
30		2	0.00239	2.5
40		3	0.00359	2.5
50		10	0.01195	2.5
25	$V_{min.} = 3.6$	8	0.00956	2.5
25	$V_{max.} = 4.2$	7	0.00837	2.5

WCDMA Mode

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	3	0.00359	2.5
-20		5	0.00598	2.5
-10		-3	-0.00359	2.5
0		-6	-0.00717	2.5
10		11	0.01315	2.5
20		-4	-0.00478	2.5
30		3	0.00359	2.5
40		11	0.01315	2.5
50		4	0.00478	2.5
25	$V_{min.} = 3.6$	-3	-0.00359	2.5
25	$V_{max.} = 4.2$	10	0.01195	2.5

PCS Band (Part 24E)**GSM Mode**

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	-2	-0.00106	pass
-20		5	0.00266	pass
-10		8	0.00426	pass
0		2	0.00106	pass
10		-1	-0.00053	pass
20		2	0.00106	pass
30		-9	-0.00479	pass
40		-5	-0.00266	pass
50		14	0.00745	pass
25	V _{min.} = 3.6	4	0.00213	pass
25	V _{max.} = 4.2	3	0.00160	pass

EDGE Mode

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	11	0.00585	pass
-20		14	0.00745	pass
-10		7	0.00372	pass
0		9	0.00479	pass
10		6	0.00319	pass
20		9	0.00479	pass
30		8	0.00426	pass
40		3	0.00160	pass
50		-6	-0.00319	pass
25	V _{min.} = 3.6	-4	-0.00213	pass
25	V _{max.} = 4.2	6	0.00319	pass

WCDMA Mode

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	7	0.00372	pass
-20		-6	-0.00319	pass
-10		8	0.00426	pass
0		2	0.00106	pass
10		-3	-0.00160	pass
20		-2	-0.00106	pass
30		2	0.00106	pass
40		-7	-0.00372	pass
50		7	0.00372	pass
25	$V_{min} = 3.6$	4	0.00213	pass
25	$V_{max} = 4.2$	4	0.00479	pass

LTE Band 2: QPSK

20.0 MHz Middle Channel, $f_0=1880\text{MHz}$				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	7	0.00373	pass
-20		8	0.00426	pass
-10		-2	-0.00106	pass
0		6	0.00319	pass
10		-4	-0.00213	pass
20		-2	-0.00106	pass
30		9	0.00479	pass
40		9	0.00479	pass
50		11	0.00585	pass
20	V _{min} = 3.6	8	0.00426	pass
	V _{max} = 4.2	-5	-0.00266	pass

LTE Band 4: QPSK

20.0 MHz Middle Channel, $f_0=1732.5\text{ MHz}$				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	-5	-0.00289	pass
-20		3	0.00173	pass
-10		6	0.00346	pass
0		-1	-0.00058	pass
10		1	0.00058	pass
20		-7	-0.00404	pass
30		8	0.00462	pass
40		7	0.00404	pass
50		-5	-0.00289	pass
20	V _{min} = 3.6	1	0.00058	pass
	V _{max} = 4.2	7	0.00404	pass

LTE Band 5: QPSK

10.0 MHz Middle Channel, $f_o=836.5$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	11	0.01315	pass
-20		13	0.01554	pass
-10		7	0.00837	pass
0		6	0.00717	pass
10		3	0.00359	pass
20		4	0.00478	pass
30		5	0.00598	pass
40		-2	-0.00239	pass
50		2	0.00239	pass
20	V _{min} = 3.6	7	0.00837	pass
	V _{max} = 4.2	5	0.00598	pass

LTE Band 7: QPSK

20.0 MHz Middle Channel, $f_o=2535$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	6	0.00237	pass
-20		-1	-0.00039	pass
-10		12	0.00473	pass
0		1	0.00039	pass
10		9	0.00355	pass
20		2	0.00079	pass
30		5	0.00197	pass
40		-1	-0.00039	pass
50		-8	-0.00316	pass
20	V _{min} = 3.6	-1	-0.00039	pass
	V _{max} = 4.2	10	0.00394	pass

***** END OF REPORT *****