



TEST REPORT

Report Reference No. : TRE1710011204 R/C : 73402

FCC ID : ZSW-30-053

Applicant's name : b mobile HK Limited

Address : Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong.

Manufacturer : b mobile HK Limited

Address : Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong.

Test item description : Mobile Phone

Trade Mark : Bmobile

Model/Type reference : AX1091

Listed Model(s) : -

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample : Oct.24, 2017

Date of testing : Oct.25, 2017 - Nov.01, 2017

Date of issue : Nov.02, 2017

Result : PASS

Compiled by
(position+printedname+signature).... : File administrators Candy Liu

Candy Liu

Supervised by
(position+printedname+signature).... : Project Engineer : Edward Pan

Edward Pan

Approved by
(position+printedname+signature).... : RF Manager Hans Hu

Hans Hu

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd.

Address : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road,
Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
<u>4.</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>10</u>
5.1.	Antenna requirement	10
5.2.	Conducted Emissions (AC Main)	11
5.3.	Conducted Peak Output Power	14
5.4.	Power Spectral Density	15
5.5.	6dB bandwidth	22
5.6.	Restricted band	28
5.7.	Band edge and Spurious Emissions (conducted)	32
5.8.	Spurious Emissions (radiated)	49
<u>6.</u>	<u>TEST SETUP PHOTOS</u>	<u>56</u>
<u>7.</u>	<u>EXTERANAL AND INTERNAL PHOTOS</u>	<u>57</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 DTS Meas Guidance v04](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating under §15.247

1.2. Report version

Version No.	Date of issue	Description
00	Nov.02, 2017	Original

2. TEST DESCRIPTION

Test Item	FCC Rule	Result	Test Engineer
Antenna requirement	15.203/15.247(c)	Pass	William Wang
Line Conducted Emissions (AC Main)	15.207	Pass	William Wang
Conducted Peak Output Power	15.247(b)(3)	Pass	Baozhu Hu
Power Spectral Density	15.247(e)	Pass	Baozhu Hu
6dB Bandwidth	15.247(a)(2)	Pass	Baozhu Hu
Restricted band	15.247(d)/15.205	Pass	Baozhu Hu
Spurious Emissions	15.247(d)/15.209	Pass	Baozhu Hu

Note: The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Client Information

Applicant:	b mobile HK Limited
Address:	Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong.
Manufacturer:	b mobile HK Limited
Address:	Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong.

3.2. Product Description

Name of EUT:	Mobile Phone
Trade Mark:	Bmobile
Model No.:	AX1091
Listed Model(s):	-
IMEI 1:	356549846541313
IMEI 2:	354564546431132
Power supply:	DC 3.8V From exchange battery
Adapter information:	Input: 100-240Va.c., 50/60Hz, 0.2A Output: 5Vd.c.,1A
Hardware version:	V1.2
Software version:	Android 7.0
WIFI	
Supported type:	802.11b/802.11g/802.11n(HT20)/802.11n(HT40)
Modulation:	DSSS for 802.11b OFDM for 802.11g/802.11n(HT20)/802.11n(HT40)
Operation frequency:	2412MHz~2462MHz for 802.11b/802.11g/802.11n(HT20) 2422MHz~2452MHz for 802.11n(HT40)
Channel number:	11 for 802.11b/802.11g/802.11n(HT20) 7 for 802.11n(HT40)
Channel separation:	5MHz
Antenna type:	PIFA
Antenna gain:	1.3dBi

3.3. Operation state

➤ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

802.11b/g/n(HT20)		802.11n(HT40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	01	-
02	2417	02	-
03	2422	03	2422
04	2427	04	2427
05	2432	05	2432
06	2437	06	2437
07	2442	07	2442
08	2447	08	2447
09	2452	09	2452
10	2457	10	-
11	2462	11	-

➤ Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit (duty cycle>98%).
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated suprious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit(duty cycle>98%). The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data Recorded in the report.

3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○	/	Manufacturer:	/
		Model No.:	/
○	/	Manufacturer:	/
		Model No.:	/

3.5. Modifications

No modifications were implemented to meet testing criteria.

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

4.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

IC-Registration No.:5377B-1

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377B-1.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emissions 9kHz~40GHz	1.60 dB	(1)
Radiated spurious emissions 9kHz~40GHz	2.20 dB	(1)
Conducted Emissions 9kHz~30MHz	3.39 dB	(1)
Radiated Emissions 30~1000MHz	4.24 dB	(1)
Radiated Emissions 1~18GHz	5.16 dB	(1)
Radiated Emissions 18~40GHz	5.54 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.5. Equipments Used during the Test

Conducted Emissions					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	2016/11/13
2	EMI Test Receiver	Rohde&Schwarz	ESCI3	100038	2016/11/13
3	Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	2016/11/13
4	EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	-	-

Radiated Emissions					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI test receiver	Rohde&Schwarz	ESI 26	100009	2016/11/13
2	Loop Antenna	Rohde&Schwarz	HFH2-Z2	100020	2016/11/13
3	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2016/11/13
4	Horn antenna	ShwarzBeck	9120D	1011	2016/11/13
5	Horn Antenna	SCHWARZBECK	BBHA9170	25841	2016/11/13
6	Amplifier	Sonoma	310N	E009-13	2016/11/13
7	JS Amplifier	Rohde&Schwarz	JS4-00101800-28-5A	F201504	2016/11/13
8	Amplifier	Compliance Direction systems	PAP1-4060	120	2016/11/13
9	High pass filter	Compliance Direction systems	BSU-6	34202	2016/11/13
10	EMI test Software	Rohde&Schwarz	ESK1	-	-
11	EMI test Software	Audix	E3	-	-
12	TURNTABLE	MATURO	TT2.0	-	-
13	ANTENNA MAST	MATURO	TAM-4.0-P	-	-

RF Conducted methods					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Spectrum Analyzer	Rohde&Schwarz	FSP	1164.4391.40	2016/11/13
2	MXA Signal Analyzer	Agilent Technologies	N9020A	MY5050187	2016/11/13

The Cal.Interval was one year.

5. TEST CONDITIONS AND RESULTS

5.1. Antenna requirement

REQUIREMENT:

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

The directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. Conducted Emissions (AC Main)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS


☒ Passed ☐ Not Applicable

Note:

- 1) Transd=Cable lose+ Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin= Limit -Level

Test Line:

L

**MEASUREMENT RESULT: "GM1711015037_fin"**

11/1/2017 1:35PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.564000	38.50	10.2	56	17.5	QP	L1	GND
0.888000	33.90	10.1	56	22.1	QP	L1	GND
1.090500	33.70	10.2	56	22.3	QP	L1	GND
2.346000	53.10	10.2	56	2.9	QP	L1	GND
3.745500	40.70	10.3	56	15.3	QP	L1	GND
4.699500	27.40	10.3	56	28.6	QP	L1	GND
5.734500	42.90	10.3	60	17.1	QP	L1	GND


MEASUREMENT RESULT: "GM1711015037_fin2"

11/1/2017 1:35PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.343500	27.80	10.2	49	21.3	AV	L1	GND
0.483000	18.40	10.2	46	27.9	AV	L1	GND
0.568500	28.90	10.2	46	17.1	AV	L1	GND
0.852000	30.40	10.1	46	15.6	AV	L1	GND
1.050000	29.90	10.2	46	16.1	AV	L1	GND
2.377500	34.70	10.2	46	11.3	AV	L1	GND
3.574500	31.00	10.3	46	15.0	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM1711015038_fin"**

11/1/2017 1:38PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.447000	48.50	10.2	57	8.4	QP	N	GND
0.969000	44.80	10.2	56	11.2	QP	N	GND
1.036500	47.30	10.2	56	8.7	QP	N	GND
2.373000	52.60	10.2	56	3.4	QP	N	GND
2.895000	43.20	10.2	56	12.8	QP	N	GND
3.475500	48.00	10.3	56	8.0	QP	N	GND
4.429500	40.20	10.3	56	15.8	QP	N	GND

MEASUREMENT RESULT: "GM1711015038_fin2"

11/1/2017 1:38PM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.447000	36.40	10.2	47	10.5	AV	N	GND
0.573000	30.70	10.2	46	15.3	AV	N	GND
0.964500	33.10	10.2	46	12.9	AV	N	GND
1.036500	31.20	10.2	46	14.8	AV	N	GND
1.104000	33.10	10.2	46	12.9	AV	N	GND
2.382000	37.90	10.2	46	8.1	AV	N	GND
3.489000	30.30	10.3	46	15.7	AV	N	GND

5.3. Conducted Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): **30dBm**:

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10: 2013 and KDB 558074 D01 for compliance to FCC 47 CFR 15.247 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector
4. Record the measurement data.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable


Type	Channel	Output power (dBm)	Limit (dBm)	Result
802.11b	01	17.21	≤30.00	Pass
	06	17.58		
	11	17.29		
802.11g	01	15.97	≤30.00	Pass
	06	16.38		
	11	15.08		
802.11n(HT20)	01	13.84	≤30.00	Pass
	06	14.46		
	11	14.37		
802.11n(HT40)	03	13.34	≤30.00	Pass
	06	13.76		
	09	13.69		

5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency=DTS channel center frequency
Span =1.5 times the DTS bandwidth
 $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$, $VBW \geq 3 \times RBW$
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS


☒ Passed ☐ Not Applicable



Type	Channel	Power Spectral Density (dBm/30kHz)	Limit (dBm/3kHz)	Result
802.11b	01	3.87	≤8.00	Pass
	06	1.65		
	11	3.43		
802.11g	01	-7.05	≤8.00	Pass
	06	-6.90		
	11	-8.29		
802.11n(HT20)	01	-8.93	≤8.00	Pass
	06	-8.48		
	11	-8.68		
802.11n(HT40)	03	-13.46	≤8.00	Pass
	06	-13.17		
	09	-12.95		

Test plot as follows:

Type:		802.11 b	
CH01			Frequency Auto Tune Center Freq 2.412000000 GHz Start Freq 2.404000000 GHz Stop Freq 2.420000000 GHz CF Step 1.600000 MHz Auto Man Freq Offset 0 Hz
CH06			Frequency Auto Tune Center Freq 2.437000000 GHz Start Freq 2.429000000 GHz Stop Freq 2.445000000 GHz CF Step 1.600000 MHz Auto Man Freq Offset 0 Hz
CH11			Frequency Auto Tune Center Freq 2.462000000 GHz Start Freq 2.454000000 GHz Stop Freq 2.470000000 GHz CF Step 1.600000 MHz Auto Man Freq Offset 0 Hz

Type:		802.11 g
CH01		Frequency Auto Tune Center Freq 2.412000000 GHz Start Freq 2.399500000 GHz Stop Freq 2.424500000 GHz CF Step 2.500000 MHz Auto Man Freq Offset 0 Hz
CH06		Frequency Auto Tune Center Freq 2.437000000 GHz Start Freq 2.424500000 GHz Stop Freq 2.449500000 GHz CF Step 2.500000 MHz Auto Man Freq Offset 0 Hz
CH11		Frequency Auto Tune Center Freq 2.462000000 GHz Start Freq 2.449500000 GHz Stop Freq 2.474500000 GHz CF Step 2.500000 MHz Auto Man Freq Offset 0 Hz

Type:		802.11n(HT20)	
CH01			
CH06			
CH11			


Type:		802.11n(HT40)	
CH03			Frequency Auto Tune Center Freq 2.422000000 GHz Start Freq 2.394500000 GHz Stop Freq 2.449500000 GHz CF Step 5.000000 MHz Auto Man Freq Offset 0 Hz
CH06			Frequency Auto Tune Center Freq 2.437000000 GHz Start Freq 2.409500000 GHz Stop Freq 2.464500000 GHz CF Step 5.000000 MHz Auto Man Freq Offset 0 Hz
CH09			Frequency Auto Tune Center Freq 2.452000000 GHz Start Freq 2.424500000 GHz Stop Freq 2.479500000 GHz CF Step 5.000000 MHz Auto Man Freq Offset 0 Hz

5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = DTS channel center frequency
Span = 2 x DTS bandwidth
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS



☒ Passed ☐ Not Applicable


Type	Channel	6dB Bandwidth (MHz)	Limit (kHz)	Result
802.11b	01	9.10	≥500	Pass
	06	9.55		
	11	9.58		
802.11g	01	15.14	≥500	Pass
	06	16.38		
	11	15.96		
802.11n(HT20)	01	17.58	≥500	Pass
	06	17.61		
	11	17.37		
802.11n(HT40)	03	36.12	≥500	Pass
	06	35.95		
	09	35.58		

Test plot as follows:

Type:	802.11 b
CH01	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.412000000 GHz Center Freq: 2.412000000 GHz Radio Std: None Trig: Free Run Avg/Hold: 500/500 #IF Gain: Low #Atten: 30 dB Radio Device: BTS Ref Offset 0.5 dB Mkr1 2.4125 GHz Ref 20.50 dBm 5.6601 dBm Center 2.412 GHz Span 25 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.4 ms Occupied Bandwidth 12.464 MHz Total Power 21.6 dBm Transmit Freq Error 46.166 kHz OBW Power 99.00 % x dB Bandwidth 9.101 MHz x dB -6.00 dB Frequency Center Freq 2.412000000 GHz CF Step 2.500000 MHz Freq Offset 0 Hz
CH06	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.437000000 GHz Center Freq: 2.437000000 GHz Radio Std: None Trig: Free Run Avg/Hold: 500/500 #IF Gain: Low #Atten: 30 dB Radio Device: BTS Ref Offset 0.5 dB Mkr1 2.437525 GHz Ref 20.50 dBm 5.9488 dBm Center 2.437 GHz Span 25 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.4 ms Occupied Bandwidth 12.518 MHz Total Power 22.0 dBm Transmit Freq Error 57.524 kHz OBW Power 99.00 % x dB Bandwidth 9.554 MHz x dB -6.00 dB Frequency Center Freq 2.437000000 GHz CF Step 2.500000 MHz Freq Offset 0 Hz
CH11	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.462000000 GHz Center Freq: 2.462000000 GHz Radio Std: None Trig: Free Run Avg/Hold: 500/500 #IF Gain: Low #Atten: 30 dB Radio Device: BTS Ref Offset 0.5 dB Mkr1 2.4605 GHz Ref 20.50 dBm 5.3618 dBm Center 2.462 GHz Span 25 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.4 ms Occupied Bandwidth 12.548 MHz Total Power 21.5 dBm Transmit Freq Error -151.53 kHz OBW Power 99.00 % x dB Bandwidth 9.575 MHz x dB -6.00 dB Frequency Center Freq 2.462000000 GHz CF Step 2.500000 MHz Freq Offset 0 Hz

Type:	802.11 g
CH01	Agilent Spectrum Analyzer - Occupied BW Center Freq 2.412000000 GHz Ref Offset 0.5 dB Ref 20.50 dBm Mkr1 2.41326 GHz 0.0051834 dBm Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Span 30 MHz Sweep 2.933 ms Occupied Bandwidth 16.374 MHz Total Power 16.8 dBm Transmit Freq Error 19.569 kHz OBW Power 99.00 % x dB Bandwidth 15.14 MHz x dB -6.00 dB Frequency Center Freq 2.412000000 GHz CF Step 3.000000 MHz Freq Offset 0 Hz
CH06	Agilent Spectrum Analyzer - Occupied BW Center Freq 2.437000000 GHz Ref Offset 0.5 dB Ref 20.50 dBm Mkr1 2.4445 GHz -2.5052 dBm Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Span 30 MHz Sweep 2.933 ms Occupied Bandwidth 16.502 MHz Total Power 15.7 dBm Transmit Freq Error 15.395 kHz OBW Power 99.00 % x dB Bandwidth 16.38 MHz x dB -6.00 dB Frequency Center Freq 2.437000000 GHz CF Step 3.000000 MHz Freq Offset 0 Hz
CH11	Agilent Spectrum Analyzer - Occupied BW Center Freq 2.462000000 GHz Ref Offset 0.5 dB Ref 20.50 dBm Mkr1 2.45453 GHz -3.0970 dBm Center 2.462 GHz #Res BW 100 kHz #VBW 300 kHz Span 30 MHz Sweep 2.933 ms Occupied Bandwidth 16.472 MHz Total Power 14.5 dBm Transmit Freq Error -46.085 kHz OBW Power 99.00 % x dB Bandwidth 15.96 MHz x dB -6.00 dB Frequency Center Freq 2.462000000 GHz CF Step 3.000000 MHz Freq Offset 0 Hz

Type:	802.11n(HT20)
CH01	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.412000000 GHz Ref Offset 0.5 dB Ref 20.50 dBm Mkr1 2.41701 GHz -3.1173 dBm Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Span 30 MHz Sweep 2.933 ms Occupied Bandwidth 17.631 MHz Total Power 15.1 dBm Transmit Freq Error 13.991 kHz OBW Power 99.00 % x dB Bandwidth 17.58 MHz x dB -6.00 dB Frequency Center Freq 2.412000000 GHz CF Step 3.000000 MHz Freq Offset 0 Hz
CH06	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.437000000 GHz Ref Offset 0.5 dB Ref 20.50 dBm Mkr1 2.43826 GHz -4.0555 dBm Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Span 30 MHz Sweep 2.933 ms Occupied Bandwidth 17.619 MHz Total Power 13.9 dBm Transmit Freq Error 21.312 kHz OBW Power 99.00 % x dB Bandwidth 17.61 MHz x dB -6.00 dB Frequency Center Freq 2.437000000 GHz CF Step 3.000000 MHz Freq Offset 0 Hz
CH11	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.462000000 GHz Ref Offset 0.5 dB Ref 20.50 dBm Mkr1 2.45702 GHz -4.2772 dBm Center 2.462 GHz #Res BW 100 kHz #VBW 300 kHz Span 30 MHz Sweep 2.933 ms Occupied Bandwidth 17.641 MHz Total Power 13.6 dBm Transmit Freq Error -38.981 kHz OBW Power 99.00 % x dB Bandwidth 17.37 MHz x dB -6.00 dB Frequency Center Freq 2.462000000 GHz CF Step 3.000000 MHz Freq Offset 0 Hz


Type:		802.11n(HT40)	
CH03		Frequency Center Freq 2.422000000 GHz CF Step 7.000000 MHz Auto Man Freq Offset 0 Hz	
CH06		Frequency Center Freq 2.437000000 GHz CF Step 7.000000 MHz Auto Man Freq Offset 0 Hz	
CH09		Frequency Center Freq 2.452000000 GHz CF Step 7.000000 MHz Auto Man Freq Offset 0 Hz	

5.6. Restricted band

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

- 1) The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
- 2) The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- 3) The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
- 4) The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
- 5) The receiver set as follow:
 RBW=1MHz, VBW=3MHz PEAK detector for Peak value.
 RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Note:

- 1) Final level= Read level + Antenna Factor+ Cable Loss- Preamp Factor

802.11b					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	14.48	28.05	6.62	0.00	49.15	74.00	-24.85	Vertical	Peak
2390.01	14.07	27.65	6.75	0.00	48.47	74.00	-25.53	Vertical	Peak
2310.00	13.38	28.05	6.62	0.00	48.05	74.00	-25.95	Horizontal	Peak
2390.01	14.55	27.65	6.75	0.00	48.95	74.00	-25.05	Horizontal	Peak
2310.00	11.31	28.05	6.62	0.00	45.98	54.00	-8.02	Vertical	Average
2390.01	10.87	27.65	6.75	0.00	45.27	54.00	-8.73	Vertical	Average
2310.00	11.33	28.05	6.62	0.00	46.00	54.00	-8.00	Horizontal	Average
2390.01	10.87	27.65	6.75	0.00	45.27	54.00	-8.73	Horizontal	Average

802.11b					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.49	14.70	27.26	6.83	0.00	48.79	74.00	-25.21	Vertical	Peak
2500.00	14.71	27.20	6.84	0.00	48.75	74.00	-25.25	Vertical	Peak
2483.49	12.58	27.26	6.83	0.00	46.67	74.00	-27.33	Horizontal	Peak
2500.00	12.53	27.20	6.84	0.00	46.57	74.00	-27.43	Horizontal	Peak
2483.49	10.89	27.26	6.83	0.00	44.98	54.00	-9.02	Vertical	Average
2500.00	10.92	27.20	6.84	0.00	44.96	54.00	-9.04	Vertical	Average
2483.49	10.93	27.26	6.83	0.00	45.02	54.00	-8.98	Horizontal	Average
2500.00	10.91	27.20	6.84	0.00	44.95	54.00	-9.05	Horizontal	Average

802.11g					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	14.81	28.05	6.62	0.00	49.48	74.00	-24.52	Vertical	Peak
2390.01	14.18	27.65	6.75	0.00	48.58	74.00	-25.42	Vertical	Peak
2310.00	14.17	28.05	6.62	0.00	48.84	74.00	-25.16	Horizontal	Peak
2390.01	15.13	27.65	6.75	0.00	49.53	74.00	-24.47	Horizontal	Peak
2310.00	11.36	28.05	6.62	0.00	46.03	54.00	-7.97	Vertical	Average
2390.01	10.90	27.65	6.75	0.00	45.30	54.00	-8.70	Vertical	Average
2310.00	11.36	28.05	6.62	0.00	46.03	54.00	-7.97	Horizontal	Average
2390.01	10.89	27.65	6.75	0.00	45.29	54.00	-8.71	Horizontal	Average

802.11g					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.49	13.44	27.26	6.83	0.00	47.53	74.00	-26.47	Vertical	Peak
2500.00	13.32	27.20	6.84	0.00	47.36	74.00	-26.64	Vertical	Peak
2483.49	14.57	27.26	6.83	0.00	48.66	74.00	-25.34	Horizontal	Peak
2500.00	12.38	27.20	6.84	0.00	46.42	74.00	-27.58	Horizontal	Peak
2483.49	11.01	27.26	6.83	0.00	45.10	54.00	-8.90	Vertical	Average
2500.00	10.88	27.20	6.84	0.00	44.92	54.00	-9.08	Vertical	Average
2483.49	10.98	27.26	6.83	0.00	45.07	54.00	-8.93	Horizontal	Average
2500.00	10.89	27.20	6.84	0.00	44.93	54.00	-9.07	Horizontal	Average

802.11n(HT20)					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	12.98	28.05	6.62	0.00	47.65	74.00	-26.35	Vertical	Peak
2390.01	13.04	27.65	6.75	0.00	47.44	74.00	-26.56	Vertical	Peak
2310.00	14.10	28.05	6.62	0.00	48.77	74.00	-25.23	Horizontal	Peak
2390.01	14.09	27.65	6.75	0.00	48.49	74.00	-25.51	Horizontal	Peak
2310.00	11.37	28.05	6.62	0.00	46.04	54.00	-7.96	Vertical	Average
2390.01	10.92	27.65	6.75	0.00	45.32	54.00	-8.68	Vertical	Average
2310.00	11.35	28.05	6.62	0.00	46.02	54.00	-7.98	Horizontal	Average
2390.01	10.89	27.65	6.75	0.00	45.29	54.00	-8.71	Horizontal	Average

802.11n(HT20)					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.49	12.24	27.26	6.83	0.00	46.33	74.00	-27.67	Vertical	Peak
2500.00	12.79	27.20	6.84	0.00	46.83	74.00	-27.17	Vertical	Peak
2483.49	12.37	27.26	6.83	0.00	46.46	74.00	-27.54	Horizontal	Peak
2500.00	12.37	27.20	6.84	0.00	46.41	74.00	-27.59	Horizontal	Peak
2483.49	11.11	27.26	6.83	0.00	45.20	54.00	-8.80	Vertical	Average
2500.00	10.91	27.20	6.84	0.00	44.95	54.00	-9.05	Vertical	Average
2483.49	11.27	27.26	6.83	0.00	45.36	54.00	-8.64	Horizontal	Average
2500.00	10.90	27.20	6.84	0.00	44.94	54.00	-9.06	Horizontal	Average

802.11n(HT40)					CH03				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	14.36	28.05	6.62	0.00	49.03	74.00	-24.97	Vertical	Peak
2389.99	13.24	27.65	6.75	0.00	47.64	74.00	-26.36	Vertical	Peak
2310.00	14.14	28.05	6.62	0.00	48.81	74.00	-25.19	Horizontal	Peak
2389.99	13.69	27.65	6.75	0.00	48.09	74.00	-25.91	Horizontal	Peak
2310.00	11.31	28.05	6.62	0.00	45.98	54.00	-8.02	Vertical	Average
2389.99	10.92	27.65	6.75	0.00	45.32	54.00	-8.68	Vertical	Average
2310.00	11.30	28.05	6.62	0.00	45.97	54.00	-8.03	Horizontal	Average
2389.99	11.52	27.65	6.75	0.00	45.92	54.00	-8.08	Horizontal	Average


802.11n(HT40)					CH09				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.50	14.16	27.26	6.83	0.00	48.25	74.00	-25.75	Vertical	Peak
2500.00	14.20	27.20	6.84	0.00	48.24	74.00	-25.76	Vertical	Peak
2483.50	13.86	27.26	6.83	0.00	47.95	74.00	-26.05	Horizontal	Peak
2500.00	15.10	27.20	6.84	0.00	49.14	74.00	-24.86	Horizontal	Peak
2483.50	11.19	27.26	6.83	0.00	45.28	54.00	-8.72	Vertical	Average
2500.00	10.95	27.20	6.84	0.00	44.99	54.00	-9.01	Vertical	Average
2483.50	11.63	27.26	6.83	0.00	45.72	54.00	-8.28	Horizontal	Average
2500.00	10.94	27.20	6.84	0.00	44.98	54.00	-9.02	Horizontal	Average

5.7. Band edge and Spurious Emissions (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure
Center frequency=DTS channel center frequency
The span = 1.5 times the DTS bandwidth.
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum PSD level

Note: the channel found to contain the maximum PSD level can be used to establish the reference level.
3. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.



TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Test Item:	Bandedge	Type:	802.11 g
CH01			
CH11			

Test Item:	Bandedge	Type:	802.11 n(HT20)																																																																																																		
CH01	 <table><tr><th>PKR</th><th>MODE</th><th>TRC</th><th>SCL</th><th>F</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.41328 GHz</td><td>-4.523 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.40000 GHz</td><td>-6.388 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.39000 GHz</td><td>-55.448 dBm</td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.31000 GHz</td><td>-60.792 dBm</td><td></td><td></td><td></td></tr><tr><td>5</td><td>N</td><td>1</td><td>f</td><td>2.39938 GHz</td><td>-47.432 dBm</td><td></td><td></td><td></td></tr></table>	PKR	MODE	TRC	SCL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.41328 GHz	-4.523 dBm				2	N	1	f	2.40000 GHz	-6.388 dBm				3	N	1	f	2.39000 GHz	-55.448 dBm				4	N	1	f	2.31000 GHz	-60.792 dBm				5	N	1	f	2.39938 GHz	-47.432 dBm				 <table><tr><th>PKR</th><th>MODE</th><th>TRC</th><th>SCL</th><th>F</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.480736 GHz</td><td>-4.862 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.483500 GHz</td><td>-55.754 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.500000 GHz</td><td>-60.051 dBm</td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.483824 GHz</td><td>-54.469 dBm</td><td></td><td></td><td></td></tr></table>	PKR	MODE	TRC	SCL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.480736 GHz	-4.862 dBm				2	N	1	f	2.483500 GHz	-55.754 dBm				3	N	1	f	2.500000 GHz	-60.051 dBm				4	N	1	f	2.483824 GHz	-54.469 dBm			
PKR	MODE	TRC	SCL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																																																																													
1	N	1	f	2.41328 GHz	-4.523 dBm																																																																																																
2	N	1	f	2.40000 GHz	-6.388 dBm																																																																																																
3	N	1	f	2.39000 GHz	-55.448 dBm																																																																																																
4	N	1	f	2.31000 GHz	-60.792 dBm																																																																																																
5	N	1	f	2.39938 GHz	-47.432 dBm																																																																																																
PKR	MODE	TRC	SCL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																																																																													
1	N	1	f	2.480736 GHz	-4.862 dBm																																																																																																
2	N	1	f	2.483500 GHz	-55.754 dBm																																																																																																
3	N	1	f	2.500000 GHz	-60.051 dBm																																																																																																
4	N	1	f	2.483824 GHz	-54.469 dBm																																																																																																
CH11	 <table><tr><th>PKR</th><th>MODE</th><th>TRC</th><th>SCL</th><th>F</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.41328 GHz</td><td>-4.523 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.40000 GHz</td><td>-6.388 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.39000 GHz</td><td>-55.448 dBm</td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.31000 GHz</td><td>-60.792 dBm</td><td></td><td></td><td></td></tr><tr><td>5</td><td>N</td><td>1</td><td>f</td><td>2.39938 GHz</td><td>-47.432 dBm</td><td></td><td></td><td></td></tr></table>	PKR	MODE	TRC	SCL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.41328 GHz	-4.523 dBm				2	N	1	f	2.40000 GHz	-6.388 dBm				3	N	1	f	2.39000 GHz	-55.448 dBm				4	N	1	f	2.31000 GHz	-60.792 dBm				5	N	1	f	2.39938 GHz	-47.432 dBm				 <table><tr><th>PKR</th><th>MODE</th><th>TRC</th><th>SCL</th><th>F</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.480736 GHz</td><td>-4.862 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.483500 GHz</td><td>-55.754 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.500000 GHz</td><td>-60.051 dBm</td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.483824 GHz</td><td>-54.469 dBm</td><td></td><td></td><td></td></tr></table>	PKR	MODE	TRC	SCL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.480736 GHz	-4.862 dBm				2	N	1	f	2.483500 GHz	-55.754 dBm				3	N	1	f	2.500000 GHz	-60.051 dBm				4	N	1	f	2.483824 GHz	-54.469 dBm			
PKR	MODE	TRC	SCL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																																																																													
1	N	1	f	2.41328 GHz	-4.523 dBm																																																																																																
2	N	1	f	2.40000 GHz	-6.388 dBm																																																																																																
3	N	1	f	2.39000 GHz	-55.448 dBm																																																																																																
4	N	1	f	2.31000 GHz	-60.792 dBm																																																																																																
5	N	1	f	2.39938 GHz	-47.432 dBm																																																																																																
PKR	MODE	TRC	SCL	F	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																																																																													
1	N	1	f	2.480736 GHz	-4.862 dBm																																																																																																
2	N	1	f	2.483500 GHz	-55.754 dBm																																																																																																
3	N	1	f	2.500000 GHz	-60.051 dBm																																																																																																
4	N	1	f	2.483824 GHz	-54.469 dBm																																																																																																


Test Item:	Bandedge	Type:	802.11 n(HT40)
CH03			
CH09			

Test Item:	SE	Type:	802.11 b
Reference level CH01			
CH01			
			

Reference level CH06




CH06



Reference level CH11



CH11



Test Item:	SE	Type:	802.11 g
Reference level CH01			
CH01			
			

Reference level CH06



CH06




Reference level CH11



CH11



Test Item:	SE	Type:	802.11 n(HT20)
Reference level CH01			
CH01			
			

Reference level CH06



CH06



Reference level CH11



CH11



Test Item:	SE	Type:	802.11 n(HT40)
Reference level CH03			
CH03			
			

Reference level CH06



CH06



Reference level CH09



CH09



5.8. Spurious Emissions (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


➤ 9kHz ~30MHz



➤ 30MHz ~ 1GHz



➤ Above 1GHz



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna.
5. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1GHz, RBW=120kHz, VBW=300kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) Above 1GHz, RBW=1MHz, VBW=3MHz PEAK detector for Peak value.
RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

Note:

- 1) Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.

➤ **9kHz ~ 30MHz**

The EUT was pre-scanned the frequency band (9kHz~30MHz), found the radiated level lower than the limit, so don't show on the report.


➤ **30MHz ~1000MHz**

Have pre-scan all modulation mode, found the 802.11b mode CH01 which it was worst case, so only the worst case's data on the test report.

➤ 30MHz ~ 1GHz

Polarization:

Vertical


**MEASUREMENT RESULT: "GM1710276062_red"**

10/27/2017 5:50PM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
47.460000	21.10	-8.8	40.0	18.9	QP	100.0	182.00	VERTICAL
57.160000	20.70	-9.4	40.0	19.3	QP	100.0	86.00	VERTICAL
101.780000	20.00	-10.5	43.5	23.5	QP	100.0	274.00	VERTICAL
284.140000	22.90	-7.6	46.0	23.1	QP	100.0	359.00	VERTICAL
536.340000	29.40	-1.0	46.0	16.6	QP	100.0	194.00	VERTICAL
922.400000	38.80	7.0	46.0	7.2	QP	100.0	166.00	VERTICAL

Polarization:

Horizontal

**MEASUREMENT RESULT: "GM1710276061_red"**

10/27/2017 5:47PM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
53.280000	21.50	-9.0	40.0	18.5	QP	100.0	7.00	HORIZONTAL
57.160000	20.60	-9.4	40.0	19.4	QP	300.0	214.00	HORIZONTAL
101.780000	19.30	-10.5	43.5	24.2	QP	300.0	285.00	HORIZONTAL
286.080000	23.00	-7.5	46.0	23.0	QP	300.0	359.00	HORIZONTAL
546.040000	29.10	-0.8	46.0	16.9	QP	100.0	315.00	HORIZONTAL
932.100000	38.60	7.1	46.0	7.4	QP	100.0	315.00	HORIZONTAL

➤ 1 GHz ~ 25 GHz

802.11b					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1680.83	35.54	25.14	5.73	36.89	29.52	74.00	-44.48	Vertical	Peak
3033.91	35.30	28.67	7.52	38.22	33.27	74.00	-40.73	Vertical	Peak
4213.21	34.53	30.03	8.95	37.64	35.87	74.00	-38.13	Vertical	Peak
5747.59	33.22	31.84	10.51	35.46	40.11	74.00	-33.89	Vertical	Peak
1613.75	35.79	24.94	5.60	36.75	29.58	74.00	-44.42	Horizontal	Peak
3010.83	36.38	28.62	7.49	38.23	34.26	74.00	-39.74	Horizontal	Peak
4181.16	35.77	29.98	8.92	37.69	36.98	74.00	-37.02	Horizontal	Peak
5617.41	33.19	31.76	10.30	35.82	39.43	74.00	-34.57	Horizontal	Peak

802.11b					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1728.56	36.70	25.26	5.82	36.99	30.79	74.00	-43.21	Vertical	Peak
3738.13	35.12	29.42	8.43	38.24	34.73	74.00	-39.27	Vertical	Peak
4871.10	46.61	31.46	9.59	36.76	50.90	74.00	-23.10	Vertical	Peak
7357.33	32.00	36.30	12.03	34.88	45.45	74.00	-28.55	Vertical	Peak
1837.46	34.17	25.36	6.02	37.17	28.38	74.00	-45.62	Horizontal	Peak
3598.09	34.79	29.29	8.27	38.27	34.08	74.00	-39.92	Horizontal	Peak
4871.10	41.68	31.46	9.59	36.76	45.97	74.00	-28.03	Horizontal	Peak
6833.77	31.29	34.24	11.64	34.96	42.21	74.00	-31.79	Horizontal	Peak

802.11b					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1724.17	35.29	25.25	5.81	36.98	29.37	74.00	-44.63	Vertical	Peak
3844.28	34.78	29.64	8.56	38.20	34.78	74.00	-39.22	Vertical	Peak
4920.96	43.27	31.42	9.62	36.62	47.69	74.00	-26.31	Vertical	Peak
7245.81	32.96	36.25	11.91	35.02	46.10	74.00	-27.90	Vertical	Peak
1759.64	36.32	25.32	5.88	37.06	30.46	74.00	-43.54	Horizontal	Peak
3709.69	35.54	29.33	8.40	38.25	35.02	74.00	-38.98	Horizontal	Peak
4920.96	35.11	31.42	9.62	36.62	39.53	74.00	-34.47	Horizontal	Peak
6678.99	33.10	34.20	11.45	35.21	43.54	74.00	-30.46	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11g					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1746.25	53.91	25.29	5.86	37.03	48.03	74.00	-25.97	Vertical	Peak
3644.18	36.16	29.30	8.32	38.26	35.52	74.00	-38.48	Vertical	Peak
4834.05	38.88	31.53	9.56	36.86	43.11	74.00	-30.89	Vertical	Peak
6594.52	32.99	34.19	11.35	35.36	43.17	74.00	-30.83	Vertical	Peak
1759.64	35.21	25.32	5.88	37.06	29.35	74.00	-44.65	Horizontal	Peak
3088.45	36.43	28.78	7.59	38.22	34.58	74.00	-39.42	Horizontal	Peak
4821.76	35.27	31.56	9.55	36.90	39.48	74.00	-34.52	Horizontal	Peak
7282.79	31.61	36.28	11.95	34.97	44.87	74.00	-29.13	Horizontal	Peak

802.11g					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1913.84	39.14	25.44	6.14	37.23	33.49	74.00	-40.51	Vertical	Peak
3570.71	35.92	29.21	8.22	38.31	35.04	74.00	-38.96	Vertical	Peak
4883.52	39.93	31.43	9.59	36.73	44.22	74.00	-29.78	Vertical	Peak
6645.07	31.57	34.20	11.41	35.28	41.90	74.00	-32.10	Vertical	Peak
2135.22	33.90	26.99	6.38	37.33	29.94	74.00	-44.06	Horizontal	Peak
3057.17	35.84	28.72	7.55	38.22	33.89	74.00	-40.11	Horizontal	Peak
4871.10	36.04	31.46	9.59	36.76	40.33	74.00	-33.67	Horizontal	Peak
5821.21	33.12	32.14	10.60	35.33	40.53	74.00	-33.47	Horizontal	Peak

802.11g					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1899.28	38.42	25.30	6.11	37.22	32.61	74.00	-41.39	Vertical	Peak
3625.67	35.35	29.30	8.30	38.26	34.69	74.00	-39.31	Vertical	Peak
4983.99	33.87	31.48	9.66	36.44	38.57	74.00	-35.43	Vertical	Peak
7319.96	31.97	36.30	11.99	34.92	45.34	74.00	-28.66	Vertical	Peak
1795.84	34.94	25.39	5.95	37.13	29.15	74.00	-44.85	Horizontal	Peak
3598.09	35.31	29.29	8.27	38.27	34.60	74.00	-39.40	Horizontal	Peak
6283.16	31.69	33.07	11.00	35.30	40.46	74.00	-33.54	Horizontal	Peak
8681.17	31.40	37.79	12.98	34.42	47.75	74.00	-26.25	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11n(HT20)					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1764.12	36.24	25.33	5.89	37.06	30.40	74.00	-43.60	Vertical	Peak
3873.75	35.87	29.67	8.60	38.19	35.95	74.00	-38.05	Vertical	Peak
6001.77	31.93	32.50	10.67	35.45	39.65	74.00	-34.35	Vertical	Peak
7470.56	32.26	36.16	12.30	34.88	45.84	74.00	-28.16	Vertical	Peak
1724.17	36.69	25.25	5.81	36.98	30.77	74.00	-43.23	Horizontal	Peak
3738.13	36.51	29.42	8.43	38.24	36.12	74.00	-37.88	Horizontal	Peak
5532.26	33.76	31.87	10.22	36.18	39.67	74.00	-34.33	Horizontal	Peak
7117.84	33.09	35.71	11.86	34.96	45.70	74.00	-28.30	Horizontal	Peak

802.11n(HT20)					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1805.01	35.54	25.39	5.97	37.14	29.76	74.00	-44.24	Vertical	Peak
3088.45	34.74	28.78	7.59	38.22	32.89	74.00	-41.11	Vertical	Peak
4883.52	35.37	31.43	9.59	36.73	39.66	74.00	-34.34	Vertical	Peak
7081.70	30.99	35.55	11.85	34.91	43.48	74.00	-30.52	Vertical	Peak
1773.13	36.87	25.35	5.91	37.08	31.05	74.00	-42.95	Horizontal	Peak
3200.50	36.20	28.80	7.72	38.20	34.52	74.00	-39.48	Horizontal	Peak
4871.10	35.30	31.46	9.59	36.76	39.59	74.00	-34.41	Horizontal	Peak
7045.74	31.95	35.44	11.85	34.86	44.38	74.00	-29.62	Horizontal	Peak

802.11n(HT20)					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1795.84	35.24	25.39	5.95	37.13	29.45	74.00	-44.55	Vertical	Peak
3815.03	35.42	29.62	8.52	38.22	35.34	74.00	-38.66	Vertical	Peak
4920.96	39.83	31.42	9.62	36.62	44.25	74.00	-29.75	Vertical	Peak
7338.62	31.91	36.30	12.01	34.90	45.32	74.00	-28.68	Vertical	Peak
1685.12	36.50	25.16	5.74	36.90	30.50	74.00	-43.50	Horizontal	Peak
3135.99	37.21	28.80	7.64	38.21	35.44	74.00	-38.56	Horizontal	Peak
4797.27	33.95	31.59	9.54	36.96	38.12	74.00	-35.88	Horizontal	Peak
6283.16	33.43	33.07	11.00	35.30	42.20	74.00	-31.80	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11n(HT40)					CH03				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1634.42	36.84	25.01	5.64	36.79	30.70	74.00	-43.30	Vertical	Peak
3616.45	36.14	29.30	8.29	38.27	35.46	74.00	-38.54	Vertical	Peak
4846.37	36.84	31.51	9.57	36.83	41.09	74.00	-32.91	Vertical	Peak
7961.43	32.44	36.95	12.49	34.63	47.25	74.00	-26.75	Vertical	Peak
1724.17	36.59	25.25	5.81	36.98	30.67	74.00	-43.33	Horizontal	Peak
3192.37	36.19	28.80	7.71	38.20	34.50	74.00	-39.50	Horizontal	Peak
4524.47	34.56	30.75	9.34	37.35	37.30	74.00	-36.70	Horizontal	Peak
6331.33	32.39	33.16	11.00	35.30	41.25	74.00	-32.75	Horizontal	Peak

802.11n(HT40)					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1746.25	37.02	25.29	5.86	37.03	31.14	74.00	-42.86	Vertical	Peak
3192.37	36.99	28.80	7.71	38.20	35.30	74.00	-38.70	Vertical	Peak
4871.10	33.10	31.46	9.59	36.76	37.39	74.00	-36.61	Vertical	Peak
6662.01	32.98	34.20	11.43	35.25	43.36	74.00	-30.64	Vertical	Peak
1800.42	36.72	25.40	5.96	37.14	30.94	74.00	-43.06	Horizontal	Peak
2577.80	47.18	27.67	6.89	37.85	43.89	74.00	-30.11	Horizontal	Peak
3598.09	37.53	29.29	8.27	38.27	36.82	74.00	-37.18	Horizontal	Peak
5689.36	32.58	31.62	10.41	35.62	38.99	74.00	-35.01	Horizontal	Peak

802.11n(HT40)					CH09				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1741.81	36.51	25.29	5.85	37.02	30.63	74.00	-43.37	Vertical	Peak
3225.04	37.29	28.65	7.75	38.24	35.45	74.00	-38.55	Vertical	Peak
4354.97	34.41	30.37	9.09	37.58	36.29	74.00	-37.71	Vertical	Peak
6662.01	32.36	34.20	11.43	35.25	42.74	74.00	-31.26	Vertical	Peak
1719.78	36.12	25.24	5.80	36.97	30.19	74.00	-43.81	Horizontal	Peak
3200.50	35.69	28.80	7.72	38.20	34.01	74.00	-39.99	Horizontal	Peak
5073.59	33.51	31.80	9.73	36.33	38.71	74.00	-35.29	Horizontal	Peak
7527.83	32.88	36.13	12.49	34.92	46.58	74.00	-27.42	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.


6. TEST SETUP PHOTOS

Conducted Emissions



Radiated Emissions





7. EXTERANAL AND INTERNAL PHOTOS

8. Reference to the test report No.: TRE1710011201.

.....**End of Report**.....