

FCC REPORT (Mobile Phone)

Applicant: B mobile HK Limited

Address of Applicant: Ground floor, 144 Un Chau Street, Sham Shui Po, Hong Kong

Equipment Under Test (EUT)

Product Name: Mobile Phone

Model No.: K106

FCC ID: ZSW- K106

FCC CFR Title 47 Part 2: 2011

Applicable standards: FCC CFR Title 47 Part22 Subpart H: 2011
FCC CFR Title 47 Part24 Subpart E: 2011

Date of sample receipt: 3 Apr., 2013

Date of Test: 3 Apr., to 18 Apr.,2013

Date of report issued: 27 Apr.,2013

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A circular blue ink seal for the CCIS Laboratory. The outer ring contains the text 'SHENZHEN ZHONGJIAN NANFANG TESTING CO., LTD.' and 'LABORATORY'. The center contains 'CCIS' and '2013. APR'. A handwritten signature in blue ink is written across the seal.

Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2. Version

Version No.	Date	Description
00	27 Apr.,2013	Original

Prepared by:

Sera

Date:

27 Apr., 2013

Report Clerk

Reviewed by:

Roger Feng

Date:

27 Apr., 2013

Project Engineer

3. Contents

	Page
1. COVER PAGE.....	1
2. VERSION.....	2
3. CONTENTS.....	3
4. TEST SUMMARY.....	4
5. GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST MODE.....	7
5.4 RELATED SUBMITTAL(S) / GRANT (S).....	7
5.5 TEST METHODOLOGY.....	7
5.6 LABORATORY FACILITY.....	7
5.7 LABORATORY LOCATION.....	7
5.8 TEST INSTRUMENTS LIST.....	8
6. SYSTEM TEST CONFIGURATION.....	9
6.1 EUT CONFIGURATION.....	9
6.2 EUT EXERCISE.....	9
6.3 CONFIGURATION OF TESTED SYSTEM.....	9
6.4 DESCRIPTION OF TEST MODES.....	9
6.5 CONDUCTED PEAK OUTPUT POWER.....	10
6.6 OCCUPY BANDWIDTH.....	12
6.7 MODULATION CHARACTERISTIC.....	17
6.8 OUT OF BAND EMISSION AT ANTENNA TERMINALS.....	17
6.9 ERP, EIRP MEASUREMENT.....	23
6.10 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT.....	26
6.11 FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT.....	31
6.12 FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT.....	35
7 TEST SETUP PHOTO.....	37
8 EUT CONSTRUCTIONAL DETAILS.....	38

4. Test Summary

Test Item	Section in CFR 47	Result
RF Exposure (SAR)	Part 1.1307 Part 2.1093	Passed* (Please refer to SAR Report)
RF Output Power	Part 2.1046 Part 22.913 (a)(2) Part 24.232 (c)	Pass
Modulation Characteristics	Part 2.1047	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917 Part 24.238	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 22.917 (a) Part 24.238 (a)	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917 (a) Part 24.238 (a)	Pass
Out of band emission, Band Edge	Part 22.917 (a) Part 24.238 (a)	Pass
Frequency stability vs. temperature	Part 2.1055(a)(1)(b)	Pass
Frequency stability vs. voltage	Part 2.1055(d)(1)(2)	Pass

Pass: The EUT complies with the essential requirements in the standard.

5. General Information

5.1 Client Information

Applicant:	B mobile HK Limited
Address of Applicant:	Ground floor, 144 Un Chau Street, Sham Shui Po, Hong Kong
Manufacturer:	PROFIT HARVEST CORPORATION LIMITED
Address of Manufacturer:	FLAT/RM 506C 5/F INNOCENTRE 72 TAT CHEE AVENUE KOWLOON TONG KL
Factory:	SHEN ZHEN SHAN ZHENG INDUSTRY CO.,LTD
Address of Factory:	3/F Buiding B.NO 20 Industry 2 Road(phase 2 Technology park),DaKan Xili,Nanshan District of shenzhen

5.2 General Description of E.U.T.

Product Name:	Mobile Phone
Model No.:	K106
Operation Frequency range:	GSM 850: 824.20MHz-848.80MHz PCS1900: 1850.20MHz-1909.80MHz
GPRS	Not Support
Type of Emission:	244KGXW
IMEI:	IMEI :358227017386340
Software Version:	JSP11DP0110_GST_SP11D_S750_BMOBILE_M10_3232_SE_V07_20130325_stone.zip
Hardware Version:	SP11D_MB_V2.0
Antenna type:	PIFA Antenna
Antenna gain:	1.5dBi
AC adapter:	Input:100-240V AC,50/60Hz 0.2A Output:5.0V DC MAX 500mA
Power supply:	Rechargeable Li-ion Battery DC4.2V/600mAh

Operation Frequency List:

GSM 850		PCS1900	
Channel:	Frequency (MHz)	Channel:	Frequency (MHz)
128	824.20	512	1850.20
129	824.40	513	1850.40
....			
189	836.40	660	1879.80
190	836.60	661	1880.00
191	836.80	662	1880.20
...	...	...	...
250	848.60	809	1909.60
251	848.80	810	1909.80

Regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

GSM850			PCS1900		
	Channel	Frequency(MHz)		Channel	Frequency(MHz)
Lowest channel	128	824.20	Lowest channel	512	1850.20
Middle channel	190	836.60	Middle channel	661	1880.00
Highest channel	251	848.80	Highest channel	810	1909.80

5.3 Test mode

Communicate mode (GSM850)	Keep the EUT in communicating mode on GSM850 band.
Communicate mode (PCS1900)	Keep the EUT in communicating mode on PCS1900 band.

5.4 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is filing to comply with Section Part 22 subpart H and Part 24 subpart E of the FCC CFR 47 Rules.

5.5 Test Methodology

Both conducted and radiated testing were performed according to the procedures document on TIA/EIA 603 and FCC CFR 47.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055 and 2.1057

5.6 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

● **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.7 Laboratory Location

All tests were performed at:

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China

Tel: 0755-23118282

Fax: 0755-23116366

5.8 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	3m Semi- Anechoic Chamber	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	June 09 2012	June 08 2013
2	EMI Test Receiver	Rohde & Schwarz	ESPI	CCIS0022	Apr 01 2013	Mar. 31 2014
3	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	CCIS0005	June 04 2012	June 03 2013
4	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	CCIS0006	May 30 2012	May 29 2013
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
6	Coaxial Cable	CCIS	N/A	CCIS0016	Apr. 01 2013	Mar. 31 2014
7	Coaxial Cable	CCIS	N/A	CCIS0017	Apr. 01 2013	Mar. 31 2014
8	Coaxial cable	CCIS	N/A	CCIS0018	Apr. 01 2013	Mar. 31 2014
9	Coaxial Cable	CCIS	N/A	CCIS0019	Apr. 01 2013	Mar. 31 2014
10	Coaxial Cable	CCIS	N/A	CCIS0087	Apr. 01 2013	Mar. 31 2014
11	Amplifier(10kHz-1.3GHz)	HP	8447D	CCIS0003	Apr. 01 2013	Mar. 31 2014
12	Amplifier(1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	June 09 2012	June 08 2013
13	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	Apr. 01 2013	Mar. 31 2014
14	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 30 2013	Mar. 29 2014
15	Universal Radio communication Tester	Rohde & Schwarz	CMU200	CCIS0069	May. 29 2012	May. 29 2013

6. System test configuration


6.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

6.2 EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency which was for the purpose of the measurements.


6.3 Configuration of Tested System



6.4 Description of Test Modes

The EUT has been tested under operating condition. EUT staying in continuous transmitting mode. Channel Low, Mid and High for each type band with rated data rate were chosen for full testing. The field strength of spurious radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for both GSM/PCS with power adaptor, earphone and Data cable. The worst-case H mode for GSM 850 band, PCS1900 band.

6.5 Conducted Peak Output Power


Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1046
Limit:	GSM850 7W PCS1900 2W
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	The transmitter output was connected to a calibrated attenuator, the other end of which was connected to the power meter(Model No.: NRVS) Transmitter output was read off the power meter in dBm.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

EUT Mode	Channel	Frequency (MHz)	Burst Average power (dBm)	Limit(dBm)	Result
GSM 850	128	824.20	31.77	38.45	Pass
	190	836.60	31.89		
	251	848.80	31.95		
PCS 1900	512	1850.20	29.22	33.00	Pass
	661	1880.00	29.21		
	810	1909.80	29.05		

-

6.6 Occupy Bandwidth


Test Requirement:	FCC part 22.913(a) and FCC part 24.232(b)
Test Method:	FCC part 2.1049
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer 2. RBW was set to about 1% of emission BW, VBW= 3 times RBW. 3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (kHz)	-26dB bandwidth (kHz)
GSM 850	128	824.20	244	320
	190	836.60	244	320
	251	848.80	244	320
PCS 1900	512	1850.20	244	320
	661	1880.00	244	322
	810	1909.80	244	326


Test plot as follows:

Test Item:	99% Occupy bandwidth	Test Mode:	GSM850
------------	----------------------	------------	--------




Date: 11.APR.2013 16:01:48

Lowest channel



Date: 11.APR.2013 15:59:57


Middle channel



Date: 11.APR.2013 15:58:41


Highest channel

Test Item:	-26dB bandwidth	Test Mode:	GSM850
------------	-----------------	------------	--------




Date: 11.APR.2013 16:02:52

Lowest channel



Date: 11.APR.2013 16:04:40


Middle channel



Date: 11.APR.2013 16:06:24


Highest channel

Test Item:	99% Occupy bandwidth	Test Mode:	PCS 1900
------------	----------------------	------------	----------




Date: 11.APR.2013 15:05:36

Lowest channel



Date: 11.APR.2013 15:07:41


Middle channel



Date: 11.APR.2013 15:09:48


Highest channel

Test Item:	-26dB bandwidth	Test Mode:	PCS 1900
------------	-----------------	------------	----------




Date: 11.APR.2013 15:14:59

Lowest channel



Date: 11.APR.2013 15:12:47

Middle channel




Date: 11.APR.2013 15:11:11

Highest channel

6.7 Modulation Characteristic

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.


6.8 Out of band emission at antenna terminals

Test Requirement:	FCC part 22.917(a) and FCC part 24.238(a)
Test Method:	FCC part 2.1051
Limit:	-13dBm
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. 2 The resolution bandwidth of the spectrum analyzer was set at 1MHz; sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic. 3 For the out of band: Set the RBW=100 kHz, VBW=300 kHz when below 1 GHz, RBW =1 MHz, VBW=3 MHz when above 1 GHz, Start=30MHz, Stop= 10th harmonic. 4 Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plot as follows:


Spurious emission

Test Mode:	GSM850	Test Channel:	Lowest channel
------------	--------	---------------	----------------



Date: 11.APR.2013 15:48:21


30MHz~1GHz



Date: 11.APR.2013 15:50:58


1GHz~9GHz

Test Mode:	GSM850	Test Channel:	Middle channel
------------	--------	---------------	----------------



Date: 11.APR.2013 15:53:44


30MHz~1GHz



Date: 11.APR.2013 15:52:32


1GHz~9GHz

Test Mode:	GSM850	Test Channel:	Highest channel
------------	--------	---------------	-----------------



Date: 11.APR.2013 15:54:46


30MHz~1GHz



Date: 11.APR.2013 15:55:51


1GHz~9GHz

Test Mode:	PCS1900	Test Channel:	Lowest channel
------------	---------	---------------	----------------



Date: 11.APR.2013 15:44:19


30MHz~1GHz



Date: 11.APR.2013 15:43:05


1GHz~20GHz

Test Mode:	PCS1900	Test Channel:	Middle channel
------------	---------	---------------	----------------



Date: 11.APR.2013 15:40:32


30MHz~1GHz



Date: 11.APR.2013 15:42:11


1GHz~20GHz

Test Mode:	PCS1900	Test Channel:	Highest channel
------------	---------	---------------	-----------------



Date: 11.APR.2013 15:39:32

30MHz~1GHz




Date: 11.APR.2013 15:38:35

1GHz~20GHz


Band edge emission:

Test Mode:	GSM850
------------	--------



Date: 11.APR.2013 16:12:11


Lowest channel



Date: 11.APR.2013 16:10:18


Highest channel

Test Mode:	PCS1900
------------	---------



Date: 11.APR.2013 15:28:11




Lowest channel



Date: 11.APR.2013 15:30:54

Highest channel

6.9 ERP, EIRP Measurement

Test Requirement:	FCC part 22.913(a) and FCC part 24.232(b)
Test Method:	FCC part 2.1046
Limit:	GSM850 7W ERP PCS1900 2W EIRP
Test setup:	Below 1GHz  Above 1GHz  Substituted method: 




Test Procedure:	1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the measurement, the EUT was communication with the station. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna from 4m to 1m. The reading was recorded and the field strength (E in dBuV/m) was calculated. 3. ERP in frequency band 824.2 –848.80.8MHz were measured using a substitution method. The EUT was replaced by dipole antenna connected, the S.G. output was recorded and ERP was calculated as follows: $\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable Loss (dB)}$ 4. EIRP in frequency band 1850.2 –1909.8MHz were measured using a substitution method. The EUT was replaced by or horn antenna connected, the S.G. output was recorded and EIRP was calculated as follows: $\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable Loss (dB)}$ 5. The worse case was relating to the conducted output power.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	All three channels of GSM850 and PCS1900 are tested, but the test data of this report only shows the worst channel.

Measurement Data (worst case)

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850	251	H	V	33.54	38.50	Pass
			H	31.16		
		E1	V	33.36		
			H	31.05		
		E2	V	33.11		
			H	30.86		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP(dBm)	Limit (dBm)	Result
PCS1900	512	H	V	27.47	33.00	Pass
			H	19.47		
		E1	V	27.33		
			H	19.39		
		E2	V	27.15		
			H	19.27		

6.10 Field strength of spurious radiation measurement

Test Requirement:	FCC part 22.917(a) and FCC part 24.238(a)
Test Method:	FCC part 2.1053
Limit:	-13dBm
Test setup:	Below 1GHz  Above 1GHz  Substituted method: 
Test Procedure:	1. The EUT was placed on a non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT

	positioned in each of its three orthogonal orientations. 3. The frequency range up to tenth harmonic was investigated for each of three fundamental frequencies (low, middle and high channels). Once spurious emission was identified, the power of the emission was determined using the substitution method. 4. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency. ERP / EIRP = S.G. output (dBm) + Antenna Gain(dBd/dBi) – Cable Loss (dB)
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

Test mode:	GSM850		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1648.40	Vertical	-43.68	-13.00	Pass
2472.60	V	-45.87		
3296.80	V	-35.67		
4121.00	V	-47.54		
4945.20	V	-48.65		
5769.40	V	-49.34		
1648.40	Horizontal	-44.71	-13.00	Pass
2472.60	H	-44.41		
3296.80	H	-40.12		
4121.00	H	-47.51		
4945.20	H	-48.19		
5769.40	H	-49.21		
Test mode:	GSM850		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1673.20	Vertical	-42.77	-13.00	Pass
2509.80	V	-45.61		
3346.40	V	-35.91		
4183.00	V	-47.24		
5019.60	V	-48.34		
5856.20	V	-49.75		
1673.20	Horizontal	-44.98	-13.00	Pass
2509.80	H	-44.88		
3346.40	H	-39.89		
4183.00	H	-47.84		
5019.60	H	-48.68		
5856.20	H	-49.71		

Remark :

1. The emission behavior belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	GSM850		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1697.60	Vertical	-43.65	-13.00	Pass
2546.40	V	-46.21		
3395.20	V	-36.41		
4244.00	V	-47.98		
5092.80	V	-48.72		
5941.60	V	-49.74		
1697.60	Horizontal	-45.21	-13.00	Pass
2546.40	H	-44.54		
3395.20	H	-39.12		
4244.00	H	-47.54		
5092.80	H	-48.97		
5941.60	H	-49.38		
Test mode:	PCS1900		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3700.40	Vertical	-33.80	-13.00	Pass
5550.60	V	-18.41		
7400.80	V	-45.68		
9251.00	V	-46.97		
11101.20	V	-47.51		
12951.40	V	-48.32		
3700.40	Horizontal	-28.28	-13.00	Pass
5550.60	H	-27.83		
7400.80	H	-46.32		
9251.00	H	-47.84		
11101.20	H	-48.33		
12951.40	H	-49.46		

Remark :


1. The emission behavior belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	PCS1900		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3760.00	Vertical	-33.12	-13.00	Pass
5640.00	V	-19.98		
7520.00	V	-45.62		
9400.00	V	-46.18		
11280.00	V	-47.62		
13160.00	V	-48.25		
3760.00	Horizontal	-28.41	-13.00	Pass
5640.00	H	-27.18		
7520.00	H	-46.35		
9400.00	H	-47.51		
11280.00	H	-48.22		
13160.00	H	-49.68		
Test mode:	PCS1900		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3819.60	Vertical	-34.21	-13.00	Pass
5729.40	V	-19.52		
7639.20	V	-45.62		
9549.00	V	-46.11		
11458.80	V	-47.27		
13368.60	V	-48.13		
3819.60	Horizontal	-28.31	-13.00	Pass
5729.40	H	-27.41		
7639.20	H	-46.21		
9549.00	H	-47.55		
11458.80	H	-48.95		
13368.60	H	-49.12		

Remark :

1. The emission behavior belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

6.11 Frequency stability V.S. Temperature measurement

Test Requirement:	FCC Part2.1055(a)(1)(b)
Test Method:	FCC Part2.1055(a)(1)(b)
Limit:	2.5ppm
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test procedure:	1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Measurement Data

Reference Frequency: GSM850 Lowest channel=128 channel=824.2MHz					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	35	0.0424654	2.5	Pass
	-20	54	0.0655181		
	-10	35	0.0424654		
	0	36	0.0436787		
	10	41	0.0497452		
	20	45	0.0545984		
	30	43	0.0521718		
	40	34	0.0412521		
	50	36	0.0436787		
Reference Frequency: PCS1900 Lowest channel=512 channel=1850.2MHz					
Power supplied (Vdc)	Temperature (℃)	Frequency error			Result
		Hz	ppm		
3.70	-30	41	0.022160	2.5	Pass
	-20	43	0.023241		
	-10	38	0.020538		
	0	43	0.023241		
	10	48	0.025943		
	20	43	0.023241		
	30	37	0.019998		
	40	35	0.018917		
	50	42	0.022700		

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	43	0.051399	2.5	Pass
	-20	58	0.069328		
	-10	35	0.041836		
	0	47	0.056180		
	10	46	0.054984		
	20	54	0.064547		
	30	53	0.063352		
	40	48	0.057375		
	50	39	0.046617		
Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (℃)	Frequency error			Result
		Hz	ppm		
3.70	-30	45	0.023936	2.5	Pass
	-20	40	0.021277		
	-10	39	0.020745		
	0	43	0.022872		
	10	38	0.020213		
	20	35	0.018617		
	30	39	0.020745		
	40	50	0.026596		
	50	47	0.025000		

Reference Frequency: GSM850 Highest channel=251 channel=848.8 MHz					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	40	0.047125	2.5	Pass
	-20	43	0.050660		
	-10	53	0.062441		
	0	38	0.044769		
	10	40	0.047125		
	20	45	0.053016		
	30	38	0.044769		
	40	36	0.042413		
	50	50	0.058907		
Reference Frequency: PCS1900 Highest channel=810 channel=1909.8MHz					
Power supplied (Vdc)	Temperature (℃)	Frequency error			Result
		Hz	ppm		
3.70	-30	40	0.020945	2.5	Pass
	-20	45	0.023563		
	-10	38	0.019897		
	0	35	0.018327		
	10	40	0.020945		
	20	37	0.019374		
	30	40	0.020945		
	40	36	0.018850		
	50	32	0.016756		

6.12 Frequency stability V.S. Voltage measurement

Test Requirement:	FCC Part2.1055(d)(1)(2)
Test Method:	FCC Part2.1055(d)(1)(2)
Limit:	2.5ppm
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test procedure:	1. Set chamber temperature to 25°C. Use a variable DC power source to power the EUT and set the voltage to rated voltage. 2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. 3. Reduce the input voltage to specified extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

Reference Frequency: GSM850 Lowest channel=128 channel=824.2MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	38	0.046105	2.5	Pass
	3.70	36	0.043679		
	3.40	50	0.060665		
Reference Frequency: PCS1900 Lowest channel=512 channel=1850.2MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	40	0.021619	2.5	Pass
	3.70	45	0.024322		
	3.40	38	0.020538		

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	55	0.065742	2.5	Pass
	3.70	43	0.051399		
	3.40	45	0.053789		
Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	44	0.023404	2.5	Pass
	3.70	42	0.022340		
	3.40	43	0.022872		

Reference Frequency: GSM850 Highest channel=251 channel=848.8MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	39	0.045947	2.5	Pass
	3.70	45	0.053016		
	3.40	42	0.049482		
Reference Frequency: PCS1900 Highest channel=810 channel=1909.8MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	35	0.018327	2.5	Pass
	3.70	49	0.025657		
	3.40	40	0.020945		