

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

FCC ID	ZY3-HB-SC24-24				
Product Description	R/C TOYS				
Model Name	SC24A13-1, DL16A01, DL16A02, DL16A03, DL16A04, DL16B01, DL16B02, DL16B03, DL16B04, DL16A01-1, DL16A02-1, DL16A03-1, DL16A04-1, DL16B01-1, DL16B02-1, DL16B03-1, DL16B04-1, SC16A01, SC16A02, SC16A03, SC16A04, SC16A05, SC16A06, SC16A07, SC16A08, SC16A01-1, SC16A02-1, SC16A03-1, SC16A04-1, SC16A05-1, SC16A06-1, SC16A07-1, SC16A08-1, SC16B01, SC16B02, SC16B03, SC16B04, SC16B05, SC16B06, SC16B07, SC16B08, SC16B01-1, SC16B02-1, SC16B03-1, SC16B04-1, SC16B05-1, SC16B06-1, SC16B07-1, SC16B08-1, SC24A01, SC24A02, SC24A03, SC24A04, SC24A05, SC24A06, SC24A07, SC24A08, SC24A09, SC24A01, SC24A11, SC24A12, SC24B01, SC24B02, SC24B03, SC24B04, SC24B05, SC24B06, SC24B07, SC24B08, SC24B09, SC24B11, SC24B12, SC24A01-1, SC24A02-1, SC24A03-1, SC24A04-1, SC24A10-1, SC24A11-1, SC24A12-1, SC24B01-1, SC24B02-1, SC24B03-1, SC24B04-1, SC24B05-1, SC24B05-1, SC24B06-1, SC24B05-1, SC24B06-1, SC24B08-1, SC24B0				
Frequency band (Operating)	SC24B09-1, SC24B10-1, SC24B11-1, SC24B12-1, SC24B13-1 WLAN: 2.412GHz ~ 2.462GHz WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz WLAN: 5.745GHz ~ 5825GHz				
Device category					
Antenna diversity	⊠Single antenna ☐Multiple antennas				
Maximum field strength	85.33dBµV/m(Peak)@3m 78.23dBµV/m(Average)@3m				
Antenna gain	0dBi				
Evaluation applied	☐MPE Evaluation SAR Evaluation				

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



2. PORTABLE DEVICE EVALUATION METHOD AND LIMIT

According to §15.247(i) and §1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v05, section 4.3.1.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,16 where

- •f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation17
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.



3. MOBILE DEVICE EVALUATION METHOD AND LIMIT

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ² , H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f ²)*	30
30 300	27.5	0.073	0.2	30
300 1500		1	f/1500	30
1500 100,000			1.0	30

^{*}Note:

- 1. f= Frequency in MHz * Plane-wave Equivalent Power Density
- 2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

S=PG/4πR²

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



4. MEASUREMENT RESULT

Test Mode	Channel Frequency (MHz)	Field Strength (dBµV/m)	Max Output power (mW)	Calculation Value (Note 1)	Threshold Value			
GFSK								
2.4G(Peak)	2405	85.33	0.1023	0.0317	3.0			
2.4G(Average)	2405	78.23	0.0199	0.0062	3.0			

Note 1:Calculation Value =[(max. power of channel, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}]$.

Fox example: $0.1023/5*\sqrt{2.405}=0.0317 \le 3.0$

Note 2:Max Power (dBm)=Field Strength of Fundamental (dBµV/m@3m)-95.23

Note 3:Max Power (mW)=10^(Max power (dBm)/10)

According to KDB447498 D01 V06, threshold at which no SAR required is ≤3.0 for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required.

5. CONCLUSION

Since Source-base time average power is below SAR test exclusion power thresholds, the SAR evaluation is not required.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.