

## 9 Appendix A - General Product Information

### Radiofrequency radiation exposure evaluation

This exposure evaluation is intended for **FCC ID: ZZN-ST100**

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances  $\leq 50$  mm, the Numeric threshold is determined as:

Step a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR

>> The fundamental frequency of the EUT is 2402-2480MHz,  
the test separation distance is  $\leq 50\text{mm}$ .  
(Manufacturer specified the separation distance is: 5mm)


Step b)

>> Numeric threshold (2457MHz),  $\text{mW} / 5\text{mm} \cdot \sqrt{2.457\text{GHz}} \leq 3.0$   
Numeric threshold (2457MHz)  $\leq 9.569\text{mW}$

>>The power of EUT measured (2457MHz) is:  $-1.26\text{dBm} = 0.748\text{mW}$

Which is smaller than the Numeric threshold.

Therefore, the device is exempt from stand-alone SAR test requirements.



Date: 11.DEC.2019 13:10:27